



**WORKBOOK 2025 BIKES**

# WORKBOOK 2025 BIKES

## STRADA

TARMAC	3
SHIV TT	13
AETHOS	14
ROUBAIX	21
ALLEZ	26
CRUX	30
DIVERGE	37

## BAMBINI

JETT	84
RIPROCK	86
HOTWALK	89
ACTIVE	
SIRRUS	90

## MOUNTAIN

EPIC	43
STUMPJUMPER	56
ENDURO	65
DEMO	68
STATUS	69
P.SERIES	71
CHISEL	73
ROCKHOPPER	80

## TURBO

LEVO	98
KENEVO	108
VADO	111
CREO	119
COMO	122
TERO	123
PORTO	127

# S-WORKS TARMAC SL8 - SRAM RED AXS



Gloss Cypress Metallic/Magenta to Gold Pearl/Satin Black Metallic



Gloss Solidity/Red to Black Pearl/Metallic White Silver

## S-WORKS TARMAC SL8 - SRAM RED AXS

	44	49	52	54	56	58	61
Frame Stack (mm)	501	514	527	544	565	591	612
Frame Reach (mm)	366	375	380	384	395	402	408
Stack to Stem (mm)	509	522	535	552	573	599	620
Reach to Stem (mm)	363	372	377	381	393	400	406
Lunghezza Tubo Sterzo (mm)	99	109	120	137	157	184	204
Angolo sterzo (degrees)	70.5	71.75	72.5	73	73.5	73.5	74
Altezza movimento centrale (mm)	266	266	266	268	268	268	268
BB Drop (mm)	74	74	74	72	72	72	72
Trail (mm)	71	63	58	58	55	55	52
Lunghezza forcella (mm)	370	370	370	370	370	370	370
Offset forcella/Rake (mm)	47	47	47	44	44	44	44
Avancorsa (mm)	572	574	577	579	592	606	613
Lunghezza Batticateni (mm)	410	410	410	410	410	410	410
Interasse (mm)	970	973	975	978	991	1006	1013
Lunghezza Tubo Orizz. virtuale (mm)	496	509	531	541	563	577	595
Altezza standover (mm)	723	735	746	768	786	808	834
Lunghezza piantone (mm)	433	445	456	473	494	515	545
Angolo Sella (degrees)	75.5	75.5	74	74	73.5	73.5	73
Lunghezza pedivella- translate here (mm)	165	165	170	172.5	172.5	175	175
Larghezza Manubrio (mm)	380	380	400	400	420	420	440
Lunghezza Attacco man. (mm)	75	75	90	100	100	110	110
Larghezza Sella (mm)	155	155	155	143	143	143	143
Lunghezza Reggisella (mm)	300	300	300	380	380	380	380

## SPECIFICHE TECNICHE

Specialized si riserva il diritto di modificare le caratteristiche senza preavviso.

Telaio	S-Works Tarmac SL8 FACT 12r Carbon, Rider First Engineered™, Win Tunnel Engineered, Clean Routing, Threaded BB, 12x142mm thru-axle, flat-mount disc
Forcella	S-Works FACT 12r Carbon, 12x100mm thru-axle, flat-mount disc
Curva manubrio	Roval Rapide Cockpit, Integrated Bar/Stem
Attacco Manubrio	Roval Rapide Cockpit, Integrated Bar/Stem
Nastro Manubrio	Supacaz Super Sticky Kush
Sella	S-Works Power with Mirror
Reggisella	S-Works Tarmac SL8 Carbon seat post, FACT Carbon, 15mm offset
Collarino Sella	Tarmac Integrated Wedge
Freno anteriore	NEW SRAM RED AXS, hydraulic disc
Freno posteriore	NEW SRAM RED AXS, hydraulic disc
Comandi cambio	NEW SRAM RED AXS, hydraulic disc
Deragliatore anteriore	NEW SRAM RED AXS, braze-on
Cambio posteriore	NEW SRAM RED AXS, 12-speed
Pacco Pignoni	NEW SRAM RED XG-1290, 12-speed, 10-33t
Guarnitura	NEW SRAM RED AXS Power Meter
Ingranaggi	48/35
Movimento Centrale	SRAM DUB BSA 68
Catena	NEW SRAM RED 12-speed
Ruota anteriore	Roval Rapide CLX II, Tubeless, 21mm internal width carbon rim, 51mm depth, Win Tunnel Engineered, Roval AFD hub, 18h, DT Swiss Aerolite spokes
Ruota posteriore	Roval Rapide CLX II, Tubeless, 21mm internal width carbon rim, 60mm depth, Win Tunnel Engineered, Roval AFD hub, 24h, DT Swiss Aerolite spokes
Pneumatico anteriore	S-works Turbo Rapidair 2BR, 700x26mm
Pneumatico posteriore	S-works Turbo Rapidair 2BR, 700x26mm
Camere d'aria	Turbo Ultralight, 60mm Front, 80mm Rear, Presta valve
Peso	6.66 kg (14 lb, 10.9 oz)
Misura pesata	56

ART. NR.	DESCRIZIONE	COLORE	MISURA
90625-0144	TARMAC SL8 SW ETAP	Gloss Cypress Metallic/Magentato Gold Pearl/Satin Black Metallic	44
90625-0149/61			49/61
90625-0044	TARMAC SL8 SW ETAP	Gloss Solidity/Red to Black Pearl/Metallic White Silver	44
90625-0049/61			49/61

Disponibile Online e Pickup in store

# S-WORKS TARMAC SL8 DI2



Gloss Dove Grey/Silver Dust Blurred Impasto/Black Pearl



Gloss Solidity/Red to Black Pearl/Metallic White Silver

S-WORKS TARMAC SL8 DI2	44	49	52	54	56	58	61
Stack (mm)	501	514	527	544	565	591	612
Reach (mm)	366	375	380	384	395	402	408
Stack to Stem (mm)	509	522	535	552	573	599	620
Reach to Stem (mm)	363	372	377	381	393	400	406
Lunghezza Tubo Sterzo (mm)	99	109	120	137	157	184	204
Angolo sterzo (degrees)	70.5	71.75	72.5	73	73.5	73.5	74
Altezza movimento centrale (mm)	266	266	266	268	268	268	268
BB Drop (mm)	74	74	74	72	72	72	72
Trail (mm)	71	63	58	58	55	55	52
Lunghezza forcella (mm)	370	370	370	370	370	370	370
Offset forcella/Rake (mm)	47	47	47	44	44	44	44
Avancorsa (mm)	572	574	577	579	592	606	613
Lunghezza Batticateni (mm)	410	410	410	410	410	410	410
Interasse (mm)	970	973	975	978	991	1006	1013
Lunghezza Tubo Orizz. virtuale (mm)	496	509	531	541	563	577	595
Altezza Standover (mm)	723	735	746	768	786	808	834
Lunghezza piantone (mm)	433	445	456	473	494	515	545
Angolo Sella (degrees)	75.5	75.5	74	74	73.5	73.5	73
Lunghezza pedivella (mm)	165	165	170	172.5	175	175	175
Larghezza Manubrio (mm)	380	380	400	400	420	420	440
Lunghezza Attacco man. (mm)	75	75	90	100	100	110	110
Larghezza Sella (mm)	155	155	155	143	143	143	143
Lunghezza Reggisella (mm)	300	300	300	380	380	380	380

SPECIFICHE TECNICHE	Specialized si riserva il diritto di modificare le caratteristiche senza preavviso.
Telaio	S-Works Tarmac SL8 FACT 12r Carbon, Rider First Engineered™, Win Tunnel Engineered, Clean Routing, Threaded BB, 12x142mm thru-axle, flat-mount disc
Forcella	S-Works FACT 12r Carbon, 12x100mm thru-axle, flat-mount disc
Curva manubrio	Roval Rapide Cockpit, Integrated Bar/Stem
Attacco Manubrio	Roval Rapide Cockpit, Integrated Bar/Stem
Nastro Manubrio	Supacaz Super Sticky Kush
Sella	Body Geometry S-Works Power with Mirror, carbon fiber rails, carbon fiber base
Reggisella	S-Works Tarmac SL8 Carbon seat post, FACT Carbon, 15mm offset
Freno anteriore	Shimano Dura-Ace R9270, hydraulic disc
Freno posteriore	Shimano Dura-Ace R9270, hydraulic disc
Collarino Sella	Tarmac integrated wedge
Comandi cambio	Shimano Dura-Ace R9270, hydraulic disc
Deragliatore anteriore	Shimano Dura-Ace R9250, braze-on
Cambio posteriore	Shimano Dura-Ace R9250, 12-speed
Pacco Pignoni	Shimano Dura-Ace, 12-speed, 11-30t
Catena	Shimano Dura-Ace, 12-speed
Guarnitura	Shimano Dura-Ace R9200, HollowTech II, 12-speed with 4iiii Precision 3+ Pro dual-sided powermeter
Ingranaggi	52/36T
Movimento Centrale	Shimano Dura-Ace, BB-R9200
Ruota anteriore	Roval Rapide CLX II, Tubeless, 21mm internal width carbon rim, 51mm depth, Win Tunnel Engineered, Roval AFD hub, 18h, DT Swiss Aerolite spokes
Ruota posteriore	Roval Rapide CLX II, Tubeless, 21mm internal width carbon rim, 60mm depth, Win Tunnel Engineered, Roval AFD hub, 24h, DT Swiss Aerolite spokes
Pneumatico anteriore	S-Works Turbo Rapidair 2BR, 700x26mm
Pneumatico posteriore	S-Works Turbo Rapidair 2BR, 700x26mm
Camere d'aria	Turbo Ultralight, 60mm Front, 80mm Rear, Presta valve
Peso	6.62 kg (14 lb, 9.5 oz)
Misura pesata	56cm

ART. NR.	DESCRIZIONE	COLORE	MISURA
94925-0049/61	SW TARMAC SL8 DI2	Gloss Dove Grey	49/61
94925-0144/61	SW TARMAC SL8 DI2	Gloss Solidity/Red to Blk pearl	44/61

# TELAIO S-WORKS TARMAC SL8



Gloss Glacial Metallic /  
Red to Gold Pearl / White



Gloss Carbon/Red to Gold Blurred  
Speckle/Metallic White Silver



Gloss Cypress Metallic/Magenta to  
Gold Pearl/Satin Black Metallic



Gloss Red to Black Pearl Over  
Deep Lake Metallic/Satin Obsidian



Gloss Solidity / Red to Black Pearl  
/ Metallic White Silver



Satin Carbon/Rebel Pink + Deep  
Lake Met.Blurred /Gloss White



Satin Liquid Silver/Multi-color Dry  
Impasto/Gloss Team Yellow Tint

## SPECIFICHE TECNICHE

<b>Specialized si riserva il diritto di modificare le caratteristiche senza preavviso.</b>	
Telaio	S-Works Tarmac SL8 FACT 12r Carbon, Rider First Engineered™, Win Tunnel Engineered, Clean Routing, Threaded BB, 12x142mm thru-axle, flat-mount disc. 685g frame.
Forcella	S-Works FACT 12r Carbon, 12x100mm thru-axle, flat-mount disc
Reggisella	S-Works Tarmac SL8 Carbon seat post, FACT Carbon, 15mm offset
Collarino Sella	Tarmac integrated wedge
Peso	1.37kg (3 lb., .3 oz)
Misura pesata	56cm, as pictured

## TELAIO S-WORKS TARMAC SL8

	44	49	52	54	56	58	61
Stack (mm)	501	514	527	544	565	591	612
Reach (mm)	366	375	380	384	395	402	408
Stack to Stem (mm)	509	522	535	552	573	599	620
Reach to Stem (mm)	363	372	377	381	393	400	406
Lunghezza Tubo Sterzo (mm)	99	109	120	137	157	184	204
Angolo sterzo (degrees)	70.5	71.75	72.5	73	73.5	73.5	74
BB Height (mm)	266	266	266	268	268	268	268
BB Drop (mm)	74	74	74	72	72	72	72
Trail (mm)	71	63	58	58	55	55	52
Lunghezza forcella (mm)	370	370	370	370	370	370	370
Offset forcella/Rake (mm)	47	47	47	44	44	44	44
Avancorsa (mm)	572	574	577	579	592	606	613
Lunghezza Batticateni (mm)	410	410	410	410	410	410	410
Interasse (mm)	970	973	975	978	991	1006	1013
Top Tube Length, Horizontal (mm)	496	509	531	541	563	577	595
Altezza Standover (mm)	723	735	746	768	786	808	834
Seat Tube Length (mm)	433	445	456	473	494	515	545
Angolo sella (degrees)	75.5	75.5	74	74	73.5	73.5	73
Lunghezza Reggisella (mm)	300	300	300	380	380	380	380

ART. NR.	DESCRIZIONE	COLORE	MISURA
74925-00	SW TARMAC FRM	Gloss Carbon/Red to Gold Blurred Speckle/Metallic White Silver	49/91
74925-01	SW TARMAC FRM	Gloss Cypress Metallic/Magenta to Gold Pearl/Satin Black Metallic	44/61
74925-02	SW TARMAC FRM	Gloss Glacial Metallic / Red to Gold Pearl / White	49/61
74925-03	SW TARMAC FRM	Gloss Red to Black Pearl Over Deep Lake Metallic/Satin Obsidian	49/61
74925-04	SW TARMAC FRM	Gloss Solidity / Red to Black Pearl / Metallic White Silver	49/61
74925-05	SW TARMAC FRM	Satin Carbon/Rebel Pink + Deep Lake Met.Blurred /Gloss White	49/61
74925-06	SW TARMAC FRM	Satin Liquid Silver/Multi-color Dry Impasto/Gloss Team Yellow Tint	49/61

## TELAIO S-WORKS TARMAC SL8 RTP



READY TO PAINT

SPECIFICHE TECNICHE	Specialized si riserva il diritto di modificare le caratteristiche senza preavviso.
Telaio	S-Works Tarmac SL8 FACT 12r Carbon, Rider First Engineered™, Win Tunnel Engineered, Clean Routing, Threaded BB, 12x142mm thru-axle, flat-mount disc. 685g frame.
Forcella	S-Works FACT 12r Carbon, 12x100mm thru-axle, flat-mount disc
Reggisella	S-Works Tarmac SL8 Carbon seat post, FACT Carbon, 15mm offset
Collarino Sella	Tarmac integrated wedge
Identificativo	277463
Peso	1.38kg (3 lb, .7 oz)
Misura pesata	56

### TELAIO S-WORKS TARMAC SL8 RTP

	44	49	52	54	56	58	61
Stack (mm)	501	514	527	544	565	591	612
Reach (mm)	366	375	380	384	395	402	408
Stack to Stem (mm)	509	522	535	552	573	599	620
Reach to Stem (mm)	363	372	377	381	393	400	406
Lunghezza Tubo Sterzo (mm)	99	109	120	137	157	184	204
Angolo sterzo (degrees)	70.5	71.75	72.5	73	73.5	73.5	74
Altezza movimento centrale (mm)	266	266	266	268	268	268	268
BB Drop (mm)	74	74	74	72	72	72	72
Trail (mm)	71	63	58	58	55	55	52
Lunghezza forcella (mm)	370	370	370	370	370	370	370
Offset Forcella/Rake (mm)	47	47	47	44	44	44	44
Avancorsa (mm)	572	574	577	579	592	606	613
Lunghezza Batticateni (mm)	410	410	410	410	410	410	410
Interasse (mm)	970	973	975	978	991	1006	1013
Lunghezza Tubo Orizz. virtuale (mm)	496	509	531	541	563	577	595
Altezza Standover (mm)	723	735	746	768	786	808	834
Lunghezza Piantone (mm)	433	445	456	473	494	515	545
Angolo sella (degrees)	75.5	75.5	74	74	73.5	73.5	73
Lunghezza Reggisella (mm)	300	300	300	380	380	380	380

ART. NR.	DESCRIZIONE	COLORE	MISURA
74925-0744	SW TARMAC SL8 FRAME READY TO PAINT		44
74925-0749			49
74925-0752			52
74925-0754			54
74925-0756			56
74925-0758			58
74925-0761			61

# TARMAC SL8 PRO UDI2



Gloss Carbon/Metallic White Silver



Gloss Liquid Silver/Satin Blue Pearl over Black Liquid Metal

TARMAC SL8 PRO UDI2	44	49	52	54	56	58	61
Stack (mm)	501	514	527	544	565	591	612
Reach (mm)	366	375	380	384	395	402	408
Stack to Stem (mm)	509	522	535	552	573	599	620
Reach to Stem (mm)	363	372	377	381	393	400	406
Lunghezza Tubo Sterzo (mm)	99	109	120	137	157	184	204
Angolo sterzo (degrees)	70.5	71.75	72.5	73	73.5	73.5	74
Altezza movimento centrale (mm)	266	266	266	268	268	268	268
BB Drop (mm)	74	74	74	72	72	72	72
Trail (mm)	71	63	58	58	55	55	52
Lunghezza forcella (mm)	370	370	370	370	370	370	370
Offset forcella/Rake (mm)	47	47	47	44	44	44	44
Avancorsa (mm)	572	574	577	579	592	606	613
Lunghezza Batticateni (mm)	410	410	410	410	410	410	410
Interasse (mm)	970	973	975	978	991	1006	1013
Lunghezza Tubo Orizz. virtuale (mm)	496	509	531	541	563	577	595
Altezza Standover (mm)	723	735	746	768	786	808	834
Lunghezza piantone (mm)	433	445	456	473	494	515	545
Angolo Sella (degrees)	75.5	75.5	74	74	73.5	73.5	73
Lunghezza pedivella (mm)	165	165	170	172.5	175	175	175
Larghezza Manubrio (mm)	380	380	400	400	420	420	440
Lunghezza Attacco man. (mm)	75	75	90	100	100	110	110
Larghezza Sella (mm)	155	155	155	143	143	143	143
Lunghezza Reggisella (mm)	300	300	300	380	380	380	380

## SPECIFICHE TECNICHE

Specialized si riserva il diritto di modificare le caratteristiche senza preavviso.

Telaio	Tarmac SL8 FACT 10r Carbon, Rider First Engineered™, Win Tunnel Engineered, Clean Routing, Threaded BB, 12x142mm thru-axle, flat-mount disc
Forcella	FACT 10r Carbon, 12x100mm thru-axle, flat-mount disc
Curva manubrio	Roval Rapide Cockpit, Integrated Bar/Stem
Attacco Manubrio	Roval Rapide Cockpit, Integrated Bar/Stem
Attacco Manubrio	Tarmac integrated stem, 6-degree
Nastro Manubrio	Supacaz Super Sticky Kush
Sella	Power Pro with Mirror
Reggisella	S-Works Tarmac SL8 Carbon seat post, FACT Carbon, 15mm offset
Freno anteriore	Shimano Ultegra Di2 R8170, hydraulic disc
Freno posteriore	Shimano Ultegra Di2 R8170, hydraulic disc
Collarino Sella	Tarmac integrated wedge
Comandi cambio	Shimano Ultegra Di2 R8170, hydraulic disc
Deragliatore anteriore	Shimano Ultegra Di2 R8150, braze-on
Cambio posteriore	Shimano Ultegra Di2 R8150, 12-speed
Pacco Pignoni	Shimano Ultegra, 12-speed, 11-30t
Guarnitura	Shimano Ultegra R8100 with 4iiii power meter
Ingranaggi	52/36T
Movimento Centrale	Shimano Threaded BSA
Catena	Shimano Ultegra, 12-speed
Ruota anteriore	Roval Rapide CL II, 21mm internal width carbon rim tubeless ready, Win Tunnel Engineered, DT for Roval 350 hub, DT Swiss Revolution spokes, 51mm depth
Ruota posteriore	Roval Rapide CL II, 21mm internal width carbon rim tubeless ready, Win Tunnel Engineered, DT for Roval 350 hub, DT Swiss Revolution spokes, 60mm depth
Pneumatico anteriore	S-Works Turbo, 2BR, 700x26mm
Pneumatico posteriore	S-Works Turbo, 2BR, 700x26mm
Camere d'aria	Turbo Ultralight, 60mm Front, 80mm Rear, Presta valve
Peso	7.16 kg (15 lb, 12.6 oz)
Misura pesata	56cm

ART. NR.	DESCRIZIONE	COLORE	MISURA
94925-1249/61	TARMAC PRO UDI2	Gloss Carbon/Metallic White Silver	49/61
94925-1349/61	TARMAC PRO UDI2	Gloss Liquid Silver/Satin Blue Pearl over Black Liquid Metal	49/61

# TARMAC SL8 PRO SRAM FORCE ETAP AXS



Gloss Carbon/Metallic White Silver



Satin Pink Tint over Silver Dust/Silver Dust

## TARMAC SL8 PRO SRAM FORCE ETAP AXS

	44	49	52	54	56	58	61
Stack (mm)	501	514	527	544	565	591	612
Reach (mm)	366	375	380	384	395	402	408
Stack to Stem (mm)	509	522	535	552	573	599	620
Reach to Stem (mm)	363	372	377	381	393	400	406
Lunghezza Tubo Sterzo (mm)	99	109	120	137	157	184	204
Angolo sterzo (degrees)	70.5	71.75	72.5	73	73.5	73.5	74
Altezza movimento centrale (mm)	266	266	266	268	268	268	268
BB Drop (mm)	74	74	74	72	72	72	72
Trail (mm)	71	63	58	58	55	55	52
Lunghezza forcella (mm)	370	370	370	370	370	370	370
Offset forcella/Rake (mm)	47	47	47	44	44	44	44
Avancorsa (mm)	572	574	577	579	592	606	613
Lunghezza Batticateni (mm)	410	410	410	410	410	410	410
Interasse (mm)	970	973	975	978	991	1006	1013
Lunghezza Tubo Orizz. virtuale (mm)	496	509	531	541	563	577	595
Altezza Standover (mm)	723	735	746	768	786	808	834
Lunghezza piantone (mm)	433	445	456	473	494	515	545
Angolo Sella (degrees)	75.5	75.5	74	74	73.5	73.5	73
Lunghezza pedivella (mm)	165	165	170	172.5	172.5	175	175
Larghezza Manubrio (mm)	380	380	400	420	420	440	440
Lunghezza Attacco man. (mm)	70	80	90	100	100	110	110
Larghezza Sella (mm)	155	155	155	143	143	143	143
Lunghezza Reggisella (mm)	300	300	300	380	380	380	380

## SPECIFICHE TECNICHE

Specialized si riserva il diritto di modificare le caratteristiche senza preavviso.

Telaio	Tarmac SL8 FACT 10r Carbon, Rider First Engineered™, Win Tunnel Engineered, Clean Routing, Threaded BB, 12x142mm thru-axle, flat-mount disc
Forcella	Tarmac SL8 FACT 10r Carbon, 12x100mm thru-axle, flat-mount disc
Curva manubrio	Roval Rapide Cockpit, Integrated Bar/Stem
Attacco Manubrio	Roval Rapide Cockpit, Integrated Bar/Stem
Attacco Manubrio	Tarmac integrated stem, 6-degree
Nastro Manubrio	Supacaz Super Sticky Kush
Sella	Power Pro with Mirror
Reggisella	S-Works Tarmac SL8 Carbon seat post, FACT Carbon, 15mm offset
Collarino Sella	Tarmac integrated wedge
Freno anteriore	SRAM Force eTAP AXS, hydraulic disc
Freno posteriore	SRAM Force eTAP AXS, hydraulic disc
Comandi cambio	SRAM Force eTap AXS
Deragliatore anteriore	SRAM Force eTAP AXS, braze-on
Cambio posteriore	SRAM Force eTAP AXS, 12-speed
Pacco Pignoni	SRAM Force, 12-speed, 10-33t
Guarnitura	SRAM Force DUB, Power Meter
Ingranaggi	48-35t
Movimento Centrale	SRAM DUB BSA 68
Catena	SRAM Force 12-speed
Ruota anteriore	Roval Rapide CL II, 21mm internal width carbon rim tubeless ready, Win Tunnel Engineered, DT for Roval 350 hub, DT Swiss Revolution spokes, 51mm depth
Ruota posteriore	Roval Rapide CL II, 21mm internal width carbon rim tubeless ready, Win Tunnel Engineered, DT for Roval 350 hub, DT Swiss Revolution spokes, 60mm depth
Pneumatico anteriore	S-Works Turbo, 2BR, 700x26mm
Pneumatico posteriore	S-Works Turbo, 2BR, 700x26mm
Camere d'aria	Turbo Ultralight, 60mm Front, 80mm Rear, Presta valve
Peso	7.44 kg (16 lb, 6.4 oz)
Misura pesata	56cm

ART. NR.	DESCRIZIONE	COLORE	MISURA
94925-10	TARMAC SL8 PRO ETAP	Gloss Carbon/Met.Wht.Silver	44/61
94925-11	TARMAC SL8 PRO ETAP	Satin Pink Tint/Silver Dust	44/61

Disponibile Online e Pickup in store

# TARMAC SL8 EXPERT DI2



Gloss Deep Lake Metallic/gm pearl



Gloss White/Black Metallic



Satin Champagne/Black Pearl

TARMAC SL8 EXPERT DI2	44	49	52	54	56	58	61
Stack (mm)	501	514	527	544	565	591	612
Reach (mm)	366	375	380	384	395	402	408
Stack to Stem (mm)	509	522	535	552	573	599	620
Reach to Stem (mm)	363	372	377	381	393	400	406
Lunghezza Tubo Sterzo (mm)	99	109	120	137	157	184	204
Angolo sterzo (degrees)	70.5	71.75	72.5	73	73.5	73.5	74
Altezza movimento centrale (mm)	266	266	266	268	268	268	268
BB Drop (mm)	74	74	74	72	72	72	72
Trail (mm)	71	63	58	58	55	55	52
Lunghezza forcella (mm)	370	370	370	370	370	370	370
Offset forcella/Rake (mm)	47	47	47	44	44	44	44
Avancorsa (mm)	572	574	577	579	592	606	613
Lunghezza Batticatena (mm)	410	410	410	410	410	410	410
Interasse (mm)	970	973	975	978	991	1006	1013
Lunghezza Tubo Orizz. virtuale (mm)	496	509	531	541	563	577	595
Altezza Standover (mm)	723	735	746	768	786	808	834
Lunghezza piantone (mm)	433	445	456	473	494	515	545
Angolo Sella (degrees)	75.5	75.5	74	74	73.5	73.5	73
Lunghezza pedivella (mm)	165	165	170	172.5	172.5	175	175
Larghezza Manubrio (mm)	360	380	400	420	420	440	440
Lunghezza Attacco man. (mm)	70	80	90	100	100	110	110
Larghezza Sella (mm)	155	155	155	143	143	143	143
Lunghezza Reggisella (mm)	300	300	300	380	380	380	380

## SPECIFICHE TECNICHE

Specialized si riserva il diritto di modificare le caratteristiche senza preavviso.

Telaio	Tarmac SL8 FACT 10r Carbon, Rider First Engineered™, Win Tunnel Engineered, Clean Routing, Threaded BB, 12x142mm thru-axle, flat-mount disc
Forcella	FACT 10r Carbon, 12x100mm thru-axle, flat-mount disc
Curva manubrio	Specialized Expert Shallow Drop, alloy, 125mm drop x 75mm reach
Attacco Manubrio	Tarmac integrated stem, 6-degree
Nastro Manubrio	Supacaz Super Sticky Kush
Reggisella	S-Works Tarmac SL8 Carbon seat post, FACT Carbon, 15mm offset
Freno anteriore	Shimano Ultegra Di2 R8170, hydraulic disc
Freno posteriore	Shimano Ultegra Di2 R8170, hydraulic disc
Collarino Sella	Tarmac integrated wedge
Comandi cambio	Shimano Ultegra R8170, hydraulic disc
Deragliatore anteriore	Shimano Ultegra R8150, braze-on
Cambio posteriore	Shimano Ultegra Di2 R8150, 12-speed
Pacco Pignoni	Shimano Ultegra, 12-speed, 11-30t
Guarnitura	Shimano Ultegra R81000
Ingranaggi	52/36T
Movimento Centrale	Shimano Threaded BSA BB
Catena	Shimano Ultegra, 12-speed
Ruota anteriore	Roval C38, 21mm internal width carbon rim
Ruota posteriore	Roval C38, 21mm internal width carbon rim
Pneumatico anteriore	S-Works Turbo, folding bead, 700x26mm
Pneumatico posteriore	S-Works Turbo, folding bead, 700x26mm
Sella	Body Geometry Power Expert
Camere d'aria	Turbo Ultralight, 48mm Presta valve
Peso	7.20kg (15 lb, 14 oz)
Misura pesata	56

ART. NR.	DESCRIZIONE	COLORE	MISURA
94925-3249/61	TARMAC SL8 EXPERT DI2	Gloss Deep Lake Metallic/gm pearl	49/61
94925-3149/61	TARMAC SL8 EXPERT DI2	Gloss White/Black Metallic	49/61
94925-3049/61	TARMAC SL8 EXPERT DI2	Satin Champagne/Black Pearl	49/61

# TARMAC SL8 EXPERT



Gloss Deep Lake Metallic/Green Pearl



Satin Champagne/Black Pear

TARMAC SL8 EXPERT	44	49	52	54	56	58	61
Stack (mm)	501	514	527	544	565	591	612
Reach (mm)	366	375	380	384	395	402	408
Stack to Stem (mm)	509	522	535	552	573	599	620
Reach to Stem (mm)	363	372	377	381	393	400	406
Lunghezza Tubo Sterzo (mm)	99	109	120	137	157	184	204
Angolo sterzo (degrees)	70.5	71.75	72.5	73	73.5	73.5	74
Altezza movimento centrale (mm)	266	266	266	268	268	268	268
BB Drop (mm)	74	74	74	72	72	72	72
Trail (mm)	71	63	58	58	55	55	52
Lunghezza forcella (mm)	370	370	370	370	370	370	370
Offset forcella/Rake (mm)	47	47	47	44	44	44	44
Avancorsa (mm)	572	574	577	579	592	606	613
Lunghezza Batticatena (mm)	410	410	410	410	410	410	410
Interasse (mm)	970	973	975	978	991	1006	1013
Lunghezza Tubo Orizz. virtuale (mm)	496	509	531	541	563	577	595
Altezza Standover (mm)	723	735	746	768	786	808	834
Lunghezza piantone (mm)	433	445	456	473	494	515	545
Angolo Sella (degrees)	75.5	75.5	74	74	73.5	73.5	73
Lunghezza pedivella (mm)	165	165	170	172.5	172.5	175	175
Larghezza Manubrio (mm)	360	380	400	420	420	440	440
Lunghezza Attacco man. (mm)	70	80	90	100	100	110	110
Larghezza Sella (mm)	155	155	155	143	143	143	143
Lunghezza Reggisella (mm)	300	300	300	380	380	380	380

SPECIFICHE TECNICHE	Specialized si riserva il diritto di modificare le caratteristiche senza preavviso.
Telaio	Tarmac SL8 FACT 10r Carbon, Rider First Engineered™, Win Tunnel Engineered, Clean Routing, Threaded BB, 12x142mm thru-axle, flat-mount disc
Forcella	Tarmac SL8 FACT 10r Carbon, 12x100mm thru-axle, flat-mount disc
Curva manubrio	Specialized Expert Shallow Drop, alloy, 125mm drop x 75mm reach
Attacco Manubrio	Tarmac integrated stem, 6-degree
Nastro Manubrio	Supacaz Super Sticky Kush
Reggisella	S-Works Tarmac SL8 Carbon seat post, FACT Carbon, 15mm offset
Collarino Sella	Tarmac integrated wedge
Freno anteriore	SRAM Rival eTap AXS, hydraulic disc
Freno posteriore	SRAM Rival eTap AXS, hydraulic disc
Comandi cambio	SRAM Rival eTap AXS
Deragliatore anteriore	SRAM Rival eTAP AXS, braze-on
Cambio posteriore	SRAM Rival eTap AXS, 12-speed
Pacco Pignoni	SRAM Rival, 12-speed, 10-36t
Guarnitura	SRAM Rival with Power Meter
Ingranaggi	48/35T
Movimento Centrale	SRAM DUB BSA 68
Catena	SRAM Rival 12-speed
Ruota anteriore	Roval C38, 21mm internal width carbon rim
Ruota posteriore	Roval C38, 21mm internal width carbon rim
Pneumatico anteriore	S-Works Turbo, folding bead, 700x26mm
Pneumatico posteriore	S-Works Turbo, folding bead, 700x26mm
Sella	Body Geometry Power Expert
Camere d'aria	Turbo Ultralight, 48mm Presta valve
Peso	7.77 kg (17 lb, 2.1 oz)
Misura pesata	56cm

ART. NR.	DESCRIZIONE	COLORE	MISURA
94925-3349/61	TARMAC SL8 EXPERT	Gloss Deep Lake Metallic/ Green Pearl	49/61
94925-3449/61	TARMAC SL8 EXPERT	Satin Champagne/Black Pear	49/61

## TELAIO TARMAC SL8



Gloss Dune White/Black Pearl



Satin Ion Metallic/Sea Foam

### SPECIFICHE TECNICHE

Specialized si riserva il diritto di modificare le caratteristiche senza preavviso.

Telaio	Tarmac SL8 FACT 10r Carbon, Rider First Engineered™, Win Tunnel Engineered, Clean Routing, Threaded BB, 12x142mm thru-axle, flat-mount disc. 780g frame.
Forcella	FACT 10r Carbon, 12x100mm thru-axle, flat-mount disc
Attacco Manubrio	Tarmac integrated stem, 6-degree
Reggisella	S-Works Tarmac SL8 Carbon seat post, FACT Carbon, 15mm offset
Collarino Sella	Tarmac integrated wedge
Peso	1.71kg (3 lb, 12.3 oz)
Misura pesata	56

TELAIO TARMAC SL8	44	49	52	54	56	58	61
Stack (mm)	501	514	527	544	565	591	612
Reach (mm)	366	375	380	384	395	402	408
Stack to Stem (mm)	509	522	535	552	573	599	620
Reach to Stem (mm)	363	372	377	381	393	400	406
Lunghezza Tubo Sterzo (mm)	99	109	120	137	157	184	204
Angolo sterzo (degrees)	70.5	71.75	72.5	73	73.5	73.5	74
Altezza movimento centrale (mm)	266	266	266	268	268	268	268
BB Drop (mm)	74	74	74	72	72	72	72
Trail (mm)	71	63	58	58	55	55	52
Lunghezza forcella (mm)	370	370	370	370	370	370	370
Offset forcella/Rake (mm)	47	47	47	44	44	44	44
Avancorsa (mm)	572	574	577	579	592	606	613
Lunghezza Batticateni (mm)	410	410	410	410	410	410	410
Interasse (mm)	970	973	975	978	991	1006	1013
Lunghezza Tubo Orizz. virtuale (mm)	496	509	531	541	563	577	595
Altezza Standover (mm)	723	735	746	768	786	808	834
Lunghezza piantone (mm)	433	445	456	473	494	515	545
Angolo Sella (degrees)	75.5	75.5	74	74	73.5	73.5	73
Lunghezza Attacco man. (mm)	70	80	90	100	100	110	110
Lunghezza Reggisella (mm)	300	300	300	380	380	380	380

ART. NR.	DESCRIZIONE	COLORE	MISURA
74925-7044/61	TELAIO TARMAC SL8	Gloss Dune White/Black Pearl	44/61
74925-7144/61	TELAIO TARMAC SL8	Satin Ion Metallic/Sea Foam	44/61

Disponibile Online e Pickup in store

# TARMAC SL7 SPORT



GLOSS CARBON / METALLIC DARK NAVY



GLOSS DUNE WHITE / 10% CHAOS PEARL



GLOSS ION METALLIC / SEA FOAM

TARMAC SL7 SPORT	44	49	52	54	56	58	61
Stack (mm)	491	504	517	534	555	581	602
Reach (mm)	369	378	383	387	398	405	411
Stack to Stem (mm)	509	522	535	552	573	599	620
Reach to Stem (mm)	363	372	377	381	393	400	406
Lunghezza Tubo Sterzo (mm)	93	102	113	131	151	178	198
Angolo sterzo (degrees)	70.5	71.75	72.5	73	73.5	73.5	74
Altezza movimento centrale (mm)	266	266	266	268	268	268	268
BB Drop (mm)	74	74	74	72	72	72	72
Trail (mm)	71	63	58	58	55	55	52
Lunghezza forcella (mm)	366	366	366	366	366	366	366
Offset Forcella/Rake (mm)	47	47	47	44	44	44	44
Avancorsa (mm)	572	574	577	579	592	606	613
Lunghezza Batticatena (mm)	410	410	410	410	410	410	410
Interasse (mm)	970	973	975	978	991	1006	1013
Lunghezza Tubo Orizz. virtuale (mm)	496	509	531	541	563	577	595
Altezza Standover (mm)	723	735	746	768	786	808	834
Lunghezza Piantone (mm)	435	447	458	475	496	517	547
Angolo sella (degrees)	75.5	75.5	74	74	73.5	73.5	73
Lunghezza pedivella (mm)	165	165	170	172.5	172.5	175	175
Larghezza Manubrio (mm)	360	380	400	420	420	440	440
Lunghezza Attacco man. (mm)	70	80	90	100	100	110	110
Larghezza Sella (mm)	155	155	155	143	143	143	143
Lunghezza Reggisella (mm)	300	300	300	380	380	380	380

## SPECIFICHE TECNICHE

SPECIFICHE TECNICHE	Specialized si riserva il diritto di modificare le caratteristiche senza preavviso.
Nastro Manubrio	Supacaz Super Sticky Kush
Sella	Body Geometry Power Sport, steel rails
Telaio	Tarmac SL7 FACT 9r Carbon, Rider First Engineered™, Win Tunnel Engineered, Clean Routing, Threaded BB, 12x142mm thru-axle, flat-mount disc
Forcella	FACT Carbon, 12x100mm thru-axle, flat-mount disc
Freno anteriore	Shimano 105, Hydraulic Disc
Freno posteriore	Shimano 105, Hydraulic Disc
Comandi cambio	Shimano 105, 12 speed Mechanical
Deragliatore anteriore	Shimano 105, Braze-on
Cambio posteriore	Shimano 105, 12 speed Mechanical
Pacco Pignoni	Shimano 105, 12-speed, 11-34t
Catena	Shimano SLX M7100, 12-speed w/ quick link
Guarnitura	Shimano 105, 12-speed
Ingranaggi	52/36T
Movimento Centrale	Shimano Threaded BSA BB
Pneumatico anteriore	Turbo Pro, 700x26
Ruota anteriore	DT R470 Disc
Pneumatico posteriore	Turbo Pro, 700x26
Ruota posteriore	DT R470 Disc
Camere d'aria	Presta Valve Standard, 48mm valves
Attacco Manubrio	Tarmac integrated stem, 6-degree
Curva manubrio	Specialized Shallow Drop, 6061, 70x125mm, 31.8mm clamp
Reggisella	2021S-Works Tarmac Carbon seat post, FACT Carbon, 20mm offset
Collarino Sella	Tarmac integrated wedge
Identificativo	221542
Peso	8.25kg (18 lb, 3 oz)
Misura pesata	56

ART. NR.	DESCRIZIONE	COLORE	MISURA
90625-6044	TARMAC SL7 SPORT	GLOSS CARBON/MET.DARKNAVY	44
90625-6049			49
90625-6052			52
90625-6054			54
90625-6056			56
90625-6058			58
90625-6061			61
90625-6144	TARMAC SL7 SPORT	GLS DUNE WHITE/CHAOS PEARL	44
90625-6149			49
90625-6152			52
90625-6154			54
90625-6156			56
90625-6158			58
90625-6161			61
90625-6244	TARMAC SL7 SPORT	GLOSS ION METALLIC/SEA FOAM	44
90625-6249			49
90625-6252			52
90625-6254			54
90625-6256			56
90625-6258			58
90625-6261			61

## S-WORKS SHIV TT MODULE



Gloss Glacial Metallic



Gloss Tarmac Black

### SPECIFICHE TECNICHE

Specialized si riserva il diritto di modificare le caratteristiche senza preavviso.

Telaio	S-Works FACT 11r carbon, Win Tunnel Engineered, UCI Legal, internal electric only cable routing, BSA Threaded, 12x142mm thru-axle, flat-mount disc
Forcella	S-Works FACT carbon, UCI Legal, 100x12mm thru-axle, flat-mount disc
Attacco Manubrio	Shiv TT Basebar with integrated stem cover
Curva manubrio	Specialized Shiv TT Integrated bar/stem aerobar
Reggisella	2019 S-Works Venge aero seatpost, FACT carbon, Di2-compatible
Collarino Sella	Shiv TT integrated wedge
Peso	221549
Peso	2.69 kg (5 lb, 14.9 oz)
Misura pesata	MD

S-WORKS SHIV TT MODULE	XS	S	M	L
Reach effettivo dal centro del Pad, Posizione arretrata (mm)	436	448	463	478
Reach effettivo dal centro del Pad, Posizione avanzata (mm)	464	476	491	506
Stack effettivo fino all'attacco del pad, Posizione BASSSA (mm)	535	545	545	545
Stack effettivo fino all'attacco del pad, Posizione ALTA (mm)	680	690	690	690
Stack (mm)	485	495	495	495
Reach (mm)	378	390	405	420
Lunghezza Tubo Sterzo (mm)	90	95	95	95
Angolo Sterzo (degrees)	71	72	72	72
Altezza movimento centrale (mm)	269	270	270	270
B-B Drop (mm)	70	72	72	72
Trail (mm)	70	63	63	63
Lunghezza forcella (mm)	363	363	363	363
Offset forcella/Rake (mm)	45	45	45	45
Avancorsa (mm)	573	579	594	609
Lunghezza Batticateni (mm)	410	410	410	410
Interasse (mm)	972	978	993	1008
Lunghezza Tubo Orizz. virtuale (mm)	512	527	538	546
Altezza Standover (mm)	769	802	802	802
Lunghezza Piantone (mm)	504	564	563	562
Angolo Sella (degrees)	74.5	74.5	75	75.75
Larghezza Manubrio (mm)	400	400	400	400
Lunghezza Attacco man. (mm)	75	75	75	75
Lunghezza Reggisella (mm)	390	390	390	390

ART. NR.	DESCRIZIONE	COLORE	MISURA
77425-0101	S-WORKS SHIV TT MODULE	Gloss Glacial Metallic	XS
77425-0102			S
77425-0103			M
77425-0104			L
77425-0201	S-WORKS SHIV TT MODULE	Gloss Tarmac Black	XS
77425-0202			S
77425-0203			M
77425-0204			L

## S-WORKS AETHOS - SRAM RED AXS



SATIN DOPPIO / GUNMETAL DRY BRUSHED / GOLD PEARL

### SPECIFICHE TECNICHE

Specialized si riserva il diritto di modificare le caratteristiche senza preavviso.

Telaio	S-Works Aethos FACT 12r Carbon, Rider First Engineered™, Threaded BB, Electronic cable routing only, 12x142mm thru-axle, flat-mount disc
Forcella	S-Works FACT Carbon, 12x100mm thru-axle, flat-mount disc
Curva manubrio	S-Works Short & Shallow, 125mm Drop, 75mm Reach w/Di2 Hole
Attacco Manubrio	Roval Alpinist, alloy, titanium bolts, 6-degree rise
Nastro Manubrio	Supacaz Super Sticky Kush
Sella	S-Works Power with Mirror
Reggisella	Roval Alpinist Carbon Seatpost
Collarino Sella	Specialized Alloy, 30.0mm, titanium bolt
Freno anteriore	NEW SRAM RED AXS, hydraulic disc
Freno posteriore	NEW SRAM RED AXS, hydraulic disc
Comandi cambio	NEW SRAM RED AXS, 12-speed
Deragliatore anteriore	NEW SRAM RED AXS, braze-on
Cambio posteriore	NEW SRAM RED AXS, 12-speed
Pacco Pignoni	NEW SRAM RED XG-1290, 12-speed, 10-33t
Guarnitura	NEW SRAM RED AXS Power Meter
Ingranaggi	48/35
Movimento Centrale	SRAM DUB BSA 68
Catena	NEW SRAM RED 12-speed
Ruota anteriore	Roval Alpinist CLX, Tubeless, 21mm internal width carbon rim, 33mm depth, Win Tunnel Engineered, Roval AFD hub, 21h, DT Swiss Aerolite spokes
Ruota posteriore	Roval Alpinist CLX, Tubeless, 21mm internal width carbon rim, 33mm depth, Win Tunnel Engineered, Roval AFD hub, 24h, DT Swiss Aerolite spokes
Pneumatico anteriore	S-works Turbo 2BR, 700x28mm
Pneumatico posteriore	S-works Turbo 2BR, 700x28mm
Camere d'aria	700x20-28, 48mm Presta Valve
Peso	6.34 kg (13 lb, 15.6 oz)
Misura pesata	56

S-WORKS AETHOS - SRAM RED AXS	49	52	54	56	58	61
Stack (mm)	514	527	544	565	591	612
Reach (mm)	375	380	384	395	402	408
Lunghezza Tubo Sterzo (mm)	109	120	137	157	184	204
Angolo sterzo (degrees)	71.75	72.5	73	73.5	73.5	74
Altezza movimento centrale (mm)	266	266	268	268	268	268
BB Drop (mm)	74	74	72	72	72	72
Trail (mm)	63	58	58	55	55	52
Lunghezza forcella (mm)	369	369	369	369	369	369
Offset forcella/Rake (mm)	47	47	44	44	44	44
Avancorsa (mm)	574	577	579	591	606	613
Lunghezza Batticateni (mm)	410	410	410	410	410	410
Interasse (mm)	973	975	978	991	1005	1012
Lunghezza Tubo Orizz. virtuale (mm)	508	531	540	562	577	595
Altezza standover (mm)	705	728	748	769	796	824
Lunghezza piantone (mm)	431	462	481	504	532	567
Angolo Sella (degrees)	75.5	74	74	73.5	73.5	73
Lunghezza pedivella- translate here (mm)	165	170	172.5	172.5	175	175
Larghezza Manubrio (mm)	380	400	420	420	440	440
Lunghezza Attacco man. (mm)	80	90	100	100	110	110
Larghezza Sella (mm)	155	155	143	143	143	143
Lunghezza Reggisella (mm)	300	300	360	360	360	360

ART. NR.	DESCRIZIONE	COLORE	MISURA
97225-0049/61	AETHOS SW ETAP	SATIN DOPPIO / GUNMETAL DRY BR	49/61

## TELAIO S-WORKS AETHOS



Gloss Sea Foam/Dry Brushed Violet + Gold Ghost Pearl/Smoke



Satin Deep Lake Metallic/Green Pearl + Burnt Gold Metallic Fades / Dark Navy



Satin Silver Dust/Team Yellow Tint/Chrome

### SPECIFICHE TECNICHE

Specialized si riserva il diritto di modificare le caratteristiche senza preavviso.

Forcella	S-Works FACT Carbon, 12x100mm thru-axle, flat-mount disc
Telaio	S-Works Aethos FACT 12r Carbon, Rider First Engineered™, Threaded BB, Electronic cable routing only, 12x142mm thru-axle, flat-mount disc
Reggisella	Roval Alpinist Carbon Seatpost
Collarino Sella	Specialized Alloy, 30.0mm, titanium bolt
Identificativo	221547
Peso	1,22 kg (2 lb, 11.0 oz)
Misura pesata	56

TELAIO S-WORKS AETHOS	49	52	54	56	58	61
Stack (mm)	514	527	544	565	591	612
Reach (mm)	375	380	384	395	402	408
Lunghezza Tubo Sterzo (mm)	109	120	137	157	184	204
Angolo sterzo (degrees)	71.75	72.5	73	73.5	73.5	74
Altezza movimento centrale (mm)	266	266	268	268	268	268
BB Drop (mm)	74	74	72	72	72	72
Trail (mm)	63	58	58	55	55	52
Lunghezza forcella (mm)	369	369	369	369	369	369
Offset Forcella/Rake (mm)	47	47	44	44	44	44
Avancorsa (mm)	574	577	579	591	606	613
Lunghezza Batticateni (mm)	410	410	410	410	410	410
Interasse (mm)	973	975	978	991	1005	1012
Lunghezza Tubo Orizz. virtuale (mm)	508	531	540	562	577	595
Altezza Standover (mm)	705	728	748	769	796	824
Lunghezza Piantone (mm)	431	462	481	504	532	567
Angolo sella (degrees)	75.5	74	74	73.5	73.5	73
Lunghezza Reggisella (mm)	300	300	360	360	360	360

ART. NR.	DESCRIZIONE	COLORE	MISURA
77225-0049	AETHOS SW FRAME	Gloss Sea Foam/Dry Brushed Violet	49
77225-0052			52
77225-0054			54
77225-0056			56
77225-0058			58
77225-0061			61
77225-0149	AETHOS SW FRAME	Satin Deep Lake Metallic/Green Pearl	49
77225-0152			52
77225-0154			54
77225-0156			56
77225-0158			58
77225-0161			61
77225-0249	AETHOS SW FRAME	Satin Silver Dust/Team Yellow Tint	49
77225-0252			52
77225-0254			54
77225-0256			56
77225-0258			58
77225-0261			61

# AETHOS PRO - SHIMANO ULTEGRA DI2



Satin Carbon / Red Pearl / Black

## SPECIFICHE TECNICHE

Specialized si riserva il diritto di modificare le caratteristiche senza preavviso.

Forcella	FACT Carbon, 12x100mm thru-axle, flat-mount disc
Nastro Manubrio	Supacaz Super Sticky Kush
Ruota anteriore	Roval Alpinist CL II, 21mm internal width carbon rim, 33mm depth, Win Tunnel Engineered, DT for Roval 350 hub, DT Swiss Aerolite spokes, Tubeless Ready
Ruota posteriore	Roval Alpinist CL II, 21mm internal width carbon rim, 33mm depth, Win Tunnel Engineered, DT for Roval 350 hub, DT Swiss Aerolite spokes, Tubeless Ready
Telaio	Aethos FACT 10r Threaded BB, 12x142mm thru-axle, flat-mnt disc
Freno anteriore	Shimano Ultegra R8170, hydraulic disc
Freno posteriore	Shimano Ultegra R8170, hydraulic disc
Comandi cambio	Shimano Ultegra Di2 R8170, hydraulic disc
Deragliatore anteriore	Shimano Ultegra Di2 R8150, braze-on
Cambio posteriore	Shimano Ultegra Di2 R8150, 12-speed
Pacco Pignoni	Shimano Ultegra, 12-speed, 11-30t
Catena	Shimano M8100, 12-speed w/ quick link
Guarnitura	Shimano Ultegra R8100 with 4iiii Precision 3+ Power Meter
Ingranaggi	52/36T
Movimento Centrale	Shimano Threaded BSA BB
Pneumatico anteriore	S-works Turbo 2BR, 700x28mm
Pneumatico posteriore	S-works Turbo 2BR, 700x28mm
Camere d'aria	700x20-28, 48mm Presta Valve
Attacco Manubrio	Specialized Pro SL, alloy, 4-bolt
Curva manubrio	S-Works Short & Shallow, 125mm Drop, 75mm Reach w/Di2 Hole
Sella	Body Geometry Power Pro with Mirror, hollow titanium rails
Reggisella	Roval Alpinist Carbon Seatpost
Collarino Sella	Specialized Alloy, 30mm
Peso	6.78kg (14 lb, 15.2 oz)
Misura pesata	56

## AETHOS PRO - SHIMANO ULTEGRA DI2

	49	52	54	56	58	61
Stack (mm)	514	527	544	565	591	612
Reach (mm)	375	380	384	395	402	408
Lunghezza Tubo Sterzo (mm)	109	120	137	157	184	204
Angolo sterzo (degrees)	71.75	72.5	73	73.5	73.5	74
Altezza movimento centrale (mm)	266	266	268	268	268	268
BB Drop (mm)	74	74	72	72	72	72
Trail (mm)	63	58	58	55	55	52
Lunghezza forcella (mm)	369	369	369	369	369	369
Offset forcella/Rake (mm)	47	47	44	44	44	44
Avancorsa (mm)	574	577	579	591	606	613
Lunghezza Batticateni (mm)	410	410	410	410	410	410
Interasse (mm)	973	975	978	991	1005	1012
Lunghezza Tubo Orizz. virtuale (mm)	508	531	540	562	577	595
Altezza Standover (mm)	705	728	748	769	796	824
Lunghezza Piantone (mm)	431	462	481	504	532	567
Angolo sella (degrees)	75.5	74	74	73.5	73.5	73
Lunghezza pedivella (mm)	165	170	172.5	172.5	175	175
Larghezza Manubrio (mm)	380	400	420	420	440	440
Lunghezza Attacco man. (mm)	80	90	100	100	110	110
Larghezza Sella (mm)	155	155	143	143	143	143
Lunghezza Reggisella (mm)	300	300	360	360	360	360

ART. NR.	DESCRIZIONE	COLORE	MISURA
97225-1149	Aethos Pro UDi2	Satin Carbon / Red Pearl / Black	49
97225-1152			52
97225-1154			54
97225-1156			56
97225-1158			58
97225-1161			61

# AETHOS EXPERT - RIVAL ETAP AXS



Gloss Burnt Gold Metallic/Doppio



Satin Deep Lake Metallic/Green Pearl

SPECIFICHE TECNICHE	Specialized si riserva il diritto di modificare le caratteristiche senza preavviso.
Forcella	FACT Carbon, 12x100mm thru-axle, flat-mount disc
Nastro Manubrio	Supacaz Super Sticky Kush
Ruota anteriore	Roval C38, 21mm internal width carbon rim, tubeless ready
Ruota posteriore	Roval C38, 21mm internal width carbon rim, tubeless ready
Telaio	Aethos FACT 10r Threaded BB, 12x142mm thru-axle, flat-mnt disc
Freno anteriore	SRAM Rival eTAP AXS, hydraulic disc
Freno posteriore	SRAM Rival eTAP AXS, hydraulic disc
Comandi cambio	SRAM Rival eTap AXS
Deragliatore anteriore	SRAM Rival eTAP AXS, braze-on
Cambio posteriore	SRAM Rival eTap AXS, 12-speed
Pacco Pignoni	SRAM Rival, 12-speed, 10-36t
Catena	SRAM Rival 12-speed
Guarnitura	SRAM Rival DUB, Power Meter, 48-35t
Ingranaggi	48/35t
Movimento Centrale	SRAM DUB BSA 68
Pneumatico anteriore	S-Works Turbo, 120 TPI, folding bead, BlackBelt protection, 700x28mm
Pneumatico posteriore	S-Works Turbo, 120 TPI, folding bead, BlackBelt protection, 700x28mm
Camere d'aria	700x20-28, 48mm Presta Valve
Attacco Manubrio	Specialized Pro SL, alloy, 4-bolt
Curva manubrio	Specialized Expert Shallow Drop, alloy, 125mm drop x 75mm reach
Sella	Body Geometry Power Expert
Reggisella	Roval Alpinist Carbon Seatpost
Collarino Sella	Specialized Alloy, 30mm
Peso	7.54kg (16 lb, 10 oz)
Misura pesata	56

AETHOS EXPERT - RIVAL ETAP AXS	49	52	54	56	58	61
Stack (mm)	514	527	544	565	591	612
Reach (mm)	375	380	384	395	402	408
Lunghezza Tubo Sterzo (mm)	109	120	137	157	184	204
Angolo sterzo (degrees)	71.75	72.5	73	73.5	73.5	74
Altezza movimento centrale (mm)	266	266	268	268	268	268
BB Drop (mm)	74	74	72	72	72	72
Trail (mm)	63	58	58	55	55	52
Lunghezza forcella (mm)	369	369	369	369	369	369
Offset forcella/Rake (mm)	47	47	44	44	44	44
Avancorsa (mm)	574	577	579	591	606	613
Lunghezza Batticateni (mm)	410	410	410	410	410	410
Interasse (mm)	973	975	978	991	1005	1012
Lunghezza Tubo Orizz. virtuale (mm)	508	531	540	562	577	595
Altezza Standover (mm)	705	728	748	769	796	824
Lunghezza Piantone (mm)	431	462	481	504	532	567
Angolo sella (degrees)	75.5	74	74	73.5	73.5	73
Lunghezza pedivella (mm)	165	170	172.5	172.5	175	175
Larghezza Manubrio (mm)	380	400	420	420	440	440
Lunghezza Attacco man. (mm)	80	90	100	100	110	110
Larghezza Sella (mm)	155	155	143	143	143	143
Lunghezza Reggisella (mm)	300	300	360	360	360	360

ART. NR.	DESCRIZIONE	COLORE	MISURA
97225-3049	AETHOS EXPERT SRAM	Gloss Burnt Gold Metallic/Doppio	49
97225-3052			52
97225-3054			54
97225-3056			56
97225-3058			58
97225-3061			61
97225-3149	AETHOS EXPERT SRAM	Satin Deep Lake MetaGreen Pearl	49
97225-3152			52
97225-3154			54
97225-3156			56
97225-3158			58
97225-3161			61

## AETHOS COMP - SHIMANO 105 DI2



GLOSS DUNE WHITE METALLIC SPRUCE

<b>SPECIFICHE TECNICHE</b>	<b>Specialized si riserva il diritto di modificare le caratteristiche senza preavviso.</b>
Telaio	Aethos FACT 9R Carbon, Rider First Engineered™, Threaded BB, 12x142mm thru-axle, flat-mount disc
Forcella	FACT Carbon, 12x100mm thru-axle, flat-mount disc
Curva manubrio	Specialized Shallow Drop, 6061, 70x125mm, 31.8mm clamp
Attacco Manubrio	Specialized Pro SL, alloy, 4-bolt
Nastro Manubrio	Roubaix S-Wrap
Sella	Body Geometry Power Sport, steel rails
Reggisella	Roval Alpinist Carbon Seatpost
Freno anteriore	Shimano 105, Hydraulic disc
Collarino Sella	Shimano 105 R7170, hydraulic disc
Freno posteriore	Shimano 105 R7170, hydraulic disc
Comandi cambio	Shimano 105 Di2 7170
Deragliatore anteriore	Shimano 105 Di2 7150, braze on
Cambio posteriore	Shimano 105 Di2 7150
Pacco Pignoni	Shimano 105, 12-speed, 11-34t
Catena	Shimano SLX M7100, 12-speed w/ quick link
Guarnitura	FC-R7100, 105, 12-Speed, Hollowtech 2
Ingranaggi	50/34T
Movimento Centrale	Shimano Threaded BSA BB
Ruota anteriore	DT R470 Disc
Ruota posteriore	DT R470 Disc
Pneumatico anteriore	Turbo Pro, 700x28
Pneumatico posteriore	Turbo Pro, 700x28
Camere d'aria	Presta Valve Standard, 48mm valves
Peso	7.5 kg (16 lb, 8.6 oz)
Misura pesata	56

<b>ART. NR.</b>	<b>DESCRIZIONE</b>	<b>COLORE</b>	<b>MISURA</b>
97225-5049/61	AETHOS COMP	GLOSS DUNE WHITE METALLIC SPRUCE	49/61

## AETHOS SPORT - SHIMANO 105



GLOSS FOG TINT CARBON DUNE WHITE



BLUE ONYX METALLIC  
OBSIDIAN

### SPECIFICHE TECNICHE

Specialized si riserva il diritto di modificare le  
caratteristiche senza preavviso.

Forcella	FACT Carbon, 12x100mm thru-axle, flat-mount disc
Nastro Manubrio	Supacaz Super Sticky Kush
Telaio	Aethos FACT 9R Carbon, Rider First Engineered™, Threaded BB, 12x142mm thru-axle, flat-mount disc
Ruota anteriore	DT R470 DISC
Ruota posteriore	DT R470 DISC
Sella	Body Geometry Power Sport, steel rails
Freno anteriore	Shimano 105, Hydraulic disc
Freno posteriore	Shimano 105, Hydraulic disc
Comandi cambio	Shimano 105, 12 speed Mechanical
Deragliatore anteriore	Shimano 105, Braze-on
Cambio posteriore	Shimano 105, 12 speed Mechanical
Pacco Pignoni	Shimano 105, 12-speed, 11-34t
Catena	Shimano SLX, M7100, 12-speed
Guarnitura	FC-R7100, 105, 12-Speed, Hollowtech 2
Ingranaggi	50/34T
Movimento Centrale	Shimano Threaded BSA BB
Pneumatico anteriore	Turbo Pro, 700x28
Pneumatico posteriore	Turbo Pro, 700x28
Camere d'aria	Presta Valve Standard, 48mm valves
Attacco Manubrio	Specialized Pro SL, alloy, 4-bolt
Curva manubrio	Specialized Shallow Drop, 6061, 70x125mm, 31.8mm clamp
Reggisella	Royal Alpinist Carbon Seatpost
Collarino Sella	Specialized Alloy, 30mm
Peso	7.8 kg (17 lb, 3.1 oz)
Misura pesata	56

AETHOS SPORT - SHIMANO 105	49	52	54	56	58	61
Stack (mm)	514	527	544	565	591	612
Reach (mm)	375	380	384	395	402	408
Lunghezza Tubo Sterzo (mm)	109	120	137	157	184	204
Angolo sterzo (degrees)	71.75	72.5	73	73.5	73.5	74
Altezza movimento centrale (mm)	266	266	268	268	268	268
BB Drop (mm)	74	74	72	72	72	72
Trail (mm)	63	58	58	55	55	52
Lunghezza forcella (mm)	369	369	369	369	369	369
Offset forcella/Rake (mm)	47	47	44	44	44	44
Avancorsa (mm)	574	577	579	591	606	613
Lunghezza Batticateni (mm)	410	410	410	410	410	410
Interasse (mm)	973	975	978	991	1005	1012
Lunghezza Tubo Orizz. virtuale (mm)	508	531	540	562	577	595
Altezza Standover (mm)	705	728	748	769	796	824
Lunghezza piantone (mm)	431	462	481	504	532	567
Angolo Sella (degrees)	75.5	74	74	73.5	73.5	73
Lunghezza pedivella (mm)	165	170	172.5	172.5	175	175
Larghezza Manubrio (mm)	380	400	420	420	440	440
Lunghezza Attacco man. (mm)	80	90	100	100	110	110
Larghezza Sella (mm)	155	155	143	143	143	143
Lunghezza Reggisella (mm)	300	300	360	360	360	360

ART. NR.	DESCRIZIONE	COLORE	MISURA
97225-6049/61	AETHOS SPORT	GLOSS FOG TINT CARBON DUNE WHITE	49/61
97225-6149/61	AETHOS SPORT	BLUE ONYX METALLIC OBSIDIAN	49/61

# TELAIO AETHOS



Satin Flake Silver / Dusky Pink + Champagne

## SPECIFICHE TECNICHE

Specialized si riserva il diritto di modificare le caratteristiche senza preavviso.

Forcella	FACT Carbon, 12x100mm thru-axle, flat-mount disc
Telaio	Test Italian Frame
Reggisella	Roval Alpinist Carbon Seatpost
Collarino Sella	Specialized Alloy, 30.0mm, titanium bolt
Peso	1.37 kg (3 lb, 0.3 oz)
Misura pesata	56

TELAIO AETHOS	49	52	54	56	58	61
Stack (mm)	514	527	544	565	591	612
Reach (mm)	375	380	384	395	402	408
Lunghezza Tubo Sterzo (mm)	109	120	137	157	184	204
Angolo sterzo (degrees)	71.75	72.5	73	73.5	73.5	74
Altezza movimento centrale (mm)	266	266	268	268	268	268
BB Drop (mm)	74	74	72	72	72	72
Trail (mm)	63	58	58	55	55	52
Lunghezza forcella (mm)	369	369	369	369	369	369
Offset forcella/Rake (mm)	47	47	44	44	44	44
Avancorsa (mm)	574	577	579	591	606	613
Lunghezza Batticateni (mm)	410	410	410	410	410	410
Interasse (mm)	973	975	978	991	1005	1012
Lunghezza Tubo Orizz. virtuale (mm)	508	531	540	562	577	595
Altezza Standover (mm)	705	728	748	769	796	824
Lunghezza Piantone (mm)	431	462	481	504	532	567
Angolo sella (degrees)	75.5	74	74	73.5	73.5	73
Lunghezza Reggisella (mm)	300	300	360	360	360	360

ART. NR.	DESCRIZIONE	COLORE	MISURA
77225-7049	AETHOS FRAME	Satin Flake Silver / Dusky Pink + Champagne	49
77225-7052			52
77225-7054			54
77225-7056			56
77225-7058			58
77225-7061			61

Disponibile Online e Pickup in store

## S-WORKS ROUBAIX SL8 - SRAM RED AXS



Gloss Toupe/Gunmetal Strata/Charcoal

S-WORKS ROUBAIX SL8 D12	44	49	52	54	56	58	61
Stack (mm)	543	549	566	585	605	630	665
Reach (mm)	353	363	370	381	389	397	403
Lunghezza Tubo Sterzo (mm)	90	90	105	122	140	168	202
Angolo sterzo (degrees)	69.3	70.8	71.5	72.3	73	73	73.5
Altezza movimento centrale (mm)	269	269	269	270	270	271	271
BB Drop (mm)	80	80	80	78	78	78	78
Trail (mm)	76	66	62	61	57	57	54
Lunghezza forcella (mm)	375	375	375	375	375	375	375
Offset Forcella/Rake (mm)	52	52	52	47	47	47	47
Avancorsa (mm)	589	587	593	598	604	620	631
Lunghezza Batticateni (mm)	418	418	418	420	420	423	423
Interasse (mm)	994	992	988	1005	1012	1031	1042
Lunghezza Tubo Orizz. virtuale (mm)	503	523	534	550	569	584	600
Altezza Standover (mm)	686	719	747	766	787	809	847
Lunghezza Piantone (mm)	365	410	445	465	485	505	545
Angolo sella (degrees)	75	74	74	74	73.5	73.5	73.5
Lunghezza pedivella (mm)	165	165	170	172.5	172.5	175	175
Larghezza Manubrio (mm)	360	380	400	420	420	440	440
Lunghezza Attacco man. (mm)	70	80	90	100	100	110	110
Larghezza Sella (mm)	155	155	155	143	143	143	143
Lunghezza Reggisella (mm)	380	380	380	380	380	450	450

### SPECIFICHE TECNICHE

Specialized si riserva il diritto di modificare le caratteristiche senza preavviso.

Telaio	FACT 12R, Rider First Engineered™ (RFE), FreeFoil Shape Library tubes, threaded BB, 12x142mm thru-axle, flat-mount disc
Forcella	Future Shock 3.3 w/ Smooth Boot, FACT Carbon 12x100mm, thru-axle, flat-mount disc
Freno anteriore	Shimano Dura-Ace, Hydraulic Disc, 160mm
Freno posteriore	Shimano Dura-Ace, Hydraulic Disc, 160mm
Comandi cambio	Shimano Dura-Ace R9270, hydraulic disc
Deragliatore anteriore	Shimano Dura-Ace R9250, braze-on
Cambio posteriore	Shimano Dura-Ace R9250, 12-speed
Pacco Pignoni	Shimano Dura-Ace, 12-speed, 11-34t
Catena	Shimano Dura-Ace, 12-speed
Guarnitura	Shimano Dura-Ace R9200, HollowTech II, 12-speed with 4iiii Precision Pro dual-sided powermeter
Ingranaggi	50/34t
Movimento Centrale	Shimano Dura-Ace, BB-R9100
Pneumatico anteriore	S-Works Mondo 2BR, 700x32c
Ruota anteriore	Roval Terra CLX II, 25mm internal width, 32mm depth, 21h, Tubeless ready, Roval LFD hub with ceramic SINC bearings, Centerlock disc, DT Swiss Aerolite spokes
Pneumatico posteriore	S-Works Mondo 2BR, 700x32c
Ruota posteriore	Roval Terra CLX II, 25mm internal width, 32mm depth, 24h, Tubeless ready, Roval LFD hub with ceramic SINC bearings, Centerlock disc, DT Swiss Aerolite spokes
Camere d'aria	700x28/38mm, 60mm Presta valve
Attacco Manubrio	S-Works Future Stem, w/ Integrated Computer Mount
Manubrio	S-Works Carbon Hover Drop 125mm, Reach 75mm, w/Di2 hole
Manopole	Supacaz Super Sticky Kush
Sella	S-Works Power with Mirror
Reggisella	S-Works Pave Seat post
Collarino Sella	Hidden drop clamp
Identificativo	221816
Peso	7.25 kg (15 lb, 15.7 oz)
Misura pesata	56

ART. NR.	DESCRIZIONE	COLORE	MISURA
94425-0244	ROUBAIX SW SL8 ETAP	Gloss Toupe/Gunmetal Strata/Ch	44
94425-0249			49
94425-0252			52
94425-0254			54
94425-0256			56
94425-0258			58
94425-0261			61

Disponibile Online e Pickup in store

# ROUBAIX SL8 EXPERT



Gloss Sea Foam/Violet/Pearl



Satin Cooper / Smoke

ROUBAIX SL8 EXPERT	44	49	52	54	56	58	61	64
Stack (mm)	543	549	566	585	605	630	665	685
Reach (mm)	353	363	370	381	389	397	403	409
Lunghezza Tubo Sterzo (mm)	90	90	105	122	140	168	202	222
Angolo sterzo (degrees)	69.3	70.8	71.5	72.3	73	73	73.5	73.5
Altezza movimento centrale (mm)	269	269	269	270	270	271	271	271
BB Drop (mm)	80	80	80	78	78	78	78	78
Trail (mm)	76	66	62	61	57	57	54	54
Lunghezza forcella (mm)	375	375	375	375	375	375	375	375
Offset forcella/Rake (mm)	52	52	52	47	47	47	47	47
Avancorsa (mm)	589	587	593	598	604	620	631	634
Lunghezza Batticateni (mm)	418	418	418	420	420	423	423	423
Interasse (mm)	994	992	998	1005	1012	1031	1042	1054
Lunghezza Tubo Orizz. virtuale (mm)	503	523	534	550	569	584	600	618
Altezza Standover (mm)	686	719	747	766	787	809	847	865
Lunghezza Piantone (mm)	365	410	446	465	485	505	545	581
Angolo sella (degrees)	75	74	74	74	73.5	73.5	73.5	73
Lunghezza pedivella (mm)	165	165	170	172.5	172.5	175	175	175
Larghezza Manubrio (mm)	360	380	400	420	420	440	440	440
Lunghezza Attacco man. (mm)	70	80	90	100	100	110	110	120
Larghezza Sella (mm)	155	155	155	143	143	143	143	143
Lunghezza Reggisella (mm)	380	380	380	380	380	450	450	450

SPECIFICHE TECNICHE	Specialized si riserva il diritto di modificare le caratteristiche senza preavviso.
Nastro Manubrio	Supacaz Super Sticky Kush
Ruota anteriore	Roval Terra C, 25mm inner width carbon rim, 32mm depth, NEW DT 370 hub, 24h, DT Swiss Comp Race spokes
Ruota posteriore	Roval Terra C, 25mm inner width carbon rim, 32mm depth, NEW DT 370 Star Ratchet hub, 24h, DT Swiss Comp Race spokes
Telaio	FACT 10R, Rider First Engineered™ (RFE), FreeFoil Shape Library tubes, threaded BB, 12x142mm thru-axle, flat-mount disc
Forcella	Future Shock 3.2 w/ Smooth Boot, FACT Carbon 12x100mm, thru-axle, flat-mount disc
Freno anteriore	SRAM Rival Hydraulic Disc
Freno posteriore	SRAM Rival eTAP AXS, hydraulic disc
Comandi cambio	SRAM Rival eTAP AXS, 12-speed
Deragliatore anteriore	SRAM Rival eTAP AXS, 12-speed
Cambio posteriore	SRAM Rival eTAP AXS, 12-speed
Pacco Pignoni	SRAM XG 1250, 10-36T
Catena	SRAM Rival, 12-Speed
Guarnitura	SRAM Rival AXS w/Power, 12-speed
Ingranaggi	46/33T
Movimento Centrale	SRAM DUB BSA
Pneumatico anteriore	S-Works Mondo 2BR, 700x32c
Pneumatico posteriore	S-Works Mondo 2BR, 700x32c
Camere d'aria	700x28/38mm, 48mm Presta valve
Attacco Manubrio	Future Stem Pro
Curva manubrio	Specialized Hover Expert, Alloy, 125mm Drop, 75mm Reach w/Di2 Hole
Sella	Body Geometry Power Expert
Reggisella	S-Works Pave Seat post
Collarino Sella	Hidden drop clamp
Peso	8.62kg (19 lb, .1 oz)
Misura pesata	56

ART. NR.	DESCRIZIONE	COLORE	MISURA
94425-3144	ROUBAIX EXPERT	Gloss Sea Foam/Violet/Pearl	44
94425-3149			49
94425-3152			52
94425-3154			54
94425-3156			56
94425-3158			58
94425-3161			61
94425-3164			64
94425-3044	ROUBAIX EXPERT	Satin Cooper / Smoke	44
94425-3049			49
94425-3052			52
94425-3054			54
94425-3056			56
94425-3058			58
94425-3061			61
94425-3064			64

# ROUBAIX SL8 COMP



Gloss Lagoon Tint Over Carbon/Morning Mist



RED GHOST PEARL OVER DUNE/METALLIC OBSIDIAN

ROUBAIX SL8 COMP	44	49	52	54	56	58	61	64
Stack (mm)	543	549	566	585	605	630	665	685
Reach (mm)	353	363	370	381	389	397	403	409
Lunghezza Tubo Sterzo (mm)	90	90	105	122	140	168	202	222
Angolo sterzo (degrees)	69.3	70.8	71.5	72.3	73	73	73.5	73.5
Altezza movimento centrale (mm)	269	269	269	270	270	271	271	271
BB Drop (mm)	80	80	80	78	78	78	78	78
Trail (mm)	76	66	62	61	57	57	54	54
Lunghezza forcella (mm)	375	375	375	375	375	375	375	375
Offset Forcella/Rake (mm)	52	52	52	47	47	47	47	47
Avancorsa (mm)	589	587	593	598	604	620	631	634
Lunghezza Batticateni (mm)	418	418	418	420	420	423	423	423
Interasse (mm)	994	992	998	1005	1012	1031	1042	1054
Lunghezza Tubo Orizz. virtuale (mm)	503	523	534	550	569	584	600	618
Altezza Standover (mm)	686	719	747	766	787	809	847	865
Lunghezza Piantone (mm)	365	410	446	465	485	505	545	581
Angolo sella (degrees)	75	74	74	74	73.5	73.5	73.5	73
Lunghezza pedivella (mm)	165	165	170	172.5	172.5	175	175	175
Larghezza Manubrio (mm)	360	380	400	420	420	440	440	440
Lunghezza Attacco man. (mm)	70	80	90	100	100	110	110	120
Larghezza Sella (mm)	155	155	155	143	143	143	143	143
Lunghezza Reggisella (mm)	380	380	380	380	380	450	450	450

## SPECIFICHE TECNICHE

	Specialized si riserva il diritto di modificare le caratteristiche senza preavviso.
Ruota anteriore	DT Swiss G540 rim, 24mm internal width, tubeless ready, 24h, Specialized full sealed bearing thru axle hub, centerlock disc, DT Swiss Champion 14G stainless steel spokes, DT Swiss brass nipples
Telaio	FACT 10R, Rider First Engineered™ (RFE), FreeFoil Shape Library tubes, threaded BB, 12x142mm thru-axle, flat-mount disc
Forcella	Future Shock 3.2 w/ Smooth Boot, FACT Carbon 12x100mm, thru-axle, flat-mount disc
Freno anteriore	Shimano 105, Hydraulic Disc, 160mm
Freno posteriore	Shimano 105, Hydraulic Disc, 160mm
Comandi cambio	Shimano 105 R7170, hydraulic disc
Deragliatore anteriore	Shimano 105 R7170, braze-on
Cambio posteriore	Shimano 105 R7150, 12-speed
Pacco Pignoni	Shimano 105, 12-Speed, 11-36t
Catena	Shimano 105, 12-Speed
Guarnitura	Shimano 105, 12-Speed
Ingranaggi	50/34T
Movimento Centrale	Shimano Threaded BSA BB
Pneumatico anteriore	S-Works Mondo 2BR, 700x32c
Pneumatico posteriore	S-Works Mondo 2BR, 700x32c
Ruota posteriore	DT Swiss G540 rim, 24mm internal width, tubeless ready, 24h, Specialized full sealed bearing thru axle hub, centerlock disc, DT Swiss Champion 14G stainless steel spokes, DT Swiss brass nipples
Camere d'aria	700x28/38mm, 48mm Presta valve
Attacco Manubrio	Future Stem Comp
Curva manubrio	Specialized Hover Comp, Alloy, 125mm Drop, 75mm Reach w/Di2 Hole
Manopole	Supacaz Super Sticky Kush
Sella	Body Geometry Power Sport, steel rails
Reggisella	S-Works Pave
Collarino Sella	Hidden drop clamp
Identificativo	221823
Peso	8.97 kg (19 lb, 12.4 oz)
Misura pesata	56

ART. NR.	DESCRIZIONE	COLORE	MISURA
94425-5044	ROUBAIX COMP Gloss Lagoon Tint / Morning Mist		44
94425-5049			49
94425-5052			52
94425-5054			54
94425-5056			56
94425-5058			58
94425-5061			61
94425-5064			64
94423-5144	ROUBAIX COMP RED GHOST PEARL		44
94423-5149			49
94423-5152			52
94423-5154			54
94423-5156			56
94423-5158			58
94423-5161			61
94423-5164			64

# ROUBAIX SL8 SPORT 105



Gloss Champagne / Smoke



METALLIC OBSIDIAN/BIRCH



METALSAPPHIRE/BLUE ONYX

ROUBAIX SL8 SPORT 105	44	49	52	54	56	58	61	64
Stack (mm)	543	549	566	585	605	630	665	685
Reach (mm)	353	363	370	381	389	397	403	409
Lunghezza Tubo Sterzo (mm)	90	90	105	122	140	168	202	222
Angolo sterzo (degrees)	69.3	70.8	71.5	72.3	73	73	73.5	73.5
Altezza movimento centrale (mm)	269	269	269	270	270	271	271	271
BB Drop (mm)	80	80	80	78	78	78	78	78
Trail (mm)	76	66	62	61	57	57	54	54
Lunghezza forcella (mm)	375	375	375	375	375	375	375	375
Offset forcella/Rake (mm)	52	52	52	47	47	47	47	47
Avancorsa (mm)	589	587	593	598	604	620	631	634
Lunghezza Batticateni (mm)	418	418	418	420	420	423	423	423
Interasse (mm)	994	992	998	1005	1012	1031	1042	1054
Lunghezza Tubo Orizz. virtuale (mm)	503	523	534	550	569	584	600	618
Altezza Standover (mm)	686	719	747	766	787	809	847	865
Lunghezza Piantone (mm)	365	410	446	465	485	505	545	581
Angolo sella (degrees)	75	74	74	74	73.5	73.5	73.5	73
Lunghezza pedivella (mm)	165	165	170	172.5	172.5	175	175	175
Larghezza Manubrio (mm)	360	380	400	420	420	440	440	440
Lunghezza Attacco man. (mm)	70	80	90	100	100	110	110	120
Larghezza Sella (mm)	155	155	155	143	143	143	143	143
Lunghezza Reggisella (mm)	380	380	380	380	380	450	450	450

SPECIFICHE TECNICHE	Specialized si riserva il diritto di modificare le caratteristiche senza preavviso.
Nastro Manubrio	Supacaz Super Sticky Kush
Ruota anteriore	DT Swiss G540 rim, 24mm internal width, tubeless ready, 24h, Specialized full sealed bearing thru axle hub, centerlock disc, DT Swiss Champion 14G stainless steel spokes, DT Swiss brass nipples
Ruota posteriore	DT Swiss G540 rim, 24mm internal width, tubeless ready, 24h, Specialized full sealed bearing thru axle hub, centerlock disc, DT Swiss Champion 14G stainless steel spokes, DT Swiss brass nipples
Sella	Body Geometry Power Sport, steel rails
Telaio	FACT 10R, Rider First Engineered™ (RFE), FreeFoil Shape Library tubes, threaded BB, 12x142mm thru-axle, flat-mount disc
Forcella	Future Shock 3.1 w/ Smooth Boot, FACT Carbon 12x100mm, thru-axle, flat-mount disc
Freno anteriore	Shimano 105 Hydraulic Disc
Freno posteriore	Shimano 105 Hydraulic Disc
Comandi cambio	Shimano 105 R7120, Hydraulic Disc
Deragliatore anteriore	Shimano 105 R7100, braze-on
Cambio posteriore	Shimano 105 R7100, 12-Speed
Pacco Pignoni	Shimano 105, 12-speed, 11-36T
Catena	Shimano 105, 12-Speed
Guarnitura	Shimano 105, 12-Speed
Ingranaggi	50/34T
Movimento Centrale	Shimano BSA
Pneumatico anteriore	S-Works Mondo 2BR, 700x32c
Pneumatico posteriore	S-Works Mondo 2BR, 700x32c
Camere d'aria	700x28/38mm, 48mm Presta valve
Attacco Manubrio	Future Stem Comp
Curva manubrio	Specialized Hover Comp, Alloy, 125mm Drop, 75mm Reach w/Di2 Hole
Reggisella	S-Works Pave Seat post
Collarino Sella	Hidden drop clamp
Peso	9.07kg (19 lb, 15.9 oz)
Misura pesata	56

ART. NR.	DESCRIZIONE	COLORE	MISURA
94425-6044	ROUBAIX SPORT 105	Gloss Champagne / Smoke	44
94425-6049			49
94425-6052			52
94425-6054			54
94425-6056			56
94425-6058			58
94425-6061			61
94425-6064			64
94424-6052/58	ROUBAIX SPORT 105	METALLIC OBSIDIAN/BIRCH	52/54 56/58
94424-6044/49/60/61			44/49/ 60/61/64
94424-6252/58	ROUBAIX SPORT 105	METALSAPPHIRE/BLUE ONYX	52/58
94424-6244/49/60/61/64			44/49/ 60/61/64

Disponibile Online e Pickup in store

# ROUBAIX SL8 SPORT APEX



Carbon / Smoke



Metallic Spruce / Forest Green

## SPECIFICHE TECNICHE

Specialized si riserva il diritto di modificare le caratteristiche senza preavviso.

Ruota anteriore	DT Swiss G540 rim, 24mm internal width, tubeless ready, 24h, Specialized full sealed bearing thru axle hub, centerlock disc, DT Swiss Champion 14G stainless steel spokes, DT Swiss brass nipples
Ruota posteriore	DT Swiss G540 rim, 24mm internal width, tubeless ready, 24h, Specialized full sealed bearing thru axle hub, centerlock disc, DT Swiss Champion 14G stainless steel spokes, DT Swiss brass nipples
Sella	Body Geometry Power Sport, steel rails
Telaio	FACT 10R, Rider First Engineered™ (RFE), FreeFoil Shape Library tubes, threaded BB, 12x142mm thru-axle, flat-mount disc
Forcella	Future Shock 3.1 w/ Smooth Boot, FACT Carbon 12x100mm, thru-axle, flat-mount disc
Freno anteriore	SRAM APEX AXS
Freno posteriore	SRAM APEX AXS
Comandi cambio	SRAM APEX eTAP AXS, hydraulic disc
Deragliatore anteriore	
Cambio posteriore	SRAM APEX XPLR eTAP AXS, 12-speed
Pacco Pignoni	SRAM APEX, PG 1231 XPLR, 11-44T
Catena	SRAM APEX, 12-Speed
Catena	SRAM CN APEX D1 12S 114LI
Guarnitura	SRAM APEX AXS, Wide 12-speed
Ingranaggi	42T
Movimento Centrale	SRAM DUB BSA
Pneumatico anteriore	S-Works Mondo 2BR, 700x32c
Pneumatico posteriore	S-Works Mondo 2BR, 700x32c
Camere d'aria	700x28/38mm, 48mm Presta valve
Attacco Manubrio	Future Stem Comp
Curva manubrio	Specialized Hover Comp, Alloy, 125mm Drop, 75mm Reach w/Di2 Hole
Reggisella	S-Works Pave Seat post
Collarino Sella	Hidden drop clamp
Pedali	PEDAL, TEST RIDE PEDALS PROVIDED BY SPECIALIZED
Accessori	SWAT
Peso	8,93kg (19 lb, 11 oz)
Misura pesata	56

ROUBAIX SL8 SPORT APEX	44	49	52	54	56	58	61	64
Stack (mm)	543	549	566	585	605	630	665	685
Reach (mm)	353	363	370	381	389	397	403	409
Lunghezza Tubo Sterzo (mm)	90	90	105	122	140	168	202	222
Angolo sterzo (degrees)	69.3	70.8	71.5	72.3	73	73	73.5	73.5
Altezza movimento centrale (mm)	269	269	269	270	270	271	271	271
BB Drop (mm)	80	80	80	78	78	78	78	78
Trail (mm)	76	66	62	61	57	57	54	54
Lunghezza forcella (mm)	375	375	375	375	375	375	375	375
Offset forcella/Rake (mm)	52	52	52	47	47	47	47	47
Avancorsa (mm)	589	587	593	598	604	620	631	634
Lunghezza Batticateni (mm)	418	418	418	420	420	423	423	423
Interasse (mm)	994	992	998	1005	1012	1031	1042	1054
Lunghezza Tubo Orizz. virtuale (mm)	503	523	534	550	569	584	600	618
Altezza Standover (mm)	686	719	747	766	787	809	847	865
Lunghezza Piantone (mm)	365	410	446	465	485	505	545	581
Angolo sella (degrees)	75	74	74	74	73.5	73.5	73.5	73
Lunghezza pedivella (mm)	165	165	170	172.5	172.5	175	175	175
Larghezza Manubrio (mm)	360	380	400	420	420	440	440	440
Lunghezza Attacco man. (mm)	70	80	90	100	100	110	110	120
Larghezza Sella (mm)	155	155	155	143	143	143	143	143
Lunghezza Reggisella (mm)	380	380	380	380	380	450	450	450

ART. NR.	DESCRIZIONE	COLORE	MISURA
94425-6144	ROUBAIX SPORT APEX	Carbon / Smoke	44
94425-6149			49
94425-6152			52
94425-6154			54
94425-6156			56
94425-6158			58
94425-6161			61
94425-6164			64
94425-6244	ROUBAIX SPORT APEX	Metallic Spruce / Forest Green	44
94425-6249			49
94425-6252			52
94425-6254			54
94425-6256			56
94425-6258			58
94425-6261			61
94425-6264			64

Disponibile Online e Pickup in store



SATIN DEEP LAKE METALLIC / BURNT GOLD METALLIC

ALLEZ SPRINT COMP	49	52	54	56	58	61
Stack (mm)	508	520	537	558	584	605
Reach (mm)	378	383	387	398	405	411
Lunghezza Tubo Sterzo (mm)	105	115	133	153	180	200
Angolo sterzo (degrees)	71.75	72.5	73	73.5	73.5	74
Altezza movimento centrale (mm)	266	266	268	268	268	268
BB Drop (mm)	74	74	72	72	72	72
Trail (mm)	63	58	58	55	55	52
Lunghezza forcella (mm)	366	366	366	366	366	366
Offset forcella/Rake (mm)	47	47	44	44	44	44
Avancorsa (mm)	575	578	580	592	607	614
Lunghezza Batticateni (mm)	410	410	410	410	410	410
Interasse (mm)	974	976	979	992	1006	1013
Lunghezza Tubo Orizz. virtuale (mm)	509	532	541	563	578	596
Altezza Standover (mm)	735	755	765	795	815	835
Lunghezza piantone (mm)	470	495	510	530	550	570
Angolo Sella (degrees)	75.5	74	74	73.5	73.5	73
Lunghezza pedivella (mm)	165	170	172.5	172.5	175	175
Larghezza Manubrio (mm)	380	400	420	420	440	440
Lunghezza Attacco man. (mm)	80	90	100	100	110	110
Larghezza Sella (mm)	155	155	143	143	143	143
Lunghezza Reggisella (mm)	300	300	300	300	380	380

## SPECIFICHE TECNICHE

Specialized si riserva il diritto di modificare le caratteristiche senza preavviso.

Telaio	Specialized E5 Premium Aluminum Disc frame with D'Aluisio Smartweld Sprint Technology, hydroformed aluminum tubing, tapered head tube, fully internally routed cables, threaded BB
Forcella	FACT Carbon, 12x100mm thru-axle, flat-mount disc
Curva manubrio	Specialized Shallow Drop, 6061, 70x125mm, 31.8mm clamp
Attacco Manubrio	Specialized Pro SL, alloy, 4-bolt
Nastro Manubrio	Supacaz Super Sticky Kush
Reggisella	2021 S-Works Tarmac Carbon seat post, FACT Carbon, 20mm offset
Freno anteriore	Shimano 105, Hydraulic disc
Collarino Sella	Allez Sprint seat collar
Freno posteriore	Shimano 105, Hydraulic disc
Comandi cambio	Shimano 105 R7020, hydraulic disc
Deragliatore anteriore	Shimano 105 R7000, braze-on
Cambio posteriore	Shimano 105 R7000 GS, medium cage, 11-speed
Pacco Pignoni	Shimano 105, 11-speed, 11-28t
Catena	Shimano SLX, M7100, 12-speed
Guarnitura	Shimano 105 R7000, HollowTech 2, 11-speed
Ingranaggi	52/36T
Movimento Centrale	Shimano Threaded BSA BB
Ruota anteriore	DT Swiss R470 rim, 20mm internal width, tubeless ready, 24h, Specialized full sealed bearing thru axle hub, centerlock disc, DT Swiss Champion 14G stainless steel spokes, DT Swiss brass nipples.
Ruota posteriore	DT Swiss R470 rim, 20mm internal width, tubeless ready, 24h, Specialized full sealed bearing thru axle hub, centerlock disc, alloy freehub body, DT Swiss Champion 14G stainless steel spokes, DT Swiss brass nipples.
Pneumatico anteriore	Turbo Pro, 60 TPI, folding bead, BlackBelt protection, 700x26mm
Sella	Body Geometry Power Sport, steel rails
Pneumatico posteriore	Turbo Pro, 60 TPI, folding bead, BlackBelt protection, 700x26mm
Camere d'aria	Presta, 40mm valve
Peso	8.68kg (19 lb, 2.2 oz)
Misura pesata	56

ART. NR.	DESCRIZIONE	COLORE	MISURA
90025-5149/61	ALLEZ SPRINT COMP	SATIN DEEP LAKE METALLIC / BURNT GOLD	49/61

## TELAIO ALLEZ SPRINT



GLOSS CHARCOAL TINT STRATA / FOG TINT



SATIN DUSTY PINK MULTICOLOR RADIAL FADE / ION METALLIC



SATIN SEA FOAM / GLOSS DUNE WHITE

### SPECIFICHE TECNICHE

**Specialized si riserva il diritto di modificare le caratteristiche senza preavviso.**

Telaio	Specialized E5 Premium Aluminum Disc frame with D'Aluisio Smartweld Sprint Technology, hydroformed aluminum tubing, tapered head tube, fully internally routed cables, threaded BB
Forcella	FACT Carbon, 12x100mm thru-axle, flat-mount disc
Reggisella	2021 S-Works Tarmac Carbon seat post, FACT Carbon, 20mm offset
Collarino Sella	Allez Sprint seat collar
Identificativo	221551
Peso	2.18 kg (4 lb, 12.9 oz)
Misura pesata	56

### TELAIO ALLEZ SPRINT

	49	52	54	56	58	61
Stack (mm)	508	520	537	558	584	605
Reach (mm)	378	383	387	398	405	411
Lunghezza Tubo Sterzo (mm)	105	115	133	153	180	200
Angolo sterzo (degrees)	71.75	72.5	73	73.5	73.5	74
Altezza movimento centrale (mm)	266	266	268	268	268	268
BB Drop (mm)	74	74	72	72	72	72
Trail (mm)	63	58	58	55	55	52
Lunghezza forcella (mm)	366	366	366	366	366	366
Offset Forcella/Rake (mm)	47	47	44	44	44	44
Avancorsa (mm)	575	578	580	592	607	614
Lunghezza Batticateni (mm)	410	410	410	410	410	410
Interasse (mm)	974	976	979	992	1006	1013
Lunghezza Tubo Orizz. virtuale (mm)	509	532	541	563	578	596
Altezza Standover (mm)	735	755	765	795	815	835
Lunghezza Piantone (mm)	470	495	510	530	550	570
Angolo sella (degrees)	75.5	74	74	73.5	73.5	73
Lunghezza Reggisella (mm)	300	300	300	300	380	380

ART. NR.	DESCRIZIONE	COLORE	MISURA
70025-7149	ALLEZ SPRINT FRM	GLOSS CHARCOAL TINT STRATA / FOG TINT	49
70025-7152			52
70025-7154			54
70025-7156			56
70025-7158			58
70025-7161			61
70025-7249	ALLEZ SPRINT FRM	SATIN DUSTY PINK MULTICOLOR	49
70025-7252			52
70025-7254			54
70025-7256			56
70025-7258			58
70025-7261			61
70025-7349	ALLEZ SPRINT FRM	SATIN SEA FOAM / GLOSS DUNE WHITE	49
70025-7352			52
70025-7354			54
70025-7356			56
70025-7358			58
70025-7361			61

Disponibile Online e Pickup in store

# ALLEZ E5 SPORT



Gloss Dove Grey/Cool Grey/Chameleon Lapis



Gloss Tarmac Black



Satin Tropical Teal

## SPECIFICHE TECNICHE

Specialized si riserva il diritto di modificare le caratteristiche senza preavviso.

Telaio	Specialized E5 Premium Aluminum, flat mount disc, rack and fender eyelets, fully manipulated tubing w/ SmoothWelds, internal cable routing, threaded BB, 12x142mm thru-axle
Forcella	Specialized FACT full carbon, flat mount disc, 1-1/8" to 1-3/8" taper, fender eyelets, 12x100mm thru-axle
Curva manubrio	Specialized Shallow Drop, 70x125mm, 31.8mm clamp
Attacco Manubrio	3D-forged alloy, 31.8mm, 7-degree rise
Nastro Manubrio	HANDLE BAR TAPE, SUPACAZ, BT-6800E, SUAVE, EMBOSSED EVA FOAM TAPE, 2000MM, BLK
Nastro Manubrio	Specialized S-Wrap
Sella	SADDLE, VELO VL-4460-PP-STL, BRIDGE THIN, STEEL RAIL, PP BASE, PU COVER, PU THIN FOAM, 155MM; SADDLE, VELO VL-4458-PP-STL, BRIDGE THIN, STEEL RAIL, PP BASE, PU COVER, PU THIN FOAM, 143MM
Freno anteriore	Shimano Tiagra, Hydraulic disc - 160mm rotor
Collarino Sella	Bolt-type, Rack Compatible 31.8mm
Freno posteriore	Shimano Tiagra, Hydraulic disc - 160mm rotor
Comandi cambio	Shimano Tiagra Disc 4720, 10-speed
Deragliatore anteriore	Shimano Tiagra, braze-on
Cambio posteriore	Shimano Tiagra, 10-speed
Pacco Pignoni	Sunrace, 10-speed, 11-32t
Guarnitura	Praxis Alba - 50/34t
Ingranaggi	50/34T
Movimento Centrale	Praxis 68mm BSA
Catena	KMC X10, 10-Speed
Ruota anteriore	Axis Sport Disc
Ruota posteriore	Axis Sport Disc
Pneumatico anteriore	Specialized Roadsport, 700X30c
Pneumatico posteriore	Specialized Roadsport, 700X30c
Camere d'aria	700x28-32, 48mm Presta Valve
Reggisella	Alloy, 2-bolt Clamp, 12mm offset, 27.2mm, anti-corrosion hardware
Sella	Body Geometry Bridge Saddle, steel rails
Peso	9.04 kg (19 lb, 14.9 oz)
Misura pesata	56

ALLEZ E5 SPORT	44	49	52	54	56	58	61
Stack (mm)	519	536	552	569	590	610	643
Reach (mm)	356	359	364	370	378	386	392
Lunghezza Tubo Sterzo (mm)	110	125	140	155	175	195	230
Angolo sterzo (degrees)	69.5	70.5	71	72	72.5	73	73
Altezza movimento centrale (mm)	273	273	273	274	274	275.5	275.5
BB Drop (mm)	77	77	77	76	76	74.5	74.5
Trail (mm)	81	74	71	64	61	58	58
Lunghezza forcella (mm)	378	378	378	378	378	378	378
Offset forcella/Rake (mm)	47	47	47	47	47	47	47
Avancorsa (mm)	576	577	583	585	594	603	619
Lunghezza Batticateni (mm)	420	420	425	425	425	425	425
Interasse (mm)	984	984	995	998	1008	1017	1033
Lunghezza Tubo Orizz. virtuale (mm)	493	500	530	541	556	569	586
Altezza Standover (mm)	715	739	761	781	801	821	852
Lunghezza piantone (mm)	430	460	490	510	530	550	580
Angolo Sella (degrees)	75.25	75.25	73.25	73.25	73.25	73.25	73.25
Lunghezza pedivella (mm)	165	165	170	172.5	172.5	175	175
Larghezza Manubrio (mm)	360	380	400	420	420	440	440
Lunghezza Attacco man. (mm)	70	80	90	100	100	110	110
Larghezza Sella (mm)	155	155	155	143	143	143	143
Lunghezza Reggisella (mm)	300	300	350	350	350	350	350

ART. NR.	DESCRIZIONE	COLORE	MISURA
90025-7344/61	ALLEZ E5 SPORT	Gloss Dove Grey	44/61
90025-7444/61	ALLEZ E5 SPORT	Gloss Tarmac Black	44/61
90025-7544/61	ALLEZ E5 SPORT	Satin Tropical Teal	44/61

Disponibili sono online & Pick Up in Store



Gloss Lagoon Blue / Cool Grey / Blaze



Satin Maroon / Silver Dust / Flo Red



Gloss Smoke / White / Silver Dust

<b>SPECIFICHE TECNICHE</b>	<b>Specialized si riserva il diritto di modificare le caratteristiche senza preavviso.</b>
Nastro Manubrio	Specialized S-Wrap
Ruota anteriore	Axis Sport Disc
Ruota posteriore	Axis Sport Disc
Telaio	Specialized E5 Premium Aluminum, flat mount disc, rack and fender eyelets, fully manipulated tubing w/ SmoothWelds, internal cable routing, threaded BB, 12x142mm thru-axle
Forcella	Specialized FACT full carbon, flat mount disc, 1-1/8" to 1-3/8" taper, fender eyelets, 12x100mm thru-axle
Freno anteriore	Tektro MD-550 Mechanical Disc - 160mm rotor
Freno posteriore	Tektro MD-550 Mechanical Disc - 160mm rotor
Comandi cambio	Shimano Claris 2000, 8-speed
Deragliatore anteriore	Shimano Claris, 8-speed, braze-on
Cambio posteriore	Shimano Claris, 8-speed
Pacco Pignoni	SunRace, 8-speed, 11-32t
Catena	KMC X8 w/ Missing Link™
Guarnitura	Shimano Claris R200 - 50/34t
Ingranaggi	50/34T
Movimento Centrale	Shimano 68mm threaded
Pneumatico anteriore	Specialized Roadsport, 700X30c
Pneumatico posteriore	Specialized Roadsport, 700X30c
Camere d'aria	700x28-32, 48mm Presta Valve
Attacco Manubrio	3D-forged alloy, 31.8mm, 7-degree rise
Curva manubrio	Specialized Shallow Drop, 70x125mm, 31.8mm clamp
Sella	Body Geometry Bridge Saddle, steel rails
Reggisella	Alloy, 2-bolt Clamp, 12mm offset, 27.2mm, anti-corrosion hardware
Collarino Sella	Bolt-type, Rack Compatible 31.8mm

<b>ALLEZ</b>	<b>44</b>	<b>49</b>	<b>52</b>	<b>54</b>	<b>56</b>	<b>58</b>	<b>61</b>
Stack (mm)	519	536	552	569	590	610	643
Reach (mm)	356	359	364	370	378	386	392
Lunghezza Tubo Sterzo (mm)	110	125	140	155	175	195	230
Angolo sterzo (degrees)	69.5	70.5	71	72	72.5	73	73
Altezza movimento centrale (mm)	273	273	273	274	274	275.5	275.5
BB Drop (mm)	77	77	77	76	76	74.5	74.5
Trail (mm)	81	74	71	64	61	58	58
Lunghezza forcella (mm)	378	378	378	378	378	378	378
Offset forcella/Rake (mm)	47	47	47	47	47	47	47
Avancorsa (mm)	576	577	583	585	594	603	619
Lunghezza Batticateni (mm)	420	420	425	425	425	425	425
Interasse (mm)	984	984	995	998	1008	1017	1033
Lunghezza Tubo Orizz. virtuale (mm)	493	500	530	541	556	569	586
Altezza Standover (mm)	715	739	761	781	801	821	852
Lunghezza Piantone (mm)	430	460	490	510	530	550	580
Angolo sella (degrees)	75.25	75.25	73.25	73.25	73.25	73.25	73.25
Lunghezza pedivella (mm)	165	165	170	170	175	175	175
Larghezza Manubrio (mm)	360	380	400	420	420	440	440
Lunghezza Attacco man. (mm)	70	80	90	100	100	110	110
Larghezza Sella (mm)	155	155	155	143	143	143	143
Lunghezza Reggisella (mm)	300	300	350	350	350	350	350

<b>ART. NR.</b>	<b>DESCRIZIONE</b>	<b>COLORE</b>	<b>MISURA</b>
90025-7044	ALLEZ E5	Gloss Lagoon Blue / Cool Grey / Blaze	44
90025-7049			49
90025-7052			52
90025-7054			54
90025-7056			56
90025-7058			58
90025-7061			61
90025-7144	ALLEZ E5	Gloss Smoke / White / Silver Dust	44
90025-7149			49
90025-7152			52
90025-7154			54
90025-7156			56
90025-7158			58
90025-7161			61
90025-7244 / 61	ALLEZ E5	Satin Maroon / Silver Dust / Flo Red	44/61

Disponibile Online e Pickup in store



Gloss Cypress Metallic / Viavi Gold to Silver Pearl

<b>SPECIFICHE TECNICHE</b>	<b>Specialized si riserva il diritto di modificare le caratteristiche senza preavviso.</b>
Forcella	S-Works FACT Carbon, 12x100mm thru-axle, flat-mount disc
Nastro Manubrio	Supacaz Super Sticky Kush
Ruota anteriore	Roval Terra CLX II, 25mm internal width, Tubeless ready, 32mm depth, 21h, Roval AFD1, Centerlock, DT Swiss Aerolite spokes
Ruota posteriore	Roval Terra CLX II, 25mm internal width, Tubeless Ready, 32mm depth, 24h, Roval AFD2, Centerlock, DT Swiss EXP internals, SRAM XDR, DT Swiss Aerolite spokes
Telaio	S-Works Crux FACT 12r Carbon, UDH dropout, Rider First Engineered™, Threaded BB, 12x142mm thru-axle, flat-mount disc
Freno anteriore	NEW SRAM Red XPLR, Hydraulic Disc
Freno posteriore	NEW SRAM Red XPLR, Hydraulic Disc
Comandi cambio	SRAM Red AXS
Cambio posteriore	NEW SRAM Red XPLR, 13sp
Pacco Pignoni	NEW SRAM Red XPLR, 13sp, 10-46t
Catena	NEW SRAM Red XPLR, 13sp
Guarnitura	SRAM Red AXS Power Meter
Ingranaggi	40T
Movimento Centrale	SRAM DUB BSA
Pneumatico anteriore	Pathfinder Pro 2Bliss Ready, Transparent Sidewall, 700x38c
Pneumatico posteriore	Pathfinder Pro 2Bliss Ready, Transparent Sidewall, 700x38c
Camere d'aria	700x28/38mm, 48mm Presta valve
Attacco Manubrio	S-Works SL, alloy, titanium bolts, 6-degree rise
Curva manubrio	Roval Terra, carbon, 103mm drop x 70mm reach x 12° flare
Sella	S-Works Power with Mirror
Reggisella	Roval Alpinist Carbon Seatpost
Collarino Sella	Specialized Alloy, 30.0mm, titanium bolt
Peso	7.28 kg (16 lb, 0.8 oz)
Misura pesata	56

<b>S-WORKS CRUX</b>	<b>49</b>	<b>52</b>	<b>54</b>	<b>56</b>	<b>58</b>	<b>61</b>
Stack (mm)	530	547	560	578	598	621
Reach (mm)	375	382	388	397	405	415
Lunghezza Tubo Sterzo (mm)	100	115	130	147	167	190
Angolo sterzo (degrees)	70.5	71.25	71.5	72	72.25	72.5
Altezza movimento centrale (mm)	284	284	286	286	286	286
BB Drop (mm)	74	74	72	72	72	72
Trail (mm)	74	69	67	64	62	60
Lunghezza forcella (mm)	401	401	401	401	401	401
Offset forcella/Rake (mm)	50	50	50	50	50	50
Avancorsa (mm)	594	600	608	618	630	644
Lunghezza Batticateni (mm)	425	425	425	425	425	425
Interasse (mm)	1008	1014	1023	1033	1045	1059
Lunghezza Tubo Orizz. virtuale (mm)	512	539	549	568	582	599
Altezza Standover (mm)	749	772	794	816	841	866
Lunghezza piantone (mm)	466	496	521	546	576	606
Angolo Sella (degrees)	75.5	74	74	73.5	73.5	73.5
Lunghezza pedivella (mm)	165	170	172.5	172.5	175	175
Larghezza Manubrio (mm)	380	400	420	420	440	440
Lunghezza Attacco man. (mm)	70	80	90	100	110	110
Larghezza Sella (mm)	155	155	143	143	143	143
Lunghezza Reggisella (mm)	300	300	300	360	360	360

<b>ART. NR.</b>	<b>DESCRIZIONE</b>	<b>COLORE</b>	<b>MISURA</b>
91425-0049/61	SW CRUX	Gloss Cypress Metallic / Viavi Gold to Silver Pearl	49/61

## TELAIO S-WORKS CRUX



Gloss Cypress Metallic / Viavi Gold to Silver Pearl



Gloss Sea Foam/Rebel Pink Dry Impasto/Ion Metallic



Satin Carbon/Multi-Color Blurred Impasto

SPECIFICHE TECNICHE	Specialized si riserva il diritto di modificare le caratteristiche senza preavviso.
Forcella	S-Works FACT Carbon, 12x100mm thru-axle, flat-mount disc
Telaio	S-Works Crux FACT 12r Carbon, Rider First Engineered™, Threaded BB, 12x142mm thru-axle, flat-mount disc
Reggisella	Roval Alpinist Carbon Seatpost
Collarino Sella	Specialized Alloy, 30.0mm, titanium bolt
Peso	1.43 kg (3 lb, 2.4 oz)
Misura pesata	56

TELAIO S-WORKS CRUX	49	52	54	56	58	61
Stack (mm)	530	547	560	578	598	621
Reach (mm)	375	382	388	397	405	415
Lunghezza Tubo Sterzo (mm)	100	115	130	147	167	190
Angolo sterzo (degrees)	70.5	71.25	71.5	72	72.25	72.5
Altezza movimento centrale (mm)	284	284	286	286	286	286
BB Drop (mm)	74	74	72	72	72	72
Trail (mm)	74	69	67	64	62	60
Lunghezza forcella (mm)	401	401	401	401	401	401
Offset forcella/Rake (mm)	50	50	50	50	50	50
Avancorsa (mm)	594	600	608	618	630	644
Lunghezza Batticateni (mm)	425	425	425	425	425	425
Interasse (mm)	1008	1014	1023	1033	1045	1059
Lunghezza Tubo Orizz. virtuale (mm)	512	539	549	568	582	599
Altezza Standover (mm)	749	772	794	816	841	866
Lunghezza piantone (mm)	466	496	521	546	576	606
Angolo Sella (degrees)	75.5	74	74	73.5	73.5	73.5
Lunghezza Reggisella (mm)	300	300	300	360	360	360

ART. NR.	DESCRIZIONE	COLORE	MISURA
71425-7549/61	CRUX SW FRMSET	Gloss Cypress Metallic / Viavi	49/61
71425-7649/61	CRUX SW FRMSET	Gloss Sea Foam/Rebel Pink Dry	49/61
71425-7749/61	CRUX SW FRMSET	Satin Carbon/Multi-Color Blurr	49/61

Disponibile Online e Pickup in store



Satin Carbon/Deep Lake Metallic/Smoke/White Sage Metallic

<b>SPECIFICHE TECNICHE</b>	<b>Specialized si riserva il diritto di modificare le caratteristiche senza preavviso.</b>
Forcella	S-Works FACT Carbon, 12x100mm thru-axle, flat-mount disc
Nastro Manubrio	Supacaz Super Sticky Kush
Ruota anteriore	Roval Terra CL, 25mm internal width, 32mm depth, 24h, Tubeless ready, DT for Roval 350 hub, Centerlock disc, DT Swiss Competition Race spokes
Ruota posteriore	Roval Terra CL, 25mm internal width, 32mm depth, 24h, Tubeless ready, DT for Roval 350 hub, Centerlock disc, DT Swiss Competition Race spokes
Telaio	Crux FACT 10r Carbon, Rider First Engineered™, Threaded BB, 12x142mm thru-axle, flat-mount disc
Freno anteriore	SRAM Force eTap AXS
Freno posteriore	SRAM Force eTap AXS
Comandi cambio	SRAM Force eTap AXS
Cambio posteriore	SRAM Force XPLR eTap AXS
Pacco Pignoni	SRAM XPLR, XG-1251, 12-speed, 10-44t
Catena	SRAM Force 12-speed
Guarnitura	SRAM Force 1x
Ingranaggi	40t
Movimento Centrale	SRAM DUB BSA 68
Pneumatico anteriore	Pathfinder Pro 2BR, Tan Sidewall, 700x38
Pneumatico posteriore	Pathfinder Pro 2BR, Tan Sidewall, 700x38
Camere d'aria	700x28/38mm, 48mm Presta valve
Attacco Manubrio	Specialized Pro SL, alloy, 4-bolt, 6-degree rise
Curva manubrio	Roval Terra, carbon, 103mm drop x 70mm reach x 12° flare
Sella	Power Pro with Mirror
Reggisella	Roval Terra Carbon Seat Post, 20mm Offset
Collarino Sella	Specialized Alloy, 30mm
Peso	7.63kg (16 lb, 13.1 oz)
Misura pesata	56

<b>CRUX PRO</b>	<b>49</b>	<b>52</b>	<b>54</b>	<b>56</b>	<b>58</b>	<b>61</b>
Stack (mm)	530	547	560	578	598	621
Reach (mm)	375	382	388	397	405	415
Lunghezza Tubo Sterzo (mm)	100	115	130	147	167	190
Angolo sterzo (degrees)	70.5	71.25	71.5	72	72.25	72.5
Altezza movimento centrale (mm)	284	284	286	286	286	286
BB Drop (mm)	74	74	72	72	72	72
Trail (mm)	74	69	67	64	62	60
Lunghezza forcella (mm)	401	401	401	401	401	401
Offset forcella/Rake (mm)	50	50	50	50	50	50
Avancorsa (mm)	594	600	608	618	630	644
Lunghezza Batticateni (mm)	425	425	425	425	425	425
Interasse (mm)	1008	1014	1023	1033	1045	1059
Lunghezza Tubo Orizz. virtuale (mm)	512	539	549	568	582	599
Altezza Standover (mm)	749	772	794	816	841	866
Lunghezza piantone (mm)	466	496	521	546	576	606
Angolo Sella (degrees)	75.5	74	74	73.5	73.5	73.5
Lunghezza pedivella (mm)	165	170	172.5	172.5	175	175
Larghezza Manubrio (mm)	380	400	420	420	440	440
Lunghezza Attacco man. (mm)	70	80	90	100	110	110
Larghezza Sella (mm)	155	155	143	143	143	143
Lunghezza Reggisella (mm)	330	330	330	380	380	380

<b>ART. NR.</b>	<b>DESCRIZIONE</b>	<b>COLORE</b>	<b>MISURA</b>
91425-1049/61	CRUX PRO	Satin Carbon/Deep Lake Metallic/ Smoke/White Sage Metallic	49/61



Gloss Dune White/Smoke Liquid Metal



SATIN CYPRESS METALLIC/  
DOPPIO/DUSKY PINK/CHAMPAGNE

SPECIFICHE TECNICHE	Specialized si riserva il diritto di modificare le caratteristiche senza preavviso.
Forcella	S-Works FACT Carbon, 12x100mm thru-axle, flat-mount disc
Nastro Manubrio	Supacaz Super Sticky Kush
Ruota anteriore	Roval Terra C, 25mm inner width carbon rim, 32mm depth, NEW DT 370 hub, 24h, DT Swiss Comp Race spokes
Ruota posteriore	Roval Terra C, 25mm inner width carbon rim, 32mm depth, NEW DT 370 hub, 24h, DT Swiss Comp Race spokes
Telaio	Crux FACT 10r Carbon, Rider First Engineered™, Threaded BB, 12x142mm thru-axle, flat-mount disc
Freno anteriore	SRAM Rival eTap AXS, hydraulic disc
Freno posteriore	SRAM Rival eTap AXS, hydraulic disc
Comandi cambio	SRAM Rival eTap AXS
Cambio posteriore	SRAM Rival XPLR eTap AXS
Pacco Pignoni	SRAM XPLR, XG-1251, 12-speed, 10-44t
Catena	SRAM Rival 12-speed
Guarnitura	SRAM Rival 1x
Ingranaggi	40T
Movimento Centrale	SRAM DUB BSA
Pneumatico anteriore	Pathfinder Pro 2BR, Tan Sidewall, 700x38
Pneumatico posteriore	Pathfinder Pro 2BR, Tan Sidewall, 700x38
Camere d'aria	700x28/38mm, 48mm Presta valve
Attacco Manubrio	Specialized Pro SL, alloy, 4-bolt, 6-degree rise
Curva manubrio	Specialized Adventure Gear, 118.9mm drop x 70mm reach x 12° flare
Sella	Body Geometry Power Expert, titanium rails
Reggisella	Roval Terra Carbon Seat Post, 20mm Offset
Collarino Sella	Specialized Alloy, 30mm
Pedali	PEDAL, TEST RIDE PEDALS PROVIDED BY SPECIALIZED
Peso	8.07kg (17 lb, 12.7 oz)
Misura pesata	56

CRUX EXPERT	49	52	54	56	58	61
Stack (mm)	530	547	560	578	598	621
Reach (mm)	375	382	388	397	405	415
Lunghezza Tubo Sterzo (mm)	100	115	130	147	167	190
Angolo sterzo (degrees)	70.5	71.25	71.5	72	72.25	72.5
Altezza movimento centrale (mm)	284	284	286	286	286	286
BB Drop (mm)	74	74	72	72	72	72
Trail (mm)	74	69	67	64	62	60
Lunghezza forcella (mm)	401	401	401	401	401	401
Offset forcella/Rake (mm)	50	50	50	50	50	50
Avancorsa (mm)	594	600	608	618	630	644
Lunghezza Batticateni (mm)	425	425	425	425	425	425
Interasse (mm)	1008	1014	1023	1033	1045	1059
Lunghezza Tubo Orizz. virtuale (mm)	512	539	549	568	582	599
Altezza Standover (mm)	749	772	794	816	841	866
Lunghezza piantone (mm)	466	496	521	546	576	606
Angolo Sella (degrees)	75.5	74	74	73.5	73.5	73.5
Lunghezza pedivella (mm)	165	170	172.5	172.5	175	175
Larghezza Manubrio (mm)	380	400	420	420	440	440
Lunghezza Attacco man. (mm)	70	80	90	100	110	110
Larghezza Sella (mm)	155	155	143	143	143	143
Lunghezza Reggisella (mm)	330	330	330	380	380	380

ART. NR.	DESCRIZIONE	COLORE	MISURA
91425-3049/61	CRUX EXPERT	Gloss Dune White/Smoke Liquid Metal	49/61
91425-3149/61	CRUX EXPERT	SATIN CYPRESS METALLIC/DOPPIO	49/61



Gloss Carbon/Purple Haze/Rebel Pink/Birch



Satin Carbon/Smoke

**SPECIFICHE TECNICHE** **Specialized si riserva il diritto di modificare le caratteristiche senza preavviso.**

Forcella	S-Works FACT Carbon, 12x100mm thru-axle, flat-mount disc
Nastro Manubrio	Supacaz Super Sticky Kush
Ruota anteriore	DT Swiss G540 rim, 24mm internal width, tubeless ready, 24h, Specialized full sealed bearing thru axle hub, centerlock disc, DT Swiss Champion 14G stainless steel spokes, DT Swiss brass nipples
Ruota posteriore	DT Swiss G540 rim, 24mm internal width, tubeless ready, 24h, Specialized full sealed bearing thru axle hub, centerlock disc, DT Swiss Champion 14G stainless steel spokes, DT Swiss brass nipples
Telaio	Crux FACT 10r Carbon, Rider First Engineered™, Threaded BB, 12x142mm thru-axle, flat-mount disc
Freno anteriore	Shimano GRX RX820
Freno posteriore	Shimano GRX RX820
Comandi cambio	Shimano GRX RX820, 1x12-speed
Cambio posteriore	Shimano GRX RX822-GS, 12-speed
Pacco Pignoni	Shimano XT, 12-speed, 10-45t
Catena	Shimano XT M8100, 12-speed w/ quick link
Guarnitura	Shimano GRX RX820
Ingranaggi	40T
Movimento Centrale	Shimano Threaded BSA BB
Pneumatico anteriore	Pathfinder Pro 2BR, Tan Sidewall, 700x38
Pneumatico posteriore	Pathfinder Pro 2BR, Tan Sidewall, 700x38
Camere d'aria	700x28/38mm, 48mm Presta valve
Attacco Manubrio	3D-forged alloy, 31.8mm, 7-degree rise
Curva manubrio	Specialized Adventure Gear, 118.9mm drop x 70mm reach x 12° flare
Sella	Body Geometry Power Sport, steel rails
Reggisella	Royal Terra Carbon Seat Post, 20mm Offset
Collarino Sella	Specialized Alloy, 30mm
Peso	8.55kg (18 lb, 13.6 oz)
Misura pesata	56

CRUX COMP	49	52	54	56	58	61
Stack (mm)	530	547	560	578	598	621
Reach (mm)	375	382	388	397	405	415
Lunghezza Tubo Sterzo (mm)	100	115	130	147	167	190
Angolo sterzo (degrees)	70.5	71.25	71.5	72	72.25	72.5
Altezza movimento centrale (mm)	284	284	286	286	286	286
BB Drop (mm)	74	74	72	72	72	72
Trail (mm)	74	69	67	64	62	60
Lunghezza forcella (mm)	401	401	401	401	401	401
Offset forcella/Rake (mm)	50	50	50	50	50	50
Avancorsa (mm)	594	600	608	618	630	644
Lunghezza Batticateni (mm)	425	425	425	425	425	425
Interasse (mm)	1008	1014	1023	1033	1045	1059
Lunghezza Tubo Orizz. virtuale (mm)	512	539	549	568	582	599
Altezza Standover (mm)	749	772	794	816	841	866
Lunghezza piantone (mm)	466	496	521	546	576	606
Angolo Sella (degrees)	75.5	74	74	73.5	73.5	73.5
Lunghezza pedivella (mm)	170	170	172.5	172.5	175	175
Larghezza Manubrio (mm)	380	400	420	420	440	440
Lunghezza Attacco man. (mm)	70	80	90	100	110	110
Larghezza Sella (mm)	155	155	143	143	143	143
Lunghezza Reggisella (mm)	330	330	330	380	380	380

ART. NR.	DESCRIZIONE	COLORE	MISURA
91425-5449/61	CRUX COMP	Gloss Carbon/Purple Haze/Rebel Pink/Birch	49/61
91425-5549/61	CRUX COMP	Satin Carbon/Smoke	49/61

## TELAIO CRUX 10R



BIRCH/ION METALLIC/SILVER DUST/TAUPE



BURNT GOLD METALLIC/  
BLACK PEARL DRY IMPASTO

### SPECIFICHE TECNICHE

Specialized si riserva il diritto di modificare le  
caratteristiche senza preavviso.

Forcella	S-Works FACT Carbon, 12x100mm thru-axle, flat-mount disc
Telaio	Crux FACT 10r Carbon, Rider First Engineered™, Threaded BB, 12x142mm thru-axle, flat-mount disc
Collarino Sella	Specialized Alloy, 30mm
Peso	1.37 kg (3 lb, 0.3 oz)
Misura pesata	56

TELAIO CRUX 10R	49	52	54	56	58	61
Stack (mm)	530	547	560	578	598	621
Reach (mm)	375	382	388	397	405	415
Lunghezza Tubo Sterzo (mm)	100	115	130	147	167	190
Angolo sterzo (degrees)	70.5	71.25	71.5	72	72.25	72.5
Altezza movimento centrale (mm)	284	284	286	286	286	286
BB Drop (mm)	74	74	72	72	72	72
Trail (mm)	74	69	67	64	62	60
Lunghezza forcella (mm)	401	401	401	401	401	401
Offset forcella/Rake (mm)	50	50	50	50	50	50
Avancorsa (mm)	594	600	608	618	630	644
Lunghezza Batticateni (mm)	425	425	425	425	425	425
Interasse (mm)	1008	1014	1023	1033	1045	1059
Lunghezza Tubo Orizz. virtuale (mm)	512	539	549	568	582	599
Altezza Standover (mm)	749	772	794	816	841	866
Lunghezza piantone (mm)	466	496	521	546	576	606
Angolo Sella (degrees)	75.5	74	74	73.5	73.5	73.5

ART. NR.	DESCRIZIONE	COLORE	MISURA
71425-7349/61	CRUX 10R FRMSET	BIRCH/ION METALLIC/SILVER DUST	49/61
71425-7449/61	CRUX 10R FRMSET	BURNT GOLD METALLIC/BLACK PEAR	49/61



GLOSS BIRCH/CLAY



SATIN SMOKE/OAK GREEN

CRUX DSW	49	52	54	56	58	61
Stack (mm)	530	547	560	578	598	621
Reach (mm)	375	382	388	397	405	415
Lunghezza Tubo Sterzo (mm)	100	115	130	147	167	190
Angolo sterzo (degrees)	70.5	71.25	71.5	72	72.25	72.5
Altezza movimento centrale (mm)	284	284	286	286	286	286
BB Drop (mm)	74	74	72	72	72	72
Trail (mm)	74	69	67	64	62	60
Lunghezza forcella (mm)	401	401	401	401	401	401
Offset forcella/Rake (mm)	50	50	50	50	50	50
Avancorsa (mm)	594	600	608	618	630	644
Lunghezza Batticateni (mm)	425	425	425	425	425	425
Interasse (mm)	1008	1014	1023	1033	1045	1059
Lunghezza Tubo Orizz. virtuale (mm)	512	539	549	568	582	599
Altezza standover (mm)	749	772	794	816	841	866
Lunghezza piantone (mm)	466	496	521	546	576	606
Angolo Sella (degrees)	75.5	74	74	73.5	73.5	73.5
Lunghezza pedivella - translate here (mm)	170	170	172.5	172.5	175	175
Larghezza Manubrio (mm)	380	400	420	420	440	440
Lunghezza Attacco man. (mm)	70	80	90	100	110	110
Larghezza Sella (mm)	155	155	143	143	143	143
Lunghezza Reggisella (mm)	350	350	350	400	400	400

## SPECIFICHE TECNICHE

Specialized si riserva il diritto di modificare le caratteristiche senza preavviso.

Telaio	Specialized E5 Premium Aluminum Disc frame with D'Aluisio Smartweld Technology, hydroformed aluminum tubing, tapered head tube, threaded BB
Forcella	FACT Carbon, 12x100mm thru-axle, flat-mount disc
Curva manubrio	Specialized Adventure Gear, 118.9mm drop x 70mm reach x 12° flare
Attacco Manubrio	Specialized, 3D-forged alloy, 4-bolt, 7-degree rise
Nastro Manubrio	Supacaz Super Sticky Kush
Freno anteriore	SRAM APEX, Hydraulic Disc
Freno posteriore	SRAM APEX, Hydraulic Disc
Comandi cambio	SRAM APEX, 12sp
Cambio posteriore	SRAM APEX XPLR, Mechanical
Pacco Pignoni	SRAM PG 1231, XPLR, 11-44
Guarnitura	SRAM APEX XPLR, 40t
Ingranaggi	40t
Movimento Centrale	SRAM DUB BSA 68 Wide
Catena	SRAM APEX 12S
Catena	SRAM CN APEX D1 12S 114LI
Ruota anteriore	DT G540, Centerlock Disc, Tubeless Ready, 25mm internal width
Ruota posteriore	DT G540, Centerlock Disc, Tubeless Ready, 25mm internal width
Pneumatico anteriore	Pathfinder Pro 2BR, 700x38
Sella	Body Geometry Power Sport, steel rails
Pneumatico posteriore	Pathfinder Pro 2BR, 700x38
Reggisella	Alloy, 2-bolt Clamp, 12mm offset, 27.2mm, anti-corrosion hardware
Camere d'aria	48mm Presta Valve, 700X28-38
Pedali	PEDAL, TEST RIDE PEDALS PROVIDED BY SPECIALIZED
Collarino Sella	Specialized Alloy, 30.8mm
Peso	9.37kg (20 lb, 10.5 oz)
Misura pesata	56

ART. NR.	DESCRIZIONE	COLORE	MISURA
91425-5249	CRUX DSW COMP	GLOSS BIRCH/CLAY	49
91425-5252			52
91425-5254			54
91425-5256			56
91425-5258			58
91425-5261			61
91425-5349	CRUX DSW COMP	SATIN SMOKE/OAK GREEN	49
91425-5352			52
91425-5354			54
91425-5356			56
91425-5358			58
91425-5361			61

# DIVERGE EXPERT CARBON



CAST BLUE METALLIC/SILVER DUST



SATIN BURNT GOLD METALLIC/BLACK LIQUID METAL

DIVERGE EXPERT CARBON	49	52	54	56	58	61	64
Stack (mm)	571	577	592	610	634	659	684
Reach (mm)	365	374	383	392	401	410	419
Lunghezza Tubo Sterzo (mm)	99	104	116	133	159	185	209
Angolo sterzo (degrees)	70	70.5	71.25	71.75	71.75	71.75	72.25
Altezza movimento centrale (mm)	270	270	270	270	270	270	270
BB Drop (mm)	80	80	80	80	80	80	80
Trail (mm)	69	66	61	57	57	57	54
Lunghezza forcella (mm)	389	389	389	389	389	389	389
Offset Forcella/Rake (mm)	55	55	55	55	55	55	55
Avancorsa (mm)	607	614	620	630	647	664	675
Lunghezza Batticateni (mm)	425	425	425	425	425	425	425
Interasse (mm)	1019	1026	1032	1042	1059	1076	1088
Lunghezza Tubo Orizz. virtuale (mm)	529	542	558	573	589	605	628
Altezza Standover (mm)	700	725	754	779	805	832	859
Lunghezza Piantone (mm)	390	430	470	500	530	560	590
Angolo sella (degrees)	74	73.75	73.5	73.5	73.5	73.5	73
Lunghezza pedivella (mm)	165	170	172.5	172.5	175	175	175
Larghezza Manubrio (mm)	380	400	420	420	440	440	440
Lunghezza Attacco man. (mm)	60	70	80	90	100	100	110
Larghezza Sella (mm)	155	155	143	143	143	143	143
Lunghezza Reggisella (mm)	330	330	380	380	380	380	380

SPECIFICHE TECNICHE	Specialized si riserva il diritto di modificare le caratteristiche senza preavviso.
Nastro Manubrio	Supacaz Super Sticky Kush
Telaio	Specialized Diverge FACT 9r carbon, SWAT™ Door integration, Future Shock suspension, threaded BB, internal routing, 12x142mm thru-axle, flat-mount disc
Collarino Sella	Specialized Alloy, 30.8mm
Forcella	Future Shock 2.0 w/ Damper, Smooth Boot, FACT carbon, 12x100 mm thru-axle, flat-mount
Freno anteriore	SRAM Rival eTAP AXS, hydraulic disc
Freno posteriore	SRAM Rival eTAP AXS, hydraulic disc
Comandi cambio	SRAM Rival ETAP AXS
Cambio posteriore	SRAM GX Eagle AXS
Pacco Pignoni	SRAM NX Eagle, 12-speed, 11-50t
Catena	SRAM GX Eagle, 12-speed
Guarnitura	SRAM Rival 1 Wide
Ingranaggi	40T
Movimento Centrale	SRAM DUB BSA 68
Pneumatico anteriore	Pathfinder Pro 2BR, Tan sidewall, 700x42
Ruota anteriore	Roval Terra C, 25mm inner width carbon rim, 32mm depth, NEW DT 370 hub, 24h, DT Swiss Comp Race spokes
Pneumatico posteriore	Pathfinder Pro 2BR, Tan sidewall, 700x42
Ruota posteriore	Roval Terra C, 25mm inner width carbon rim, 32mm depth, NEW DT 370 Star Ratchet hub, 24h, DT Swiss Comp Race spokes
Camere d'aria	Presta valve, 48mm
Attacco Manubrio	Future Stem, Pro
Curva manubrio	Specialized Adventure Gear Hover, 103mm drop x 70mm reach x 12° flare
Sella	Body Geometry Power Expert
Reggisella	Roval Terra Carbon Seat Post, 20mm Offset
Accessori	Integrated SWAT door, internal storage system
Identificativo	221370
Peso	9.52kg (20 lb, 15.8 oz)
Misura pesata	56

ART. NR.	DESCRIZIONE	COLORE	MISURA
95425-3049	DIVERGE EXPERT CARBON	CAST BLUE METALLIC	49
95425-3052			52
95425-3054			54
95425-3056			56
95425-3058			58
95425-3061			61
95425-3064			64
95425-3149	DIVERGE EXPERT CARBON	SATIN BURNT GOLD METAL	49
95425-3152			52
95425-3154			54
95425-3156			56
95425-3158			58
95425-3161			61
95425-3164			64

Disponibile Online e Pickup in store

## DIVERGE COMP CARBON



GLOSS BIRCH/WHITE



SATIN OAK GREEN/SMOKE

DIVERGE COMP CARBON	49	52	54	56	58	61
Stack (mm)	571	577	592	610	634	659
Reach (mm)	365	374	383	392	401	410
Lunghezza Tubo Sterzo (mm)	99	104	116	133	159	185
Angolo sterzo (degrees)	70	70.5	71.25	71.75	71.75	71.75
Altezza movimento centrale (mm)	270	270	270	270	270	270
BB Drop (mm)	80	80	80	80	80	80
Trail (mm)	69	66	61	57	57	57
Lunghezza forcella (mm)	389	389	389	389	389	389
Offset forcella/Rake (mm)	55	55	55	55	55	55
Avancorsa (mm)	607	614	620	630	647	664
Lunghezza Batticateni (mm)	425	425	425	425	425	425
Interasse (mm)	1019	1026	1032	1042	1059	1076
Lunghezza Tubo Orizz. virtuale (mm)	529	542	558	573	589	605
Altezza Standover (mm)	700	725	754	779	805	832
Lunghezza piantone (mm)	390	430	470	500	530	560
Angolo Sella (degrees)	74	73.75	73.5	73.5	73.5	73.5
Lunghezza pedivella (mm)	165	170	172.5	172.5	175	175
Larghezza Manubrio (mm)	380	400	420	420	440	440
Lunghezza Attacco man. (mm)	60	70	80	90	100	100
Larghezza Sella (mm)	155	155	143	143	143	143
Lunghezza Reggisella (mm)	330	330	380	380	380	380

### SPECIFICHE TECNICHE

Specialized si riserva il diritto di modificare le caratteristiche senza preavviso.

Telaio	Specialized Diverge FACT 9r carbon, SWAT™ Door integration, Future Shock suspension, threaded BB, internal routing, 12x142mm thru-axle, flat-mount disc
Forcella	Future Shock 2.0 w/ Smooth Boot, 12x100mm thru-axle, flat-mount disc
Curva manubrio	Specialized Adventure Gear Hover, 103mm drop x 70mm reach x 12° flare
Attacco Manubrio	Future Stem, Comp
Nastro Manubrio	Supacaz Super Sticky Kush
Sella	Body Geometry Power Sport, steel rails
Freno anteriore	SRAM Apex eTAP AXS, hydraulic disc
Freno posteriore	SRAM Apex eTAP AXS, hydraulic disc
Cambio posteriore	SRAM X1 Eagle AXS
Comandi cambio	SRAM Apex eTap AXS
Pacco Pignoni	SRAM PG1210, 12-Speed, 11-50t
Catena	SRAM, NX Eagle, 12-speed
Guarnitura	SRAM Apex DUB Wide
Ingranaggi	40T
Movimento Centrale	SRAM DUB BSA
Ruota anteriore	DT Swiss G540 rim, 24mm internal width, tubeless ready, 24h, Specialized full sealed bearing thru axle hub, centerlock disc, DT Swiss Champion 14G stainless steel spokes, DT Swiss brass nipples
Ruota posteriore	DT Swiss G540 rim, 24mm internal width, tubeless ready, 24h, Specialized full sealed bearing thru axle hub, centerlock disc, DT Swiss Champion 14G stainless steel spokes, DT Swiss brass nipples
Pneumatico anteriore	Pathfinder Pro 2BR, Tan sidewall, 700x42
Pneumatico posteriore	Pathfinder Pro 2BR, Tan sidewall, 700x42
Camere d'aria	700x28/38mm, 48mm Presta valve
Reggisella	Roval Terra Carbon Seat Post, 20mm Offset
Collarino Sella	Specialized Alloy, 30.8mm
Accessori	Integrated SWAT door, internal storage system
Peso	9.99kg/22lbs, .4oz
Misura pesata	56cm

ART. NR.	DESCRIZIONE	COLORE	MISURA
95425-5049/61	DIVERGE COMP CARBON	GLOSS BIRCH/WHITE	49/61
95425-5449/61	DIVERGE COMP CARBON	SATIN OAK GREEN/SMOKE	49/61

# DIVERGE SPORT CARBON



SATIN CARBON/BLUE ONYX



SATIN DOPPIO/GUNMETAL



SATIN METALLIC SPRUCE/SPRUCE

DIVERGE SPORT CARBON	44	49	52	54	56	58	61	64
Stack (mm)	568	571	577	592	610	634	659	684
Reach (mm)	357	365	374	383	392	401	410	419
Lunghezza Tubo Sterzo (mm)	99	99	104	116	133	159	185	209
Angolo sterzo (degrees)	69.5	70	70.5	71.25	71.75	71.75	71.75	72.25
Altezza movimento centrale (mm)	270	270	270	270	270	270	270	270
BB Drop (mm)	80	80	80	80	80	80	80	80
Trail (mm)	72	69	66	61	57	57	57	54
Lunghezza forcella (mm)	390	390	390	390	390	390	390	390
Offset Forcella/Rake (mm)	55	55	55	55	55	55	55	55
Avancorsa (mm)	604	607	614	620	630	647	664	675
Lunghezza Batticateni (mm)	425	425	425	425	425	425	425	425
Interasse (mm)	1016	1019	1026	1032	1042	1059	1076	1088
Lunghezza Tubo Orizz. virtuale (mm)	515	529	542	558	573	589	605	628
Altezza Standover (mm)	683	700	725	754	779	805	832	859
Lunghezza Piantone (mm)	363	390	430	470	500	530	560	590
Angolo sella (degrees)	74.5	74	73.75	73.5	73.5	73.5	73.5	73
Lunghezza pedivella (mm)	165	165	170	172.5	172.5	175	175	175
Larghezza Manubrio (mm)	380	380	400	420	420	440	440	440
Lunghezza Attacco man. (mm)	60	60	70	80	90	100	100	110
Larghezza Sella (mm)	155	155	155	143	143	143	143	143
Lunghezza Reggisella (mm)	350	350	350	400	400	400	400	400

ART. NR.	DESCRIZIONE	COLORE	MISURA
95425-6044	DIVERGE SPORT CARBON	SATIN CARBON/BLUE ONYX	44
95425-6049			49
95425-6052			52
95425-6054			54
95425-6056			56
95425-6058			58
95425-6061			61
95425-6064			64
95425-6144	DIVERGE SPORT CARBON	SATIN DOPPIO/GUNMETAL	44
95425-6149			49
95425-6152			52
95425-6154			54
95425-6156			56
95425-6158			58
95425-6161			61
95425-6164			64
95425-6244	DIVERGE SPORT CARBON	SATIN METALLIC SPRUCE	44
95425-6249			49
95425-6252			52
95425-6254			54
95425-6256			56
95425-6258			58
95425-6261			61
95425-6264			64

Disponibile Online e Pickup in store

SPECIFICHE TECNICHE	Specialized si riserva il diritto di modificare le caratteristiche senza preavviso.
Forcella	Future Shock 1.5 w/Smooth Boot, FACT carbon, 12x100 mm thru-axle, flat-mount
Nastro Manubrio	Supacaz Super Sticky Kush
Ruota anteriore	DT Swiss G540 rim, 24mm internal width, tubeless ready, 24h, Specialized full sealed bearing thru axle hub, centerlock disc, DT Swiss Champion 14G stainless steel spokes, DT Swiss brass nipples
Ruota posteriore	DT Swiss G540 rim, 24mm internal width, tubeless ready, 24h, Specialized full sealed bearing thru axle hub, centerlock disc, DT Swiss Champion 14G stainless steel spokes, DT Swiss brass nipples
Sella	Body Geometry Power Sport, steel rails
Telaio	Specialized Diverge FACT 8r carbon, Future Shock suspension, threaded BB, internal routing, 12x142mm thru-axle, flat-mount disc
Collarino Sella	Specialized Alloy, 30.8mm
Freno anteriore	Shimano GRX RX400
Freno posteriore	Shimano GRX RX400
Comandi cambio	Shimano GRX RX610, 2x12-speed
Deragliatore anteriore	Shimano GRX RX820
Cambio posteriore	Shimano GRX RX820, 12-speed
Pacco Pignoni	Shimano 105 12-speed 11-36
Catena	Shimano SLX, M7100, 12-speed
Guarnitura	Shimano GRX RX610
Ingranaggi	46/30T
Movimento Centrale	Shimano Threaded BSA BB
Pneumatico anteriore	Pathfinder Pro 2BR, Tan sidewall, 700x42
Pneumatico posteriore	Pathfinder Pro 2BR, Tan sidewall, 700x42
Camere d'aria	700x28/38mm, 48mm Presta valve
Attacco Manubrio	Future Stem, Comp
Curva manubrio	Specialized Adventure Gear Hover, 103mm drop x 70mm reach x 12° flare
Reggisella	Carbon, single-bolt, 27.2mm
Identificativo	223496
Peso	10.10kg (22 lb, 4.3 oz)
Misura pesata	56



GLOSS METALLIC OBSIDIAN/METALLIC PINE GREEN



GLOSS TAUPE/SLATE



SATIN DEEP ORANGE/DEEP LAKE

## SPECIFICHE TECNICHE

Specialized si riserva il diritto di modificare le caratteristiche senza preavviso.

Forcella	Future Shock 1.5 w/Smooth Boot, FACT carbon, 12x100 mm thru-axle, flat-mount
Nastro Manubrio	Supacaz Suave
Ruota anteriore	AXIS Elite Disc
Ruota posteriore	AXIS Elite Disc
Sella	Body Geometry Power Sport, steel rails
Telaio	Specialized Diverge E5 Premium Aluminum, Future Shock suspension, threaded BB, internal routing, 12x142mm thru-axle, flat-mount disc
Collarino Sella	Alloy, 30.8mm
Freno anteriore	SRAM Apex
Freno posteriore	SRAM Apex
Comandi cambio	SRAM Apex 1x12-speed
Cambio posteriore	SRAM Apex Eagle 12-speed
Pacco Pignoni	SRAM PG-1210 Eagle, 11-50t
Catena	SRAM NX Eagle, 12-speed
Guarnitura	SRAM Apex DUB Wide
Ingranaggi	40T
Movimento Centrale	SRAM DUB BSA
Pneumatico anteriore	Pathfinder Pro 2BR, Tan sidewall, 700x42
Pneumatico posteriore	Pathfinder Pro 2BR, Tan sidewall, 700x42
Camere d'aria	Presta valve, 48mm
Attacco Manubrio	Future Stem, Comp
Curva manubrio	Specialized Adventure Gear Hover, 103mm drop x 70mm reach x 12° flare
Reggisella	Alloy, 2-bolt Clamp, 12mm offset, 27.2mm, anti-corrosion hardware
Identificativo	223497
Peso	10.30kg (22 lb, 11.3 oz)
Misura pesata	56

DIVERGE E5 COMP	49	52	54	56	58	61	64
Stack (mm)	571	577	592	610	634	659	684
Reach (mm)	365	374	383	392	401	410	419
Lunghezza Tubo Sterzo (mm)	99	104	116	133	159	185	209
Angolo sterzo (degrees)	70	70.5	71.25	71.75	71.75	71.75	72.25
Altezza movimento centrale (mm)	270	270	270	270	270	270	270
BB Drop (mm)	80	80	80	80	80	80	80
Trail (mm)	69	66	61	57	57	57	54
Lunghezza forcella (mm)	390	390	390	390	390	390	390
Offset Forcella/Rake (mm)	55	55	55	55	55	55	55
Avancorsa (mm)	607	614	620	630	647	664	675
Lunghezza Batticateni (mm)	432	432	432	432	432	432	432
Interasse (mm)	1026	1033	1039	1049	1066	1083	1095
Lunghezza Tubo Orizz. virtuale (mm)	529	542	558	573	589	605	628
Altezza Standover (mm)	697	722	738	777	800	823	849
Lunghezza Piantone (mm)	390	430	470	500	530	560	590
Angolo sella (degrees)	74	73.75	73.5	73.5	73.5	73.5	73
Lunghezza pedivella (mm)	165	170	172.5	172.5	175	175	175
Larghezza Manubrio (mm)	380	400	420	420	440	440	440
Lunghezza Attacco man. (mm)	60	70	80	90	100	100	110
Larghezza Sella (mm)	155	155	143	143	143	143	143
Lunghezza Reggisella (mm)	350	350	400	400	400	400	400

ART. NR.	DESCRIZIONE	COLORE	MISURA
95425-5149	DIVERGE E5 COMP	GLOSS METALLIC OBSIDIAN/METALLIC PINE GREEN	49
95425-5152			52
95425-5154			54
95425-5156			56
95425-5158			58
95425-5161			61
95425-5164			64
95425-5349	DIVERGE E5 COMP	GLOSS TAUPE/SLATE	49
95425-5352			52
95425-5354			54
95425-5356			56
95425-5358			58
95425-5361			61
95425-5364			64
95425-5249	DIVERGE E5 COMP	SATIN DEEP ORANGE/DEEP LAKE	49
95425-5252			52
95425-5254			54
95425-5256			56
95425-5258			58
95425-5261			61
95425-5264			64

Disponibile Online e Pickup in store

## DIVERGE E5 ELITE



GLOSS SEA FOAM/DUNE WHITE



SATIN ASHEN/OBSIDIAN

### SPECIFICHE TECNICHE

Specialized si riserva il diritto di modificare le caratteristiche senza preavviso.

Nastro Manubrio	Supacaz Suave
Ruota anteriore	AXIS Elite Disc
Ruota posteriore	AXIS Elite Disc
Telaio	Specialized Diverge E5 Premium Aluminum, threaded BB, internal routing, 12x142mm thru-axle, flat-mount disc
Collarino Sella	Alloy, 30.8mm
Forcella	FACT carbon, full carbon steerer, 12x100 mm thru-axle, flat-mount disc
Freno anteriore	Shimano GRX, Hydraulic disc
Freno posteriore	Shimano GRX, Hydraulic disc
Comandi cambio	Shimano GRX RX400 hydraulic brake levers, 2x10 speed mechanical shifting
Deragliatore anteriore	Shimano GRX RX400, braze-on
Cambio posteriore	Shimano GRX RX400, 10-speed
Pacco Pignoni	Shimano CS-HG50-10, 10-Speed 11-36t
Catena	KMC X10, 10-speed w/ reusable Missing Link™
Guarnitura	Shimano GRX RX600
Ingranaggi	46/30T
Movimento Centrale	Shimano 68mm threaded
Pneumatico anteriore	Specialized Pathfinder Sport, 700x38c
Pneumatico posteriore	Specialized Pathfinder Sport, 700x38c
Camere d'aria	700x28/38mm, 48mm Presta valve
Attacco Manubrio	3D-forged alloy, 31.8mm, 7-degree rise
Curva manubrio	Specialized Shallow Drop, 6061, 70x125mm, 31.8mm clamp
Sella	Body Geometry Bridge Saddle, steel rails
Reggisella	Alloy, 2-bolt Clamp, 12mm offset, 27.2mm, anti-corrosion hardware
Identificativo	223495
Peso	10.0kg (22 lb., .7 oz)
Misura pesata	56

DIVERGE E5 ELITE	44	49	52	54	56	58	61
Stack (mm)	529	545	561	578	599	618	635
Reach (mm)	357	365	374	383	392	401	410
Lunghezza Tubo Sterzo (mm)	110	125	140	155	175	195	213
Angolo sterzo (degrees)	69.5	70	70.5	71.25	71.75	71.75	71.75
Altezza movimento centrale (mm)	270	270	270	270	270	270	270
BB Drop (mm)	80	80	80	80	80	80	80
Trail (mm)	72	69	66	61	57	57	57
Lunghezza forcella (mm)	390	390	390	390	390	390	390
Offset Forcella/Rake (mm)	55	55	55	55	55	55	55
Avancorsa (mm)	589	598	608	615	626	641	656
Lunghezza Batticateni (mm)	432	432	432	432	432	432	432
Interasse (mm)	1008	1017	1027	1035	1046	1061	1076
Lunghezza Tubo Orizz. virtuale (mm)	504	521	538	554	570	584	598
Altezza Standover (mm)	680	703	723	763	789	808	834
Lunghezza Piantone (mm)	363	390	430	470	500	530	560
Angolo sella (degrees)	74.5	74	73.75	73.5	73.5	73.5	73.5
Lunghezza pedivella (mm)	165	165	170	172.5	172.5	175	175
Larghezza Manubrio (mm)	360	380	400	420	420	440	440
Lunghezza Attacco man. (mm)	60	60	70	80	90	100	100
Larghezza Sella (mm)	155	155	155	143	143	143	143
Lunghezza Reggisella (mm)	350	350	350	400	400	400	400

ART. NR.	DESCRIZIONE	COLORE	MISURA
95425-4244	DIVERGE E5 ELITE	GLOSS SEA FOAM/DUNE WHITE	44
95425-4249			49
95425-4252			52
95425-4254			54
95425-4256			56
95425-4258			58
95425-4261			61
95425-4144	DIVERGE E5 ELITE	SATIN ASHEN/OBSIDIAN	44
95425-4149			49
95425-4152			52
95425-4154			54
95425-4156			56
95425-4158			58
95425-4161			61



GLOSS DUNE WHITE/ASHEN



GLOSS SPICE/GUNMETAL



SATIN METALLIC DEEP LAKE/WHITE

<b>SPECIFICHE TECNICHE</b>	<b>Specialized si riserva il diritto di modificare le caratteristiche senza preavviso.</b>
Nastro Manubrio	Supacaz Suave
Ruota anteriore	AXIS Elite Disc
Ruota posteriore	AXIS Elite Disc
Telaio	Specialized Diverge E5 Premium Aluminum, threaded BB, internal routing, 12x142mm thru-axle, flat-mount disc
Collarino Sella	Alloy, 30.8mm
Forcella	FACT carbon, full carbon steerer, 12x100 mm thru-axle, flat-mount disc
Freno anteriore	Tektro Mira, flat-mount, mechanical disc
Freno posteriore	Tektro Mira, flat-mount, mechanical disc
Comandi cambio	Shimano Claris
Comandi cambio	Shimano Claris 2000, 8-speed
Deragliatore anteriore	Shimano Claris, 8-speed, braze-on
Cambio posteriore	Shimano Claris, 8-speed
Pacco Pignoni	SunRace, 8-speed, 11-34t
Catena	KMC X8 w/ Missing Link™
Guarnitura	Shimano Claris R200
Ingranaggi	50/34T
Movimento Centrale	Shimano 68mm threaded
Pneumatico anteriore	Specialized Pathfinder Sport, 700x38c
Pneumatico posteriore	Specialized Pathfinder Sport, 700x38c
Camere d'aria	700x28/38mm, 48mm Presta valve
Attacco Manubrio	3D-forged alloy, 31.8mm, 7-degree rise
Curva manubrio	Specialized Shallow Drop, 6061, 70x125mm, 31.8mm clamp
Sella	Body Geometry Bridge Saddle, steel rails
Reggisella	Alloy, 2-bolt Clamp, 12mm offset, 27.2mm, anti-corrosion hardware
Identificativo	221375
Peso	10.24kg (22 lb, 9.2 oz)
Misura pesata	56

<b>DIVERGE E5</b>	<b>44</b>	<b>49</b>	<b>52</b>	<b>54</b>	<b>56</b>	<b>58</b>	<b>61</b>
Stack (mm)	529	545	561	578	599	618	635
Reach (mm)	357	365	374	383	392	401	410
Lunghezza Tubo Sterzo (mm)	110	125	140	155	175	195	213
Angolo sterzo (degrees)	69.5	70	70.5	71.25	71.75	71.75	71.75
Altezza movimento centrale (mm)	270	270	270	270	270	270	270
BB Drop (mm)	80	80	80	80	80	80	80
Trail (mm)	72	69	66	61	57	57	57
Lunghezza forcella (mm)	390	390	390	390	390	390	390
Offset Forcella/Rake (mm)	55	55	55	55	55	55	55
Avancorsa (mm)	589	598	608	615	626	641	656
Lunghezza Batticateni (mm)	432	432	432	432	432	432	432
Interasse (mm)	1008	1017	1027	1035	1046	1061	1076
Lunghezza Tubo Orizz. virtuale (mm)	504	521	538	554	570	584	598
Altezza Standover (mm)	680	703	723	763	789	808	834
Lunghezza Sella (mm)	363	390	430	470	500	530	560
Angolo sella (degrees)	74.5	74	73.75	73.5	73.5	73.5	73.5
Lunghezza pedivella (mm)	165	165	170	170	170	175	175
Larghezza Manubrio (mm)	360	380	400	420	420	440	440
Lunghezza Attacco man. (mm)	60	60	70	80	90	100	100
Larghezza Sella (mm)	155	155	155	143	143	143	143
Lunghezza Reggisella (mm)	350	350	350	400	400	400	400

<b>ART. NR.</b>	<b>DESCRIZIONE</b>	<b>COLORE</b>	<b>MISURA</b>
95425-7044	DIVERGE E5	GLOSS DUNE WHITE/ASHEN	44
95425-7049			49
95425-7052			52
95425-7054			54
95425-7056			56
95425-7058			58
95425-7061			61
95425-7144	DIVERGE E5	GLOSS SPICE/GUNMETAL	44
95425-7149			49
95425-7152			52
95425-7154			54
95425-7156			56
95425-7158			58
95425-7161			61
95425-7244	DIVERGE E5	SATIN METALLIC DEEP LAKE/WHITE	44
95425-7249			49
95425-7252			52
95425-7254			54
95425-7256			56
95425-7258			58
95425-7261			61

# S-WORKS EPIC 8



Gloss Carbon/Astral Blue/Electric Green/Cyan Edge Fade/Metallic White Silver



Gloss Carbon/Metallic Vivid Pink/  
Viavi Magenta Gold/Metallic Midnight Shadow

S-WORKS EPIC 8	S	M	L	XL
Stack (mm)	597	598	610	628
Reach (BB basso) (mm)	420	450	475	500
Lunghezza Tubo Sterzo (mm)	92	95	110	130
Angolo sterzo (basso) (degrees)	65.9	65.9	65.9	65.9
Angolo sterzo (high) (degrees)	66.4	66.4	66.4	66.4
Altezza movimento centrale (BB basso) (mm)	324	326	328	328
Altezza movimento centrale (BB alto) (mm)	329	331	333	333
BB Drop (BB Basso) (mm)	46	44	42	42
Trail (mm)	117	117	117	117
Lunghezza forcella (mm)	530	530	530	530
Offset forcella/Rake (mm)	44	44	44	44
Avancorsa (mm)	716	747	778	811
Lunghezza Batticateni (mm)	435	435	435	435
Interasse (mm)	1147	1179	1210	1243
Altezza standover (mm)	755	760	769	774
Lunghezza piantone (mm)	390	410	450	500
Angolo Sella (degrees)	76	75.5	75.5	75.5
Lunghezza Tubo Orizz. virtuale (mm)	569	605	633	662
Lunghezza pedivella- translate here (mm)	170	170	175	175
Larghezza Manubrio (mm)	760	760	760	760
Lunghezza Attacco man. (mm)	60	60	60	60
Larghezza Sella (mm)	155	143	143	143
Lunghezza Reggisella (mm)	125	125	150	170

## SPECIFICHE TECNICHE

	Specialized si riserva il diritto di modificare le caratteristiche senza preavviso.
Telaio	S-Works FACT 12m Carbon, Progressive XC Race Geometry, Rider-First Engineered™, SWAT downtube storage, threaded BB, 12x148mm UDH compatible rear dropout, internal cable routing, 120mm of travel, Optimized for wireless drivetrain and seatpost
Componenti SWAT	SWAT internal downtube storage
Ammortizzatore Post.	RockShox SIDLuxe ULTIMATE Flight Attendant, Ride Dynamics developed 3 position, Solo Air, 190x45mm
Forcella	RockShox SID ULTIMATE Flight Attendant, Ride Dynamics developed 3 position, Debon Air, 15x110mm, 44mm offset, 120mm Travel
Manopole	Specialized Trail Grips
Sella	Body Geometry S-Works Power, carbon fiber rails, carbon fiber base
Manubrio	Roval Control SL Integrated cockpit, 60mm X- 12 degree integrated stem, 8-degree backsweep, 1 degree upsweep, 760mm wide
Manopole	Specialized Trail Grips
Freno anteriore	SRAM Level Ultimate Stealth, 4-piston caliper, hydraulic disc, 180mm rotor
Freno posteriore	SRAM Level Ultimate Stealth, 4-piston caliper, hydraulic disc, 160mm rotor
Cambio posteriore	SRAM XX SL Eagle AXS
Comandi cambio	SRAM AXS POD Ultimate Controller
Pacco Pignoni	SRAM XX Eagle SL 10-52t
Catena	SRAM XX SL Eagle
Guarnitura	SRAM XX SL Eagle Power Meter Crankset, 170mm/175mm
Ingranaggi	Alloy 34T
Movimento Centrale	SRAM DUB, BSA 73mm, Threaded
Cerchi	Roval Control SL, Carbon offset design, 29mm internal width, 4mm hook width, Tubeless ready, 24h, Quarq TyreWiz 2.0
Mozzo anteriore	Roval Control SL, DT Swiss Internals, Ceramic Bearings, 6-bolt, 15mm thru-axle, 110mm spacing, Torque caps, 24h straight pull
Mozzo posteriore	Roval Control SL, DT Swiss 180 Internals, DT Swiss Ratchet EXP, Ceramic bearings, 12mm thru-axle, 148mm spacing, 24h straight-pull
Raggi	DT Swiss Aerolite T-head
Pneumatico anteriore	Specialized Fast Trak, Control Casing, T7 Compound, 29x2.35
Pneumatico posteriore	Specialized Renegade, Control Casing, T5 Compound, 29x2.35
Camere d'aria	Specialized Turbo Tube
Reggisella	RockShox Reverb AXS, 30.9mm, S/M: 125, L:150, XL: 170mm
Collarino Sella	Specialized Alloy 34.9, Titanium Bolt
Peso	10.24kg (22 lb, 9.2 oz)
Misura pesata	MD

ART. NR.	DESCRIZIONE	COLORE	MISURA
90324-0102	EPIC 8 SW	Gloss Carbon/Astral Blue/Electric Green/ Cyan Edge Fade/Metallic White Silver	S
90324-0103			M
90324-0104			L
90324-0105			XL
90324-0002	EPIC 8 SW	Gloss Carbon/Metallic Vivid Pink/Viavi Magenta Gold/Metallic Midnight Shadow	S
90324-0003			M
90324-0004			L
90324-0005			XL

## TELAIO S-WORKS EPIC 8



Gloss Astral Blue/Metallic Sapphire/Black



Gloss Carbon/Metallic Vivid Pink/  
Viavi Magenta Gold/Metallic Midnight Shadow

### SPECIFICHE TECNICHE

**Specialized si riserva il diritto di modificare le caratteristiche senza preavviso.**

Telaio	S-Works FACT 12m Carbon, Progressive XC Race Geometry, Rider-First Engineered™, SWAT downtube storage, threaded BB, 12x148mm UDH compatible rear dropout, internal cable routing, 120mm of travel, Optimized for wireless drivetrain and seatpost
Componenti SWAT	SWAT internal downtube storage
Ammortizzatore Post.	RockShox SIDLuxe ULTIMATE, Ride Dynamics developed 3 position, TwistLoc remote adjust, Solo Air, 190x45mm
Forcella	RockShox SID ULTIMATE, Ride Dynamics developed 3 position, TwistLoc remote adjust, Debon Air, 15x110mm, 44mm offset, 120mm Travel
Manopole	SRAM Slip on with Twist-Loc
Reggisella	Roval Control SL carbon seatpost, Two-bolt clamp, 0mm offset, 415/370mm x 30.9
Collarino Sella	Specialized Alloy 34.9, Titanium Bolt
Peso	3.6kg (7 lb, 15 oz)
Misura pesata	MD (weight includes frame and fork as pictured)

### TELAIO S-WORKS EPIC 8

	S	M	L	XL
Stack (mm)	597	598	610	628
Reach (BB basso) (mm)	420	450	475	500
Lunghezza Tubo Sterzo (mm)	92	95	110	130
Angolo sterzo (basso) (degrees)	65.9	65.9	65.9	65.9
Angolo sterzo (high) (degrees)	66.4	66.4	66.4	66.4
Altezza movimento centrale (BB basso) (mm)	324	326	328	328
Altezza movimento centrale (BB alto) (mm)	329	331	333	333
BB Drop (BB Basso) (mm)	46	44	42	42
Trail (mm)	117	117	117	117
Lunghezza forcella (mm)	530	530	530	530
Offset forcella/Rake (mm)	44	44	44	44
Avancorsa (mm)	716	747	778	811
Lunghezza Batticateni (mm)	435	435	435	435
Interasse (mm)	1147	1179	1210	1243
Altezza standover (mm)	755	760	769	774
Lunghezza piantone (mm)	390	410	450	500
Angolo Sella (degrees)	76	75.5	75.5	75.5
Lunghezza Tubo Orizz. virtuale (mm)	569	605	633	662
Lunghezza Reggisella (mm)	370	370	415	415

ART. NR.	DESCRIZIONE	COLORE	MISURA
70324-0002	EPIC 8 SW FRMSET	Gloss Carbon/Metallic Vivid Pi	S
70324-0003			M
70324-0004			L
70324-0005			XL
70324-0102	EPIC 8 SW FRMSET	Gloss Astral Blue/Metallic Sap	S
70324-0103			M
70324-0104			L
70324-0105			XL



Gloss Lagoon Blue / Liquid Metal / Yellow



Satin Carbon/Metallic Sapphire/Metallic White Silver

EPIC 8 PRO	S	M	L	XL
Stack (mm)	597	598	610	628
Reach (BB basso) (mm)	420	450	475	500
Lunghezza Tubo Sterzo (mm)	92	95	110	130
Angolo sterzo (basso) (degrees)	65.9	65.9	65.9	65.9
Angolo sterzo (alto) (degrees)	66.4	66.4	66.4	66.4
Altezza movimento centrale (BB basso) (mm)	324	326	328	328
Altezza movimento centrale (BB alto) (mm)	329	331	333	333
BB Drop (BB Basso) (mm)	46	44	42	42
Trail (mm)	117	117	117	117
Lunghezza forcella (mm)	530	530	530	530
Offset Forcella/Rake (mm)	44	44	44	44
Avancorsa (mm)	716	747	778	811
Lunghezza Batticateni (mm)	435	435	435	435
Interasse (mm)	1147	1179	1210	1243
Altezza Standover (mm)	755	760	769	774
Lunghezza Piantone (mm)	390	410	450	500
Angolo sella (degrees)	76	75.5	75.5	75.5
Lunghezza Tubo Orizz. virtuale (mm)	569	605	633	662
Lunghezza pedivella (mm)	170	170	175	175
Larghezza Manubrio (mm)	760	760	760	760
Lunghezza Attacco man. (mm)	60	60	60	60
Larghezza Sella (mm)	155	143	143	143
Lunghezza Reggisella (mm)	100	125	125	125

SPECIFICHE TECNICHE	Specialized si riserva il diritto di modificare le caratteristiche senza preavviso.
Componenti SWAT	SWAT internal downtube storage
Manubrio	S-Works Carbon XC Mini Rise, 6-degree upsweep, 8-degree backsweep, 10mm rise, 760mm, 31.8mm
Telaio	FACT 11m Carbon, Progressive XC Geometry, Rider-First Engineered™, SWAT downtube storage, threaded BB, 12x148mm UDH compatible rear dropout, internal cable routing, 120mm of travel
Collarino Sella	Specialized Alloy 34.9, Steel Bolt
Ammortizzatore Post.	RockShox SIDLuxe ULTIMATE, Ride Dynamics developed 3 position, TwistLoc remote adjust, Solo Air, 190x45mm
Forcella	RockShox SID ULTIMATE, Ride Dynamics developed 3 position, TwistLoc remote adjust, Debon Air, 15x110mm, 44mm offset, 120mm Travel
Freno anteriore	SRAM Level Silver Stealth, 4-piston caliper, hydraulic disc, 180mm rotor
Freno posteriore	SRAM Level Silver Stealth, 4-piston caliper, hydraulic disc, 160mm rotor
Comandi cambio	SRAM AXS POD Controller
Cambio posteriore	SRAM XO AXS Transmission
Pacco Pignoni	SRAM XS-1295, 12-speed, 10-52t
Catena	SRAM XO Transmission
Guarnitura	SRAM XO Eagle, Quarq Spindle power meter, DUB, 170/175mm
Ingranaggi	34t
Movimento Centrale	SRAM DUB Threaded Wide
Cerchi	Roval Control, Carbon offset design, 29mm internal width, 4mm hook width, Tubeless ready, 28h
Mozzo anteriore	DT Swiss 350, 6-bolt, 15mm Thru-axle, 110mm spacing, 28h straight-pull
Mozzo posteriore	DT Swiss 350, 6-bolt, DT Swiss Ratchet, 12x148mm thru axle, XD freehub body, 28h straight-pull
Raggi	DT Swiss Comp Race
Pneumatico anteriore	Specialized Fast Trak, Control Casing, T7 Compound, 29x2.35
Pneumatico posteriore	Specialized Renegade, Control Casing, T5 Compound, 29x2.35
Camere d'aria	Standard 40mm PV 29x1.75-2.4
Attacco Manubrio	Specialized Pro SL, alloy, 4-bolt
Manopole	SRAM Slip on with Twist-Loc
Sella	
Reggisella	Specialized Alloy, 34.9, Steel bolt
Identificativo	221503
Peso	10.87kg (23 lb, 15.4 oz)
Misura pesata	MD

ART. NR.	DESCRIZIONE	COLORE	MISURA
90325-1202	EPIC 8 PRO	Gloss Lagoon Blue / Liquid Metal / Yellow	S
90325-1203			M
90325-1204			L
90325-1205			XL
90324-1002	EPIC 8 PRO	Satin Carbon/Metallic Sapphire/MetWhite Silver	S
90324-1003			M
90324-1004			L
90324-1005			XL



Satin/Redsky White



Gloss Carbon/Black Pearl White

EPIC 8 EXPERT	XS	S	M	L	XL
Stack (mm)	603	597	598	610	628
Reach (BB basso) (mm)	390	420	450	475	500
Lunghezza Tubo Sterzo (mm)	92	92	95	110	130
Angolo sterzo (basso) (degrees)	65.9	65.9	65.9	65.9	65.9
Angolo sterzo (high) (degrees)	66.4	66.4	66.4	66.4	66.4
Altezza movimento centrale (BB basso) (mm)	318	324	326	328	328
Altezza movimento centrale (BB alto) (mm)	323	329	331	333	333
BB Drop (BB Basso) (mm)	52	46	44	42	42
Trail (mm)	117	117	117	117	117
Lunghezza forcella (mm)	530	530	530	530	530
Offset forcella/Rake (mm)	44	44	44	44	44
Avancorsa (mm)	687	716	747	778	811
Lunghezza Batticateni (mm)	435	435	435	435	435
Interasse (mm)	1117	1147	1179	1210	1243
Altezza standover (mm)	748	755	760	769	774
Lunghezza piantone (mm)	370	390	410	450	500
Angolo Sella (degrees)	76.5	76	75.5	75.5	75.5
Lunghezza Tubo Orizz. virtuale (mm)	535	569	605	633	662
Lunghezza pedivella- translate here (mm)	165	170	170	175	175
Larghezza Manubrio (mm)	750	750	750	750	750
Lunghezza Attacco man. (mm)	60	60	60	60	60
Larghezza Sella (mm)	155	155	143	143	143
Lunghezza Reggisella (mm)	100	125	125	150	170

## SPECIFICHE TECNICHE

	Specialized si riserva il diritto di modificare le caratteristiche senza preavviso.
Telaio	FACT 11m Carbon, Progressive XC Race Geometry, Rider-First Engineered™, SWAT downtube storage, threaded BB, 12x148mm UDH compatible rear dropout, internal cable routing, 120mm of travel
Componenti SWAT	SWAT internal downtube storage
Ammortizzatore Post.	RockShox SIDLuxe Select+, Ride Dynamics developed 3 position, TwistLoc remote adjust, Solo Air, 190x45mm
Curva manubrio	Specialized Alloy Minirise, 10mm rise, 750mm, 31.8mm clamp
Forcella	RockShox SID Select+, Ride Dynamics developed 3 position, TwistLoc remote adjust, Debon Air, 15x110mm, 44mm offset, 120mm Travel
Attacco Manubrio	Specialized XC, 3D-forged alloy, 4-bolt, 6-degree rise
Sella	Body Geometry Power Sport, steel rails
Manopole	SRAM Slip on with Twist-Loc
Freno anteriore	SRAM Level Bronze Stealth, 4-piston caliper, hydraulic disc, 180mm rotor
Freno posteriore	SRAM Level Bronze Stealth, 4-piston caliper, hydraulic disc, 160mm rotor
Comandi cambio	SRAM AXS POD Controller
Cambio posteriore	SRAM GX Eagle AXS Transmission
Pacco Pignoni	SRAM XS 1275, 12-speed, 10-52t
Catena	SRAM GX Eagle T-Type chain
Guarnitura	SRAM GX Eagle, DUB, 165/170/175mm
Ingranaggi	Steel, 34T
Movimento Centrale	SRAM DUB Threaded Wide
Cerchi	Roval Control, Carbon offset design, 29mm internal width, 4mm hook width, Tubeless ready, 28h
Mozzo anteriore	DT Swiss 350, 6-bolt, 15mm Thru-axle, 110mm spacing, 28h straight-pull
Mozzo posteriore	DT Swiss 350 straight-pull, 6-bolt, DT Swiss Ratchet, 12x148mm thru axle, XD freehub body, 28h straight-pull
Raggi	DT Swiss Comp Race
Pneumatico anteriore	Specialized Fast Trak, Control Casing, T7 Compound, 29x2.35
Pneumatico posteriore	Specialized Renegade, Control Casing, T5 Compound, 29x2.35
Camere d'aria	Standard, Presta Valve
Reggisella	X-Fusion Manic, 30.9, 100/125/150/170mm travel
Collarino Sella	Specialized Alloy, 34.9, Steel bolt
Peso	11.10kg (24 lb, 7.5 oz)
Misura pesata	MD

ART. NR.	DESCRIZIONE	COLORE	MISURA
90324-3101	EPIC 8 EXPERT	Gloss Carbon/Black Pearl White	XS
90324-3102			S
90324-3103			M
90324-3104			L
90324-3105			XL
90324-3001	EPIC 8 EXPERT	Satin/Redsky White	XS
90324-3002			S
90324-3003			M
90324-3004			L
90324-3005			XL



Gloss Ashen Gray / White



Satin Deep Orange White

EPIC 8 COMP	XS	S	M	L	XL
Stack (mm)	603	597	598	610	628
Reach (BB basso) (mm)	390	420	450	475	500
Lunghezza Tubo Sterzo (mm)	92	92	95	110	130
Angolo sterzo (basso) (degrees)	65.9	65.9	65.9	65.9	65.9
Angolo sterzo (high) (degrees)	66.4	66.4	66.4	66.4	66.4
Altezza movimento centrale (BB basso) (mm)	318	324	326	328	328
Altezza movimento centrale (BB alto) (mm)	323	329	331	333	333
BB Drop (BB Basso) (mm)	52	46	44	42	42
Trail (mm)	117	117	117	117	117
Lunghezza forcella (mm)	530	530	530	530	530
Offset forcella/Rake (mm)	44	44	44	44	44
Avancorsa (mm)	687	716	747	778	811
Lunghezza Batticateni (mm)	435	435	435	435	435
Interasse (mm)	1117	1147	1179	1210	1243
Altezza Standover (mm)	748	755	760	769	774
Seat Tube Length (mm)	370	390	410	450	500
Angolo sella (degrees)	76.5	76	75.5	75.5	75.5
Top Tube Length, Horizontal (mm)	535	569	605	633	662
Lunghezza pedivella (mm)	165	170	170	175	175
Larghezza Manubrio (mm)	750	750	750	750	750
Lunghezza Attacco man. (mm)	60	60	60	60	60
Larghezza Sella (mm)	155	155	143	143	143
Lunghezza Reggisella (mm)	100	125	150	150	170

SPECIFICHE TECNICHE	Specialized si riserva il diritto di modificare le caratteristiche senza preavviso.
Componenti SWAT	SWAT internal downtube storage
Telaio	FACT 11m Carbon, Progressive XC Race Geometry, Rider-First Engineered™, SWAT downtube storage, threaded BB, 12x148mm UDH compatible rear dropout, internal cable routing, 120mm of travel
Collarino Sella	Specialized Alloy, 34.9, Steel bolt
Ammortizzatore Post.	RockShox SIDLuxe Select+, Ride Dynamics developed 3 position, TwistLoc remote adjust, Solo Air, 190x45mm
Forcella	RockShox SID Select, Ride Dynamics developed 3 position, TwistLoc remote adjust, Debon Air, 15x110mm, 44mm offset, 120mm Travel
Freni	SRAM Level Bronze Stealth, 4-piston caliper, hydraulic disc, 160/180 mm rotor
Comandi cambio	Sram AXS POD Controller
Cambio posteriore	SRAM S-1000 Eagle Transmission
Pacco Pignoni	SRAM XS 1270 Transmission, 10-52t
Catena	SRAM GX Transmission
Guarnitura	SRAM S1000 Eagle, DUB, 165/170/175mm, 34T
Movimento Centrale	SRAM DUB Threaded Wide
Cerchi	Specialized Alloy 29, 28mm internal width, tubeless
Mozzo anteriore	Specialized alloy front hub disc, sealed cartridge bearings, 6-bolt, 15x110mm thru-axle, 32h
Mozzo posteriore	Alloy, sealed cartridge bearings, 12x148mm thru-axle, 32h
Raggi	DT Swiss Industry
Pneumatico anteriore	Specialized Fast Trak, Control Casing, T7 Compound, 29x2.35
Pneumatico posteriore	Specialized Renegade, Control Casing, T5 Compound, 29x2.35
Camere d'aria	Standard 40mm PV 29x1.75-2.4
Attacco Manubrio	Specialized, 3D-forged alloy, 4-bolt, 7-degree rise
Curva manubrio	Specialized Alloy Minirise, 10mm rise, 750mm, 31.8mm clamp
Manopole	SRAM Slip on with Twist-Loc
Sella	Body Geometry Power Sport, steel rails
Reggisella	X-Fusion Manic, 30.9, 125/150/170 Travel, 0mm offset
Peso	11.89kg (26 lb, 3.4 oz)
Misura pesata	MD

ART. NR.	DESCRIZIONE	COLORE	MISURA
90325-5001	EPIC 8 COMP	Gloss Ashen Gray / White	XS
90325-5002			S
90325-5003			M
90325-5004			L
90325-5005			XL
90325-5101	EPIC 8 COMP	Satin Deep Orange White	XS
90325-5102			S
90325-5103			M
90325-5104			L
90325-5105			XL



Satin Forest Green/Spruce/Metallic Spruce

EPIC 8 EVO PRO	S	M	L	XL
Stack (mm)	600	601	613	632
Reach (mm)	415	445	470	495
Lunghezza Tubo Sterzo (mm)	92	95	110	130
Angolo sterzo (basso) (degrees)	65.4	65.4	65.4	65.4
Angolo sterzo (high) (degrees)	65.9	65.9	65.9	65.9
Altezza movimento centrale (BB basso) (mm)	327	329	331	331
Altezza movimento centrale (BB alto) (mm)	333	335	337	337
BB Drop (BB Basso) (mm)	43	41	39	39
Trail (mm)	120	120	120	120
Lunghezza forcella (mm)	540	540	540	540
Offset forcella/Rake (mm)	44	44	44	44
Avancorsa (mm)	720	751	782	815
Lunghezza Batticatena (mm)	435	435	435	435
Interasse (mm)	1151	1183	1214	1247
Altezza standover (mm)	761	766	775	779
Lunghezza piantone (mm)	390	410	450	500
Angolo Sella (degrees)	75.5	75	75	75
Lunghezza Tubo Orizz. virtuale (mm)	569	605	633	662
Lunghezza pedivella- translate here (mm)	170	170	175	175
Larghezza Manubrio (mm)	780	780	780	780
Lunghezza Attacco man. (mm)	50	50	50	50
Larghezza Sella (mm)	155	143	143	143
Lunghezza Reggisella (mm)	125	150	175	175

## SPECIFICHE TECNICHE

Specialized si riserva il diritto di modificare le caratteristiche senza preavviso.

Telaio	FACT 11m Carbon, Progressive XC Race Geometry, Rider-First Engineered™, SWAT downtube storage, threaded BB, 12x148mm UDH compatible rear dropout, internal cable routing, 120mm of travel
Componenti SWAT	SWAT internal downtube storage
Ammortizzatore Post.	Fox Float Factory, Evol LV, Ride Dynamics Tuned, LSC/Rebound adjust, 190x45mm
Forcella	Fox 34 Factory, Grip2 Damper, 4 way adjust, 130mm travel, 44mm offset, 15x110mm
Attacco Manubrio	Raceface Turbine R, 50mm, 35mm clamp
Manopole	Specialized Trail Grips
Manubrio	Royal Control Rise Carbon Handlebar, 780mm wide, 20mm rise, 35mm
Manopole	Specialized Trail Grips
Freno anteriore	SRAM Code Silver Stealth, 4-piston caliper, hydraulic disc, 180/200mm HS2 rotor
Freno posteriore	SRAM Code Silver Stealth, 4-piston caliper, hydraulic disc, 180mm HS2 rotor
Comandi cambio	SRAM AXS POD Controller
Cambio posteriore	SRAM X0 Eagle Transmission
Pacco Pignoni	SRAM XS 1295, 12 speed, 10-52
Catena	Sram X0 Eagle
Guarnitura	SRAM X0 Eagle, DUB, 170/175mm
Ingranaggi	Alloy, 32T
Movimento Centrale	SRAM DUB Threaded Wide
Cerchi	Royal Control, Carbon offset design, 29mm internal width, 4mm hook width, Tubeless ready, 28h
Mozzo anteriore	Industry Nine 1/1, 6-bolt, 15mm Thru-axle, 110mm spacing, 28h
Mozzo posteriore	Industry Nine 1/1, 12x148mm thru axle, XD freehub body, 28h
Raggi	Stainless, 14g, black
Pneumatico anteriore	Specialized Purgatory, GRID Casing, T9 Compound, 29x2.4
Pneumatico posteriore	Specialized Ground Control, GRID Casing, T7 Compound, 29x2.35
Camere d'aria	Standard, Presta Valve
Sella	Body Geometry Power Expert
Reggisella	Fox Transfer Factory, 30.9, 1X remote, (SM:125mm, MD:150mm, L-XL: 175mm)
Collarino Sella	Specialized Alloy, 34.9, Steel bolt
Peso	12.12kg (26 lb, 11.5 oz)
Misura pesata	MD

ART. NR.	DESCRIZIONE	COLORE	MISURA
90324-1102	EPIC 8 PRO EVO	Satin Forest Green/Spruce/Meta	S
90324-1103			M
90324-1104			L
90324-1105			XL



Gloss Cast Lilac / Dune White



Satin Silver Dust / Gunmetal

EPIC 8 EVO EXPERT	XS	S	M	L	XL
Stack (mm)	606	600	601	613	632
Reach (mm)	385	415	445	470	495
Lunghezza Tubo Sterzo (mm)	92	92	95	110	130
Angolo sterzo (basso) (degrees)	65.4	65.4	65.4	65.4	65.4
Angolo sterzo (high) (degrees)	65.9	65.9	65.9	65.9	65.9
Altezza movimento centrale (BB basso) (mm)	322	327	329	331	331
Altezza movimento centrale (BB alto) (mm)	327	333	335	337	337
BB Drop (BB Basso) (mm)	49	43	41	39	39
Trail (mm)	120	120	120	120	120
Lunghezza forcella (mm)	540	540	540	540	540
Offset forcella/Rake (mm)	44	44	44	44	44
Avancorsa (mm)	690	720	751	782	815
Lunghezza Batticateni (mm)	435	435	435	435	435
Interasse (mm)	1121	1151	1183	1214	1247
Altezza Standover (mm)	754	761	766	775	779
Lunghezza piantone (mm)	370	390	410	450	500
Angolo Sella (degrees)	76	75.5	75	75	75
Lunghezza Tubo Orizz. virtuale (mm)	535	569	605	633	662
Lunghezza pedivella (mm)	165	170	170	175	175
Larghezza Manubrio (mm)	780	780	780	780	780
Lunghezza Attacco man. (mm)	50	50	50	50	50
Larghezza Sella (mm)	155	155	143	143	143
Lunghezza Reggisella (mm)	125	125	150	170	170

## SPECIFICHE TECNICHE

Specialized si riserva il diritto di modificare le caratteristiche senza preavviso.

Telaio	FACT 11m Carbon, Progressive XC Geometry, Rider-First Engineered™, SWAT downtube storage, threaded BB, 12x148mm UDH compatible rear dropout, internal cable routing, 120mm of travel
Componenti SWAT	SWAT internal downtube storage
Ammortizzatore Post.	Fox Float Performance Elite, Evol LV, Ride Dynamics Tuned, 2-position compression adjust, 190x45mm
Forcella	Fox 34 Performance Elite, Grip X Damper, HSC, LSC, LSR adjust, 130mm travel, 44mm offset, 15x110mm
Attacco Manubrio	Alloy Stem, 35mm clamp, 50mm
Manopole	Specialized Trail Grips
Sella	Body Geometry Power Sport, steel rails
Manubrio	Specialized Alloy, 20mm rise, 35mm, 760mm wide
Freno anteriore	SRAM Code Bronze Stealth, 4-piston caliper, hydraulic disc, 180/200mm rotor
Freno posteriore	SRAM Code Bronze Stealth, 4-piston caliper, hydraulic disc, 180mm rotor
Comandi cambio	SRAM XS-1275, 12-speed, 10-52t
Cambio posteriore	SRAM GX AXS Transmission
Pacco Pignoni	SRAM AXS POD Controller
Catena	SRAM GX Transmission
Guarnitura	SRAM GX Eagle, DUB, 165/170/175mm, 32T
Ingranaggi	32t
Movimento Centrale	SRAM DUB Threaded Wide
Cerchi	Roval Control, Carbon offset design, 29mm internal width, 4mm hook width, Tubeless ready, 28h
Mozzo anteriore	Industry Nine 1/1, 6-bolt, 15mm Thru-axle, 110mm spacing, 28h
Mozzo posteriore	Industry Nine 1/1, 12x148mm thru axle, XD freehub body, 28h
Raggi	Sapim D-light
Pneumatico anteriore	Specialized Purgatory, GRID Casing, T9 Compound, 29x2.4
Pneumatico posteriore	Specialized Ground Control, GRID Casing, T7 Compound, 29x2.35
Camere d'aria	Standard 40mm PV 29x1.75-2.4
Reggisella	X-Fusion Manic, 30.9, 125/150/170 Travel, 0mm offset
Collarino Sella	Specialized Alloy, 34.9, Steel bolt
Peso	275710
Peso	12.16kg (26 lb, 12.9 oz)
Misura pesata	MD

ART. NR.	DESCRIZIONE	COLORE	MISURA
90325-3201/5	EPIC 8 EVO EXPERT	Gloss Cast Lilac / Dune White	XS-XL
90325-3301/5	EPIC 8 EVO EXPERT	Satin Silver Dust / Gunmetal	XS-XL



GLOSS SEA FOAM / CAST BLUE METALLIC



SATIN DARK MOSS GREEN / DUNE WHITE

EPIC 8 EVO COMP	XS	S	M	L	XL
Stack (mm)	606	600	601	613	632
Reach (mm)	385	415	445	470	495
Lunghezza Tubo Sterzo (mm)	92	92	95	110	130
Angolo sterzo (basso) (degrees)	65.4	65.4	65.4	65.4	65.4
Angolo sterzo (high) (degrees)	65.9	65.9	65.9	65.9	65.9
Altezza movimento centrale (BB basso) (mm)	322	327	329	331	331
Altezza movimento centrale (BB alto) (mm)	327	333	335	337	337
BB Drop (BB Basso) (mm)	49	43	41	39	39
Trail (mm)	120	120	120	120	120
Lunghezza forcella (mm)	540	540	540	540	540
Offset forcella/Rake (mm)	44	44	44	44	44
Avancorsa (mm)	690	720	751	782	815
Lunghezza Batticateni (mm)	435	435	435	435	435
Interasse (mm)	1121	1151	1183	1214	1247
Altezza Standover (mm)	754	761	766	775	779
Seat Tube Length (mm)	370	390	410	450	500
Angolo sella (degrees)	76	75.5	75	75	75
Top Tube Length, Horizontal (mm)	535	569	605	633	662
Lunghezza pedivella (mm)	165	170	170	175	175
Larghezza Manubrio (mm)	780	780	780	780	780
Lunghezza Attacco man. (mm)	50	50	50	50	50
Larghezza Sella (mm)	155	155	143	143	143
Lunghezza Reggisella (mm)	125	125	150	170	170

SPECIFICHE TECNICHE	Specialized si riserva il diritto di modificare le caratteristiche senza preavviso.
Componenti SWAT	SWAT internal downtube storage
Telaio	FACT 11m Carbon, Progressive XC Geometry, Rider-First Engineered™, SWAT downtube storage, threaded BB, 12x148mm UDH compatible rear dropout, internal cable routing, 120mm of travel
Collarino Sella	Specialized Alloy, 34.9, Steel bolt
Ammortizzatore Post.	Fox Float Performance, Evol LV, Ride Dynamics Tuned, 2-position compression adjust, 190x45mm
Forcella	Fox 34 Performance, Grip Damper, Compression adjust, 130mm travel, 44mm offset, 15x110mm
Freno anteriore	SRAM Code Bronze Stealth, 4-piston caliper, hydraulic disc, 180/200mm rotor
Freno posteriore	SRAM Code Bronze Stealth, 4-piston caliper, hydraulic disc, 180mm rotor
Comandi cambio	Sram AXS POD Controller
Cambio posteriore	SRAM S-1000 Eagle Transmission
Pacco Pignoni	SRAM XS 1270 Transmission, 10-52t
Catena	SRAM GX Transmission
Guarnitura	SRAM S1000 Eagle, DUB, 165/170/175mm, 32T
Ingranaggi	32t
Movimento Centrale	SRAM DUB Threaded Wide
Cerchi	Specialized Alloy 29, 27mm internal width, tubeless
Mozzo anteriore	Alloy, sealed cartridge bearings, 15x110mm thru-axle, 28h
Mozzo posteriore	Alloy, sealed cartridge bearings, 148mmx12mm thru-axle, 28h
Raggi	DT Swiss Industry
Pneumatico anteriore	Specialized Purgatory, GRID Casing, T9 Compound, 29x2.4
Pneumatico posteriore	Specialized Ground Control, GRID Casing, T7 Compound, 29x2.35
Camere d'aria	Standard 40mm PV 29x1.75-2.4
Attacco Manubrio	Alloy Stem, 35mm clamp, 60mm
Manubrio	Specialized Alloy, 20mm rise, 35mm, 760mm wide
Manopole	Specialized Trail Grips
Sella	Body Geometry Power Sport, steel rails
Reggisella	X-Fusion Manic, 30.9, 125/150/170 Travel, 0mm offset
Peso	12.75kg (28 lb, 1.7 oz)
Misura pesata	MD

ART. NR.	DESCRIZIONE	COLORE	MISURA
90325-5201	EPIC 8 EVO COMP	GLOSS SEA FOAM / CAST BLUE METALLIC	XS
90325-5202			S
90325-5203			M
90325-5204			L
90325-5205			XL
90325-5301	EPIC 8 EVO COMP	SATIN DARK MOSS GREEN / DUNE WHITE	XS
90325-5302			S
90325-5303			M
90325-5304			L
90325-5305			XL

## EPIC HARDTAIL COMP



Gloss Rebel Pink / Obsidian



Satin Gunmetal / Metallic White Silver

EPIC HARDTAIL COMP	XS	S	M	L	XL
Stack (mm)	594	608	608	622	636
Reach (mm)	385	405	430	455	480
Lunghezza Tubo Sterzo (mm)	95	95	95	110	125
Angolo sterzo (degrees)	68.5	68.5	68.5	68.5	68.5
BB altezza (mm)	309	309	309	309	309
BB Drop (mm)	63	63	63	63	63
Trail (mm)	101	101	101	101	101
Lunghezza forcella (mm)	486	506	506	506	506
Offset forcella/Rake (mm)	44	44	44	44	44
Avancorsa (mm)	643	670	695	725	755
Lunghezza Batticatena (mm)	430	430	430	430	430
Interasse (mm)	1064	1092	1117	1148	1178
Tubo Orizzontale (mm)	555	579	604	633	662
Altezza Standover (mm)	732	762	792	816	847
Lunghezza piantone (mm)	367	400	430	470	520
Angolo sella (degrees)	74	74	74	74	74
Lunghezza pedivella (mm)	165	170	170	175	175
Larghezza Manubrio (mm)	750	750	750	750	750
Lunghezza Attacco man. (mm)	60	60	70	70	70
Larghezza Sella (mm)	155	155	143	143	143
Lunghezza Reggisella (mm)	350	350	400	400	400

SPECIFICHE TECNICHE	Specialized si riserva il diritto di modificare le caratteristiche senza preavviso.
Componenti SWAT	SWAT EMT Tool
Telaio	Specialized FACT 11m, Progressive XC Geometry, Rider-First Engineered™, threaded BB, UDH, 12x148mm rear spacing, internal cable routing
Collarino Sella	Specialized Alloy 34.9, Alloy Bolt
Forcella	Rockshox SID SL, Rush RL Damper, Debon Air, 15x110mm, 44mm offset, 100mm
Freno anteriore	SRAM Level Bronze 2-piston, Stealth, 180/160mm rotor
Freno posteriore	SRAM Level Bronze 2-piston, Stealth, 160mm rotor
Comandi cambio	Sram AXS POD Controller
Cambio posteriore	SRAM S-1000 Eagle Transmission
Pacco Pignoni	SRAM XS 1270 Transmission, 10-52t
Catena	SRAM GX Transmission
Guarnitura	SRAM S1000 Eagle, DUB, 165/170/175mm, 34T
Ingranaggi	34t
Movimento Centrale	SRAM DUB Threaded Wide
Cerchi	Specialized 29, 27mm inner width, 28h, tubeless ready
Mozzo anteriore	Specialized alloy, sealed cartridge bearings, 6-bolt, 15x110mm thru-axle, 28h
Mozzo posteriore	Specialized alloy, sealed cartridge bearings, 6-bolt, 12x148mm thru-axle, 28h
Raggi	DT Swiss Industry
Pneumatico anteriore	Specialized Fast Trak, Control Casing, T7 Compound, 29x2.35
Pneumatico posteriore	Specialized Renegade, Control Casing, T5 Compound, 29x2.35
Camere d'aria	Standard 40mm PV 29x1.75-2.4
Attacco Manubrio	Specialized, 3D-forged alloy, 4-bolt, 7-degree rise
Curva manubrio	Specialized Alloy Minirise, 10mm rise, 750mm, 31.8mm clamp
Manopole	Specialized Trail Grips
Sella	Body Geometry Power Sport, steel rails
Reggisella	Specialized Alloy, Single Bolt, 30.9mm
Peso	10.37 kg (22 lb, 13.8 oz)
Misura pesata	LG

ART. NR.	DESCRIZIONE	COLORE	MISURA
91325-5001/5	EPIC HT COMP	Gloss Rebel Pink / Obsidian	XS-XL
91325-5101/5	EPIC HT COMP	Satin Gunmetal / Metallic White Silver	XS-XL

# S-WORKS EPIC WORLD CUP



Gloss Carbon / Red Pearl / Chameleon Fade



Gloss Glacial Metallic Granite / Brushed Chrome

S-WORKS EPIC WORLD CUP	S	M	L	XL
Stack (mm)	600	600	614	628
Reach (mm)	415	440	465	490
Lunghezza Tubo Sterzo (mm)	93	95	110	125
Angolo sterzo (degrees)	66.5	66.5	66.5	66.5
BB Altezza (mm)	313	313	313	313
BB Drop (mm)	58	57	57	57
Trail (mm)	113	113	113	113
Lunghezza forcella (mm)	516	516	516	516
Offset forcella/Rake (mm)	44	44	44	44
Avancorsa (mm)	701	726	757	788
Lunghezza Batticateni (mm)	430	430	430	430
Interasse (mm)	1124	1150	1181	1212
Altezza Standover (mm)	761	764	774	786
Lunghezza Piantone (mm)	395	410	450	500
Angolo sella (degrees)	74.5	74.5	74.5	74.5
Lunghezza tubo orizzontale (mm)	581	612	641	670
Lunghezza pedivella (mm)	170	170	175	175
Larghezza Manubrio (mm)	760	760	760	760
Lunghezza Attacco man. (mm)	60	70	70	70
Larghezza Sella (mm)	155	143	143	143
Lunghezza Reggisella (mm)	370	415	415	415

SPECIFICHE TECNICHE	Specialized si riserva il diritto di modificare le caratteristiche senza preavviso.
Componenti SWAT	SWAT EMT Cage-Mount Tool
Telaio	S-Works FACT 12m Carbon, WCID suspension design, Progressive XC Race Geometry, Rider-First Engineered™, threaded BB, 12x148mm UDH compatible rear spacing, internal cable routing, 75mm of travel
Collarino Sella	Specialized Alloy 34.9, Titanium Bolt
Ammortizzatore Post.	RockShox-Specialized SIDLuxe WCID Ultimate, Ride Dynamics Developed, Independent negative spring, Rebound Adjust, 215x40mm
Forcella	RockShox SID SL Ultimate, 3-position Raceday damper, Debon Air, 15x110mm, 44mm offset, 110mm Travel
Freno anteriore	SRAM Level Ultimate, 4-piston caliper, hydraulic disc, stealth, 180/160mm rotor
Freno posteriore	SRAM Level Ultimate, 4-piston caliper, hydraulic disc, stealth, 160mm rotor
Comandi cambio	SRAM POD Ultimate AXS controller
Cambio posteriore	SRAM XX SL Eagle Transmission
Pacco Pignoni	SRAM CS-1299 10-52t
Catena	SRAM XX SL Eagle
Guarnitura	Quarq XX SL power meter crankset, Carbon, 168 Q-Factor, DUB, 170/175mm, 34T
Ingranaggi	34t
Movimento Centrale	SRAM DUB, BSA 73mm, Threaded
Cerchi	Roval Control SL, Carbon offset design, 29mm internal width, 4mm hook width, Tubeless ready, 24h
Mozzo anteriore	Roval Control SL, DT Swiss Internals, Ceramic Bearings, 6-bolt, 15mm thru-axle, 110mm spacing, Torque caps, 24h straight pull t-head
Mozzo posteriore	Roval Control SL, DT Swiss 180 Internals, DT Swiss Ratchet EXP, Ceramic bearings, 12mm thru-axle, 148mm spacing, 24h straight-pull t-head
Raggi	DT Swiss Aerolite Straight-pull t-head
Pneumatico anteriore	Specialized S-Works Fast Trak, S-Works Casing, T5/T7 Compound, 29x2.35
Pneumatico posteriore	Specialized Renegade, Control Casing, T5 Compound, 29x2.35
Camere d'aria	Specialized Turbo Tube 40mm PV 29x1.75-2.4
Manubrio	Roval Control SL Integrated cockpit, 60mm/70mm X-12 degree integrated stem, 8-degree backsweep, 1 degree upsweep, 760mm wide
Manopole	SRAM Slip on with Twist-Loc
Sella	Body Geometry S-Works Power, carbon fiber rails, carbon fiber base
Reggisella	Roval Control SL carbon seatpost, Two-bolt clamp, 0mm offset, 415/370mm x 30.9
Peso	9.22kg (20 lb, 5.2 oz)
Misura pesata	MD

ART. NR.	DESCRIZIONE	COLORE	MISURA
93125-0202/5	EPIC WC S-WORKS	Gloss Carbon / Red Pearl / Chameleon Fade	S-XL
93125-0302/5	EPIC WC S-WORKS	Gloss Glacial Metallic Granite / Brushed Chrome	S-XL

## TELAIO S-WORKS EPIC WORLD CUP



Gloss Carbon / Red Pearl /Chameleon



Gloss Dune White / Ashen Grey

### SPECIFICHE TECNICHE

SPECIFICHE TECNICHE	Specialized si riserva il diritto di modificare le caratteristiche senza preavviso.
Telaio	S-Works FACT 12m Carbon, WCID suspension design.
Collarino Sella	Specialized Alloy 34.9, Titanium Bolt
Ammortizzatore Post.	RockShox-Specialized SIDLuxe WCID Ultimate, Ride Dynamics Developed, Independent negative spring, Rebound Adjust, 215x40mm
Reggisella	Roval Control SL carbon seatpost, Two-bolt clamp, 0mm offset, 415/370mm x 30.9
Peso	1.96kg (4 lb, 5.1 oz)
Misura pesata	MD (weight includes frame and fork as pictured)

TELAIO S-WORKS EPIC WORLD CUP	XS	S	M	L	XL
Stack (mm)	603	600	600	614	628
Reach (mm)	380	415	440	465	490
Lunghezza Tubo Sterzo (mm)	93	93	95	110	125
Angolo sterzo (degrees)	66.5	66.5	66.5	66.5	66.5
BB Height (mm)	309	313	313	313	313
BB Drop (mm)	61	58	57	57	57
Trail (mm)	113	113	113	113	113
Lunghezza forcella (mm)	516	516	516	516	516
Offset forcella/Rake (mm)	44	44	44	44	44
Avancorsa (mm)	665	701	726	757	788
Lunghezza Batticateni (mm)	430	430	430	430	430
Interasse (mm)	1089	1124	1150	1181	1212
Altezza Standover (mm)	738	761	764	774	786
lunghezza Piantone (mm)	392	395	410	450	500
Angolo sella (degrees)	74.5	74.5	74.5	74.5	74.5
Lunghezza tubo orizzontale (mm)	541	581	612	641	670
Lunghezza Reggisella (mm)	370	370	415	415	415

ART. NR.	DESCRIZIONE	COLORE	MISURA
73125-0101	EPIC WC SW FRM	Gloss Carbon / Red Pearl /Chameleon	XS
73125-0102/5	EPIC WC SW FRM	Gloss Carbon / Red Pearl /Chameleon	S-XL
73125-0001/5	EPIC WC SW FRM	Gloss Dune White / Ashen Grey	XS-XL

Disponibile Online e Pickup in store



Satin Burnt Gold Metallic

<b>SPECIFICHE TECNICHE</b>	<b>Specialized si riserva il diritto di modificare le caratteristiche senza preavviso.</b>
Componenti SWAT	SWAT EMT Cage-Mount Tool
Manubrio	S-Works Carbon XC Mini Rise, 6-degree upsweep, 8-degree backsweep, 10mm rise, 760mm, 31.8mm
Telaio	Fact 11m Carbon, WCID suspension design
Collarino Sella	Specialized Alloy 34.9, Steel Bolt
Ammortizzatore Post.	RockShox-Specialized SIDLuxe WCID Ultimate, Ride Dynamics Developed, Independent negative spring, Rebound Adjust, 215x40mm
Forcella	RockShox SID SL Ultimate, 3-position Raceday damper, Debon Air, 15x110mm, 44mm offset, 110mm Travel
Freno anteriore	SRAM Level Silver, 2-piston caliper, hydraulic disc, stealth,
Freno posteriore	SRAM Level Silver, 2-piston caliper, hydraulic disc, stealth,
Comandi cambio	SRAM POD AXS controller
Cambio posteriore	SRAM XO Eagle Transmission
Pacco Pignoni	SRAM XS 1295, 12 speed, 10-52
Catena	SRAM XO Eagle
Guarnitura	SRAM/Quarq XO power meter crankset, DUB, 170/175mm, 34T
Ingranaggi	34t
Movimento Centrale	SRAM DUB Threaded Wide
Cerchi	Roval Control, Carbon offset design, 29mm internal width, 4mm hook width, Tubeless ready, 28h
Mozzo anteriore	DT Swiss 350, 6-bolt, 15mm Thru-axle, 110mm spacing, 28h straight-pull
Mozzo posteriore	DT Swiss 350 straight-pull, 6-bolt, DT Swiss Ratchet, 12x148mm thru axle, XD freehub body, 28h straight-pull
Raggi	DT Swiss Competition Race Straight-pull
Pneumatico anteriore	Specialized Fast Trak, Control Casing, T7 Compound, 29x2.35
Pneumatico posteriore	Specialized Renegade, Control Casing, T5 Compound, 29x2.35
Camere d'aria	Specialized Turbo Tube 40mm PV 29x1.75-2.4
Attacco Manubrio	Specialized Pro SL, alloy, 4-bolt
Manopole	SRAM Slip on with Twist-Loc
Sella	Body Geometry Power Expert
Reggisella	Roval Control SL carbon seatpost, Two-bolt clamp, 0mm offset, 415/370mm x 30.9
Peso	10.11kg (22 lb, 4.6 oz)
Misura pesata	MD

<b>EPIC WORLD CUP PRO</b>	<b>S</b>	<b>M</b>	<b>L</b>	<b>XL</b>
Stack (mm)	600	600	614	628
Reach (mm)	415	440	465	490
Lunghezza Tubo Sterzo (mm)	93	95	110	125
Angolo sterzo (degrees)	66.5	66.5	66.5	66.5
BB Altezza (mm)	313	313	313	313
BB Drop (mm)	58	57	57	57
Trail (mm)	113	113	113	113
Lunghezza forcella (mm)	516	516	516	516
Offset forcella/Rake (mm)	44	44	44	44
Avancorsa (mm)	701	726	757	788
Lunghezza Batticateni (mm)	430	430	430	430
Interasse (mm)	1124	1150	1181	1212
Altezza Standover (mm)	761	764	774	786
Lunghezza Piantone (mm)	395	410	450	500
Angolo sella (degrees)	74.5	74.5	74.5	74.5
Lunghezza tubo orizzontale (mm)	581	612	641	670
Lunghezza pedivella (mm)	170	170	175	175
Larghezza Manubrio (mm)	760	760	760	760
Lunghezza Attacco man. (mm)	60	70	70	70
Larghezza Sella (mm)	155	143	143	143
Lunghezza Reggisella (mm)	370	415	415	415

<b>ART. NR.</b>	<b>DESCRIZIONE</b>	<b>COLORE</b>	<b>MISURA</b>
93125-1102/5	EPIC WC PRO	Satin Burnt Gold Metallic	S-XL



Gloss Cypress Metallic / Ion



Satin Metallic Deep Lake

**SPECIFICHE TECNICHE**

**Specialized si riserva il diritto di modificare le caratteristiche senza preavviso.**

Telaio	S-Works FACT 11m Carbon, WCID suspension design, Progressive XC Race Geometry, Rider-First Engineered™, threaded BB, 12x148mm UDH compatible rear spacing, internal cable routing, 75mm of travel
Collarino Sella	Specialized Alloy 34.9, Steel Bolt
Ammortizzatore Post.	RockShox-Specialized SIDLux WCID Ultimate, Ride Dynamics Developed, Independent negative spring, Rebound Adjust, 215x40mm
Forcella	RockShox SID SL Select+, 3-position damper, Debon Air, 15x110mm, 44mm offset, 110mm Travel
Freno anteriore	SRAM Level Bronze, 4-piston caliper, hydraulic disc, stealth
Freno posteriore	SRAM Level Bronze, 4-piston caliper, hydraulic disc, stealth
Comandi cambio	SRAM XS-1275, 12-speed, 10-52t
Cambio posteriore	SRAM GX AXS Transmission
Pacco Pignoni	SRAM AXS POD Controller
Catena	SRAM GX Transmission
Guarnitura	SRAM GX Eagle, DUB, 165/170/175mm, 34T
Ingranaggi	34t
Movimento Centrale	SRAM DUB Threaded Wide
Cerchi	Roval Control, Carbon offset design, 29mm internal width, 4mm hook width, Tubeless ready, 28h
Mozzo anteriore	DT Swiss 350, 6-bolt, 15mm Thru-axle, 110mm spacing, 28h straight -pull
Mozzo posteriore	DT Swiss 350 straight-pull, 6-bolt, DT Swiss Ratchet, 12x148mm thru axle, XD freehub body, 28h straight-pull
Raggi	DT Swiss Competition Race Straight-pull
Pneumatico anteriore	Specialized Fast Trak, Control Casing, T7 Compound, 29x2.35
Pneumatico posteriore	Specialized Renegade, Control Casing, T5 Compound, 29x2.35
Camere d'aria	Standard 40mm PV 29x1.75-2.4
Attacco Manubrio	Specialized XC, 3D-forged alloy, 4-bolt, 6-degree rise
Curva manubrio	Specialized Alloy Minirise, 10mm rise, 750mm, 31.8mm clamp
Manopole	SRAM Slip on with Twist-Loc
Sella	Body Geometry Power Sport, steel rails
Reggisella	Specialized Alloy, Single Bolt, 30.9mm
Peso	10.40 kg (22 lb, 14.8 oz)
Misura pesata	MD

EPIC WORLD CUP EXPERT	XS	S	M	L	XL
Stack (mm)	603	600	600	614	628
Reach (mm)	380	415	440	465	490
Lunghezza Tubo Sterzo (mm)	93	93	95	110	125
Angolo sterzo (degrees)	66.5	66.5	66.5	66.5	66.5
BB Altezza(mm)	309	313	313	313	313
BB Drop (mm)	61	58	57	57	57
Trail (mm)	113	113	113	113	113
Lunghezza forcella (mm)	516	516	516	516	516
Offset forcella/Rake (mm)	44	44	44	44	44
Avancorsa (mm)	665	701	726	757	788
Lunghezza Batticateni (mm)	430	430	430	430	430
Interasse (mm)	1089	1124	1150	1181	1212
Altezza Standover (mm)	738	761	764	774	786
Lunghezza Piantone (mm)	392	395	410	450	500
Angolo sella (degrees)	74.5	74.5	74.5	74.5	74.5
Lunghezza Tubo orizzontale (mm)	541	581	612	641	670
Lunghezza pedivella (mm)	165	170	170	175	175
Larghezza Manubrio (mm)	750	750	750	750	750
Lunghezza Attacco man. (mm)	60	60	70	70	70
Larghezza Sella (mm)	155	155	143	143	143
Lunghezza Reggisella (mm)	370	370	420	420	420

ART. NR.	DESCRIZIONE	COLORE	MISURA
93125-3001/5	EPIC WC EXPERT	Gloss Cypress Metallic / Ion	XS
93125-3101/5	EPIC WC EXPERT	Satin Metallic Deep Lake /	XS

# S-WORKS STUMPJUMPER 15



Satin Gunmetal / Clay / White MTN /  
Dove Grey / Gloss Bronze

S-WORKS STUMPJUMPER 15	S1	S2	S3	S4	S5	S6
Stack (mm)	608	618	627	640	654	667
Reach (mm)	400	425	450	475	500	530
Lunghezza tubo sterzo (mm)	95	100	110	125	140	155
Angolo sterzo (degrees)	64.5	64.5	64.5	64.5	64.5	64.5
Altezza movimento centrale (mm)	334	337	337	337	337	337
BB Drop (mm)	41	38	38	38	38	38
Trail (mm)	129	130	130	130	130	130
Lunghezza forcella (mm)	551	561	561	561	561	561
Offset forcella/Rake (mm)	44	44	44	44	44	44
Avancorsa (mm)	720	751	780	812	843	879
Lunghezza Batticateni (mm)	430	432	435	435	445	445
Interasse (mm)	1149	1181	1213	1244	1285	1322
Lunghezza Tubo Orizz. virtuale (mm)	541	573	595	624	647	677
Altezza Standover (mm)	738	751	745	745	745	751
Lunghezza piantone (mm)	385	385	405	425	445	465
Angolo Sella (degrees)	78	77	77	76.5	76.5	76.5
Saddle Height for Effective ST Angle (mm)	645	690	735	780	825	870
Max. Inserimento Reggisella (mm)	245	245	255	255	285	285
Min. Inserimento Reggisella (mm)	80	80	80	80	80	80
Lunghezza pedivella (mm)	165	165	165	170	170	170
Larghezza Manubrio (mm)	780	780	800	800	800	800
Lunghezza Attacco man. (mm)	35	35	35	35	35	35
Larghezza Sella (mm)	155	155	143	143	143	143
Lunghezza Reggisella (mm)	125	150	170	170	170	170

## SPECIFICHE TECNICHE

Specialized si riserva il diritto di modificare le caratteristiche senza preavviso.

Telaio	FACT 11m carbon chassis, rear-end, and link, Trail Geometry, SWAT™ Door integration, head tube angle adjustment, threaded BB, internal brake and dropper cable routing, 12x148mm dropouts, sealed cartridge bearing pivots, SRAM UDH compatible, 145mm of travel
Componenti SWAT	SWAT 4.0 internal downtube storage
Ammortizzatore Post.	FOX FLOAT Factory with Specialized GENIE Shock Tech, Ride Dynamics Trail Tune, 2-position lever w/3 setting Open mode tuning range, LSR adjustment, S1:210x52.5mm, S2-S6:210x55mm
Forcella	FOX FLOAT 36 Factory, GRIP X2 damper, HS and LS rebound and compression adjustment, 15x110mm QR axle, 44mm offset, S1:140mm of travel, S2-S6:150mm of travel
Attacco Manubrio	Deity, 35mm clamp, 35mm length
Manubrio	Royal Traverse SL Carbon, riser bar, 6-degree upsweep, 8-degree backsweep, 30mm rise, S1-S2: 780mm; S3-S6: 800mm
Manopole	Deity Lockjaw
Freno anteriore	SRAM Maven Ultimate, 4-piston caliper, hydraulic disc, 200mm HS2 Rotor
Freno posteriore	SRAM Maven Ultimate, 4-piston caliper, hydraulic disc, S1-S2: 180mm, S3-S6: 200mm HS2 Rotor
Cambio posteriore	SRAM XX Eagle Transmission Derailleur
Comandi cambio	SRAM AXS POD Ultimate Controller
Pacco Pignoni	SRAM XX Eagle SL Transmission Cassette, 12spd, 10-52t
Catena	SRAM XX Eagle SL Transmission Flattop Chain
Guarnitura	SRAM XX Eagle Crankset, 32T ring, Integrated Guard, 55mm Chainline, S1-S3:165mm, S4-S6: 170mm
Movimento Centrale	SRAM DUB, BSA 73mm Wide, Threaded
Cerchi	Royal Traverse SL II, hookless carbon, 30mm inner width, tubeless ready, 28h, Front: 29, Rear: S1-S2: 27.5, S3-S6: 29
Mozzo anteriore	DT Swiss 240, 15x110mm, 28h
Mozzo posteriore	DT Swiss 240, 12x148mm, 28h
Raggi	DT Swiss Aerolite
Pneumatico anteriore	Butcher, GRID TRAIL casing, GRIPTON® T9 compound, 2Bliss Ready, 29x2.3"
Pneumatico posteriore	Eliminator, GRID TRAIL casing, GRIPTON® T7 compound, 2Bliss Ready, S1-S2: 27.5x2.3, S3-S6: 29x2.3"
Sella	Power Pro Mirror, Hollow Ti rails, S1-S2: 155mm, S3-S6: 143mm
Camere d'aria	Standard, Presta valve
Reggisella	RockShox, Reverb AXS, 30.9, S1: 125mm, S2: 150mm, S3-S6: 170mm
Collarino Sella	Alloy, 38.6mm
Peso	221406
Peso	13.56kg (29 lb, 14.3 oz)
Misura pesata	S4

ART. NR.	DESCRIZIONE	COLORE	MISURA
93325-0001	SJ 15 SW	Satin Gunmetal / Clay / White MTN / Dove Grey / Gloss Bronze	S1
93325-0002			S2
93325-0003			S3
93325-0004			S4
93325-0005			S5
93325-0006			S6

Disponibile Online e Pickup in store

# STUMPJUMPER 15 PRO



Satin Green Tint / Gunmetal /  
Satin Metal Sulphur

STUMPJUMPER 15 PRO	S1	S2	S3	S4	S5	S6
Stack (mm)	608	618	627	640	654	667
Reach (mm)	400	425	450	475	500	530
Lunghezza tubo sterzo (mm)	95	100	110	125	140	155
Angolo sterzo (degrees)	64.5	64.5	64.5	64.5	64.5	64.5
Altezza movimento centrale (mm)	334	337	337	337	337	337
BB Drop (mm)	41	38	38	38	38	38
Trail (mm)	129	130	130	130	130	130
Lunghezza forcella (mm)	551	561	561	561	561	561
Offset forcella/Rake (mm)	44	44	44	44	44	44
Avancorsa (mm)	720	751	780	812	843	879
Lunghezza Batticateni (mm)	430	432	435	435	445	445
Interasse (mm)	1149	1181	1213	1244	1285	1322
Lunghezza Tubo Orizz. virtuale (mm)	541	573	595	624	647	677
Altezza Standover (mm)	738	751	745	745	745	751
Lunghezza piantone (mm)	385	385	405	425	445	465
Angolo Sella (degrees)	78	77	77	76.5	76.5	76.5
Saddle Height for Effective ST Angle (mm)	645	690	735	780	825	870
Max. Inserimento Reggisella (mm)	245	245	255	255	285	285
Min. Inserimento Reggisella (mm)	80	80	80	80	80	80
Lunghezza pedivella (mm)	165	165	165	170	170	170
Larghezza Manubrio (mm)	780	780	800	800	800	800
Lunghezza Attacco man. (mm)	40	40	40	40	40	40
Larghezza Sella (mm)	155	155	143	143	143	143
Lunghezza Reggisella (mm)	125	160	185	185	213	213

## SPECIFICHE TECNICHE

Specialized si riserva il diritto di modificare le caratteristiche senza preavviso.

Telaio	FACT 11m carbon chassis and rear-end, Trail Geometry, SWAT™ Door integration, head tube angle adjustment, threaded BB, internal brake and dropper cable routing, 12x148mm dropouts, sealed cartridge bearing pivots, SRAM UDH compatible, 145mm of travel
Componenti SWAT	SWAT 4.0 internal downtube storage
Ammortizzatore Post.	FOX FLOAT Factory with Specialized GENIE Shock Tech, Ride Dynamics Trail Tune, 2-position lever w/3 setting Open mode tuning range, LSR adjustment, S1:210x52.5mm,S2-S6:210x55mm
Forcella	FOX FLOAT 36 Factory, GRIP X2 damper, HS and LS rebound and compression adjustment, 15x110mm QR axle, 44mm offset, S1:140mm of travel, S2-S6:150mm of travel
Attacco Manubrio	Industry 9 Mountain stem, 35mm clamp, 40mm length
Manubrio	Roval Traverse SL Carbon, riser bar, 6-degree upsweep, 8-degree backsweep, 30mm rise, S1-S2: 780mm: S3-S6: 800mm
Manopole	Deity Lockjaw
Freno anteriore	SRAM Maven Silver, 4-piston caliper, hydraulic disc, 200mm HS2 Rotor
Freno posteriore	SRAM Maven Silver, 4-piston caliper, hydraulic disc, S1-S2: 180mm, S3-S6: 200mm HS2 Rotor
Comandi cambio	SRAM AXS POD Controller
Cambio posteriore	SRAM X0 Eagle Transmission Derailleur
Pacco Pignoni	SRAM X0 Eagle Transmission Cassette, 12spd, 10-52t
Catena	SRAM X0 Eagle Transmission Flattop Chain
Guarnitura	SRAM X0 Eagle Crankset, 32T ring, Integrated Guard, 55mm Chainline, S1-S3:165mm, S4-S6: 170mm
Movimento Centrale	SRAM DUB, BSA 73mm Wide, Threaded
Cerchi	Roval Traverse SL II, hookless carbon, 30mm inner width, tubeless ready, Front: 29, Rear: S1-S2: 27.5, S3- S6: 29
Mozzo anteriore	Industry 9 1/1, 15x110mm, 28h
Mozzo posteriore	Industry 9 1/1, 12x148mm, 28h
Raggi	Sapim D-Light
Pneumatico anteriore	Butcher, GRID TRAIL casing, GRIPTON® T9 compound, 2Bliss Ready, 29x2.3"
Pneumatico posteriore	Eliminator, GRID TRAIL casing, GRIPTON® T7 compound, 2Bliss Ready, S1-S2: 27.5x2.3, S3- S6: 29x2.3"
Camere d'aria	Standard, Presta valve
Sella	Bridge Expert with MIMIC, Hollow Ti rails, S1-S2: 155mm, S3-S6: 143mm
Reggisella	Bike Yoke, Revive Max, 34.9, S1: 125mm, S2: 160mm, S3-S4: 185mm, S5-S6: 213mm
Collarino Sella	Alloy, 38.6mm
Peso	221403
Peso	13.99kg (30 lb, 13.5 oz)
Misura pesata	S4

ART. NR.	DESCRIZIONE	COLORE	MISURA
<b>93325-1001</b>	SJ 15 PRO	Satin Green Tint / Gunmetal / Satin Metal Sulphur	<b>S1</b>
93325-1002			S2
93325-1003			S3
93325-1004			S4
93325-1005			S5
<b>93325-1006</b>			<b>S6</b>

Disponibile Online e Pickup in store

# STUMPJUMPER 15 EXPERT



Gloss Gunmetal / White Mountains



Satin Electric Green / Satin Forest Green

STUMPJUMPER 15 EXPERT	S1	S2	S3	S4	S5	S6
Stack (mm)	608	618	627	640	654	667
Reach (mm)	400	425	450	475	500	530
Lunghezza tubo sterzo (mm)	95	100	110	125	140	155
Angolo sterzo (degrees)	64.5	64.5	64.5	64.5	64.5	64.5
Altezza movimento centrale (mm)	334	337	337	337	337	337
BB Drop (mm)	41	38	38	38	38	38
Trail (mm)	129	130	130	130	130	130
Lunghezza forcella (mm)	551	561	561	561	561	561
Offset forcella/Rake (mm)	44	44	44	44	44	44
Avancorsa (mm)	720	751	780	812	843	879
Lunghezza Batticateni (mm)	430	432	435	435	445	445
Interasse (mm)	1149	1181	1213	1244	1285	1322
Lunghezza Tubo Orizz. virtuale (mm)	541	573	595	624	647	677
Altezza Standover (mm)	738	751	745	745	745	751
Lunghezza piantone (mm)	385	385	405	425	445	465
Angolo Sella (degrees)	78	77	77	76.5	76.5	76.5
Saddle Height for Effective ST Angle (mm)	645	690	735	780	825	870
Max. Inserimento Reggisella (mm)	245	245	255	255	285	285
Min. Inserimento Reggisella (mm)	80	80	80	80	80	80
Lunghezza pedivella (mm)	165	165	165	170	170	170
Larghezza Manubrio (mm)	780	780	800	800	800	800
Lunghezza Attacco man. (mm)	40	40	40	40	40	40
Larghezza Sella (mm)	155	155	143	143	143	143
Lunghezza Reggisella (mm)	125	150	170	200	200	200

## SPECIFICHE TECNICHE

Specialized si riserva il diritto di modificare le caratteristiche senza preavviso.

Telaio	FACT 11m carbon chassis and rear-end, Trail Geometry, SWAT™ Door integration, head tube angle adjustment, threaded BB, internal brake and dropper cable routing, 12x148mm dropouts, sealed cartridge bearing pivots, SRAM UDH compatible, 145mm of travel
Componenti SWAT	SWAT 4.0 internal downtube storage
Ammortizzatore Post.	FOX FLOAT Performance Elite with Specialized GENIE Shock Tech, Ride Dynamics Trail Tune, 2-position lever w/3 setting Open mode tuning range, LSR adjustment, S1:210x52.5mm, S2-S6:210x55mm
Forcella	FOX FLOAT 36 Performance Elite, GRIP X2 damper, HS and LS rebound and compression adjustment, 15x110mm QR axle, 44mm offset, S1:140mm of travel, S2-S6:150mm of travel
Attacco Manubrio	Alloy Trail Stem, 35mm bar bore
Sella	Bridge Comp, Hollow Cr-mo rails, S1-S2: 155mm, S3-S6: 143mm
Manubrio	Specialized, 6000 series alloy, 6-degree upsweep, 8-degree backsweep. S1-S2: 780 width, 20mm rise; S3-S4: 800 width, 30mm rise; S5-S6: 800 width, 40mm rise
Manopole	Deity Lockjaw
Freno anteriore	SRAM Maven Bronze, 4-piston caliper, hydraulic disc, 200mm HS2 Rotor
Freno posteriore	SRAM Maven Bronze, 4-piston caliper, hydraulic disc, S1-S2: 180mm, S3-S6: 200mm HS2 Rotor
Comandi cambio	SRAM AXS POD Controller
Cambio posteriore	SRAM GX Eagle Transmission Derailleur
Pacco Pignoni	SRAM GX Eagle Transmission Cassette, 12spd, 10-52t
Catena	SRAM GX Eagle Transmission Flattop Chain
Guarnitura	SRAM GX Eagle Crankset, 32T ring, Integrated Guard, 55mm Chainline, S1-S3:165mm, S4-S6: 170mm
Movimento Centrale	SRAM DUB, BSA 73mm Wide, Threaded
Cerchi	Roval Traverse, hookless alloy, 30mm inner width, tubeless ready, Front: 29, Rear: S1-S2: 27.5, S3- S6: 29
Mozzo anteriore	DT Swiss 370, 15x110mm, 28h
Mozzo posteriore	DT Swiss 370, 12x148mm, 28h
Raggi	Sapim Force
Pneumatico anteriore	Butcher, GRID TRAIL casing, GRIPTON® T9 compound, 2Bliss Ready, 29x2.3"
Pneumatico posteriore	Eliminator, GRID TRAIL casing, GRIPTON® T7 compound, 2Bliss Ready, S1-S2: 27.5x2.3, S3- S6: 29x2.3"
Camere d'aria	Standard, Presta valve
Reggisella	PNW Loam Dropper, tool-less travel adjust, Range lever, 34.9, S1: 125mm, S2: 150mm, S3: 170mm, S4-S6: 200mm
Collarino Sella	Alloy, 38.6mm
Peso	221401
Peso	14.47kg (31 lb, 14.4 oz)
Misura pesata	S4

ART. NR.	DESCRIZIONE	COLORE	MISURA
93325-3102/5	SJ 15 EXPERT	Gloss Gunmetal / White Mountains	S2- S5
<b>93325-3101/3106</b>			<b>S1/S6</b>
93325-3002/5	SJ 15 EXPERT	Satin Electric Green / Satin Forest Green	S2 - S5
<b>93325-3001/3006</b>			<b>S1/S6</b>

Disponibile Online e Pickup in store

# STUMPJUMPER 15 COMP



GLOSS SEAFOAM / SILVER DUST



SATIN BURNT GOLD / GUNMETAL

STUMPJUMPER 15 COMP	S1	S2	S3	S4	S5	S6
Stack (mm)	608	618	627	640	654	667
Reach (mm)	400	425	450	475	500	530
Lunghezza tubo sterzo (mm)	95	100	110	125	140	155
Angolo sterzo (degrees)	64.5	64.5	64.5	64.5	64.5	64.5
Altezza movimento centrale (mm)	334	337	337	337	337	337
BB Drop (mm)	41	38	38	38	38	38
Trail (mm)	129	130	130	130	130	130
Lunghezza forcella (mm)	551	561	561	561	561	561
Offset forcella/Rake (mm)	44	44	44	44	44	44
Avancorsa (mm)	720	751	780	812	843	879
Lunghezza Batticateni (mm)	430	432	435	435	445	445
Interasse (mm)	1149	1181	1213	1244	1285	1322
Lunghezza Tubo Orizz. virtuale (mm)	541	573	595	624	647	677
Altezza Standover (mm)	738	751	745	745	745	751
Lunghezza piantone (mm)	385	385	405	425	445	465
Angolo Sella (degrees)	78	77	77	76.5	76.5	76.5
Saddle Height for Effective ST Angle (mm)	645	690	735	780	825	870
Max. Inserimento Reggisella (mm)	245	245	255	255	285	285
Min. Inserimento Reggisella (mm)	80	80	80	80	80	80
Lunghezza pedivella (mm)	165	165	165	170	170	170
Larghezza Manubrio (mm)	780	780	800	800	800	800
Lunghezza Attacco man. (mm)	40	40	40	40	40	40
Larghezza Sella (mm)	155	155	143	143	143	143
Lunghezza Reggisella (mm)	125	150	170	190	190	190

## SPECIFICHE TECNICHE

Specialized si riserva il diritto di modificare le caratteristiche senza preavviso.

Telaio	FACT 11m carbon chassis and rear-end, Trail Geometry, SWAT™ Door integration, head tube angle adjustment, threaded BB, internal brake and dropper cable routing, 12x148mm dropouts, sealed cartridge bearing pivots, SRAM UDH compatible, 145mm of travel
Componenti SWAT	SWAT 4.0 internal downtube storage
Ammortizzatore Post.	FOX FLOAT Performance with Specialized GENIE Shock Tech, Ride Dynamics Trail Tune, 2-position lever w/ LSR adjustment, S1:210x52.5mm, S2-S6:210x55mm
Forcella	FOX FLOAT 36 Rhythm, GRIP damper, two position Sweep adjustment, 15x110mm QR axle, 44mm offset, S1:140mm of travel, S2-S6:150mm of travel
Attacco Manubrio	Alloy Trail Stem, 35mm bar bore
Manopole	Specialized Trail Grips
Sella	Bridge Comp, Hollow Cr-mo rails, S1-S2: 155mm, S3-S6: 143mm
Manubrio	Specialized, 6000 series alloy, 6-degree upsweep, 8-degree backsweep. S1-S2: 780 width, 20mm rise; S3-S4: 800 width, 30mm rise; S5-S6: 800 width, 40mm rise
Freno anteriore	SRAM Maven Bronze, 4-piston caliper, hydraulic disc, 200mm
Freno posteriore	SRAM Maven Bronze, 4-piston caliper, hydraulic disc, S1-S2: 180mm, S3-S6: 200mm
Comandi cambio	SRAM AXS POD Controller
Cambio posteriore	SRAM S1000 Eagle Transmission Derailleur
Pacco Pignoni	SRAM XS-1270 Transmission Cassette, 12spd, 10-52t
Catena	SRAM GX Eagle Transmission Flattop Chain
Guarnitura	SRAM S1000 Crankset, 32T ring, Integrated Guard, 55mm Chainline, S1-S3:165mm, S4-S6: 170mm
Movimento Centrale	SRAM DUB, BSA 73mm Wide, Threaded
Cerchi	Specialized, hookless alloy, 30mm inner width, tubeless ready, Front: 29, Rear: S1-S2:27.5, S3-S6:29
Mozzo anteriore	Alloy, sealed cartridge bearings, 15x110mm thru-axle, 28h
Mozzo posteriore	Alloy, sealed cartridge bearings, 12x148mm thru-axle, 28h
Raggi	DT Swiss Industry
Pneumatico anteriore	Butcher, GRID TRAIL casing, GRIPTON® T9 compound, 2Bliss Ready, 29x2.3"
Pneumatico posteriore	Eliminator, GRID TRAIL casing, GRIPTON® T7 compound, 2Bliss Ready, S1-S2: 27.5x2.3, S3-S6: 29x2.3"
Camere d'aria	Standard, Presta valve
Reggisella	X-Fusion Manic, infinite adjustable, two-bolt head, bottom mount cable routing, remote SLR LE lever, 34.9, S1: 125mm, S2: 150mm, S3: 170mm, S4-S6: 190mm
Collarino Sella	Alloy, 38.6mm
Peso	221395
Peso	14.87kg (32 lb, 12.5 oz)
Misura pesata	S4

ART. NR.	DESCRIZIONE	COLORE	MISURA
93325-5001/6	SJ 15 COMP	GLOSS SEAFOAM / SILVER DUST	S1 - S6
93325-5101/6	SJ 15 COMP	SATIN BURNT GOLD / GUNMETAL	S1 - S6

# STUMPJUMPER 15 ÖHLINS COIL



Satin Copper Speckle / SatinSilver Dust

STUMPJUMPER 15 ÖHLINS COIL	S2	S3	S4	S5	S6
Stack (mm)	621	630	644	657	671
Reach (mm)	420	445	470	495	525
Lunghezza tubo sterzo (mm)	100	110	125	140	155
Angolo sterzo (degrees)	64	64	64	64	64
Altezza movimento centrale (mm)	340	340	340	340	340
BB Drop (mm)	35	35	35	35	35
Trail (mm)	134	134	134	134	134
Lunghezza forcella (mm)	573	573	573	573	573
Offset forcella/Rake (mm)	44	44	44	44	44
Avancorsa (mm)	755	785	816	848	884
Lunghezza Batticateni (mm)	432	432	432	442	442
Interasse (mm)	1186	1216	1247	1288	1325
Lunghezza Tubo Orizz. virtuale (mm)	574	596	625	649	678
Altezza Standover (mm)	751	745	745	745	751
Lunghezza piantone (mm)	385	405	425	445	465
Angolo Sella (degrees)	76.5	76.5	76	76	76
Saddle Height for Effective ST Angle (mm)	690	735	780	825	870
Max. Inserimento Reggisella (mm)	245	255	255	285	285
Min. Inserimento Reggisella (mm)	80	80	80	80	80
Lunghezza pedivella (mm)	165	165	170	170	170
Larghezza Manubrio (mm)	810	810	810	810	810
Lunghezza Attacco man. (mm)	35	35	35	35	35
Larghezza Sella (mm)	155	143	143	143	143
Lunghezza Reggisella (mm)	150	170	200	200	200

## SPECIFICHE TECNICHE

	Specialized si riserva il diritto di modificare le caratteristiche senza preavviso.
Telaio	FACT 11m carbon chassis and rear-end, Trail Geometry, SWAT™ Door integration, head tube angle adjustment, threaded BB, internal brake and dropper cable routing, 12x148mm dropouts, sealed cartridge bearing pivots, SRAM UDH compatible, 145mm of travel
Componenti SWAT	SWAT 4.0 internal downtube storage
Ammortizzatore Post.	Öhlins TTX 22 M Coil, Ride Dynamics trail tune, external rebound adjust, external high and low speed compression adjustment, 210x55, S2: 434lbs, S3: 480lbs, S4: 525lbs, S5: 571lbs, S6: 605lbs
Forcella	Öhlins RFX38 M.2 29, TTX Twin Tube Damping, external low speed rebound adjust, external high and low speed compression adjustment, 15x110mm, 44mm offset, 160mm of travel
Attacco Manubrio	Deity, 35mm clamp, 35mm length
Sella	Bridge Comp, Hollow Cr-mo rails, S1-S2: 155mm, S3-S6: 143mm
Manubrio	Deity, Racepoint, 5-degree upsweep, 9-degree backsweep, 810 width, S2: 25mm rise; S3-S6: 38mm rise
Freno anteriore	TRP DH-R EVO, 4-piston caliper, hydraulic disc, 220mm
Manopole	Diety, Supracush, Black
Freno posteriore	TRP DH-R EVO, 4-piston caliper, hydraulic disc, 203mm
Comandi cambio	SRAM AXS POD Controller
Cambio posteriore	SRAM GX Eagle Transmission Derailleur
Pacco Pignoni	SRAM GX Eagle Transmission Cassette, 12spd, 10-52t
Catena	SRAM GX Eagle Transmission Flattop Chain
Guarnitura	SRAM GX Eagle Crankset, 32T ring, 55mm Chainline, S2-S3:165mm, S4-S6: 170mm
Movimento Centrale	SRAM DUB, BSA 73mm Wide, Threaded
Cerchi	Roval Traverse, hookless alloy, 30mm inner width, tubeless ready, Front: 29, Rear: 27.5
Mozzo anteriore	DT Swiss 370, 15x110mm, 28h
Mozzo posteriore	DT Swiss 370, 12x148mm, 32h
Raggi	Sapim Force
Pneumatico anteriore	Butcher, GRID TRAIL casing, GRIPTON® T9 compound, 2Bliss Ready, 29x2.3"
Pneumatico posteriore	Eliminator, GRID GRAVITY casing, GRIPTON® T9/T7 compound, 2Bliss Ready, 27.5x2.3"
Camere d'aria	Standard, Presta valve
Reggisella	PNW Loam Dropper, tool-less travel adjust, Range lever, 34.9, S2: 150mm, S3: 170mm, S4-S6: 200mm
Collarino Sella	Alloy, 38.6mm
Peso	221405
Peso	15.30kg (33 lb, 11.7 oz)
Misura pesata	S4

ART. NR.	DESCRIZIONE	COLORE	MISURA
93325-7502/6	SJ 15 ÖHLINS COIL	Satin Copper Speckle / SatinSilver Dust	S2 - S6

# STUMPJUMPER 15 FOX COIL ALLOY



Satin Brushed Aluminum / Cast Blue

STUMPJUMPER 15 FOX COIL ALLOY	S2	S3	S4	S5	S6
Stack (mm)	621	630	644	657	671
Reach (mm)	420	445	470	495	525
Lunghezza tubo sterzo (mm)	100	110	125	140	155
Angolo sterzo (degrees)	64	64	64	64	64
Altezza movimento centrale (mm)	340	340	340	340	340
BB Drop (mm)	35	35	35	35	35
Trail (mm)	134	134	134	134	134
Lunghezza forcella (mm)	573	573	573	573	573
Offset forcella/Rake (mm)	44	44	44	44	44
Avancorsa (mm)	755	785	816	848	884
Lunghezza Batticateni (mm)	432	432	432	442	442
Interasse (mm)	1186	1216	1247	1288	1325
Lunghezza Tubo Orizz. virtuale (mm)	574	596	625	649	678
Altezza Standover (mm)	751	745	745	745	751
Lunghezza Piantone (mm)	385	405	425	445	465
Angolo sella (degrees)	76.5	76.5	76	76	76
Altezza sella per Angolo Sella effettivo (mm)	690	735	780	825	870
Max. Inserimento Reggisella (mm)	245	255	255	285	285
Min. Inserimento Reggisella (mm)	80	80	80	80	80
Lunghezza pedivella (mm)	165	165	170	170	170
Larghezza Manubrio (mm)	810	810	810	810	810
Lunghezza Attacco man. (mm)	35	35	35	35	35
Larghezza Sella (mm)	155	143	143	143	143
Lunghezza Reggisella (mm)	150	170	200	200	200

## SPECIFICHE TECNICHE

Specialized si riserva il diritto di modificare le caratteristiche senza preavviso.

Componenti SWAT	SWAT internal downtube storage
Telaio	M5 Alloy chassis and rear-end, Trail Geometry, SWAT™ Door integration, head tube angle adjustment, threaded BB, internal cable routing, 12x148mm dropouts, sealed cartridge bearing pivots, SRAM UDH compatible, 145mm of travel
Collarino Sella	Alloy, 38.6mm
Ammortizzatore Post.	FOX DHX Factory, Ride Dynamics Trail Tune, 210x55mm, S2: 400lbs, S3: 450lbs, S4: 500lbs, S5: 550lbs, S6: 600lbs
Forcella	FOX FLOAT 38 Factory, GRIP X2 damper, HS and LS rebound and compression adjustment, 15x110mm QR axle, 44mm offset, 160mm of travel
Freno anteriore	TRP DH-R EVO, 4-piston caliper, hydraulic disc, 220mm
Freno posteriore	TRP DH-R EVO, 4-piston caliper, hydraulic disc, 203mm
Comandi cambio	Shimano SLX, M7100, 12spd
Cambio posteriore	Shimano SLX M7100, SGS, 12-speed
Pacco Pignoni	Shimano SLX, CS-M7100, 12-speed, 10-51t
Catena	Shimano SLX, M7100, 12-speed
Guarnitura	Shimano SLX, M7120, 32T ring, 55mm chainline, S2-S3:165mm, S4-S6: 170mm
Movimento Centrale	Shimano, BB-MT801, Threaded
Cerchi	Roval Traverse, hookless alloy, 30mm inner width, tubeless ready, Front: 29, Rear: 27.5
Mozzo anteriore	DT Swiss 370, 15x110mm, 28h
Mozzo posteriore	DT Swiss 370, 12x148mm, 32h
Raggi	Sapim Force
Pneumatico anteriore	Butcher, GRID TRAIL casing, GRIPTON® T9 compound, 2Bliss Ready, 29x2.3"
Pneumatico posteriore	Eliminator, GRID GRAVITY casing, GRIPTON® T9/T7 compound, 2Bliss Ready, 27.5x2.3"
Camere d'aria	Standard, Presta valve
Attacco Manubrio	Deity, 35mm clamp, 35mm length
Manubrio	Deity, Racepoint, 5-degree upsweep, 9-degree backsweep, 810 width, S2: 25mm rise; S3-S6: 38mm rise
Manopole	Deity, Knuckleduster, Black
Sella	Bridge Comp, Hollow Cr-mo rails, S1-S2: 155mm, S3-S6: 143mm
Reggisella	PNW Loam OE Dropper, tool-less travel adjust, Range lever, 34.9, S2: 150mm, S3: 170mm, S4-S6: 200mm
Peso	16.90 kg (37 lb, 4.1 oz)
Misura pesata	S4

ART. NR.	DESCRIZIONE	COLORE	MISURA
93325-7402/6	SJ ALLOY FOX COIL	Satin Brushed Aluminum /	S2-S6

# STUMPJUMPER 15 COMP ALLOY



Gloss Smoke / Cool Grey



Satin Powder Indigo / Smoke

STUMPJUMPER 15 COMP ALLOY	S1	S2	S3	S4	S5	S6
Stack (mm)	608	618	627	640	654	667
Reach (mm)	400	425	450	475	500	530
Lunghezza tubo sterzo (mm)	95	100	110	125	140	155
Angolo sterzo (degrees)	64.5	64.5	64.5	64.5	64.5	64.5
Altezza movimento centrale (mm)	334	337	337	337	337	337
BB Drop (mm)	41	38	38	38	38	38
Trail (mm)	129	130	130	130	130	130
Lunghezza forcella (mm)	551	561	561	561	561	561
Offset forcella/Rake (mm)	44	44	44	44	44	44
Avancorsa (mm)	720	751	780	812	843	879
Lunghezza Batticateni (mm)	430	432	435	435	445	445
Interasse (mm)	1149	1181	1213	1244	1285	1322
Lunghezza Tubo Orizz. virtuale (mm)	541	573	595	624	647	677
Altezza Standover (mm)	738	751	745	745	745	751
Lunghezza Piantone (mm)	385	385	405	425	445	465
Angolo sella (degrees)	78	77	77	76.5	76.5	76.5
Altezza sella per Angolo Sella effettivo (mm)	645	690	735	780	825	870
Max. Inserimento Reggisella (mm)	245	245	255	255	285	285
Min. Inserimento Reggisella (mm)	80	80	80	80	80	80
Lunghezza pedivella (mm)	165	165	165	170	170	170
Larghezza Manubrio (mm)	780	780	800	800	800	800
Lunghezza Attacco man. (mm)	40	40	40	40	40	40
Larghezza Sella (mm)	155	155	143	143	143	143
Lunghezza Reggisella (mm)	125	150	170	190	190	190

SPECIFICHE TECNICHE	Specialized si riserva il diritto di modificare le caratteristiche senza preavviso.
Componenti SWAT	SWAT internal downtube storage
Telaio	M5 Alloy chassis and rear-end, Trail Geometry, SWAT™ Door integration, head tube angle adjustment, threaded BB, internal cable routing, 12x148mm dropouts, sealed cartridge bearing pivots, SRAM UDH compatible, 145mm of travel
Collarino Sella	Alloy, 38.6mm
Ammortizzatore Post.	FOX FLOAT Performance with Specialized GENIE Shock Tech, Ride Dynamics Trail Tune, 2-position lever w/ LSR adjustment, S1-S2:210x52.5mm, S2-S6:210x55mm
Forcella	FOX FLOAT 36 Rhythm, GRIP damper, two position Sweep adjustment, 15x110mm QR axle, 44mm offset, S1-S2:140mm of travel, S2-S6:150mm of travel
Freno anteriore	TRP Trail EVO, 4-piston caliper, hydraulic disc, 203mm
Freno posteriore	TRP Trail EVO, 4-piston caliper, hydraulic disc, S1-S2: 180mm, S3-S6: 203mm
Comandi cambio	Shimano SLX, M7100, 12spd
Cambio posteriore	Shimano SLX M7100, SGS, 12-speed
Pacco Pignoni	Shimano SLX, CS-M7100, 12-speed, 10-51t
Catena	Shimano SLX, M7100, 12-speed
Guarnitura	Shimano SLX, M7120, 32T ring, 55mm chainline, S1-S3:165mm, S4-S6: 170mm
Movimento Centrale	Shimano, BB-MT801, Threaded
Cerchi	Specialized, hookless alloy, 30mm inner width, tubeless ready, Front: 29, Rear: S1-S2: 27.5, S3- S6: 29
Mozzo anteriore	Alloy, sealed cartridge bearings, 15x110mm thru-axle, 28h
Mozzo posteriore	Alloy, sealed cartridge bearings, 12x148mm thru-axle, 28h
Raggi	DT Swiss Industry
Pneumatico anteriore	Butcher, GRID TRAIL casing, GRIPTON® T9 compound, 2Bliss Ready, 29x2.3"
Pneumatico posteriore	Eliminator, GRID TRAIL casing, GRIPTON® T7 compound, 2Bliss Ready, S1-S2: 27.5x2.3, S3- S6: 29x2.3"
Camere d'aria	Standard, Presta valve
Attacco Manubrio	Alloy Trail Stem, 35mm bar bore
Manubrio	Specialized, 6000 series alloy, 6-degree upsweep, 8-degree backsweep. S1-S2: 780 width, 20mm rise; S3-S4: 800 width, 30mm rise; S5-S6: 800 width, 40mm rise
Manopole	Specialized Trail Grips
Sella	Bridge Comp, Hollow Cr-mo rails, S1-S2: 155mm, S3-S6: 143mm
Reggisella	X-Fusion Manic, infinite adjustable, two-bolt head, bottom mount cable routing, remote SLR LE lever, 34.9, S1: 125mm, S2: 150mm, S3: 170mm, S4-S6: 190mm
Peso	16.17 kg (35 lb, 10.4 oz)
Misura pesata	S4

ART. NR.	DESCRIZIONE	COLORE	MISURA
93325-5401/6	SJ COMP ALLOY	Gloss Smoke / Cool Grey	S1-S6
93325-5501/6	SJ COMP ALLOY	Satin Powder Indigo / Smoke	S1-S6

# STUMPJUMPER 15 ALLOY



GLOSS WHITE MOUNTAINS / DARK MOSS GREEN



SATIN CAST BLUE / DOVE GREY

STUMPJUMPER 15 ALLOY	S1	S2	S3	S4	S5	S6
Stack (mm)	608	618	627	640	654	667
Reach (mm)	400	425	450	475	500	530
Lunghezza tubo sterzo (mm)	95	100	110	125	140	155
Angolo sterzo (degrees)	64.5	64.5	64.5	64.5	64.5	64.5
Altezza movimento centrale (mm)	334	337	337	337	337	337
BB Drop (mm)	41	38	38	38	38	38
Trail (mm)	129	130	130	130	130	130
Lunghezza forcella (mm)	551	561	561	561	561	561
Offset forcella/Rake (mm)	44	44	44	44	44	44
Avancorsa (mm)	720	751	780	812	843	879
Lunghezza Batticateni (mm)	430	432	435	435	445	445
Interasse (mm)	1149	1181	1213	1244	1285	1322
Lunghezza Tubo Orizz. virtuale (mm)	541	573	595	624	647	677
Altezza Standover (mm)	738	751	745	745	745	751
Lunghezza Piantone (mm)	385	385	405	425	445	465
Angolo sella (degrees)	78	77	77	76.5	76.5	76.5
Altezza sella per Angolo Sella effettivo (mm)	645	690	735	780	825	870
Max. Inserimento Reggisella (mm)	245	245	255	255	285	285
Min. Inserimento Reggisella (mm)	80	80	80	80	80	80
Lunghezza pedivella (mm)	165	165	165	170	170	170
Larghezza Manubrio (mm)	780	780	800	800	800	800
Lunghezza Attacco man. (mm)	40	40	40	40	40	40
Larghezza Sella (mm)	155	155	143	143	143	143
Lunghezza Reggisella (mm)	125	150	170	200	200	200

## SPECIFICHE TECNICHE

Componenti SWAT	SWAT internal downtube storage
Telaio	M5 Alloy chassis and rear-end, Trail Geometry, SWAT™ Door integration, head tube angle adjustment, threaded BB, internal cable routing, 12x148mm dropouts, sealed cartridge bearing pivots, SRAM UDH compatible, 145mm of travel
Collarino Sella	Alloy, 38.6mm
Ammortizzatore Post.	X-Fusion O2 Pro RL, Ride Dynamics Trail Tune, rebound adjust, lockout S1:210x52.5mm, S2-S6:210x55mm
Forcella	RockShox, Psylo Silver, Motion Control Damper, 15x110 axle, 44mm offset, S1:140mm of travel, S2-S6:150mm of travel
Freno anteriore	Shimano, BR-MT420, 4-piston caliper, hydraulic disc, 203mm
Freno posteriore	Shimano, BR-MT420, 4-piston caliper, hydraulic disc, S1-S2: 180mm, S3-S6: 203mm
Comandi cambio	Shimano Deore, M6100, 12spd
Cambio posteriore	Shimano Deore, M6100, 12pd, Shadow Plus
Pacco Pignoni	Shimano Deore M6100, 12spd w/Hyperglide+, 10-51t
Catena	Shimano Deore, M6100, 12-speed
Guarnitura	Shimano Deore, M6120, 30T ring, 55mm chainline, S1-S3:165mm, S4-S6: 170mm
Cerchi	Specialized Alloy, Tubeless Ready, 29mm internal width, 28h, Front: 29, Rear: S1-S2: 27.5, S3-S6: 29
Mozzo anteriore	Alloy, sealed cartridge bearings, 15x110mm thru-axle, 28h
Mozzo posteriore	Alloy, sealed cartridge bearings, 12x148mm thru-axle, 28h
Raggi	Stainless, 14g
Pneumatico anteriore	Butcher, GRID TRAIL casing, GRIPTON® T9 compound, 2Bliss Ready, 29x2.3"
Pneumatico posteriore	Eliminator, GRID TRAIL casing, GRIPTON® T7 compound, 2Bliss Ready, S1-S2: 27.5x2.3, S3-S6: 29x2.3"
Camere d'aria	Standard, Presta valve
Attacco Manubrio	Alloy Trail Stem, 35mm bar bore
Manubrio	Specialized, 6000 series alloy, 6-degree upsweep, 8-degree backsweep. S1-S2: 780 width, 20mm rise; S3-S4: 800 width, 30mm rise; S5-S6: 800 width, 40mm rise
Manopole	Specialized Trail Grips
Sella	Bridge, Steel rails, S1-S2: 155mm, S3-S6: 143mm
Reggisella	TranzX Dropper, remote SLR LE lever, 34.9, S1: 125mm, S2: 150mm, S3: 170mm, S4-S6: 200mm
Peso	16.57 kg (36 lb, 8.5 oz)
Misura pesata	S4

ART. NR.	DESCRIZIONE	COLORE	MISURA
93325-7601/6	SJ ALLOY	GLOSS WHITE MOUNTAINS / DARK MOSS GREEN	S1-S6
93325-7701/6	SJ ALLOY	SATIN CAST BLUE / DOVE GREY	S1-S6

# TELAIO STUMPJUMPER 15 ALLOY



Satin Obsidian / Silver Dust



Satin Olive Green / Metallic Obsidian

## SPECIFICHE TECNICHE

Specialized si riserva il diritto di modificare le caratteristiche senza preavviso.

Componenti SWAT	SWAT Internal Downtube Storage
Telaio	M5 alloy chassis and rear-end, Trail Geometry, SWAT™ Door integration, head tube angle adjustment, threaded BB, internal cable routing, 12x148mm dropouts, sealed cartridge bearing pivots, SRAM UDH compatible, 145mm of travel
Collarino Sella	Alloy, 38.6mm
Ammortizzatore Post.	FOX FLOAT Performance with Specialized GENIE Shock Tech, Ride Dynamics Trail Tune, 2-position lever w/LSR adjustment, S1:210x52.5mm, S2-S6:210x55mm
Peso	4.31 kg (9 lb, 8.0 oz)
Misura pesata	S4

TELAIO STUMPJUMPER 15 ALLOY	S1	S2	S3	S4	S5	S6
Stack (mm)	608	618	627	640	654	667
Reach (mm)	400	425	450	475	500	530
Lunghezza tubo sterzo (mm)	95	100	110	125	140	155
Angolo sterzo (degrees)	64.5	64.5	64.5	64.5	64.5	64.5
Altezza movimento centrale (mm)	334	337	337	337	337	337
BB Drop (mm)	41	38	38	38	38	38
Trail (mm)	129	130	130	130	130	130
Lunghezza forcella (mm)	551	561	561	561	561	561
Offset forcella/Rake (mm)	44	44	44	44	44	44
Avancorsa (mm)	720	751	780	812	843	879
Lunghezza Batticateni (mm)	430	432	435	435	445	445
Interasse (mm)	1149	1181	1213	1244	1285	1322
Lunghezza Tubo Orizz. virtuale (mm)	541	573	595	624	647	677
Altezza Standover (mm)	738	751	745	745	745	751
Lunghezza Piantone (mm)	385	385	405	425	445	465
Angolo sella (degrees)	78	77	77	76.5	76.5	76.5
Altezza sella per Angolo Sella effettivo (mm)	645	690	735	780	825	870
Max. Inserimento Reggisella (mm)	245	245	255	255	285	285
Min. Inserimento Reggisella (mm)	80	80	80	80	80	80

ART. NR.	DESCRIZIONE	COLORE	MISURA
73325-7001/6	SJ ALLOY FRM	Satin Obsidian / Silver Dust	S1-S6
73325-7201/6	SJ ALLOY FRM	Satin Olive Green / Metallic Obsidian	S1-S6

Disponibile Online e Pickup in store



GLOSS REBEL PINK TINT CARBON / FOG TINT

## SPECIFICHE TECNICHE

**Specialized si riserva il diritto di modificare le caratteristiche senza preavviso.**

Telaio	FACT 11m carbon chassis and rear-end, 29 S-Sizing Enduro Race Geometry, Carbon upper and lower links, SRAM Universal Derrailuer Hanger, SWAT™ Door integration, threaded BB, internal cable routing, 12x148mm dropouts, sealed cartridge bearing pivots, 170mm of travel
Collarino Sella	Alloy, 38.6mm
Componenti SWAT	SWAT internal downtube storage
Ammortizzatore Post.	RockShox Vivid Ultimate, Ride Dynamics Trail Tune, adjustable hydraulic bottom out, adjustable rebound and high/low speed compression, 205x60, Trunnion
Identificativo	276009
Peso	3.82kg (8 lb, 6.7 oz)
Misura pesata	S4

TELAIO S-WORKS ENDURO	S2	S3	S4	S5
Stack (BB basso) (mm)	616	620	629	638
Reach (BB basso) (mm)	437	464	487	511
Lunghezza Tubo Sterzo (mm)	95	100	110	120
Angolo sterzo (BB basso) (degrees)	63.9	63.9	63.9	63.9
Angolo Sterzo (mm)	64.3	64.3	64.3	64.3
Altezza BB (BB basso) (mm)	347	347	347	347
Altezza movimento centrale (mm)	354	354	354	354
BB Drop (BB basso) (mm)	28	28	28	28
B-B Drop (mm)	21	21	21	21
Trail (BB basso) (mm)	132	132	132	132
Lunghezza forcella (mm)	581	581	581	581
Offset Forcella/Rake (mm)	46	46	46	46
Avancorsa (BB basso) (mm)	777	806	833	862
Lunghezza Batticateni (mm)	442	442	442	442
Interasse (mm)	1217	1246	1274	1302
Lunghezza Piantone (mm)	400	420	440	465
Angolo Sella (degrees)	76	76	76	76
Lunghezza Tubo Orizz. virtuale (mm)	591	619	644	670

ART. NR.	DESCRIZIONE	COLORE	MISURA
73625-7002/5	SW ENDURO FRM	GLOSS REBEL PINK TINT CARBON	S2 - S5

Disponibile online & Pick Up in Store



SATIN CYPRESS METALLIC / ION METALLIC

ENDURO PRO	S2	S3	S4	S5
Stack (BB basso) (mm)	616	620	629	638
Reach (BB basso) (mm)	437	464	487	511
Lunghezza Tubo Sterzo (mm)	95	100	110	120
Angolo sterzo (BB basso) (degrees)	63.9	63.9	63.9	63.9
Angolo Sterzo (mm)	64.3	64.3	64.3	64.3
Altezza BB (BB basso) (mm)	347	347	347	347
Altezza movimento centrale (mm)	354	354	354	354
BB Drop (BB basso) (mm)	28	28	28	28
B-B Drop (mm)	21	21	21	21
Trail (BB basso) (mm)	132	132	132	132
Lunghezza forcella (mm)	581	581	581	581
Offset Forcella/Rake (mm)	46	46	46	46
Avancorsa (BB basso) (mm)	777	806	833	862
Lunghezza Batticatena (mm)	442	442	442	442
Interasse (mm)	1217	1246	1274	1302
Lunghezza Piantone (mm)	400	420	440	465
Angolo Sella (degrees)	76	76	76	76
Lunghezza Tubo Orizz. virtuale (mm)	591	619	644	670
Lunghezza pedivella (mm)	165	165	170	170
Larghezza Manubrio (mm)	780	800	800	800
Lunghezza Attacco man. (mm)	40	40	40	40
Larghezza Sella (mm)	155	143	143	143
Lunghezza Reggisella (mm)	160	160	185	185

## SPECIFICHE TECNICHE

Specialized si riserva il diritto di modificare le caratteristiche senza preavviso.

Telaio	FACT 11m carbon chassis and rear-end, 29 S-Sizing Enduro Race Geometry, SRAM Universal Derailleur Hanger, SWAT™ Door integration, threaded BB, internal cable routing, 12x148mm dropouts, sealed cartridge bearing pivots, 170mm of travel
Collarino Sella	Alloy, 38.6mm
Componenti SWAT	SWAT internal downtube storage
Ammortizzatore Post.	RockShox Vivid Ultimate, Ride Dynamics Trail Tune, adjustable hydraulic bottom out, adjustable rebound and high/low speed compression, 205x60, Trunnion
Forcella	RockShox Zeb Ultimate, Charger 3.1 damper, 15x110mm, 44mm offset, 170mm of travel
Freno anteriore	SRAM Maven Silver, 4-piston caliper, hydraulic disc, 220mm HS2 Rotor
Freno posteriore	SRAM Maven Silver, 4-piston caliper, hydraulic disc, 200mm HS2 Rotor
Comandi cambio	SRAM AXS POD Controller
Cambio posteriore	SRAM X0 Eagle Transmission Derailleur
Pacco Pignoni	SRAM X0 Eagle Transmission Cassette, 12spd, 10-52t
Catena	SRAM X0 Eagle Transmission Flattop Chain
Guarnitura	SRAM X0 Eagle Crankset, 32T ring, S2-S3:165mm, S5-S6: 170mm
Movimento Centrale	SRAM DUB, BSA 73mm Wide, Threaded
Cerchi	Royal Traverse HD, hookless carbon, 30mm inner width, tubeless ready
Mozzo anteriore	Industry 9 1/1, 15x110mm, 28h
Mozzo posteriore	Industry 9 1/1, 12x148mm, 32h
Raggi	Sapim D-Light
Pneumatico anteriore	Butcher, GRID TRAIL casing, GRIPTON® T9 compound, 2Bliss Ready, 29x2.3"
Pneumatico posteriore	Butcher, GRID GRAVITY casing, GRIPTON® T9 compound, 2Bliss Ready, 29x2.3"
Camere d'aria	Standard, Presta valve
Attacco Manubrio	Industry 9 Mountain stem, 35mm clamp, 40mm length
Manubrio	Royal Traverse SL Carbon, riser bar, 6-degree upsweep, 8-degree backsweep, 30mm rise, S2: 780mm; S3-S5: 800mm
Manopole	Deity Lockjaw
Sella	Bridge Expert with MIMIC, Hollow Ti rails, S2: 155mm, S3-S5: 143mm
Reggisella	Bike Yoke, Revive Max, 34.9, S2-S3: 160mm, S4-S5: 185mm
Identificativo	276010
Peso	16.04kg (35 lb, 5.8 oz)
Misura pesata	S4

ART. NR.	DESCRIZIONE	COLORE	MISURA
93625-3002/5	Enduro Pro	SATIN CYPRESS METALLIC / ION METALLIC	S2 - S5



GLOSS GUNMETAL / WHITE MOUNTAINS

ENDURO COMP	S2	S3	S4	S5
Stack (BB basso) (mm)	616	620	629	638
Reach (BB basso) (mm)	437	464	487	511
Lunghezza Tubo Sterzo (mm)	95	100	110	120
Angolo sterzo (BB basso) (degrees)	63.9	63.9	63.9	63.9
Angolo Sterzo (mm)	64.3	64.3	64.3	64.3
Altezza BB (BB basso) (mm)	347	347	347	347
Altezza movimento centrale (mm)	354	354	354	354
BB Drop (BB basso) (mm)	28	28	28	28
B-B Drop (mm)	21	21	21	21
Trail (BB basso) (mm)	132	132	132	132
Lunghezza forcella (mm)	581	581	581	581
Offset Forcella/Rake (mm)	46	46	46	46
Avancorsa (BB basso) (mm)	777	806	833	862
Lunghezza Batticatena (mm)	442	442	442	442
Interasse (mm)	1217	1246	1274	1302
Lunghezza Piantone (mm)	400	420	440	465
Angolo Sella (degrees)	76	76	76	76
Lunghezza Tubo Orizz. virtuale (mm)	591	619	644	670
Lunghezza pedivella (mm)	165	165	170	170
Larghezza Manubrio (mm)	780	800	800	800
Lunghezza Attacco man. (mm)	40	40	40	40
Larghezza Sella (mm)	155	143	143	143
Lunghezza Reggisella (mm)	150	150	170	170

## SPECIFICHE TECNICHE

Specialized si riserva il diritto di modificare le caratteristiche senza preavviso.

Telaio	FACT 11m carbon chassis and rear-end, 29 S-Sizing Enduro Race Geometry, SRAM Universal Derailleur Hanger, SWAT™ Door integration, threaded BB, internal cable routing, 12x148mm dropouts, sealed cartridge bearing pivots, 170mm of travel
Collarino Sella	Alloy, 38.6mm
Componenti SWAT	SWAT internal downtube storage
Ammortizzatore Post.	RockShox Vivid Select Plus, Ride Dynamics Trail Tune, adjustable hydraulic bottom out, adjustable rebound and compression, 205x60, Trunnion
Forcella	RockShox Zeb Select, Charger RC damper, 15x110mm, 44mm offset, 170mm of travel
Freno anteriore	TRP Trail EVO, 4-piston caliper, hydraulic disc, 220mm
Freno posteriore	TRP Trail EVO, 4-piston caliper, hydraulic disc, 203mm
Comandi cambio	Shimano SLX, M7100, 12spd
Cambio posteriore	Shimano SLX, M7100, SGS, 12-speed
Pacco Pignoni	Shimano SLX, CS-M7100, 12-speed, 10-51t
Catena	Shimano SLX, M7100, 12-speed
Guarnitura	Shimano SLX, M7120, 30T ring, 52mm chainline, S2-S3:165mm, S4-S5: 170mm
Movimento Centrale	Shimano, BB-MT801, Threaded
Cerchi	Specialized, hookless alloy, 30mm inner width, tubeless ready
Mozzo anteriore	Alloy, sealed cartridge bearings, 15x110mm thru-axle, 28h
Mozzo posteriore	Alloy, sealed cartridge bearings, 12x148mm thru-axle, 32h
Raggi	DT Swiss Industry
Pneumatico anteriore	Butcher, GRID TRAIL casing, GRIPTON® T9 compound, 2Bliss Ready, 29x2.3"
Pneumatico posteriore	Butcher, GRID GRAVITY casing, GRIPTON® T9 compound, 2Bliss Ready, 29x2.3"
Camere d'aria	Standard, Presta valve
Attacco Manubrio	Alloy Trail Stem, 35mm bar bore
Manubrio	Specialized, 6061 alloy, 6-degree upsweep, 8-degree backsweep, 30mm rise. S2: 780mm, S3-S5:800mm width
Manopole	Specialized Trail Grips
Sella	Bridge Comp, Hollow Cr-mo rails, S2: 155mm, S3-S5: 143mm
Reggisella	X-Fusion Manic, infinite adjustable, two-bolt head, bottom mount cable routing, remote SRL LE lever, 34.9mm, S2-S3:150mm, S4-S5:170mm
Identificativo	276011
Peso	16.21kg (35 lb, 11.8 oz)
Misura pesata	S4

ART. NR.	DESCRIZIONE	COLORE	MISURA
93625-5002/5	ENDURO COMP	GLOSS GUNMETAL / WHITE MNT	S2 - S5



Gloss Obsidian / Brushed / Chameleon Supernova



Satin Taupe / Black / Brushed

DEMO RACE	S2	S3	S4
Stack (mm)	632	632	632
Stack (29 mid) (mm)	629	629	629
Stack (27.5 mid) (mm)	635	635	635
Reach (mm)	426	446	466
Reach (29 mid) (mm)	430	450	470
Reach (27.5 mid) (mm)	423	443	463
Lunghezza Tubo Sterzo (mm)	105	105	105
Angolo Sterzo (degrees)	62.8	62.8	62.8
Angolo Sterzo (29 mid) (degrees)	63.2	63.2	63.2
Angolo Sterzo (27.5 mid) (degrees)	62.5	62.5	62.5
Altezza movimento centrale (mm)	350	350	350
Altezza movimento centrale (29 mid) (mm)	355	355	355
Altezza movimento centrale (27.5 mid) (mm)	345	345	345
B-B Drop (mm)	25	25	25
Trail (mm)	130	130	130
Trail (29 mid) (mm)	127	127	127
Trail (27.5 mid) (mm)	132	132	132
Forcella Rake/Offset (mm)	56	56	56
Avancorsa (mm)	801	821	841
Avancorsa (29 mid) (mm)	801	821	841
Avancorsa (27.5 mid) (mm)	801	821	841
Lunghezza Batticateni (29) (mm)	448	448	448
Lunghezza Batticateni (27.5) (mm)	438	438	438
Lunghezza Batticateni (mid) (mm)	443	443	443
Interasse (27.5) (mm)	1239	1259	1279
Interasse (29) (mm)	1249	1269	1289
Interasse (mid) (mm)	1244	1264	1284
Lunghezza Piantone (mm)	394	420	420
Angolo Sella (degrees)	78.2	76.8	76.8
Angolo Sella (29 mid) (degrees)	78.5	77.1	77.1
Angolo Sella (27.5 mid) (degrees)	77.8	76.4	76.4

**SPECIFICHE TECNICHE**

Specialized si riserva il diritto di modificare le caratteristiche senza preavviso.

Sella	Body Geometry Henge DH, hollow titanium rails, 130mm
Telaio	M5 alloy, Style-Specific DH Geometry, horst pivot flip chip for 27.5 or 29 rear wheel, BSA threaded BB, full internal cable routing with option for full external brake, 148mm rear spacing, sealed cartridge bearing pivots, replaceable derailleur hanger, 200mm of travel
Collarino Sella	Alloy, 34.9mm
Ammortizzatore Post.	Öhlins TTX22M.2 Coil, external rebound adjust, external high and low speed compression adjustment, Trunnion mount, 225x75
Forcella	Öhlins DH38 M.1 29, TTX Twin Tube Damping, external low speed rebound adjust, external high and low speed compression adjustment, 20x110mm, 58mm offset, 200mm of travel
Freno anteriore	SRAM Maven Ultimate, 4-piston caliper, hydraulic disc, 220mm
Freno posteriore	SRAM Maven Ultimate, 4-piston caliper, hydraulic disc, 200mm
Comandi cambio	SRAM X01 DH, trigger, 7-speed
Cambio posteriore	SRAM X01 DH, 7-speed, trigger
Pacco Pignoni	SRAM X01 DH, 7-speed, 10-24t
Catena	Sram PC1130 w/ Powerlink, 11-speed
Guarnitura	SRAM X01 DH, DUB, carbon, Direct mount ring, 165mm
Movimento Centrale	SRAM DUB, 83mm
Cerchi	Roval Traverse Alloy 29" / 27.5", 32h alloy rim, 28mm inner rim width
Mozzo anteriore	DT Swiss 350 hub, 20x110mm
Mozzo posteriore	DT Swiss 350 hub, 12x148mm
Raggi	Sapim D-Light
Pneumatico anteriore	Cannibal, GRID GRAVITY casing, GRIPTON® T9 compound, 2Bliss Ready, 29x2.3"
Pneumatico posteriore	Cannibal, GRID GRAVITY casing, GRIPTON® T9 compound, 2Bliss Ready, 27.5x2.3"
Camere d'aria	Standard, Presta
Attacco Manubrio	Renthal Integra 35mm Direct Mount Stem, 45mm length
Manubrio	Renthal Fatbar 35, 5-degree upsweep, 7-degree backsweep, 30mm rise, 800mm, 35.0mm
Manopole	Deity Lockjaw
Reggisella	Thomson, alloy, straight, 12-degree clamp

ART. NR.	DESCRIZIONE	COLORE	MISURA
94525-7202	DEMO RACE	Gloss Obsidian / Brushed / Cham.	S2
94525-7203			S3
94525-7204			S4
94525-7302	DEMO RACE	Satin Taupe / Black / Brushed	S2
94525-7303			S3
94525-7304			S4

Disponibile solo online & Pick Up in Store



SATIN METALLIC SPRUCE / PURPLE HAZE

STATUS 170 2 DH	S2	S3	S4	S5
Stack (basso) (mm)	625	634	643	652
Stack (alto) (mm)	620	629	638	647
Reach (BB basso) (mm)	445	470	495	520
Reach (high) (mm)	451	476	501	526
Lunghezza tubo sterzo (mm)	100	110	120	130
Angolo Sterzo (basso - gradi)	63.5	63.5	63.5	63.5
Angolo Sterzo (alto - gradi)	64	64	64	64
Altezza movimento centrale (BB basso) (mm)	342	342	342	342
Altezza movimento centrale (BB alto) (mm)	350	350	350	350
BB Drop (BB Basso) (mm)	34	34	34	34
BB Drop (BB Alto) (mm)	26	26	26	26
Trail (basso) (mm)	138	138	138	138
Trail (alto) (mm)	133	133	133	133
Lunghezza forcella (mm)	581	581	581	581
Offset forcella/Rake (mm)	44	44	44	44
Avancorsa (mm)	789	819	848	878
Lunghezza batticatena (basso) (mm)	432	432	437	437
Lunghezza batticatena (alto) (mm)	436	436	441	441
Interasse (mm)	1221	1250	1285	1314
Lunghezza Tubo Orizz. virtuale (mm)	595	635	676	716
Altezza Standover (mm)	735	742	748	752
Lunghezza piantone (mm)	400	420	440	465
Angolo Sella (basso - gradi)	77	77	77	77
Angolo Sella (alto - gradi)	77.6	77.6	77.6	77.6
Lunghezza pedivella (mm)	165	165	165	165
Larghezza Manubrio (mm)	780	800	800	800
Lunghezza Attacco man. (mm)	50	50	50	50
Larghezza Sella (mm)	130	130	130	130
Lunghezza Reggisella (mm)	375	375	375	375

## SPECIFICHE TECNICHE

Specialized si riserva il diritto di modificare le caratteristiche senza preavviso.

Telaio	M5 Alloy chassis and rear-end, Trail Geometry, horst pivot geo adjustment, threaded BB, internal cable routing with external rear brake option, 12x148mm dropouts, sealed cartridge bearing pivots, SRAM UDH compatible, 170mm of travel
Ammortizzatore Post.	RockShox Super Deluxe Select Coil, external rebound adjust, hydraulic bottom out, 230x62.5mm
Forcella	RockShox BoXXer 29, Charger 3 RC damper, adjustable low-speed compression, adjustable rebound, 20x110mm thru-axle, 44mm offset, 180mm of travel
Attacco Manubrio	Descendant 35mm Direct Mount Stem, 50mm length
Manubrio	Specialized, 6061 alloy, 6-degree upsweep, 8-degree backsweep, 30mm rise, S2: 780mm, S3-S5: 800mm
Manopole	Deity Lockjaw
Freno posteriore	SRAM Maven Bronze, 4-piston caliper, hydraulic disc, 200mm
Freno anteriore	SRAM Maven Bronze, 4-piston caliper, hydraulic disc, 220mm
Cambio posteriore	SRAM GX DH, 7-speed, trigger
Comandi cambio	SRAM GX DH, trigger, 7-speed
Pacco Pignoni	SRAM GX DH, 7-speed, 11-24t
Catena	SRAM PC1110 w/ Powerlink™
Guarnitura	SRAM DESCENDANT DH, DUB, alloy, Direct, 34T ring, 165mm
Movimento Centrale	SRAM DUB Threaded Wide
Cerchi	Roval Alloy DH, 28mm internal width, tubeless ready. Front: 29", 28H; Rear 27.5", 32H
Mozzo anteriore	Alloy, sealed cartridge bearings, 20x110mm, 28h
Mozzo posteriore	Alloy, sealed cartridge bearings, 12x148mm thru-axle, 32h
Pneumatico anteriore	Butcher, GRID GRAVITY casing, GRIPTON® T9 compound, 2Bliss Ready, 29x2.3"
Raggi	DT Swiss Industry
Pneumatico posteriore	Butcher, GRID GRAVITY casing, GRIPTON® T9 compound, 2Bliss Ready, 27.5x2.3"
Camere d'aria	Standard, Presta valve
Sella	Body Geometry Henge DH, hollow Cro-Mo rails, 130mm
Reggisella	Specialized 2-bolt head, forged alloy, 5mm offset, micro-adjust, 34.9mm
Collarino Sella	Alloy, 38.6mm
Peso	221356
Peso	17.18kg (37 lb, 14 oz)
Misura pesata	S3

ART. NR.	DESCRIZIONE	COLORE	MISURA
93724-7002/4	STATUS 170 2 DH	SATIN METALLIC SPRUCE / PURPLE	S2- S4
<b>93724-7005</b>			<b>S5</b>

Disponibile Online e Pickup in store



SATIN HARVEST GOLD TINT / OBSIDIAN DUNE WHITE



SATIN OBSIDIAN / DUNE WHITE

STATUS 170 2	S1	S2	S3	S4	S5
Stack (basso) (mm)	620	625	634	643	652
Stack (alto) (mm)	616	620	629	638	647
Reach (BB basso) (mm)	420	445	470	495	520
Reach (BB Alto) (mm)	426	451	476	501	526
Lunghezza tubo sterzo (mm)	95	100	110	120	130
Angolo sterzo (basso - gradi)	63.5	63.5	63.5	63.5	63.5
Angolo sterzo (alto - gradi)	64	64	64	64	64
Altezza movim. centrale (BB basso) (mm)	342	342	342	342	342
Altezza movim. centrale (BB alto) (mm)	350	350	350	350	350
BB Drop (BB Basso) (mm)	34	34	34	34	34
BB Drop (BB Alto) (mm)	26	26	26	26	26
Trail (basso) (mm)	138	138	138	138	138
Trail (alto) (mm)	133	133	133	133	133
Lunghezza forcella (mm)	581	581	581	581	581
Offset forcella/Rake (mm)	44	44	44	44	44
Avancorsa (mm)	762	789	819	848	878
Lunghezza batticatena (basso) (mm)	432	432	432	437	437
Lunghezza batticatena (alto) (mm)	436	436	436	441	441
Interasse (mm)	1193	1221	1250	1285	1314
Lunghezza Tubo Orizz. virtuale (mm)	554	595	635	676	716
Altezza Standover (mm)	735	735	742	748	752
Lunghezza piantone (mm)	390	400	420	440	465
Angolo Sella (basso - gradi)	77	77	77	77	77
Angolo Sella (alto - gradi)	77.6	77.6	77.6	77.6	77.6
Lunghezza pedivella (mm)	165	165	165	165	170
Larghezza Manubrio (mm)	780	800	800	800	800
Lunghezza Attacco man. (mm)	40	40	40	40	40
Larghezza Sella (mm)	143	143	143	143	143
Lunghezza Reggisella (mm)	125	150	170	170	190

## SPECIFICHE TECNICHE

	Specialized si riserva il diritto di modificare le caratteristiche senza preavviso.
Telaio	M5 Alloy chassis and rear-end, Trail Geometry, horst pivot geo adjustment, threaded BB, internal cable routing with external rear brake option, 12x148mm dropouts, sealed cartridge bearing pivots, SRAM UDH compatible, 170mm of travel
Ammortizzatore Post.	FOX DHX Performance, Ride Dynamics Trail Tune, S1:230x60mm; S2-S5:230x62.5mm
Forcella	FOX FLOAT 38 Rhythm, GRIP damper, two position Sweep adjustment, 15x110mm QR axle, 44mm offset, 170mm of travel
Attacco Manubrio	Alloy Trail Stem, 35mm bar bore
Manubrio	Specialized, 6061 alloy, 6-degree upsweep, 8-degree backsweep, 30mm rise, S1: 780mm width; S2-S5: 800mm width
Manopole	Deity Knuckleduster
Freno anteriore	TRP Trail EVO, 4-piston caliper, hydraulic disc, 203mm
Freno posteriore	TRP Trail EVO, 4-piston caliper, hydraulic disc, 203mm
Cambio posteriore	Shimano Deore, M6100, 12pd, Shadow Plus
Comandi cambio	Shimano Deore, M6100, I-Spec EV, 12 speed
Pacco Pignoni	Shimano Deore M6100, 12spd w/Hyperglide+, 10-51t
Catena	Shimano Deore M6100, 12spd
Guarnitura	Shimano Deore, M6120, 32T ring, 55mm chainline, S1-4:165mm, S5: 170mm
Cerchi	Specialized, hookless alloy, 30mm inner width, tubeless ready
Mozzo anteriore	Alloy, sealed cartridge bearings, 15x110mm thru-axle, 28h
Mozzo posteriore	Alloy, sealed cartridge bearings, 12x148mm thru-axle, 32h
Raggi	DT Swiss Industry
Pneumatico posteriore	Butcher, GRID GRAVITY casing, GRIPTON® T9 compound, 2Bliss Ready, 27.5x2.3"
Pneumatico anteriore	Butcher, GRID TRAIL casing, GRIPTON® T9 compound, 2Bliss Ready, 29x2.3"
Camere d'aria	Standard, Presta valve
Sella	Bridge Comp, Hollow Cr-mo rails, 143mm
Reggisella	X-Fusion Manic, infinite adjustable, two-bolt head, bottom mount cable routing, remote SLR LE lever, 34.9, S1: 125mm, S2: 150mm, S3-S4: 170mm, S5: 190mm
Collarino Sella	Alloy, 38.6mm
Peso	221254
Peso	15.56 kg (34 lb, 4.9 oz)
Misura pesata	S3

ART. NR.	DESCRIZIONE	COLORE	MISURA
93723-7701/5	STATUS 170 2	SATIN HARV GOLD TINT / OBS DUNE WHITE	S1/S5
93723-7501/5	STATUS 170 2	SATIN OBSIDIAN / DUNE WHITE	S1/S5



GLOSS WHITE MOUNTAINS / AMBER GLOW



SATIN METTALIC PINE DIFFUSED / SPRUCE

P.SERIES P.1 TRAIL	P1
Dimensione ruote (inch)	20
Stack (mm)	429
Reach (mm)	310
Lunghezza Tubo Sterzo (mm)	90
Angolo Sterzo (degrees)	68.5
Altezza movimento centrale (mm)	259
B-B Drop (mm)	5
Trail (mm)	61
Lunghezza forcella (mm)	380
Offset forcella/Rake (mm)	40
Avancorsa (mm)	520
Lunghezza Batticatena (mm)	320
Interasse (mm)	840
Lunghezza Tubo Orizz. virtuale (mm)	449
Altezza Standover (mm)	561
Lunghezza Piantone (mm)	265
Angolo Sella (degrees)	72
Lunghezza pedivella (mm)	115
Larghezza Manubrio (mm)	600
Lunghezza Attacco man. (mm)	35
Larghezza Sella (mm)	110
Lunghezza Reggisella (mm)	250

**SPECIFICHE TECNICHE**

**Specialized si riserva il diritto di modificare le caratteristiche senza preavviso.**

Telaio	Specialized A1 Premium Aluminum, 20" Compatible, fully butted tubing, tapered head tube, BSA threaded 73mm BB shell, 12x148 thru-axle sliding dropouts, Single speed or geared compatible, internal cable routing, 30.9mm seat tube, dropper post compatible
Forcella	HAYES MANITOU JUNIT COMP 20", 80MM TRAVEL, Tapered alloy STEER TUBE, 15MM THRU AXLE, 40MM OFFSET, POST DISC MOUNT, W/ FENDER
Attacco Manubrio	Mini Rise, Alloy Double Butted, 6-degree Backsweep, 600mm Width, 31.8mm, 19mm Bar End Diameter
Manubrio	Specialized Trail Grips, 19mm bar end diameter, lock-on
Manopole	3D-forged alloy, 31.8mm, 6-degree rise
Freno anteriore	TEKTRO HD-J285, SHORT REACH LEVER, 160mm ROTOR
Freno posteriore	TEKTRO HD-J285, SHORT REACH LEVER, 160mm ROTOR
Cambio posteriore	microSHIFT Advent RD-M6195S, SUPER SHORT CAGE WITH CLUTCH 1X9 SPEED
Comandi cambio	microSHIFT Advent SL-M6190, short reach light action trigger+D48 9 speed
Pacco Pignoni	MICROSHIFT, CS-H094, 11T-38T, 9 speed HG freehub
Catena	KMC X9EPT, 9-speed, anti-corrosion coating w/ reusable Missing Link™
Guarnitura	Specialized P.Series, Forged single speed, 51.5mm CL, 115mm length
Ingranaggi	30T
Pedali	Specialized Platform
Movimento Centrale	Square Taper, 73mm Shell Width, 124.5mm Spindle Width
Mozzo anteriore	Alloy, 6-Bolt, 28H, 15x110 Boost
Cerchi	Specialized P.Series, 20", 28h, 26mm internal width, Disc Brake Only
Mozzo posteriore	Alloy, 6-Bolt, 28H, 12x148 Boost, 11-speed compatible
Pneumatico anteriore	Specialized GROUND CONTROL CONTROL, 20x2.35
Pneumatico posteriore	Specialized GROUND CONTROL CONTROL, 20x2.35
Raggi	Stainless, 14g
Camere d'aria	20" Inner Tube, SV
Sella	Specialized P.series, Steel Rails
Collarino Sella	Quick Release, 34.9mm ID Clamp
Reggisella	Specialized, 6061 alloy, 2-bolt clamp, 0mm setback, 30.9mm
Peso	224175
Peso	10.89kg (24 lb, .1 oz)
Misura pesata	One Size

ART. NR.	DESCRIZIONE	COLORE	MISURA
91924-8120	P.1 TRAIL	GLOSS WHITE MOUNTAINS / AMBER GLOW	20"
91924-8020	P.1 TRAIL	SATIN METTALIC PINE DIFFUSED / SPRUCE	20"

Disponibile Online e Pickup in store

## P.SERIES P.2 TRAIL



SATIN METALLIC SULPHUR / OAK GREEN



GLOSS OBSIDIAN DIFFUSED / SLATE GREY / BIRCH

P.SERIES P.2 TRAIL	P2
Dimensione ruote (inch)	24
Stack (mm)	523
Reach (mm)	360
Lunghezza Tubo Sterzo (mm)	95
Angolo Sterzo (degrees)	68.5
Altezza movimento centrale (mm)	290
B-B Drop (mm)	25
Trail (mm)	81
Lunghezza forcella (mm)	455
Offset forcella/Rake (mm)	40
Avancorsa (mm)	600
Lunghezza Batticatena (mm)	360
Interasse (mm)	958
Lunghezza Tubo Orizz. virtuale (mm)	530
Altezza Standover (mm)	645
Lunghezza Piantone (mm)	300
Angolo Sella (degrees)	72
Lunghezza pedivella (mm)	140
Larghezza Manubrio (mm)	680
Lunghezza Attacco man. (mm)	35
Larghezza Sella (mm)	110
Lunghezza Reggisella (mm)	80

### SPECIFICHE TECNICHE

Specialized si riserva il diritto di modificare le caratteristiche senza preavviso.

Telaio	Specialized A1 Premium Aluminum, 24" Compatible, fully butted tubing, tapered head tube, BSA threaded 73mm BB shell, 12x148 thru-axle sliding dropouts, Single speed or geared compatible, internal cable routing, 30.9mm seat tube, dropper post compatible
Forcella	HAYES MANITOU JUNIT COMP 24", 100MM TRAVEL, Tapered alloy STEER TUBE, 15MM THRU AXLE, 40MM OFFSET, POST DISC MOUNT, W/ FENDER
Attacco Manubrio	Specialized Alloy Trail Stem, 25mm Length, 31.8mm Clamp
Manubrio	Specialized P.Series MTB Dirt, 6061 alloy, 9-degree backsweep, 6-degree upsweep, 38mm rise, 750mm width, 31.8mm clamp
Manopole	Specialized Trail Grips, lock-on
Freno anteriore	SRAM Level 160mm rotor
Freno posteriore	SRAM Level 160mm rotor
Comandi cambio	microSHIFT Advent SL-M8195, trigger 9 speed
Cambio posteriore	microSHIFT Advent RD-M6195M, MEDIUM CAGE WITH CLUTCH 1X9 SPEED
Catena	KMC X9EPT, 9-speed, anti-corrosion coating w/ reusable Missing Link™
Pacco Pignoni	MICROSHIFT, CS-H094, 11T-42T, 9 speed HG freehub
Ingranaggi	30T
Guarnitura	Specialized P.Series, Forged single speed, 140mm length
Movimento Centrale	73mm, W/ Ø24MM SPINDLE
Pedali	Specialized Body Geometry Fitness, Platform, Plastic
Cerchi	Specialized P.Series, 24", 28/32h, 26mm internal width, Disc Brake Only
Mozzo anteriore	Alloy, sealed cartridge bearings, 15x110mm thru-axle, 28h
Mozzo posteriore	Alloy, sealed cartridge bearings, 12x148mm thru-axle, 32h
Pneumatico anteriore	Specialized GROUND CONTROL CONTROL, 24x2.35
Raggi	Stainless, 14g
Pneumatico posteriore	Specialized GROUND CONTROL CONTROL, 24x2.35
Camere d'aria	24" Inner Tube, SV
Sella	Specialized P.series, Steel Rails
Reggisella	TranzX Dropper, 30.9mm, 2-bolt clamp, 0mm setback, 80mm travel
Collarino Sella	Alloy, single-bolt, 34.9mm
Peso	224174
Peso	12.12kg (26 lb, 11.5 oz)
Misura pesata	One Size

ART. NR.	DESCRIZIONE	COLORE	MISURA
91924-7124	P.2 TRAIL	SATIN METALLIC SULPHUR / OAK G	24"
91924-7024	P.2 TRAIL	GLOSS OBSIDIAN DIFFUSED / SLAT	24"

Disponibile Online e Pickup in store



Gloss Dark Moss Green / Liquid Metal

CHISEL COMP SHIMANO	XS	S	M	L	XL
Stack (mm)	602.3	593	606	620	629
Reach (mm)	390	415	445	470	495
Lunghezza Tubo Sterzo (mm)	95	95	110	125	135
Angolo sterzo (basso) (degrees)	66.5	66.5	66.5	66.5	66.5
Altezza movimento centrale (BB basso) (mm)	226	336	336	336	336
Altezza movimento centrale (BB alto) (mm)	332	342	342	342	342
BB Drop (BB Basso) (mm)	46	36	36	36	36
Trail (mm)	113	113	113	113	113
Lunghezza forcella (mm)	530	530	530	530	530
Offset forcella/Rake (mm)	44	44	44	44	44
Avancorsa (mm)	682	706	742	773	802
Lunghezza Batticatena (mm)	437	437	437	437	437
Interasse (mm)	1115	1141	1177	1208	1237
Altezza standover (mm)	756	777	777	787	790
Lunghezza piantone (mm)	375	392	410	450	500
Angolo Sella (degrees)	75.5	75.5	75.5	75.5	75.5
Lunghezza Tubo Orizz. virtuale (mm)	527	565	602	634	664
Lunghezza pedivella- translate here (mm)	165m	170	170	175	175
Larghezza Manubrio (mm)	760	760	760	760	760
Lunghezza Attacco man. (mm)	60	60	60	60	60
Larghezza Sella (mm)	155	155	143	143	143
Lunghezza Reggisella (mm)	357	412	412	459	459

SPECIFICHE TECNICHE	Specialized si riserva il diritto di modificare le caratteristiche senza preavviso.
Telaio	Specialized D'Aluisio Smartweld M5 Alloy, Hydroformed tubes, Progressive XC Geometry, 110mm travel, internal cable routing, BSA BB, 12x148mm spacing, 30.9mm Dropper post compatible
Ammortizzatore Post.	RockShox Deluxe Select+, Ride Dynamics Tuned, Two Position, Rebound Adjust, 190x40mm
Forcella	RockShox SID, Rush damper, 44mm offset, 15x110mm thru-axle, 120mm of travel, Maxle Stealth
Attacco Manubrio	Specialized, 3D-forged alloy, 4-bolt, 7-degree rise
Manopole	Specialized Trail Grips
Manubrio	Specialized Alloy, 20mm rise, 31.8mm, 760mm wide
Freno anteriore	Shimano M6100, 2-piston caliper, hydraulic disc, 180mm rotor
Freno posteriore	Shimano M6100, 2-piston caliper, hydraulic disc, 160mm rotor
Comandi cambio	Shimano SLX, M7100, 12spd
Pacco Pignoni	Shimano Deore M6100, 12spd w/Hyperglide+, 10-51t
Cambio posteriore	Shimano SLX M7100, SGS, 12-speed
Catena	Shimano Deore M6100, 12spd w/quick link
Guarnitura	Shimano MT-511, 32t chainring
Ingranaggi	32t
Movimento Centrale	Shimano BB-MT501 BSA
Cerchi	Specialized Alloy, Tubeless ready, 27mm inner width, disc, 28h
Mozzo anteriore	Shimano MT410-B, Centerlock 28h, 15x110 Boost
Mozzo posteriore	Shimano MT410-B, Centerlock 28h, 12x148 Boost, Microspline
Pneumatico anteriore	Specialized Ground Control, Control Casing, T5 Compound, 29x2.35
Pneumatico posteriore	Specialized Fast Trak, Control Casing, T5 Compound, 29x2.35
Raggi	Stainless, 14g
Camere d'aria	Standard 40mm PV 29x1.75-2.4
Sella	Body Geometry Power Sport, steel rails
Reggisella	TranzX Dropper post, 30.9mm, XS-SM: 100mm, M: 125mm, L-XL: 150mm
Collarino Sella	Specialized Alloy, 34.9mm
Peso	12.86kg (28 lb, 5.6 oz)
Misura pesata	MD

ART. NR.	DESCRIZIONE	COLORE	MISURA
93825-5101	CHISEL COMP SHIMANO	Gloss Dark Moss Green/Liquid	XS
93825-5102			S
93825-5103			M
93825-5104			L
93825-5105			XL

Disponibile Online e Pickup in store



Gloss Ion/ Smoke Liquid Metal



Satin Metallic Deep Lake / Gloss White

CHISEL COMP	XS	S	M	L	XL
Stack (mm)	602.3	593	606	620	629
Reach (mm)	390	415	445	470	495
Lunghezza Tubo Sterzo (mm)	95	95	110	125	135
Angolo sterzo (basso) (degrees)	66.5	66.5	66.5	66.5	66.5
Angolo sterzo (alto) (degrees)	67	67	67	67	67
Altezza movimento centrale (BB basso) (mm)	226	336	336	336	336
Altezza movimento centrale (BB alto) (mm)	332	342	342	342	342
BB Drop (BB Basso) (mm)	46	36	36	36	36
Trail (mm)	113	113	113	113	113
Lunghezza forcella (mm)	530	530	530	530	530
Offset Forcella/Rake (mm)	44	44	44	44	44
Avancorsa (mm)	682	706	742	773	802
Lunghezza Batticateni (mm)	437	437	437	437	437
Interasse (mm)	1115	1141	1177	1208	1237
Altezza Standover (mm)	756	777	777	787	790
Lunghezza Piantone (mm)	375	392	410	450	500
Angolo sella (degrees)	75.5	75.5	75.5	75.5	75.5
Lunghezza Tubo Orizz. virtuale (mm)	527	565	602	634	664
Lunghezza pedivella (mm)	165	170	170	175	175
Larghezza Manubrio (mm)	760	760	760	760	760
Lunghezza Attacco man. (mm)	60	60	60	60	60
Larghezza Sella (mm)	155	155	143	143	143
Lunghezza Reggisella (mm)	357	412	412	459	459

## SPECIFICHE TECNICHE

Specialized si riserva il diritto di modificare le caratteristiche senza preavviso.

Manubrio	Specialized Alloy, 20mm rise, 31.8mm, 760mm wide
Sella	Body Geometry Power Sport, steel rails
Telaio	Specialized D'Aluisio Smartweld M5 Alloy, Hydroformed tubes, Progressive XC Geometry, 110mm travel, internal cable routing, BSA BB, 12x148mm spacing, 30.9mm Dropper post compatible
Collarino Sella	Specialized Alloy, 34.9mm
Ammortizzatore Post.	RockShox Deluxe Select+, Ride Dynamics Tuned, Two Position, Rebound Adjust, 190x40mm
Forcella	RockShox SID, Rush damper, 44mm offset, 15x110mm thru-axle, 120mm of travel, Maxle Stealth
Freno anteriore	SRAM Level T hydraulic disc, 2-Piston Caliper, 180mm rotor
Freno posteriore	SRAM Level T hydraulic disc, 2-Piston Caliper, 160mm rotor
Comandi cambio	SRAM GX, trigger, 12-speed
Cambio posteriore	SRAM GX Eagle, 12-speed
Pacco Pignoni	SRAM PG-1230 Eagle, 11-50t
Catena	SRAM SX Eagle, 12-speed
Guarnitura	SRAM X1000 Eagle, DUB, 165/170/175mm
Ingranaggi	32T
Movimento Centrale	SRAM DUB, BSA 73mm, Threaded
Cerchi	Specialized Alloy, Tubeless ready, 27mm inner width, disc, 28h
Mozzo anteriore	Specialized alloy front hub, disc, sealed cartridge bearings, 6-bolt, 15x110mm thru-axle, 28h
Mozzo posteriore	Specialized alloy, disc, sealed cartridge bearings, 6-bolt, 12x148mm thru-axle, 28h
Raggi	Stainless, 14g
Pneumatico anteriore	Specialized Ground Control, Control Casing, T5 Compound, 29x2.35
Pneumatico posteriore	Specialized Fast Trak, Control Casing, T5 Compound, 29x2.35
Camere d'aria	Standard 40mm PV 29x1.75-2.4
Attacco Manubrio	Specialized, 3D-forged alloy, 4-bolt, 7-degree rise
Manopole	Specialized Trail Grips
Reggisella	TranzX Dropper, 30.9mm, XS: 100mm, SM-M: 125mm, L-XL: 150mm
Identificativo	221770
Peso	12.80 kg (28 lb, 3.5 oz)
Misura pesata	MD

ART. NR.	DESCRIZIONE	COLORE	MISURA
93825-5201	CHISEL COMP	Gloss Ion/ Smoke Liquid Metal	XS
93825-5202			S
93825-5203			M
93825-5204			L
93825-5205			XL
93825-5301	CHISEL COMP	Satin Metallic Deep Lake / Gloss White	XS
93825-5302			S
93825-5303			M
93825-5304			L
93825-5305			XL



Gloss Sea Foam / Deep Orange

CHISEL SHIMANO	XS	S	M	L	XL
Stack (mm)	602.3	593	606	620	629
Reach (mm)	390	415	445	470	495
Lunghezza Tubo Sterzo (mm)	95	95	110	125	135
Angolo sterzo (basso) (degrees)	66.5	66.5	66.5	66.5	66.5
Altezza movimento centrale (BB basso) (mm)	326	336	336	336	336
Altezza movimento centrale (BB alto) (mm)	332	342	342	342	342
BB Drop (BB Basso) (mm)	46	36	36	36	36
Trail (mm)	113	113	113	113	113
Lunghezza forcella (mm)	530	530	530	530	530
Offset forcella/Rake (mm)	44	44	44	44	44
Avancorsa (mm)	682	706	742	773	802
Lunghezza Batticateni (mm)	437	437	437	437	437
Interasse (mm)	1115	1141	1177	1208	1237
Altezza standover (mm)	756	777	777	787	790
Lunghezza piantone (mm)	375	392	410	450	500
Angolo Sella (degrees)	75.5	75.5	75.5	75.5	75.5
Lunghezza Tubo Orizz. virtuale (mm)	527	565	602	634	664
Lunghezza pedivella - translate here (mm)	165	170	170	175	175
Larghezza Manubrio (mm)	760	760	760	760	760
Lunghezza Attacco man. (mm)	60	60	60	60	60
Larghezza Sella (mm)	155	155	143	143	143
Lunghezza Reggisella (mm)	357	412	412	459	459

SPECIFICHE TECNICHE	Specialized si riserva il diritto di modificare le caratteristiche senza preavviso.
Telaio	Specialized D'Aluisio Smartweld M5 Alloy, Hydroformed tubes, Progressive XC Geometry, 110mm travel, internal cable routing, BSA BB, 12x148mm spacing, 30.9mm Dropper post compatible
Ammortizzatore Post.	X-Fusion PRO-02, 190x40mm, Ride Dynamics Tuned, Rebound adjust, Compression Adjust
Forcella	Rockshox Recon Silver RL, 120mm travel, Motion Control damper, 42mm offset, Maxle Stealth, 15x110 thru-axle
Attacco Manubrio	Specialized, 3D-forged alloy, 4-bolt, 7-degree rise
Manopole	Specialized Trail Grips
Manubrio	Specialized Alloy, 20mm rise, 31.8mm, 760mm wide
Freno anteriore	Shimano M4100, 2-piston caliper, hydraulic disc, 180mm rotor
Freno posteriore	Shimano M4100, 2-piston caliper, hydraulic disc, 160mm rotor
Cambio posteriore	Shimano Deore, M6100, 12pd, Shadow Plus
Comandi cambio	Shimano Deore, M6100, I-Spec EV, 12 speed
Pacco Pignoni	Shimano Deore M6100, 12spd w/Hyperglide+, 10-51t
Catena	KMC X12EPT, 12-speed, anti-corrosion coating w/ reusable Missing Link™
Ingranaggi	32t
Guarnitura	Alloy crankset, 1x direct mount chainring, 165/170/175mm
Movimento Centrale	BSA Bottom Bracket, PW-MBB73
Cerchi	Specialized Alloy, Tubeless ready, 27mm inner width, disc, 28h
Mozzo anteriore	Shimano MT410-B, Centerlock 28h, 15x110 Boost
Mozzo posteriore	Shimano MT410-B, Centerlock 28h, 12x148 Boost, Microspline
Pneumatico anteriore	Specialized Ground Control, Control Casing, T5 Compound, 29x2.35
Pneumatico posteriore	Specialized Fast Trak, Control Casing, T5 Compound, 29x2.35
Raggi	Stainless, 14g
Camere d'aria	Standard 40mm PV 29x1.75-2.4
Sella	Body Geometry Power Sport, steel rails
Reggisella	TranzX Dropper, 30.9mm, XS-SM: 100mm, M: 125mm, L-XL: 150mm
Collarino Sella	Specialized Alloy, 34.9mm
Peso	13.73kg (30 lb, 4.3 oz)
Misura pesata	MD

ART. NR.	DESCRIZIONE	COLORE	MISURA
93825-5001	CHISEL BASE SHIMANO	Gloss Sea Foam / Deep Orange	XS
93825-5002			S
93825-5003			M
93825-5004			L
93825-5005			XL

Disponibile Online e Pickup in store



Gloss Dove Grey / Ashen Grey



Gloss Maroon / White

CHISEL	XS	S	M	L	XL
Stack (mm)	602.3	593	606	620	629
Reach (mm)	390	415	445	470	495
Lunghezza Tubo Sterzo (mm)	95	95	110	125	135
Angolo sterzo (basso) (degrees)	66.5	66.5	66.5	66.5	66.5
Angolo sterzo (high) (degrees)	70	70	70	70	70
Altezza movimento centrale (BB basso) (mm)	226	336	336	336	336
Altezza movimento centrale (BB alto) (mm)	332	342	342	342	342
BB Drop (BB Basso) (mm)	46	36	36	36	36
Trail (mm)	113	113	113	113	113
Lunghezza forcella (mm)	530	530	530	530	530
Offset forcella/Rake (mm)	44	44	44	44	44
Avancorsa (mm)	682	706	742	773	802
Lunghezza Batticateni (mm)	437	437	437	437	437
Interasse (mm)	1115	1141	1177	1208	1237
Altezza Standover (mm)	756	777	777	787	790
Lunghezza Piantone (mm)	375	392	410	450	500
Angolo sella (degrees)	75.5	75.5	75.5	75.5	75.5
Lunghezza Tubo Orizz. virtuale (mm)	527	565	602	634	664
Lunghezza pedivella (mm)	165	170	170	175	175
Larghezza Manubrio (mm)	760	760	760	760	760
Lunghezza Attacco man. (mm)	60	60	60	60	60
Larghezza Sella (mm)	155	155	143	143	143
Lunghezza Reggisella (mm)	357	412	412	459	459

## SPECIFICHE TECNICHE

**Specialized si riserva il diritto di modificare le caratteristiche senza preavviso.**

Manubrio	Specialized Alloy, 20mm rise, 31.8mm, 760mm wide
Sella	Body Geometry Power Sport, steel rails, 143/155mm
Telaio	Specialized D'Aluisio Smartweld M5 Alloy, Hydroformed tubes, Progressive XC Geometry, 110mm travel, internal cable routing, BSA BB, 12x148mm spacing, 30.9mm Dropper post compatible
Collarino Sella	Specialized Alloy, 34.9mm
Ammortizzatore Post.	X-Fusion PRO-02, 190x40mm, Ride Dynamics Tuned, Rebound adjust, Compression Adjust
Forcella	Rockshox Recon Silver RL, 120mm travel, Motion Control damper, 42mm offset, Maxle Stealth, 15x110 thru-axle
Freno anteriore	SRAM Level T hydraulic disc, 2-Piston Caliper, 180mm rotor
Freno posteriore	SRAM Level T hydraulic disc, 2-Piston Caliper, 160mm rotor
Comandi cambio	SRAM SX Eagle, trigger, 12-speed
Cambio posteriore	SRAM NX Eagle, 12-speed
Pacco Pignoni	SRAM PG-1210 Eagle 11-50t
Catena	SRAM SX Eagle, 12-speed
Guarnitura	SRAM SX Eagle, Powerspline, 32t chainring, 165/170/175mm
Ingranaggi	32t
Movimento Centrale	SRAM Powerspline BSA
Cerchi	Specialized Alloy, Tubeless ready, 27mm inner width, disc, 28h
Mozzo anteriore	Specialized alloy front hub, disc, sealed cartridge bearings, 6-bolt, 15x110mm thru-axle, 28h
Mozzo posteriore	Specialized alloy, disc, sealed cartridge bearings, 6-bolt, 12x148mm thru-axle, 28h
Raggi	Stainless, 14g
Pneumatico anteriore	Specialized Ground Control, Control Casing, T5 Compound, 29x2.35
Pneumatico posteriore	Specialized Fast Trak, Control Casing, T5 Compound, 29x2.35
Camere d'aria	Standard 40mm PV 29x1.75-2.4
Attacco Manubrio	Specialized, 3D-forged alloy, 4-bolt, 7-degree rise
Manopole	Specialized Trail Grips
Reggisella	TranzX Dropper Seatpost, 30.9mm, XS-SM: 100mm, M: 125mm, L-XL: 150mm
Identificativo	221775
Peso	13.87kg (30 lb, 9.2 oz)
Misura pesata	MD

ART. NR.	DESCRIZIONE	COLORE	MISURA
93825-7001	CHISEL	Gloss Dove Grey / Ashen Grey	XS
93825-7002			S
93825-7003			M
93825-7004			L
93825-7005			XL
93825-7101	CHISEL	Gloss Maroon / White	XS
93825-7102			S
93825-7103			M
93825-7104			L
93825-7105			XL

Disponibile solo online & Pick Up in Store

## CHISEL HARDTAIL COMP



GLOSS METALLIC DEEP MARINE / WHITE



GLOSS ION METALLIC / SMOKE LIQUID METAL

CHISEL HARDTAIL COMP	XS	S	M	L	XL
Stack (mm)	591	605	605	619	633
Reach (mm)	385	405	430	455	480
Lunghezza Tubo Sterzo (mm)	95	95	95	110	125
Angolo sterzo (degrees)	68	68	68	68	68
Altezza movimento centrale (mm)	304	309	309	309	309
BB Drop (mm)	68	63	63	63	63
Trail (mm)	103	103	103	103	103
Lunghezza forcella (mm)	486	506	506	506	506
Offset Forcella/Rake (mm)	44	44	44	44	44
Avancorsa (mm)	647	674	699	730	760
Lunghezza Batticateni (mm)	432	432	432	432	432
Interasse (mm)	1070	1099	1124	1154	1185
Lunghezza Tubo Orizz. virtuale (mm)	555	578	603	632	661
Altezza Standover (mm)	732	762	792	816	847
Lunghezza Piantone (mm)	367	400	430	470	520
Angolo sella (degrees)	74	74	74	74	74
Lunghezza pedivella (mm)	165m	170	170	175	175
Larghezza Manubrio (mm)	750	750	750	750	750
Lunghezza Attacco man. (mm)	60	60	70	70	70
Larghezza Sella (mm)	155	155	143	143	143
Lunghezza Reggisella (mm)	350	350	400	400	400

### SPECIFICHE TECNICHE

SPECIFICHE TECNICHE	Specialized si riserva il diritto di modificare le caratteristiche senza preavviso.
Manubrio	Specialized Alloy XC minirise, double-butted alloy, 8-degree backsweep, 6-degree upsweep, 10mm rise, 31.8mm
Telaio	Specialized D'Aluisio Smartweld M5 Alloy, Hydroformed tubes, Progressive XC Geometry, internal cable routing, BSA BB, 12x148mm spacing, 30.9mm Dropper post compatible
Collarino Sella	Specialized Alloy, 34.9mm
Forcella	RockShox Judy Gold, Motion Control damper, Solo Air, 42mm offset, 15x10mm thru-axle, 100mm of travel (XS - 80mm travel)
Freno anteriore	SRAM Level T hydraulic disc, 2-Piston Caliper
Freno posteriore	SRAM Level T hydraulic disc, 2-Piston Caliper
Comandi cambio	SRAM NX Eagle, trigger, 12-speed
Cambio posteriore	SRAM NX Eagle, 12-speed
Pacco Pignoni	SRAM NX Eagle, 12-speed, 11-50t
Catena	SRAM XX1 Eagle, 12-speed
Guarnitura	SRAM FC X1 1000 EAGLE B148 DUB 32ST
Ingranaggi	32t
Movimento Centrale	SRAM DUB, BSA 73mm, Threaded
Cerchi	Specialized 29, 27mm inner width, 28h, tubeless ready
Mozzo anteriore	Alloy front hub, sealed cartridge bearings, 6-bolt, 15x10mm thru-axle, 28h
Mozzo posteriore	Alloy rear hub, sealed cartridge bearings, 12x148mm thru-axle, 6-bolt, 28h
Raggi	Stainless, 14g
Pneumatico anteriore	Specialized Fast Trak, Control Casing, T7 Compound, 29x2.35
Pneumatico posteriore	Specialized Fast Trak, Control Casing, T5 Compound, 29x2.35
Camere d'aria	Standard 40mm PV 29x1.75-2.4
Attacco Manubrio	Specialized, 3D-forged alloy, 4-bolt, 7-degree rise
Manopole	Specialized Trail Grips
Sella	Body Geometry Power Sport, steel rails
Reggisella	Specialized Alloy, Single Bolt, 30.9mm
Identificativo	221772
Peso	11.76 kg (25 lb, 14.8 oz)
Misura pesata	LG

ART. NR.	DESCRIZIONE	COLORE	MISURA
91725-5001	CHISEL HT COMP	GLOSS MET. DEEP MARINE / WHITE	XS
91725-5002			S
91725-5003			M
91725-5004			L
91725-5005			XL
91725-5101 / 5105	CHISEL HT COMP	GLOSS ION METALLIC / SMOKE LIQUID METAL	



Gloss Black / Taupe



Satin Black / Metallic Obsidian

CHISEL COMP EVO	XS	S	M	L	XL
Stack (mm)	606	596	610	624	633
Reach (mm)	385	410	440	465	490
Lunghezza Tubo Sterzo (mm)	95	95	110	125	135
Angolo sterzo (basso) (degrees)	66	66	66	66	66
Angolo sterzo (alto) (degrees)	66.5	66.5	66.5	66.5	66.5
Altezza movimento centrale (BB basso) (mm)	330	339	339	339	339
Altezza movimento centrale (BB alto) (mm)	336	345	345	345	345
BB Drop (BB Basso) (mm)	42	33	33	33	33
Trail (mm)	117	117	117	117	117
Lunghezza forcella (mm)	540	540	540	540	540
Offset Forcella/Rake (mm)	44	44	44	44	44
Avancorsa (mm)	685	709	745	776	805
Lunghezza Batticateni (mm)	437	437	437	437	437
Interasse (mm)	1119	1145	1181	1212	1241
Altezza Standover (mm)	762	783	783	792	795
Lunghezza Piantone (mm)	375	392	410	450	500
Angolo sella (degrees)	75	75	75	75	75
Lunghezza Tubo Orizz. virtuale (mm)	528	566	603	635	665
Lunghezza pedivella (mm)	165	170	170	175	175
Larghezza Manubrio (mm)	760	760	760	760	760
Lunghezza Attacco man. (mm)	60	60	60	60	60
Larghezza Sella (mm)	155	155	143	143	143
Lunghezza Reggisella (mm)	100	125	150	170	170

## SPECIFICHE TECNICHE

Specialized si riserva il diritto di modificare le caratteristiche senza preavviso.

Telaio	Specialized D'Aluisio Smartweld M5 Alloy, Hydroformed tubes, Progressive XC Geometry, 110mm travel, internal cable routing, BSA BB, 12x148mm spacing, 30.9mm Dropper post compatible
Collarino Sella	Specialized Alloy, 34.9mm
Ammortizzatore Post.	Fox Float Performance, Evol LV, Ride Dynamics Tuned, 2-position compression adjust, 190x40mm
Forcella	Fox 34 Performance Elite, Grip2 Damper, Compression adjust, 130mm travel, 44mm offset, 15x110mm
Freno anteriore	SRAM G2 RS hydraulic disc, 4-Piston Caliper, 180mm rotor
Freno posteriore	SRAM G2 RS hydraulic disc, 4-Piston Caliper, 180mm rotor
Comandi cambio	SRAM GX, trigger, 12-speed
Cambio posteriore	SRAM GX Eagle, 12-speed
Pacco Pignoni	SRAM PG-1230 Eagle 11-50t
Catena	SRAM SX Eagle, 12-speed
Guarnitura	SRAM X1000 Eagle, DUB, 165/170/175mm
Ingranaggi	32t
Movimento Centrale	SRAM DUB, BSA 73mm, Threaded
Cerchi	Specialized 29, hookless alloy, 30mm inner width, tubeless ready
Mozzo anteriore	Alloy, sealed cartridge bearings, 15x110mm thru-axle, 28h
Mozzo posteriore	Alloy, sealed cartridge bearings, 12x148mm thru-axle, 28h
Raggi	DT Swiss Industry
Pneumatico anteriore	Specialized Purgatory, GRID Casing, T9 Compound, 29x2.4
Pneumatico posteriore	Specialized Ground Control, GRID Casing, T7 Compound, 29x2.35
Camere d'aria	Standard 40mm PV 29x1.75-2.4
Attacco Manubrio	Alloy Stem, 35mm clamp, 60mm
Manubrio	Specialized Alloy, 20mm rise, 35mm, 760mm wide
Manopole	Specialized Trail Grips
Sella	Body Geometry Power Comp, steel rails
Reggisella	X-Fusion Manic, 30.9, 125/150/170 Travel, 0mm offset
Identificativo	274939
Peso	13.53 kg (29 lb, 13.3 oz)
Misura pesata	MD

ART. NR.	DESCRIZIONE	COLORE	MISURA
93825-5601/5	CHISEL COMP EVO	Gloss Black / Taupe	XS - XL
93825-5701/5	CHISEL COMP EVO	Satin Black / Metallic Obsidian	XS - XL

Disponibile online & Pick Up in Store

## TELAIO CHISEL HARDTAIL



GLOSS PURPLE TINT LINEAR BRUSHED / REBEL PINK

### SPECIFICHE TECNICHE

**Specialized si riserva il diritto di modificare le caratteristiche senza preavviso.**

Telaio	Specialized D'Aluisio Smartweld M5 Alloy, Hydroformed tubes, Progressive XC Geometry, internal cable routing, BSA BB, 12x148mm spacing, 30.9mm Dropper post compatible
Collarino Sella	Specialized Alloy, 34.9mm
Reggisella	Specialized Alloy, Single Bolt, 30.9mm
Peso	1.96kg (4 lb, 5.1 oz)
Misura pesata	LG

TELAIO CHISEL HARDTAIL	XS	S	M	L	XL
Stack (mm)	591	605	605	619	633
Reach (mm)	385	405	430	455	480
Lunghezza Tubo Sterzo (mm)	95	95	95	110	125
Angolo sterzo (degrees)	68	68	68	68	68
Altezza movimento centrale (mm)	304	309	309	309	309
BB Drop (mm)	68	63	63	63	63
Trail (mm)	103	103	103	103	103
Lunghezza forcella (mm)	486	506	506	506	506
Offset Forcella/Rake (mm)	44	44	44	44	44
Avancorsa (mm)	647	674	699	730	760
Lunghezza Batticateni (mm)	432	432	432	432	432
Interasse (mm)	1070	1099	1124	1154	1185
Lunghezza Tubo Orizz. virtuale (mm)	555	578	603	632	661
Altezza Standover (mm)	732	762	792	816	847
Lunghezza Piantone (mm)	367	400	430	470	520
Angolo sella (degrees)	74	74	74	74	74
Lunghezza Reggisella (mm)	350	350	400	400	400

ART. NR.	DESCRIZIONE	COLORE	MISURA
71725-7001	CHISEL HT FRAME	GLOSS PURPLE TINT	XS
71725-7002			S
71725-7003			M
71725-7004			L
71725-7005			XL

Disponibile solo online & Pick Up in Store

# ROCKHOPPER EXPERT



GLOSS SILVER DUST / SATIN BURNT GOLD METALLIC



SATIN CAST BLUE METALLIC / GLOSS ASTRAL BLUE

ROCKHOPPER EXPERT	XS	S	M	S	M	L	XL	XXL
	27.5	27.5	27.5	29	29	29	29	29
Dimensione ruote (in)	27.5	27.5	27.5	29	29	29	29	29
Stack (mm)	559	573	589	607	616	626	640	654
Reach (mm)	375	395	415	405	425	445	465	485
Lunghezza Tubo Sterzo (mm)	95	100	105	95	95	105	120	135
Angolo Sterzo (degrees)	68	68	68	68.5	68.5	68.5	68.5	68.5
Altezza movimento centrale (mm)	310	310	310	310	310	310	310	310
B-B Drop (mm)	43	43	43	62	62	62	62	62
Trail (mm)	97	97	97	97	97	97	97	97
Lunghezza forcella (mm)	475	485	495	505	515	515	515	515
Offset Forcella/Rake (mm)	42	42	42	46	46	46	46	46
Avancorsa (mm)	630	656	682	672	696	719	745	770
Lunghezza Batticateni (mm)	440	440	440	440	440	440	440	440
Interasse (mm)	1067	1092	1118	1105	1128	1152	1178	1203
Lunghezza Tubo Orizz. virtuale (mm)	541	565	589	586	608	630	654	679
Altezza Standover (mm)	658	695	735	732	754	781	820	853
Lunghezza Piantone (mm)	310	350	400	360	400	450	500	560
Angolo Sella (degrees)	73.5	73.5	73.5	73.5	73.5	73.5	73.5	73.5
Lunghezza pedivella (mm)	165	165	170	170	170	175	175	175
Larghezza manubrio (mm)	700	720	740	720	740	740	740	740
Lunghezza Attacco Manubrio (mm)	35	45	60	45	60	60	70	70
Lunghezza reggisella (mm)	300	350	400	350	400	400	400	400
Larghezza sella (mm)	155	155	143	155	143	143	143	143

## SPECIFICHE TECNICHE

Specialized si riserva il diritto di modificare le caratteristiche senza preavviso.

Manubrio	Alloy Mini Rise, 9-degree backsweep, 15mm rise, 31.8mm
Telaio	Specialized A1 premium butted alloy, zero-stack head tube, internal cable routing, 135x9mm forged dropouts, chainstay-mounted disc brake, replaceable alloy derailleur hanger, stealth rack mounts, dropper post compatible
Collarino Sella	Alloy, quick release, 34.9
Forcella	RockShox Judy, Solo Air, Turnkey damper, 46mm offset, QR, 80/90/100mm travel (size-specific), alloy steerer
Freno anteriore	Shimano BR-MT200, hydraulic disc, 180mm
Freno posteriore	Shimano BR-MT200, hydraulic disc, 180mm
Comandi cambio	SRAM SX Eagle, trigger, 12-speed
Cambio posteriore	SRAM NX Eagle, 12-speed
Pacco Pignoni	SRAM PG-1210 Eagle, 11-50t
Catena	SRAM SX Eagle, 12-speed
Guarnitura	Stylo Cranks
Movimento Centrale	SRAM Powerspline
Cerchi	Specialized Alloy, hookless, Tubeless ready, 25mm inner width
Mozzo anteriore	Formula DC-20, 6-Bolt, disc, 100x9mm spacing, quick-release
Mozzo posteriore	Formula DC-22, 6-Bolt freehub, disc, 135x9mm spacing, quick-release
Raggi	Stainless, 14g
Pneumatico anteriore	Ground Control 2BR 27.5/29X2.35
Pneumatico posteriore	Ground Control 2BR 27.5/29X2.35
Camere d'aria	Standard, Presta Valve
Attacco Manubrio	3D-forged alloy, 31.8mm, 7-degree rise
Manopole	Specialized Trail Grips, lock-on
Sella	Bridge Sport, Steel rails, 155/143mm
Reggisella	Alloy, 2-bolt clamp, 30.9mm
Pedali	Specialized Body Geometry Fitness, Platform, Plastic
Identificativo	279941
Peso	13.12 kg (28 lb, 14.8 oz)
Misura pesata	MD

ART. NR.	DESCRIZIONE	COLORE	MISURA
91825-3802	ROCKHOPPER EXPERT	GLOSS SILVER DUST	S - 29
91825-3803			M - 29
91825-3804			L - 29
91825-3805			XL - 29
91825-3806			XXL - 29
91825-3902	ROCKHOPPER EXPERT	SATIN CAST BLUE METALLIC	S - 29
91825-3903			M - 29
91825-3904			L - 29
91825-3905			XL - 29
91825-3906			XXL - 29



GLOSS METALLIC SPRUCE / SMOKE



GLOSS PURPLE HAZE / ASTRAL BLUE



SATIN METALLIC OAK GREEN / SMOKE

## SPECIFICHE TECNICHE

Specialized si riserva il diritto di modificare le caratteristiche senza preavviso.

Manubrio	Alloy Mini Rise, 9-degree backsweep, 15mm rise, 31.8mm
Telaio	Specialized A1 premium butted alloy, zero-stack head tube, internal cable routing, 135x9mm forged dropouts, chainstay-mounted disc brake, replaceable alloy derailleur hanger, stealth rack mounts, dropper post compatible
Collarino Sella	Alloy, quick release, 34.9
Forcella	RockShox Judy, Solo Air, Turnkey damper, 46mm offset, QR, 80/90/100mm travel (size-specific), steel steerer
Freno anteriore	Shimano BR-MT200, hydraulic disc, 180mm
Freno posteriore	Shimano BR-MT200, hydraulic disc, 180mm
Comandi cambio	Shimano Deore, RapidFire Plus, 10-speed
Cambio posteriore	Shimano Deore, RD-M5120, 10spd
Pacco Pignoni	Sunrace, 11-46t, 10spd
Catena	KMC, X10, EPT anti-corrosion coating, 10-speed w/ Missing Link™
Guarnitura	Stout 1x, forged alloy
Movimento Centrale	Square-tapered, 73mm, internal bearings, 122.5mm spindle
Cerchi	Specialized Alloy, hookless, Tubeless ready, 25mm inner width
Mozzo anteriore	Formula DC-20, 6-Bolt, disc, 100x9mm spacing, quick-release
Mozzo posteriore	Formula DC-22, 6-Bolt freehub, disc, 135x9mm spacing, quick-release
Raggi	Stainless, 14g
Pneumatico anteriore	FAST TRAK SPORT, 650B/29x2.35
Pneumatico posteriore	FAST TRAK SPORT, 650B/29x2.35
Camere d'aria	Standard 40mm PV 650B/29x1.75-2.4
Attacco Manubrio	3D-forged alloy, 31.8mm, 7-degree rise
Manopole	Specialized Trail Grips, lock-on
Sella	Bridge Sport, Steel rails, 155/143mm
Reggisella	Alloy, 2-bolt clamp, 30.9mm
Pedali	PLATFORM PEDAL, VP, SBC-54, PP (POLYPROPYLENE) BODY, BUSHING BEARING, 10B21.9/16 INCH SPINDLE
Identificativo	279940

## ROCKHOPPER COMP

XS S - M - S - M - L - XL - XXL  
27.5 27.5 27.5 29 29 29 29 29

Dimensione ruote (in)	27.5	27.5	27.5	29	29	29	29	29
Stack (mm)	559	573	589	607	616	626	640	654
Reach (mm)	375	395	415	405	425	445	465	485
Lunghezza Tubo Sterzo (mm)	95	100	105	95	95	105	120	135
Angolo Sterzo (degrees)	68	68	68	68.5	68.5	68.5	68.5	68.5
Altezza movimento centrale (mm)	310	310	310	310	310	310	310	310
B-B Drop (mm)	43	43	43	62	62	62	62	62
Trail (mm)	97	97	97	97	97	97	97	97
Lunghezza forcella (mm)	475	485	495	505	515	515	515	515
Offset Forcella/Rake (mm)	42	42	42	46	46	46	46	46
Avancorsa (mm)	630	656	682	672	696	719	745	770
Lunghezza Batticateni (mm)	440	440	440	440	440	440	440	440
Interasse (mm)	1067	1092	1118	1105	1128	1152	1178	1203
Lunghezza Tubo Orizz. virtuale (mm)	541	565	589	586	608	630	654	679
Altezza Standover (mm)	658	695	735	732	754	781	820	853
Lunghezza Piantone (mm)	310	350	400	360	400	450	500	560
Angolo Sella (degrees)	73.5	73.5	73.5	73.5	73.5	73.5	73.5	73.5
Lunghezza pedivella (mm)	165	165	170	170	170	175	175	175
Larghezza manubrio (mm)	700	720	740	720	740	740	740	740
Lunghezza Attacco Manubrio (mm)	35	45	60	45	60	60	70	70
Lunghezza reggisella (mm)	300	350	400	350	400	400	400	400
Larghezza sella (mm)	155	155	143	155	143	143	143	143

ART. NR.	DESCRIZIONE	COLORE	MISURA
91825-5002	ROCKHOPPER COMP	GLOSS METALLIC SPRUCE / SMOKE	S - 29
91825-5003			M - 29
91825-5004			L - 29
91825-5005			XL - 29
91825-5006			XXL - 29
91825-5102	ROCKHOPPER COMP	GLOSS PURPLE HAZE / ASTRAL BLUE	S - 29
91825-5103			M - 29
91825-5104			L - 29
91825-5105			XL - 29
91825-5106			XXL - 29
91525-5201	ROCKHOPPER COMP	SATIN MET. OAK GREEN / SMOKE	XS - 27.5
91525-5202			S - 27.5
91525-5203			M - 27.5
91825-5202			S - 29
91825-5203			M - 29
91825-5204			L - 29
91825-5205			XL - 29
91825-5206			XXL - 29

Disponibile Online e Pickup in store

# ROCKHOPPER SPORT



GLOSS PINE GREEN / OBSIDIAN



GLOSS SAPPHIRE / DUNE WHITE



SATIN CLAY / BLACK LIQUID



SATIN BLACK LIQUID METAL / WHITE

## ROCKHOPPER SPORT

## XS S - M - S - M - L - XL XXL

	27.5	27.5	27.5	29	29	29	29	29
Dimensione ruote (in)	27.5	27.5	27.5	29	29	29	29	29
Stack (mm)	559	573	589	607	616	626	640	654
Reach (mm)	375	395	415	405	425	445	465	485
Lunghezza Tubo Sterzo (mm)	95	100	105	95	95	105	120	135
Angolo Sterzo (degrees)	68	68	68	68.5	68.5	68.5	68.5	68.5
Altezza movimento centrale (mm)	310	310	310	310	310	310	310	310
B-B Drop (mm)	43	43	43	62	62	62	62	62
Trail (mm)	97	97	97	97	97	97	97	97
Lunghezza forcella (mm)	475	485	495	505	515	515	515	515
Offset Forcella/Rake (mm)	42	42	42	46	46	46	46	46
Avancorsa (mm)	630	656	682	672	696	719	745	770
Lunghezza Batticateni (mm)	440	440	440	440	440	440	440	440
Interasse (mm)	1067	1092	1118	1105	1128	1152	1178	1203
Lunghezza Tubo Orizz. virtuale (mm)	541	565	589	586	608	630	654	679
Altezza Standover (mm)	658	695	735	732	754	781	820	853
Lunghezza Piantone (mm)	310	350	400	360	400	450	500	560
Angolo Sella (degrees)	73.5	73.5	73.5	73.5	73.5	73.5	73.5	73.5
Lunghezza pedivella (mm)	165	165	170	170	170	175	175	175
Larghezza manubrio (mm)	700	720	740	720	740	740	740	740
Lunghezza Attacco Manubrio (mm)	35	45	60	45	60	60	70	70
Lunghezza reggisella (mm)	300	350	400	350	400	400	400	400
Larghezza sella (mm)	155	155	143	155	143	143	143	143

ART. NR.	DESCRIZIONE	COLORE	MISURA
91525-6001	ROCKHOPPER SPORT	GLOSS PINE GREEN / OBSIDIAN	XS - 27.5
91525-6002			S - 27.5
91525-6003			M - 27.5
91825-6002			S - 29
91825-6003			M - 29
91825-6004			L - 29
91825-6005			XL - 29
91825-6006			XXL - 29
91525-6101	ROCKHOPPER SPORT	GLOSS SAPPHIRE / DUNE WHITE	XS - 27.5
91525-6102			S - 27.5
91525-6103			M - 27.5
91825-6102			S - 29
91825-6103			M - 29
91825-6104			L - 29
91825-6105			XL - 29
91825-6106			XXL - 29

## SPECIFICHE TECNICHE

Specialized si riserva il diritto di modificare le caratteristiche senza preavviso.

Manubrio	Alloy Mini Rise, 9-degree backsweep, 15mm rise, 31.8mm
Telaio	Specialized A1 premium butted alloy, zero-stack head tube, internal cable routing, 135x9mm forged dropouts, chainstay-mounted disc brake, replaceable alloy derailleur hanger, stealth rack mounts, dropper post compatible
Collarino Sella	Alloy, quick release, 34.9
Forcella	SR Suntour XCM 29, 30mm stanchions, Rx Tune, coil spring, QR, 90/100mm travel (size-specific), 42mm offset
Freno anteriore	Tektro HD-M275, hydraulic disc, 180/160mm
Freno posteriore	Tektro HD-M275, hydraulic disc, 160mm
Comandi cambio	Shimano, SL-U4000-9R, CUES, Right, 9-Speed Rapidfire, W/ Optical Gear Display
Cambio posteriore	Shimano, RD-U4000, CUES, Gs 9-Speed, Top Normal, Shadow Design, Direct Attachment
Pacco Pignoni	Shimano, CS-LG300-9, CUES, 9-Speed, 11-41T
Catena	SHIMANO BICYCLE CHAIN, CN-LG500,XXXLINKS FOR LG 9/10/11 SPEED, W/QUICK-LINK, BULK
Guarnitura	Stout 1x, forged alloy
Movimento Centrale	Square-tapered, 73mm, internal bearings, 122.5mm spindle
Cerchi	Specialized alloy, disc only, double-wall, 25mm inner width, 32h
Mozzo anteriore	Formula 6-Bolt, disc, 100x9mm spacing, quick-release, 32H
Mozzo posteriore	Formula SP-2125, 6-Bolt freehub, disc, 135x9mm spacing, quick-release
Raggi	Stainless, 14g
Pneumatico anteriore	FAST TRAK SPORT, 26/650B/29x2.35
Pneumatico posteriore	FAST TRAK SPORT, 26/650B/29x2.35
Camere d'aria	Standard 40mm SV 26/650B/29x1.75-2.4
Attacco Manubrio	3D-forged alloy, 31.8mm, 7-degree rise
Manopole	Specialized Trail Grips, lock-on
Sella	Bridge Sport, Steel rails, 155/143mm
Reggisella	Alloy, 2-bolt clamp, 30.9mm
Pedali	Specialized Body Geometry Fitness, Platform, Plastic
Identificativo	279942

ART. NR.	DESCRIZIONE	COLORE	MISURA
91525-6201	ROCKHOPPER SPORT	SATIN BLACK LIQ METAL / WHITE	XS - 27.5
91525-6202			S - 27.5
91525-6203			M - 27.5
91825-6202			S - 29
91825-6203			M - 29
91825-6204			L - 29
91825-6205			XL - 29
91825-6206			XXL - 29
91525-6301	ROCKHOPPER SPORT	SATIN CLAY / BLACK LIQUID	XS - 27.5
91525-6302			S - 27.5
91525-6303			M - 27.5
91825-6302			S - 29
91825-6303			M - 29
91825-6304			L - 29
91825-6305			XL - 29
91825-6306			XXL - 29

Disponibile Online e Pickup in store



GLOSS SAGE GREEN / OLIVE GREEN



SATIN CAST LILAC / SEA FOAM



SATIN SLATE / COOL GREY

## ROCKHOPPER

**XS S - M - S - M - L - XL - XXL**  
**27.5 27.5 27.5 29 29 29 29 29**

Dimensione ruote (in)	27.5	27.5	27.5	29	29	29	29	29
Stack (mm)	559	573	589	607	616	626	640	654
Reach (mm)	375	395	415	405	425	445	465	485
Lunghezza Tubo Sterzo (mm)	95	100	105	95	95	105	120	135
Angolo Sterzo (degrees)	68	68	68	68.5	68.5	68.5	68.5	68.5
Altezza movimento centrale (mm)	310	310	310	310	310	310	310	310
B-B Drop (mm)	43	43	43	62	62	62	62	62
Trail (mm)	97	97	97	97	97	97	97	97
Lunghezza forcella (mm)	475	485	495	505	515	515	515	515
Offset Forcella/Rake (mm)	42	42	42	46	46	46	46	46
Avancorsa (mm)	630	656	682	672	696	719	745	770
Lunghezza Batticateni (mm)	440	440	440	440	440	440	440	440
Interasse (mm)	1067	1092	1118	1105	1128	1152	1178	1203
Lunghezza Tubo Orizz. virtuale (mm)	541	565	589	586	608	630	654	679
Altezza Standover (mm)	658	695	735	732	754	781	820	853
Lunghezza Piantone (mm)	310	350	400	360	400	450	500	560
Angolo Sella (degrees)	73.5	73.5	73.5	73.5	73.5	73.5	73.5	73.5
Lunghezza pedivella (mm)	165	165	170	170	170	175	175	175
Larghezza manubrio (mm)	700	720	740	720	740	740	740	740
Lunghezza Attacco Manubrio (mm)	35	45	60	45	60	60	70	70
Lunghezza reggisella (mm)	300	350	400	350	400	400	400	400
Larghezza sella (mm)	155	155	143	155	143	143	143	143

## SPECIFICHE TECNICHE

Specialized si riserva il diritto di modificare le caratteristiche senza preavviso.

Manubrio	Alloy Mini Rise, 9-degree backsweep, 15mm rise, 31.8mm
Telaio	Specialized A1 premium butted alloy, zero-stack head tube, internal cable routing, 135x9mm forged dropouts, chainstay-mounted disc brake, replaceable alloy derailleur hanger, stealth rack mounts, dropper post compatible
Collarino Sella	Alloy, quick release, 34.9
Forcella	SR Suntour XCM 27.5, 30mm stanchions, Rx Tune, coil spring, QR, 80/90/100mm travel (size-specific), 42mm offset
Freno anteriore	Shimano BR-MT200, hydraulic disc, 180mm
Freno posteriore	Shimano BR-MT200, hydraulic disc, 180mm
Comandi cambio	Shimano Altus, RapidFire Plus, 9-speed
Deragliatore anteriore	Shimano Altus FD-M2020 2-speed
Cambio posteriore	SHIMANO SHADOW RD-M2000 9-spd
Pacco Pignoni	SunRace, 9-Speed, 11-36t
Catena	KMC X9EPT, 9-speed, anti-corrosion coating w/ reusable Missing Link™
Guarnitura	Stout 2x, forged alloy
Movimento Centrale	Square-tapered, 73mm, internal bearings, 122.5mm spindle
Cerchi	Specialized alloy, disc only, double-wall, 25mm inner width, 32h
Mozzo anteriore	Formula 6-Bolt, disc, 100x9mm spacing, quick-release, 32H
Mozzo posteriore	Formula SP-2125, 6-Bolt freehub, disc, 135x9mm spacing, quick-release
Raggi	Stainless, 14g
Pneumatico anteriore	Fast Trak Sport, 27.5/29x2.35 ;
Pneumatico posteriore	Fast Trak Sport, 27.5/29x2.35 ;
Camere d'aria	Standard 40mm SV 650B/29x1.75-2.4
Attacco Manubrio	Stout 3D-forged alloy, 31.8mm, 6-degree rise
Manopole	Specialized Trail Grips, lock-on
Sella	Bridge Sport, Steel rails, 155/143mm
Reggisella	Alloy, 2-bolt clamp, 30.9mm
Peso	13.87kg (30 lb, 9.2 oz)
Misura pesata	MD

ART. NR.	DESCRIZIONE	COLORE	MISURA
91525-7601	ROCKHOPPER 27.5	GLOSS SAGE GREEN / OLIVE GREEN	XS - 27.5
91525-7602			S - 27.5
91525-7603			M - 27.5
91825-7602	ROCKHOPPER 29	GLOSS SAGE GREEN / OLIVE GREEN	S - 29
91825-7603			M - 29
91825-7604			L - 29
91825-7605			XL - 29
91825-7606			XXL - 29
91525-7701	ROCKHOPPER 27.5	SATIN CAST LILAC / SEA FOAM	XS - 27.5
91525-7702			S - 27.5
91525-7703			M - 27.5
91825-7702	ROCKHOPPER 29	SATIN CAST LILAC / SEA FOAM	S - 29
91825-7703			M - 29
91825-7704			L - 29
91825-7705			XL - 29
91825-7706			XXL - 29

ART. NR.	DESCRIZIONE	COLORE	MISURA
91525-7801	ROCKHOPPER 27.5	SATIN SLATE / COOL GREY	XS - 27.5
91525-7802			S - 27.5
91525-7803			M - 27.5
91825-7802	ROCKHOPPER 29	SATIN SLATE / COOL GREY	S - 29
91825-7803			M - 29
91825-7804			L - 29
91825-7805			XL - 29
91825-7806			XXL - 29

Disponibile Online e Pickup in store



GLOSS TEAL TINT / FLAKE SILVER



SATIN REDWOOD / WHITE



SATIN REDWOOD / WHITE

SPECIFICHE TECNICHE	Specialized si riserva il diritto di modificare le caratteristiche senza preavviso.
Telaio	A1 Premium Butted Alloy, unisex frame, internal cable routing, 135x10mm forged dropouts, replaceable derailleur hanger
Forcella	A1 Premium Butted Alloy, Alloy steerer, V-Brake
Attacco Manubrio	3D Forged Aluminum, 35mm length, 6 degree rise, 25.4mm clamp diameter
Manubrio	Alloy Mini Rise, Double Butted, 80mm Rise, 5-degree Backsweep, 600mm Width, 25.4mm Clamp Diameter
Manopole	Jett Body Geometry, lock-on
Reggisella	Alloy, 2-bolt, 14mm offset, 27.2mm
Freno anteriore	V-brake w/ tool-less reach adjust brake lever
Freno posteriore	V-brake w/ tool-less reach adjust brake lever
Cambio posteriore	microSHIFT RD-M26S, 8-speed
Comandi cambio	microSHIFT, TS39-8R, 8 speed
Catena	KMC HV500
Guarnitura	Forged Alloy, Square Taper, Adjustable 130/150mm Length, w/ Chainguard
Pacco Pignoni	SunRace, 8-speed, 11-34t
Ingranaggi	34T
Movimento Centrale	Square taper, Plastic cups, 113mm spindle
Pedali	Nylon platform w/ reflectors
Cerchi	Alloy, 14mm Depth, 23mm Internal Width, 28H
Mozzo anteriore	Alloy, Loose Ball Bearings, Bolt type, 100mm Spacing, 28H
Mozzo posteriore	Alloy, Loose Ball Bearings, Bolt type, 135mm Spacing, 28H
Raggi	Stainless, 14g
Pneumatico anteriore	Pathfinder Sport, 24x2.0"
Pneumatico posteriore	Pathfinder Sport, 24x2.0"
Camere d'aria	Schrader valve
Sella	Kids Bridge Saddle, 130mm
Collarino Sella	Bolt-type, 31.8mm

JETT 24	24"
Stack (mm)	459
Reach (mm)	325
Lunghezza Tubo Sterzo (mm)	105
Angolo sterzo (degrees)	69
Altezza BB (mm)	270
B-B Drop (mm)	40
Trail (mm)	74
Lunghezza forcella (mm)	355
Offset forcella/Rake (mm)	42
Avancorsa (mm)	532
Lunghezza Batticateni (mm)	400
Interasse (mm)	929
Lunghezza Tubo Orizz. virtuale (mm)	465
Altezza standover (mm)	580
Lunghezza piantone (mm)	330
Angolo sella (degrees)	73

ART. NR.	DESCRIZIONE	COLORE	MISURA
92722-8224	JETT 24 INT	GLOSS TEAL TINT / FLAKE SILVER	24
92722-8324	JETT 24 INT	SATIN REDWOOD / WHITE	24
92722-8124	JETT 24 INT	GLOSS FLO RED / BLACK	24



GLOSS CAST BLACK / SMOKE



GLOSS OASIS / FOREST GREEN



GLOSS RASPBERRY / UV LILAC



CBLT/ICEBLU

**SPECIFICHE TECNICHE**

Specialized si riserva il diritto di modificare le caratteristiche senza preavviso.

Telaio	A1 Premium Butted Alloy, unisex frame, internal cable routing, 135x10mm forged dropouts, replaceable derailleur hanger
Forcella	A1 Premium Butted Alloy, Alloy steerer, V-Brake
Attacco Manubrio	3D Forged Aluminum, 35mm length, 6 degree rise, 25.4mm clamp diameter
Manubrio	Alloy Mini Rise, Double Butted, 60mm Rise, 5-degree Backsweep, 580mm Width, 25.4mm Clamp Diameter, 19mm Bar End Diameter
Manopole	Jett Body Geometry, 19mm Internal Diameter, lock-on
Freno anteriore	V-brake w/ tool-less reach adjust brake lever
Reggisella	Alloy, 2-bolt, 14mm offset, 27.2mm
Freno posteriore	V-brake w/ tool-less reach adjust brake lever
Cambio posteriore	microSHIFT RD-M26S, 7-speed
Comandi cambio	microSHIFT TS39 Trigger shift, 7-speed
Pacco Pignoni	SunRace, 7-Speed, 11-34t
Catena	KMC HV500
Guarnitura	Forged Alloy, Square Taper, Adjustable 105/125mm Length, w/ Chainguard
Movimento Centrale	Square taper, Plastic cups, 113mm spindle
Ingranaggi	34T
Pedali	Nylon platform w/ reflectors
Cerchi	Alloy, 14mm Depth, 23mm Internal Width, 28H
Mozzo anteriore	Alloy, Loose Ball Bearings, Bolt type, 100mm Spacing, 28H
Mozzo posteriore	Alloy, Loose Ball Bearings, Bolt type, 135mm Spacing, 28H
Raggi	Stainless, 14g
Pneumatico anteriore	Pathfinder Sport, 20x2.0"
Pneumatico posteriore	Pathfinder Sport, 20x2.0"
Camere d'aria	Schrader valve
Sella	Kids Bridge Saddle, 130mm
Collarino Sella	Bolt-type, 31.8mm

JETT 20	20"
Stack (mm)	398
Reach (mm)	295
Lunghezza Tubo Sterzo (mm)	100
Angolo sterzo (degrees)	69
Altezza BB (mm)	229.5
B-B Drop (mm)	30
Trail (mm)	57
Lunghezza forcella (mm)	305
Offset forcella/Rake (mm)	40
Avancorsa (mm)	480
Lunghezza Batticateni (mm)	350
Interasse (mm)	828
Lunghezza Tubo Orizz. virtuale (mm)	417
Altezza standover (mm)	510
Lunghezza piantone (mm)	290
Angolo sella (degrees)	73

ART. NR.	DESCRIZIONE	COLORE	MISURA
92722-6120	JETT 20 INT	GLOSS CAST BLACK / SMOKE	20
92722-6320	JETT 20 INT	GLOSS OASIS / FOREST GREEN	20
92722-6420	JETT 20 INT	GLOSS RASPBERRY / UV LILAC	20
92722-6220	JETT 20 INT	CBLT/ICEBLU	20



GLOSS SLPHR OAKGRN



GLOSS WHTMTN AMBRLW



SATIN CSTBLK SMK



SATIN METSPR DARK MOSS GREEN

**SPECIFICHE TECNICHE**

**Specialized si riserva il diritto di modificare le caratteristiche senza preavviso.**

Telaio	A1 Premium Butted Alloy, unisex frame, internal cable routing, 148mm thru-axle, 30.9mm dropper post ready, replaceable derailleur hanger compatible
Forcella	A1 Premium Butted Alloy, Alloy steerer, 15x110 mm, W/Mini Fender
Curva manubrio	Double-butted alloy, 9-degree backsweep, 31.8mm
Attacco Manubrio	Stout 3D-forged alloy, 31.8mm, 6-degree rise
Manopole	Specialized Trail Grips, lock-on
Freno anteriore	Promax DSK-926, Hydraulic Disc Brake, 160mm Rotor, Adjustable Reach
Freno posteriore	Promax DSK-926, Hydraulic Disc Brake, 160mm Rotor, Adjustable Reach
Comandi cambio	microSHIFT Advent Quick Trigger SL-M6190, 9-Speed, short reach triggers for easy operation
Cambio posteriore	microSHIFT Advent, RD-M6195M, w/ clutch
Catena	KMC X9EPT, 9-speed, anti-corrosion coating w/ reusable Missing Link™
Pacco Pignoni	microSHIFT Advent CS-H094, 11-42T, 9-speed
Guarnitura	Forged Alloy, 115mm length, narrow Q-factor, w/ chainguard
Ingranaggi	40T
Movimento Centrale	Square-tapered, 68mm
Pedali	Nylon platform w/ reflectors
Cerchi	Alloy, 16mm depth, 25mm internal width, 28H
Mozzo anteriore	Alloy, 6-Bolt, 28H, 15x110 Boost
Mozzo posteriore	Alloy, 6-Bolt, 28H, 12x148 Boost, 11-speed compatible
Pneumatico anteriore	Ground Control Sport, 24x2.35"
Pneumatico posteriore	Ground Control Sport, 24x2.35"
Raggi	Stainless, 14g
Camere d'aria	OE Standard 32mm PV 24x2.0-2.4
Sella	Kids Bridge Saddle, 130mm
Collarino Sella	Bolt-type, 34.9mm
Reggisella	Specialized, 6061 alloy, 2-bolt clamp, 0mm setback, 30.9mm
Peso	10.75 kg (23 lb, 11.2 oz)
Misura pesata	One Size

<b>RIPROCK 24</b>	<b>24"</b>
Stack (mm)	449
Reach (mm)	350
Lunghezza Tubo Sterzo (mm)	95
Angolo sterzo (degrees)	68
Altezza BB (mm)	287.5
B-B Drop (mm)	30
Trail (mm)	83
Lunghezza forcella (mm)	370
Offset forcella/Rake (mm)	42
Avancorsa (mm)	565
Lunghezza Batticatena (mm)	390
Interasse (mm)	953
Lunghezza Tubo Orizz. virtuale (mm)	479
Altezza standover (mm)	593
Lunghezza piantone (mm)	310
Angolo sella (degrees)	73.5
Lunghezza pedivella (mm)	140
Larghezza Manubrio (mm)	620
Lunghezza Attacco man. (mm)	35
Larghezza Sella (mm)	130

<b>ART. NR.</b>	<b>DESCRIZIONE</b>	<b>COLORE</b>	<b>MISURA</b>
96524-8124	RIPROCK 24 INT	GLOSS SLPHR OAKGRN	24
96524-8324	RIPROCK 24 INT	GLOSS WHTMTN AMBRLW	24
96524-8224	RIPROCK 24 INT	SATIN CSTBLK SMK	24
96524-8024	RIPROCK 24 INT	SATIN METSPR DARK MOSS GREEN	24



GLOSS AMBRGLW REDWD



GLOSS DUNE WHITE PNGRN



GLOSS PDRNDGO SLT



GLOSS SPHR EGRN

**SPECIFICHE TECNICHE**

**Specialized si riserva il diritto di modificare le caratteristiche senza preavviso.**

Telaio	A1 Premium Butted Alloy, unisex frame, internal cable routing, 148mm thru-axle, 30.9mm dropper post ready, replaceable derailleur hanger compatible
Forcella	A1 Premium Butted Alloy, Alloy steerer, 15x110 mm, W/Mini Fender
Manubrio	Mini Rise, Alloy Double Butted, 6-degree Backsweep, 600mm Width, 31.8mm, 19mm Bar End Diameter
Attacco Manubrio	Stout 3D-forged alloy, 31.8mm, 6-degree rise
Manopole	Specialized Trail Grips, 19mm bar end diameter, lock-on
Freno anteriore	Promax DSK-926, Hydraulic Disc Brake, 160mm Rotor, Adjustable Reach
Freno posteriore	Promax DSK-926, Hydraulic Disc Brake, 160mm Rotor, Adjustable Reach
Cambio posteriore	microSHIFT Super Short derailleur RD-M5185S, 8-Speed, w/ Clutch
Cambio anteriore	DERAILLEUR, MICROSHIFT, RD-M5185S, REAR, SHORT CAGE, W/ CLUTCH
Comandi cambio	SHIFTER, MICROSHIFT, SL-M6285-SR, REAR, MOUNTAIN, HANDLE BAR MOUNT, SHORT REACH SHIFTER FOR 19MM BAR, W/ GEAR DISPLAY, 8 SP, W GREY RUBBER PAD LEVER, SHIMANO NOT COMPATIBLE
Comandi cambio	microSHIFT Acolyte Quick Trigger SL-M6280, 8-Speed, short reach triggers for easy operation
Pacco Pignoni	microSHIFT CS-H083, 11-38T, 8-speed
Guarnitura	Forged Alloy, 115mm length, narrow Q-factor, w/ chainguard
Ingranaggi	40T
Movimento Centrale	Square-tapered, 68mm
Pedali	Nylon platform w/ reflectors
Cerchi	Alloy, 16mm depth, 25mm internal width, 28H
Catena	KMC X8 w/ Missing Link™
Mozzo anteriore	Alloy, 6-Bolt, 28H, 15x110 Boost
Mozzo posteriore	Alloy, 6-Bolt, 28H, 12x148 Boost, 11-speed compatible
Pneumatico anteriore	Ground Control Sport, 20x2.35"
Pneumatico posteriore	Ground Control Sport, 20x2.35"
Camere d'aria	Schrader valve
Raggi	Stainless, 14g
Sella	Kids Bridge Saddle, 130mm
Collarino Sella	Bolt-type, 34.9mm
Reggisella	Specialized, 6061 alloy, 2-bolt clamp, 0mm setback, 30.9mm
Peso	9.79 kg (21 lb, 9.3 oz)
Misura pesata	One Size

<b>RIPROCK 20</b>	<b>20"</b>
Stack (mm)	385
Reach (mm)	295
Lunghezza Tubo Sterzo (mm)	75
Angolo sterzo (degrees)	68
Altezza BB (mm)	239
B-B Drop (mm)	30
Trail (mm)	66
Lunghezza forcella (mm)	320
Offset forcella/Rake (mm)	40
Avancorsa (mm)	482
Lunghezza Batticateni (mm)	350
Interasse (mm)	830
Lunghezza Tubo Orizz. virtuale (mm)	405
Altezza standover (mm)	520
Lunghezza piantone (mm)	290
Angolo sella (degrees)	73.5
Lunghezza pedivella (mm)	115
Larghezza Manubrio (mm)	600
Lunghezza Attacco man. (mm)	35
Larghezza Sella (mm)	130

ART. NR.	DESCRIZIONE	COLORE	MISURA
96524-8020	RIPROCK 20 INT	GLOSS AMBRGLW REDWD	20
96524-8220	RIPROCK 20 INT	GLOSS DUNE WHITE PNGRN	20
96524-8120	RIPROCK 20 INT	GLOSS PDRNDGO SLT	20
96524-8320	RIPROCK 20 INT	GLOSS SPHR EGRN	20

# RIPROCK COASTER 16



GLOSS WHITE SAGE / DUNE WHITE



SATIN FIERY RED / WHITE



SATIN MYSTIC BLUE / FIERY RED

## SPECIFICHE TECNICHE

Specialized si riserva il diritto di modificare le caratteristiche senza preavviso.

Telaio	Specialized A1 Premium Aluminum
Forcella	Hi-Ten steel
Attacco Manubrio	Die Cast Aluminum, 37mm length, 10 degree, 22.2 clamp diameter
Manubrio	BMX, steel, 10-degree backsweep, 4-degree upsweep, 115mm rise, 520mm width, 22.2mm
Manopole	Specialized, slip-on
Catena	KMC Z510, single-speed, anti-drop, 1/2"x1/8"
Guarnitura	Hi-Ten steel, 89mm
Ingranaggi	Steel, 26T
Movimento Centrale	Feimin FP-B701, 68MM
Pedali	Nylon platform w/ reflectors
Cerchi	16" alloy, 16mm depth, 21mm internal width, 28h
Reggisella	Steel, 22.2mm
Mozzo anteriore	Steel, bolt-on, 100mm spacing, loose ball bearings, 28h
Mozzo posteriore	Coaster brake, bolt-on, loose ball bearings, 110mm spacing, 16T cog, 28h
Raggi	Stainless, 14g
Pneumatico anteriore	Rhythm Lite, 30 TPI, wire bead, 16x2.3"
Pneumatico posteriore	Rhythm Lite, 30 TPI, wire bead, 16x2.3"
Camere d'aria	Schrader valve
Sella	Specialized Kids' Henge
Collarino Sella	Bolt-type, 28.6mm
Peso	9.1kg (20 lb, 1 oz)
Misura pesata	One Size

RIPROCK COASTER 16	16
Lunghezza piantone c/f (mm)	210
Lunghezza Tubo Orizz. virtuale (mm)	395
BB Drop (mm)	27
Lunghezza Batticateni (mm)	310
Angolo Sella (degrees)	71
Angolo sterzo (degrees)	70
Offset forcella/Rake (mm)	5
Trail (mm)	72
Avancorsa (mm)	399
Interasse (mm)	707
Altezza Standover (mm)	405
Lunghezza Tubo Sterzo (mm)	80
Reach (mm)	272
Stack (mm)	358

ART. NR.	DESCRIZIONE	COLORE	MISURA
96523-4216	RIPROCK CSTR 16 INT	GLOSS WHITE SAGE / DUNE WHITE	16
96523-4016	RIPROCK CSTR 16 INT	SATIN FIERY RED / WHITE	16
96523-4116	RIPROCK CSTR 16 INT	SATIN MYSTIC BLUE / FIERY RED	16



Gloss Deep Orange / Amber Glow



Gloss Dune White / Team Yellow



Gloss Astral Blue / Storm Grey



Gloss Powder Indigo / Purple Haze

## SPECIFICHE TECNICHE

Specialized si riserva il diritto di modificare le caratteristiche senza preavviso.

Forcella	Formed steel tubes, 95mm Spacing
Collarino Sella	Bolt-type, 25.4mm
Telaio	Specialized A1 Premium Aluminum, 1" threaded headset
Cerchi	12" alloy, 16mm depth, 21mm internal width
Mozzo anteriore	Bolt-on, 95mm spacing, loose ball bearings, 16h
Mozzo posteriore	Bolt-on, 95mm spacing, loose ball bearings, 16h
Raggi	Stainless, 14g
Pneumatico anteriore	Rhythm Lite Airless, 12x2.3
Pneumatico posteriore	Rhythm Lite Airless, 12x2.3
Attacco Manubrio	Die Cast Aluminum, 35mm length, 22.2 clamp diameter
Manubrio	Steel, 400mm width, 20mm rise, 8-degree backsweep
Manopole	Specialized, slip-on
Sella	Hotwalk Integrated Saddle/Seatpost
Reggisella	Steel, 22.2mm
Identificativo	274937
Peso	4.1 kg (9 lb, 0.6 oz)
Misura pesata	One Size

## HOTWALK

unisex

Stack (mm)	319
Reach (mm)	185
Lunghezza Tubo Sterzo (mm)	70
Angolo Sterzo (degrees)	69
Altezza movimento centrale (mm)	118
B-B Drop (mm)	55
Trail (mm)	57
Lunghezza forcella (mm)	205
Offset Forcella/Rake (mm)	5
Avancorsa (mm)	297
Lunghezza Batticateni (mm)	258
Interasse (mm)	544
Lunghezza Tubo Orizz. virtuale (mm)	295
Altezza Standover (mm)	281
Lunghezza Piantone (mm)	160
Angolo Sella (degrees)	71
Larghezza Manubrio (mm)	400
Lunghezza Attacco man. (mm)	35
Larghezza Sella (mm)	110
Lunghezza Reggisella (mm)	230

ART. NR.	DESCRIZIONE	COLORE	MISURA
94025-7512	HOTWALK	Gloss Deep Orange / Amber Glow	12
94025-7712	HOTWALK	Gloss Dune White / Team Yellow	12
94025-7412	HOTWALK	Gloss Astral Blue / Storm Grey	12
94025-7612	HOTWALK	Gloss Powder Indigo / Purple Haze	12



STN REFL.SILDST CLGRY

SIRRUS X 4.0	XXS	XS	S	M	L	XL
Stack (mm)	587	590	606	635	651	672
Reach (mm)	355	371	376	382	386	398
Lunghezza Tubo Sterzo (mm)	111	125	143	169	186	208
Angolo Sterzo (degrees)	69.5	70	70	71	71	71
Altezza movimento centrale (mm)	284	284	284	284	284	284
B-B Drop (mm)	70	70	70	70	70	70
Trail (mm)	78	75	75	68	68	68
Lunghezza forcella (mm)	395	395	395	395	395	395
Offset Forcella/Rake (mm)	51	51	51	51	51	51
Avancorsa (mm)	602	618	629	634	644	663
Lunghezza Batticateni (mm)	440	440	440	440	440	440
Interasse (mm)	1033	1049	1060	1065	1074	1093
Lunghezza Tubo Orizz. virtuale (mm)	529	549	559	573	581	599
Altezza Standover (mm)	700	722	750	778	810	831
Lunghezza Piantone (mm)	360	395	440	470	510	530
Angolo Sella (degrees)	73.5	73.5	73.5	73.5	73.5	73.5
Lunghezza pedivella (mm)	165	165	170	170	175	175
Larghezza Manubrio (mm)	680	680	680	680	680	680
Lunghezza Attacco man. (mm)	60	60	70	80	90	100
Larghezza Sella (mm)	155	155	155	143	143	143
Lunghezza Reggisella (mm)	300	300	350	350	400	400

## SPECIFICHE TECNICHE

SPECIFICHE TECNICHE	Specialized si riserva il diritto di modificare le caratteristiche senza preavviso.
Forcella	Specialized FACT 9r Carbon Monocoque, flat-mount disc, 12x100mm thru-axle, low rider mounts, Plug + Play fender mounts, Future Shock 1.5
Manopole	Specialized Neutralizer, Body Geometry, locking grip
Manubrio	Alloy Mini Rise, 9-degree backsweep, 15mm rise, 31.8mm
Ingranaggi	34T
Telaio	Specialized A1 SL Premium Aluminum, Fitness Geometry, fully manipulated butted tubing, internal cable routing, flat-mount disc, 12x142mm thru-axle, Plug + Play rack/fender mounts
Freno anteriore	Tektro HD-R510, hydraulic disc, 160mm
Freno posteriore	Tektro HD-R510, hydraulic disc, 160mm
Comandi cambio	Shimano Cues SL-U6000, 11-Speed
Cambio posteriore	Shimano Cues Shadow RD-U6000, 11-Speed
Pacco Pignoni	Shimano, CS-LG400-11, Cues, 11-Speed, 11-50T
Catena	KMC eGlide for 9-Speed Cues
Guarnitura	PROWHEEL, Alloy, 165mm
Movimento Centrale	Threaded BSA 68mm, 24mm spindle
Cerchi	700C disc, double-wall alloy, 22mm depth, 21mm internal width, 32h
Mozzo anteriore	Alloy, Center lock Disc, High-Low Flange, Sealed Cartridge Bearing, 24H, 12mm Axle, 100mm Spacing
Mozzo posteriore	Alloy, Center lock Disc, High-Low Flange, Sealed Cartridge Bearing, 32H, 12mm Axle, 142mm Spacing
Raggi	Stainless, 14g
Pneumatico anteriore	Pathfinder Sport, 700x38
Pneumatico posteriore	Pathfinder Sport, 700x38
Camere d'aria	Standard 40mm SV 700x32-50
Attacco Manubrio	Future Stem, Comp
Sella	Power Comp, Hollow Cr-mo rails, 155/143mm
Reggisella	Alloy, 2-bolt, 14mm offset, 27.2mm
Collarino Sella	Bolt-type, 31.8mm
Pedali	Specialized Body Geometry Fitness, Platform, Plastic
Identificativo	221896
Peso	10.64kg (23 lb, 7.3 oz)
Misura pesata	LG

ART. NR.	DESCRIZIONE	COLORE	MISURA
92425-5100	SIRRUS X 4.0	STN REFL.SILDST CLGRY	XXS
92425-5101			XS
92425-5102			S
92425-5103			M
92425-5104			L
92425-5105			XL

Disponibile solo online & Pick up in Store



STN REFL STRMGRY CHAR

SIRRUS X 4.0 EQ	XS	S	M	L	XL
Stack (mm)	590	606	635	651	672
Reach (mm)	371	376	382	386	398
Lunghezza Tubo Sterzo (mm)	125	143	169	186	208
Angolo Sterzo (degrees)	70	70	71	71	71
Altezza movimento centrale (mm)	284	284	284	284	284
B-B Drop (mm)	70	70	70	70	70
Trail (mm)	75	75	68	68	68
Lunghezza forcella (mm)	395	395	395	395	395
Offset Forcella/Rake (mm)	51	51	51	51	51
Avancorsa (mm)	618	629	634	644	663
Lunghezza Batticateni (mm)	440	440	440	440	440
Interasse (mm)	1049	1060	1065	1074	1093
Lunghezza Tubo Orizz. virtuale (mm)	549	559	573	581	599
Altezza Standover (mm)	722	750	778	810	831
Lunghezza Piantone (mm)	395	440	470	510	530
Angolo Sella (degrees)	73.5	73.5	73.5	73.5	73.5
Lunghezza pedivella (mm)	N/A	170	170		
Larghezza Manubrio (mm)	N/A	680	680		
Lunghezza Attacco man. (mm)	N/A	80	90		
Larghezza Sella (mm)	N/A	155	143		
Lunghezza Reggisella (mm)	N/A	350	350		

## SPECIFICHE TECNICHE

	Specialized si riserva il diritto di modificare le caratteristiche senza preavviso.
Forcella	Specialized FACT 9r Carbon Monocoque, flat-mount disc, 12x100mm thru-axle, low rider mounts, Plug + Play fender mounts, Future Shock 1.5
Manopole	Specialized Neutralizer, Body Geometry, locking grip
Manubrio	Alloy Mini Rise, 9-degree backsweep, 15mm rise, 31.8mm
Telaio	Specialized A1 SL Premium Aluminum, Fitness Geometry, fully manipulated butted tubing, internal cable routing, flat-mount disc, 12x142mm thru-axle, Plug + Play rack/fender mounts
Forcella	FC075, 2022 SIRRUS 9r Disc
Freno anteriore	Tektro HD-R510, hydraulic disc, 160mm
Freno posteriore	Tektro HD-R510, hydraulic disc, 160mm
Comandi cambio	Shimano Deore M6100, 12-speed
Cambio posteriore	Shimano Deore, M6100, 12pd, Shadow Plus
Pacco Pignoni	Sunrace CSMZ800, 12-speed, 11-51t
Catena	KMC X12EPT, 12-speed, anti-corrosion coating w/ reusable Missing Link™
Guarnitura	Forged aluminum arms, 24mm spindle, Narrow-wide steel chainring 40t, chainguard
Ingranaggi	48/32 w/ chainguard
Movimento Centrale	Threaded BSA 68mm
Cerchi	700c disc brake, double-wall alloy, 22mm depth, 21mm internal width
Mozzo anteriore	Shimano Dynamo, Center Lock disc, 12x100mm Thru-axle spacing, 32H
Mozzo posteriore	Alloy, Center lock Disc, High-Low Flange, Sealed Cartridge Bearing, 32H, 12mm Axle, 142mm Spacing
Raggi	Stainless, 14g
Pneumatico anteriore	Pathfinder Sport, 700x38
Pneumatico posteriore	Pathfinder Sport, 700x38
Camere d'aria	Standard 40mm SV 700x32-50
Attacco Manubrio	Specialized, 3D-forged alloy, 4-bolt, 7-degree rise
Sella	Power Comp, Hollow Cr-mo rails, 155/143mm
Reggisella	Alloy, 2-bolt, 14mm offset, 27.2mm
Collarino Sella	Bolt-type, 31.8mm
Pedali	Specialized Body Geometry Fitness, Platform, Plastic
Fanale anteriore	Herrmans H-Black Pro Dynamo LED Head Light
Fanalino posteriore	Herrmans H-Trace Mini Dynamo Rear Light
Portapacchi	Tubus, Rear Rack, 15kg Weight Limit, Aluminum
Parafanghi	DryTech Fender, Front & Rear, Aluminum with Black Finish
Identificativo	221897
Peso	12.57 kg (27 lb, 11.4 oz)
Misura pesata	LG

ART. NR.	DESCRIZIONE	COLORE	MISURA
92425-5202	SIRRUS X 4.0 EQ	STN REFL STRMGRY CHAR	S
92425-5203			M
92425-5204			L
92425-5205			XL

Disponibile solo online & Pick up in Store



GLS REFL ASHGRY BLKLQDMET

SIRRUS X 3.0 EQ	XXS	XS	S	M	L	XL
Stack (mm)	536	555	563	593	608	633
Reach (mm)	373	388	393	398	402	414
Lunghezza Tubo Sterzo (mm)	121	139	147	175	191	217
Angolo Sterzo (degrees)	69.5	70	70	71	71	71
Altezza movimento centrale (mm)	288	288	288	288	288	288
B-B Drop (mm)	70	70	70	70	70	70
Trail (mm)	79	76	76	69	69	69
Lunghezza forcella (mm)	395	395	395	395	395	395
Offset Forcella/Rake (mm)	51	51	51	51	51	51
Avancorsa (mm)	606	623	631	636	645	665
Lunghezza Batticateni (mm)	440	440	440	440	440	440
Interasse (mm)	1036	1053	1061	1067	1076	1096
Lunghezza Tubo Orizz. virtuale (mm)	532	552	560	574	582	602
Altezza Standover (mm)	702	725	755	785	815	837
Lunghezza Piantone (mm)	360	395	440	470	510	530
Angolo Sella (degrees)	73.5	73.5	73.5	73.5	73.5	73.5
Lunghezza pedivella (mm)	N/A	N/A	170	170		
Larghezza Manubrio (mm)	N/A	N/A	680	680		
Lunghezza Attacco man. (mm)	N/A	N/A	70	80		
Larghezza Sella (mm)	N/A	N/A	155	143		
Lunghezza Reggisella (mm)	N/A	N/A	350	350		

## SPECIFICHE TECNICHE

Specialized si riserva il diritto di modificare le caratteristiche senza preavviso.

Forcella	A1 Premium Aluminum, flat-mount disc, Plug + Play fender mounts, low rider rack mounts, quick-release
Manopole	Specialized Neutralizer, Body Geometry, locking grip
Manubrio	Alloy Mini Rise, 9-degree backsweep, 15mm rise, 31.8mm
Telaio	Specialized A1 Premium Aluminum, Fitness Geometry, butted tubing, internal cable routing, flat-mount disc, quick-release, Plug + Play rack/fender mounts
Freno anteriore	Tektro HD-R280, hydraulic disc, 160 mm rotor
Freno posteriore	Tektro HD-R280, hydraulic disc, resin pads, flat-mount, 140mm
Comandi cambio	Shimano Cues SL-U6000, 11-Speed
Cambio posteriore	Shimano Cues Shadow RD-U6000, 11-Speed
Pacco Pignoni	Shimano, CS-LG400-11, Cues, 11-Speed, 11-50T
Catena	KMC eGlide for 9-Speed Cues
Guarnitura	Shimano Cues FC-U6000, 165mm
Ingranaggi	50/34T
Movimento Centrale	Shimano 68mm threaded
Cerchi	700C disc brake, double-wall alloy, 22mm depth, 21mm internal width
Mozzo anteriore	Shimano Dynamo, 6-bolt disc, 100mm spacing, quick-release, 32h
Mozzo posteriore	Alloy, Shimano 11speed Freehub, 6 Bolt Disc, 32H, 10mm Axle, 135mm Spacing
Raggi	Stainless, 14g
Pneumatico anteriore	Pathfinder Sport, 700x38
Pneumatico posteriore	Pathfinder Sport, 700x38
Camere d'aria	Standard 40mm SV 700x32-50
Attacco Manubrio	3D-forged alloy, 31.8mm, 7-degree rise
Sella	Bridge Sport, Steel rails, 155/143mm
Reggisella	Alloy, 12mm offset, 2-bolt clamp, 27.2mm
Collarino Sella	Bolt-type, 31.8mm
Pedali	Specialized Body Geometry Fitness, Platform, Plastic
Fanale anteriore	H-Black MR4 Dynamo Front Light
Fanalino posteriore	Herrmans H-Trace Mini Dynamo Rear Light
Portapacchi	Tubus, Rear Rack, 15kg Weight Limit, Aluminum
Parafanghi	DryTech Fender, Front & Rear, Aluminum with Black Finish
Identificativo	221893
Peso	13.07 kg (28 lb, 13 oz)
Misura pesata	LG

ART. NR.	DESCRIZIONE	COLORE	MISURA
92425-7302	SIRRUS X 3.0 EQUIP GLS	REFL ASHGRY BLKLQDMET	S
92425-7303			M
92425-7304			L
92425-7305			XL

Disponibile solo online & Pick up in Store

# SIRRUS X 3.0 STEP-THROUGH



GLS REFL ASHGRY BLKLQDMET

SIRRUS X 3.0 STEP-THROUGH	XS	S	M
Stack (mm)	555	563	593
Reach (mm)	393	400	408
Lunghezza Tubo Sterzo (mm)	139	147	175
Angolo Sterzo (degrees)	70	70	71
Altezza movimento centrale (mm)	288	288	288
B-B Drop (mm)	70	70	70
Trail (mm)	76	76	69
Lunghezza forcella (mm)	395	395	395
Offset Forcella/Rake (mm)	51	51	51
Avancorsa (mm)	628	637	646
Lunghezza Batticateni (mm)	440	440	440
Interasse (mm)	1058	1068	1077
Lunghezza Tubo Orizz. virtuale (mm)	557	567	584
Altezza Standover (mm)	636	636	641
Lunghezza Piantone (mm)	395	450	500
Angolo Sella (degrees)	73.5	73.5	73.5
Lunghezza pedivella (mm)	165	170	170
Larghezza Manubrio (mm)	680	680	680
Lunghezza Attacco man. (mm)	60	70	80
Larghezza Sella (mm)	155	155	143
Lunghezza Reggisella (mm)	300	350	350

SPECIFICHE TECNICHE	Specialized si riserva il diritto di modificare le caratteristiche senza preavviso.
Manopole	Specialized Neutralizer, Body Geometry, locking grip
Manubrio	Alloy Mini Rise, 9-degree backsweep, 15mm rise, 31.8mm
Telaio	Specialized A1 Premium Aluminum, Fitness Geometry, butted tubing, internal cable routing, flat-mount disc, quick-release, Plug + Play rack/fender mounts
Forcella	A1 Premium Aluminum, flat-mount disc, Plug + Play fender mounts, low rider rack mounts, quick-release
Freno anteriore	Tektro HD-R280, hydraulic disc, 160 mm rotor
Freno posteriore	Tektro HD-R280, hydraulic disc, resin pads, flat-mount, 140mm
Comandi cambio	Shimano Deore M5100, 11-speed
Cambio posteriore	microSHIFT Advent RD-M6195M, 9-Speed
Pacco Pignoni	microSHIFT Advent CS-H093, 11-46t, 9-speed
Catena	KMC X9, 9-speed w/ Missing Link™
Guarnitura	Forged aluminum arms, 24mm spindle, Narrow-wide steel chainring 40t, chainguard
Ingranaggi	48/32 w/ chainguard
Movimento Centrale	Threaded BSA 68mm
Cerchi	700C disc, double-wall alloy, 22mm depth, 21mm internal width, 32h
Mozzo anteriore	Alloy, 6-bolt disc, loose ball bearing, quick-release, 32h
Mozzo posteriore	Alloy, 6-bolt disc, 8-/9-speed freehub, loose ball bearing, quick-release, 32h
Raggi	Stainless, 14g
Pneumatico anteriore	Pathfinder Sport, 700x42mm
Pneumatico posteriore	Pathfinder Sport, 700x42mm
Camere d'aria	Standard 40mm PV 700x32-50
Attacco Manubrio	3D-forged alloy, 31.8mm, 7-degree rise
Sella	Bridge Sport, Steel rails, 155/143mm
Reggisella	Alloy, 12mm offset, 2-bolt clamp, 27.2mm
Collarino Sella	Bolt-type, 31.8mm
Pedali	Specialized Body Geometry Fitness, Platform, Plastic
Identificativo	276249
Peso	11.61 kg (25 lb, 9.4 oz)
Misura pesata	MD

ART. NR.	DESCRIZIONE	COLORE	MISURA
92425-7501	SIRRUS X 3.0 ST	GLS REFL ASHGRY BLKLQDMET	XS
92425-7502			S
92425-7503			M

Disponibile online & Pick Up in Store



GLS REFL DUNEWHIT DOVGRY



GLS REFL ION SILDST



STN REFL CSTLLC ASHGRY

SIRRUS X 2.0	XXS	XS	S	M	L	XL
Stack (mm)	536	555	563	593	608	633
Reach (mm)	373	388	393	398	402	414
Lunghezza Tubo Sterzo (mm)	121	139	147	175	191	217
Angolo Sterzo (degrees)	69.5	70	70	71	71	71
Altezza movimento centrale (mm)	288	288	288	288	288	288
B-B Drop (mm)	70	70	70	70	70	70
Trail (mm)	79	76	76	69	69	69
Lunghezza forcella (mm)	395	395	395	395	395	395
Offset Forcella/Rake (mm)	51	51	51	51	51	51
Avancorsa (mm)	606	623	631	636	645	665
Lunghezza Batticateni (mm)	440	440	440	440	440	440
Interasse (mm)	1036	1053	1061	1067	1076	1096
Lunghezza Tubo Orizz. virtuale (mm)	532	552	560	574	582	602
Altezza Standover (mm)	702	725	755	785	815	837
Lunghezza Piantone (mm)	360	395	440	470	510	530
Angolo Sella (degrees)	73.5	73.5	73.5	73.5	73.5	73.5
Lunghezza pedivella (mm)	165	165	170	170	175	175
Larghezza Manubrio (mm)	680	680	680	680	680	680
Lunghezza Attacco man. (mm)	60	60	70	80	90	100
Larghezza Sella (mm)	155	155	155	143	143	143
Lunghezza Reggisella (mm)	300	300	350	350	400	400

SPECIFICHE TECNICHE	Specialized si riserva il diritto di modificare le caratteristiche senza preavviso.
Manopole	Specialized Neutralizer, Body Geometry, locking grip
Manubrio	Alloy Mini Rise, 9-degree backsweep, 15mm rise, 31.8mm
Ingranaggi	Narrow-wide chainring w/ chainguard, 40t
Telaio	Specialized A1 Premium Aluminum, Fitness Geometry, butted tubing, internal cable routing, flat-mount disc, quick-release, Plug + Play rack/fender mounts
Forcella	Hi-Ten steel, flat-mount disc, Plug + Play fender mounts, low rider rack mounts, quick-release
Freno anteriore	Promax F1, hydraulic disc, flat-mount, 160mm
Freno posteriore	Promax F1, hydraulic disc, flat-mount, 160mm
Comandi cambio	microSHIFT Acolyte 8 Speed
Cambio posteriore	microSHIFT Acolyte RD-M5185M, 8-speed
Pacco Pignoni	microSHIFT Acolyte CS-H084, 12-42t, 8-speed
Catena	KMC X8 w/ Missing Link™, 8-speed
Guarnitura	Alloy Forged Arms
Movimento Centrale	BSA, square-taper, 68mm
Cerchi	700c disc, double-wall alloy, 22mm depth, 21mm internal width, 32h
Mozzo anteriore	Alloy, 6-bolt disc, loose ball bearing, quick-release, 32h
Mozzo posteriore	Alloy, 6-bolt disc, 8-/9-speed freehub, loose ball bearing, quick-release, 32h
Raggi	Stainless, 14g
Pneumatico anteriore	Pathfinder Sport, 700x42
Pneumatico posteriore	Pathfinder Sport, 700x42
Camere d'aria	Standard 40mm SV 700x32-50
Attacco Manubrio	3D-forged alloy, 31.8mm, 7-degree rise
Sella	Bridge Sport, Steel rails, 155/143mm
Reggisella	Alloy, 12mm offset, 2-bolt clamp, 27.2mm
Collarino Sella	Bolt-type, 31.8mm
Pedali	Specialized Body Geometry Fitness, Platform, Plastic
Identificativo	221888
Peso	12.08 kg (26 lb, 10.1 oz)
Misura pesata	LG

ART. NR.	DESCRIZIONE	COLORE	MISURA
92425-8001	SIRRUS X 2.0	GLS REFL DUNEWHIT DOVGRY	XS
92425-8002			S
92425-8003			M
92425-8004			L
92425-8005			XL
92425-8101	SIRRUS X 2.0	GLS REFL ION SILDST	XS
92425-8102			S
92425-8103			M
92425-8104			L
92425-8105			XL
92425-8200			XXS
92425-8201	SIRRUS X 2.0	STN REFL CSTLLC ASHGRY	XS
92425-8202			S
92425-8203			M
92425-8204			L
92425-8205			XL

## SIRRUS X 2.0 STEP-THROUGH



STN REFL SPC DPORG

SIRRUS X 2.0 STEP-THROUGH	XS	S	M
Stack (mm)	555	563	593
Reach (mm)	393	400	408
Lunghezza Tubo Sterzo (mm)	139	147	175
Angolo Sterzo (degrees)	70	70	71
Altezza movimento centrale (mm)	288	288	288
B-B Drop (mm)	70	70	70
Trail (mm)	76	76	69
Lunghezza forcella (mm)	395	395	395
Offset Forcella/Rake (mm)	51	51	51
Avancorsa (mm)	628	637	646
Lunghezza Batticateni (mm)	440	440	440
Interasse (mm)	1058	1068	1077
Lunghezza Tubo Orizz. virtuale (mm)	557	567	584
Altezza Standover (mm)	636	636	641
Lunghezza Piantone (mm)	395	450	500
Angolo Sella (degrees)	73.5	73.5	73.5
Lunghezza pedivella (mm)	165	165	170
Larghezza Manubrio (mm)	680	680	680
Lunghezza Attacco man. (mm)	60	70	80
Larghezza Sella (mm)	155	155	143
Lunghezza Reggisella (mm)	300	350	350

SPECIFICHE TECNICHE	Specialized si riserva il diritto di modificare le caratteristiche senza preavviso.
Manopole	Specialized Neutralizer, Body Geometry, locking grip
Manubrio	Alloy Mini Rise, 9-degree backsweep, 15mm rise, 31.8mm
Ingranaggi	34T
Telaio	Specialized A1 Premium Aluminum, Fitness Geometry, butted tubing, internal cable routing, flat-mount disc, quick-release, Plug + Play rack/fender mounts
Forcella	Hi-Ten steel, flat-mount disc, Plug + Play fender mounts, low rider rack mounts, quick-release
Freno anteriore	Lee Chi, Hydraulic Disc, 140/160
Freno posteriore	Lee Chi, Hydraulic Disc, 160
Comandi cambio	microSHIFT Acolyte, SL-M6280-R, 8-speed
Cambio posteriore	microSHIFT Acolyte RD-M5185M, 8-speed
Cambio anteriore	MicroSHIFT Acolyte 8 Speed, with Clutch
Pacco Pignoni	microSHIFT CS-H084, 11-42T, 8-speed
Catena	KMC X8 w/ Missing Link™
Catena	KMC X8 w/ Missing Link™, 8-speed
Guarnitura	PROWHEEL, Alloy, 165mm
Movimento Centrale	BSA, square-taper, 68mm
Cerchi	700C disc, double-wall alloy, 22mm depth, 21mm internal width, 32h
Mozzo anteriore	Alloy, 6-bolt disc, loose ball bearing, quick-release, 32h
Mozzo posteriore	Alloy, 6-bolt disc, 8-/9-speed freehub, loose ball bearing, quick-release, 32h
Raggi	Stainless, 14g
Pneumatico anteriore	Pathfinder Sport, 700x42
Pneumatico posteriore	Pathfinder Sport, 700x42
Camere d'aria	Standard 40mm SV 700x32-50
Attacco Manubrio	3D-forged alloy, 31.8mm, 7-degree rise
Sella	Bridge Sport, Steel rails, 155/143mm
Reggisella	Alloy, 12mm offset, 2-bolt clamp, 27.2mm
Collarino Sella	Bolt-type, 31.8mm
Pedali	Specialized Body Geometry Fitness, Platform, Plastic
Identificativo	221889
Peso	12.08 kg (26 lb, 10.1 oz)
Misura pesata	MD

ART. NR.	DESCRIZIONE	COLORE	MISURA
92425-8501	SIRRUS X 2.0 ST STN REFL SPC DPORG		XS
92425-8502			S
92425-8503			M



GLS REFL DPORG REDWD



GLS REFL SEA DUNEWHT

SIRRUS X 1.0	XXS	XS	S	M	L	XL
Stack (mm)	536	555	563	593	608	633
Reach (mm)	373	388	393	398	402	414
Lunghezza Tubo Sterzo (mm)	121	139	147	175	191	217
Angolo Sterzo (degrees)	69.5	70	70	71	71	71
Altezza movimento centrale (mm)	288	288	288	288	288	288
B-B Drop (mm)	70	70	70	70	70	70
Trail (mm)	79	76	76	69	69	69
Lunghezza forcella (mm)	395	395	395	395	395	395
Offset Forcella/Rake (mm)	51	51	51	51	51	51
Avancorsa (mm)	606	623	631	636	645	665
Lunghezza Batticateni (mm)	440	440	440	440	440	440
Interasse (mm)	1036	1053	1061	1067	1076	1096
Lunghezza Tubo Orizz. virtuale (mm)	532	552	560	574	582	602
Altezza Standover (mm)	702	725	755	785	815	837
Lunghezza Sella (mm)	360	395	440	470	510	530
Angolo Sella (degrees)	73.5	73.5	73.5	73.5	73.5	73.5
Lunghezza pedivella (mm)	165	165	170	170	175	175
Larghezza Manubrio (mm)	660	660	660	660	660	660
Lunghezza Attacco man. (mm)	60	60	75	90	90	110
Larghezza Sella (mm)	155	155	155	143	143	143
Lunghezza Reggisella (mm)	300	300	350	350	400	400

SPECIFICHE TECNICHE	Specialized si riserva il diritto di modificare le caratteristiche senza preavviso.
Manopole	Specialized Neutralizer, Body Geometry, locking grip
Manubrio	Double-butted alloy, 5-degree backsweep, 25.4mm
Ingranaggi	34T
Telaio	Specialized A1 Premium Aluminum, Fitness Geometry, butted tubing, internal cable routing, flat-mount disc, quick-release, Plug + Play rack/fender mounts
Forcella	Hi-Ten steel, flat-mount disc, Plug + Play fender mounts, low rider rack mounts, quick-release
Freno anteriore	Lee Chi, Mechanical Disc, 160
Freno posteriore	Lee Chi, Mechanical Disc, 160
Comandi cambio	Shimano Altus SL-M315-7R, 7-Speed
Cambio posteriore	Shimano Acera RD-M3020, 7-Speed
Pacco Pignoni	microSHIFT CS-H074, 12-40t, 7-Speed
Catena	KMC X8 w/ Missing Link™
Guarnitura	PROWHEEL, Alloy, 165mm
Movimento Centrale	Square-tapered, 68mm
Cerchi	700C disc brake, double-wall alloy, 22mm depth, 21mm internal width
Mozzo anteriore	Alloy, 6-bolt disc, loose ball bearing, quick-release, 32h
Mozzo posteriore	Alloy, 6-bolt disc, 7-speed freehub, loose ball bearing, quick-release, 32h
Raggi	Stainless, 14g
Pneumatico anteriore	Pathfinder Sport, 700x42mm
Pneumatico posteriore	Pathfinder Sport, 700x42mm
Camere d'aria	Standard 40mm SV 700x32-50
Attacco Manubrio	Alloy, 25.4mm, 10deg.
Sella	Bridge Sport, Steel rails, 155/143mm
Reggisella	Alloy, 12mm offset, 2-bolt clamp, 27.2mm
Collarino Sella	Bolt-type, 31.8mm
Pedali	Specialized Body Geometry Fitness, Platform, Plastic
Identificativo	221999
Peso	11.58 kg (25 lb, 8.47 oz)
Misura pesata	LG

ART. NR.	DESCRIZIONE	COLORE	MISURA
92425-9001	SIRRUS X 1.0	GLS REFL DPORG REDWD	XS
92425-9002			S
92425-9003			M
92425-9004			L
92425-9005			XL
<b>92425-9000</b>			<b>XXS</b>
92425-9101	SIRRUS X 1.0	GLS REFL SEA DUNEWHT	XS
92425-9102			S
92425-9103			M
92425-9104			L
92425-9105			XL
<b>92425-9100</b>			<b>XXS</b>

Disponibili solo online & Pick Up in Store

## SIRRUS X 1.0 STEP THROUGH



GLS REFL SEA DUNEWH T

SIRRUS X 1.0 STEP THROUGH	XS	S	M
Stack (mm)	555	563	593
Reach (mm)	393	400	408
Lunghezza Tubo Sterzo (mm)	139	147	175
Angolo Sterzo (degrees)	70	70	71
Altezza movimento centrale (mm)	288	288	288
B-B Drop (mm)	70	70	70
Trail (mm)	76	76	69
Lunghezza forcella (mm)	395	395	395
Offset Forcella/Rake (mm)	51	51	51
Avancorsa (mm)	628	637	646
Lunghezza Batticateni (mm)	440	440	440
Interasse (mm)	1058	1068	1077
Lunghezza Tubo Orizz. virtuale (mm)	557	567	584
Altezza Standover (mm)	636	636	641
Lunghezza Piantone (mm)	395	450	500
Angolo Sella (degrees)	73.5	73.5	73.5
Lunghezza pedivella (mm)	165	165	170
Larghezza Manubrio (mm)	660	660	660
Lunghezza Attacco man. (mm)	60	60	75
Larghezza Sella (mm)	155	155	143
Lunghezza Reggisella (mm)	300	300	350

SPECIFICHE TECNICHE	Specialized si riserva il diritto di modificare le caratteristiche senza preavviso.
Manopole	Specialized Neutralizer, Body Geometry, locking grip
Manubrio	Double-butted alloy, 5-degree backsweep, 25.4mm
Ingranaggi	34T
Telaio	Specialized A1 Premium Aluminum, Fitness Geometry, butted tubing, internal cable routing, flat-mount disc, quick-release, Plug + Play rack/fender mounts
Forcella	Hi-Ten steel, flat-mount disc, Plug + Play fender mounts, low rider rack mounts, quick-release
Freno anteriore	Tektro MD-U310R, Mechanical Disc
Freno posteriore	Tektro MD-U310R, Mechanical Disc
Comandi cambio	Shimano Altus SL-M315-7R, 7-Speed
Cambio posteriore	Shimano Acera RD-M3020, 7-Speed
Pacco Pignoni	microSHIFT CS-H074, 12-40t, 7-Speed
Catena	KMC X8 w/ Missing Link™
Guarnitura	PROWHEEL, Alloy, 165mm
Movimento Centrale	Square-tapered, 68mm
Cerchi	700c disc brake, double-wall alloy, 22mm depth, 21mm internal width
Mozzo anteriore	Alloy, 6-bolt disc, loose ball bearing, quick-release, 32h
Mozzo posteriore	Alloy, 6-bolt disc, 7-speed freehub, loose ball bearing, quick-release, 32h
Raggi	Stainless, 14g
Pneumatico anteriore	Pathfinder Sport, 700x42mm
Pneumatico posteriore	Pathfinder Sport, 700x42mm
Camere d'aria	Standard 40mm SV 700x32-50
Attacco Manubrio	Alloy, 25.4mm, 10deg.
Sella	Bridge Sport, Steel rails, 155/143mm
Reggisella	Alloy, 12mm offset, 2-bolt clamp, 27.2mm
Collarino Sella	Bolt-type, 31.8mm
Pedali	Specialized Body Geometry Fitness, Platform, Plastic
Identificativo	222049

ART. NR.	DESCRIZIONE	COLORE	MISURA
92425-9201	SIRRUS X 1.0 STEP THRU	GLS REFL SEA DUNEWH T	XS
92425-9202			S
92425-9203			M



BROWN TINT / GUNMETAL IMPASTO / ASHEN GREY / BRUSHED LIQUID METAL



POWDERED INDIGO TINT / COOL GREY IMPASTO / MIDNIGHT SHADOW / BRONZE

S-WORKS LEVO SL	S1	S2	S3	S4	S5	S6
Stack (mm)	609	617	626	635	645	654
Reach (mm)	405	425	445	470	495	525
Lunghezza Tubo Sterzo (mm)	95	100	110	120	130	140
Angolo Sterzo (degrees)	64.6	64.6	64.6	64.6	64.6	64.6
Altezza movimento centrale (mm)	343	348	348	348	348	348
B-B Drop (mm)	-34	-29	-29	-29	-29	-29
Trail (mm)	132	132	132	132	132	132
Lunghezza forcella (mm)	560	570	570	570	570	570
Offset Forcella/Rake (mm)	42	42	42	42	42	42
Avancorsa (mm)	726	752	776	806	835	869
Lunghezza Batticateni (mm)	433	432	432	432	432	432
Interasse (mm)	1158	1184	1208	1238	1267	1301
Lunghezza Tubo Orizz. virtuale (mm)	560	582	604	631	659	691
Altezza Standover (mm)	727	763	766	767	773	778
Lunghezza Piantone (mm)	385	385	405	425	445	465
Angolo Sella (degrees)	75.8	75.8	75.8	75.8	75.8	75.8
Lunghezza pedivella (mm)	165	165	165	165	165	165
Larghezza Manubrio (mm)	800	800	800	800	800	800
Lunghezza Attacco man. (mm)	40	40	40	40	40	40
Larghezza Sella (mm)	155	155	143	143	143	143
Lunghezza Reggisella (mm)	100	125	150	170	170	170

SPECIFICHE TECNICHE	Specialized si riserva il diritto di modificare le caratteristiche senza preavviso.
Motore	Specialized 1.2 SL Custom Rx Trail Tuned Motor
Batteria	Specialized SL1-320, fully integrated, 320Wh
Interfaccia	Specialized MasterMind TCU, percentage of remaining charge, 120 possible display configurations, MicroTune assist adjustment, over-the-air updates, ANT+/Bluetooth®, w/Handlebar remote
Cablaggio	Custom Specialized wiring harness
Caricatore	Custom charger, 48V System w/ SL system charger plug
Telaio	Levo SL carbon Frame, Fact 11m carbon, alloy shock extension, 150mm travel, adjustable head angle, BB height, and compatible with 27.5 or 29" wheels.
Collarino Sella	Alloy, 38.6mm
Ammortizzatore	FOX FLOAT Factory with Specialized GENIE Shock Tech, Ride Dynamics Trail Tune, 2-position lever w/3 setting Open mode tuning range, LSR adjustment, S1:210x52.5mm, S2-S6:210x55mm
Forcella	Fox 36 Factory series, 29", Grip X2 damper, Kashima, S1: 150mm, S2-S6: 160mm
Freno anteriore	SRAM Maven Ultimate w/Hs2 rotor, 200mm
Freno posteriore	SRAM Maven Ultimate w/Hs2 rotor, 200mm
Comandi cambio	SRAM AXS POD Ultimate Controller
Cambio posteriore	SRAM XX Eagle Transmission Derailleur
Pacco Pignoni	SRAM XX Eagle Transmission Cassette, 12spd, 10-52t
Catena	SRAM XX Eagle Transmission Flattop Chain
Guarnitura	SRAM Eagle Crankset, 32T ring, Integrated Guard, 55mm Chainline, 165mm
Ingranaggi	SRAM T-type ring, 32t
Pneumatico anteriore	Butcher, GRID TRAIL casing, GRIPTON® T9 compound, 2Bliss Ready, 29x2.3"
Ruota anteriore	Traverse HD 240, 29"
Pneumatico posteriore	Eliminator, GRID GRAVITY casing, GRIPTON® T9/T7 compound, 2Bliss Ready, 27.5x2.3"
Ruota posteriore	Traverse HD 240, 27.5", XD freehub body
Camere d'aria	Standard, Presta Valve
Attacco Manubrio	Industry 9 A35 stem, 40mm length, 35mm clamp diameter
Manubrio	Raceface Era Carbon, S3-S6: 40mm rise, S1/S2: 20mm rise
Manopole	Diety Lockjaw grips
Sella	Specialized Power Pro Mirror, hollow Ti rail
Reggisella	RockShox Reverb AXS, 30.9, 1X remote, (S1:100mm, S2: 125mm, S3: 150mm, S4-S6: 170mm)
Accessori SWAT	SWAT CC steerer tube integrated tool with chain tool and link
Identificativo	221298
Peso	18.15 kg (40 lb, 0.2 oz)
Misura pesata	S4

ART. NR.	DESCRIZIONE	COLORE	MISURA
96825-0102/5	LEVO SL SW CARBON	BROWN TINT	S2 - S5
<b>96825-0101-6</b>			<b>S1 - S6</b>
96825-0202/5	LEVO SL SW CARBON	POWDERED INDIGO TINT	S2 - S5
<b>96825-0201-6</b>			<b>S1 - S6</b>

Disponibile solo online & Pick up in Store

# TELAIO S-WORKS TURBO LEVO SL



TEAM YELLOW TINT / PEARL IMPASTO / DARK MOSS GREEN / METALLIC WHITE SILVER

SPECIFICHE TECNICHE	Specialized si riserva il diritto di modificare le caratteristiche senza preavviso.
Motore	Specialized 1.2 SL Custom Rx Trail Tuned Motor
Batteria	Specialized SL1-320, fully integrated, 320Wh
Interfaccia	Specialized MasterMind TCU, percentage of remaining charge, 120 possible display configurations, MicroTune assist adjustment, ANT+/Bluetooth®, w/Handlebar remote
Cablaggio	Custom Specialized wiring harness
Caricatore	Custom charger, 48V System w/ SL system charger plug
Telaio	Levo SL carbon Frame, Fact 11m carbon, alloy shock extension, 150mm travel, adjustable head angle, BB height, and compatible with 27.5 or 29" wheels.
Collarino Sella	Alloy, 38.6mm
Ammortizzatore	FOX FLOAT Factory with Specialized GENIE Shock Tech, Ride Dynamics Trail Tune, 2-position lever w/3 setting Open mode tuning range, LSR adjustment, S1:210x52.5mm, S2-S6:210x55mm
Guarnitura	SRAM Eagle Crankset, 32T ring, Integrated Guard, 55mm Chainline, 165mm
Ingranaggi	SRAM T-type ring, 32t
Identificativo	221302
Peso	5.86 kg (12 lb, 14.7 oz)
Misura pesata	S4

## TELAIO S-WORKS TURBO LEVO SL

	S1	S2	S3	S4	S5	S6
Stack (mm)	609	617	626	635	645	654
Reach (mm)	405	425	445	470	495	525
Lunghezza Tubo Sterzo (mm)	95	100	110	120	130	140
Angolo Sterzo (degrees)	64.6	64.6	64.6	64.6	64.6	64.6
Altezza movimento centrale (mm)	343	348	348	348	348	348
B-B Drop (mm)	-34	-29	-29	-29	-29	-29
Trail (mm)	132	132	132	132	132	132
Lunghezza forcella (mm)	560	570	570	570	570	570
Offset Forcella/Rake (mm)	42	42	42	42	42	42
Avancorsa (mm)	726	752	776	806	835	869
Lunghezza Batticateni (mm)	433	432	432	432	432	432
Interasse (mm)	1158	1184	1208	1238	1267	1301
Lunghezza Tubo Orizz. virtuale (mm)	560	582	604	631	659	691
Altezza Standover (mm)	727	763	766	767	773	778
Lunghezza Piantone (mm)	385	385	405	425	445	465
Angolo Sella (degrees)	75.8	75.8	75.8	75.8	75.8	75.8
Lunghezza pedivella (mm)	165	165	165	165	165	165

ART. NR.	DESCRIZIONE	MISURA
76825-0001/6	LEVO SL SW CARBON FRMSET	S1 - S6
COLORE	TEAM YELLOW TINT / PEARL IMPASTO / DARK MOSS GREEN / METALLIC WHITE SILVER	

# TURBO LEVO SL PRO



ORANGE TINT / COOL GREY IMPASTO / COPPER

TURBO LEVO SL PRO	S1	S2	S3	S4	S5	S6
Stack (mm)	609	617	626	635	645	654
Reach (mm)	405	425	445	470	495	525
Lunghezza Tubo Sterzo (mm)	95	100	110	120	130	140
Angolo Sterzo (degrees)	64.6	64.6	64.6	64.6	64.6	64.6
Altezza movimento centrale (mm)	343	348	348	348	348	348
B-B Drop (mm)	-34	-29	-29	-29	-29	-29
Trail (mm)	132	132	132	132	132	132
Lunghezza forcella (mm)	560	570	570	570	570	570
Offset Forcella/Rake (mm)	42	42	42	42	42	42
Avancorsa (mm)	726	752	776	806	835	869
Lunghezza Batticateni (mm)	433	432	432	432	432	432
Interasse (mm)	1158	1184	1208	1238	1267	1301
Lunghezza Tubo Orizz. virtuale (mm)	560	582	604	631	659	691
Altezza Standover (mm)	727	763	766	767	773	778
Lunghezza Piantone (mm)	385	385	405	425	445	465
Angolo Sella (degrees)	75.8	75.8	75.8	75.8	75.8	75.8
Lunghezza pedivella (mm)	165	165	165	165	165	165
Larghezza Manubrio (mm)	800	800	800	800	800	800
Lunghezza Attacco man. (mm)	40	40	40	40	40	40
Larghezza Sella (mm)	155	155	143	143	143	143
Lunghezza Reggisella (mm)	125	125	160	185	213	213

SPECIFICHE TECNICHE	Specialized si riserva il diritto di modificare le caratteristiche senza preavviso.
Motore	Specialized 1.2 SL Custom Rx Trail Tuned Motor
Batteria	Specialized SL1-320, fully integrated, 320Wh
Interfaccia	Specialized MasterMind TCU, percentage of remaining charge, 120 possible display configurations, MicroTune assist adjustment, ANT+/Bluetooth®, w/Handlebar remote
Cablaggio	Custom Specialized wiring harness
Caricatore	Custom charger, 48V System w/ SL system charger plug
Telaio	Levo SL carbon Frame, Fact 11m carbon, alloy shock extension, 150mm travel, adjustable head angle, BB height, and compatible with 27.5 or 29" wheels.
Collarino Sella	Alloy, 38.6mm
Ammortizzatore	FOX FLOAT Factory with Specialized GENIE Shock Tech, Ride Dynamics Trail Tune, 2-position lever w/3 setting Open mode tuning range, LSR adjustment, S1:210x52.5mm, S2-S6:210x55mm
Forcella	Fox 36 Factory series, 29", Grip X2 damper, Kashima, S1: 150mm, S2-S6: 160mm
Freno anteriore	SRAM Maven Silver w/Hs2 rotor, 200mm
Freno posteriore	SRAM Maven Silver w/Hs2 rotor, 200mm
Comandi cambio	SRAM AXS POD Controller
Cambio posteriore	SRAM X0 Eagle Transmission Derailleur
Pacco Pignoni	SRAM X0 Eagle Transmission Cassette, 12spd, 10-52t
Catena	SRAM X0 Eagle Transmission Flattop Chain
Guarnitura	SRAM Eagle Crankset, 32T ring, Integrated Guard, 55mm Chainline, 165mm
Ingranaggi	SRAM T-type ring, 32t
Pneumatico anteriore	Butcher, GRID TRAIL casing, GRIPTON® T9 compound, 2Bliss Ready, 29x2.3"
Ruota anteriore	Traverse HD 350, 29"
Pneumatico posteriore	Eliminator, GRID GRAVITY casing, GRIPTON® T9/T7 compound, 2Bliss Ready, 27.5x2.3"
Ruota posteriore	Traverse HD 350, 27.5", XD freehub body
Camere d'aria	Standard, Presta Valve
Attacco Manubrio	Industry 9 A35 stem, 40mm length, 35mm clamp diameter
Manubrio	RaceFace Era Carbon, riser bar, 5-degree upsweep, 8-degree backsweep, S2:20mm Rise, S3-S6:40mm Rise, 800mm
Manopole	Diety Lockjaw grips
Sella	Specialized Bridge Expert Mimic, hollow ti rail
Reggisella	Bike Yoke, Revive Max, 34.9, S1: 125mm, S2: 160mm, S3-S4: 185mm, S5-S6: 213mm
Accessori SWAT	SWAT CC steerer tube integrated tool with chain tool and link
Identificativo	221299
Peso	18.15 kg (40 lb, 0.2 oz)
Misura pesata	S4

ART. NR.	DESCRIZIONE	COLORE	MISURA
96825-1002/5	LEVO SL PRO CARBON	ORANGE TINT / COOL GREY IMPASTO / COPPER	S2 - S5
96825-1001-6			S1 - S6

Disponibile solo online & Pick up in Store

# TURBO LEVO SL EXPERT



CARBON / OBSIDIAN / BRONZE



CHAMPAIGN / COOL GREY / METALLIC OBSIDIAN

TURBO LEVO SL EXPERT	S1	S2	S3	S4	S5	S6
Stack (mm)	609	617	626	635	645	654
Reach (mm)	405	425	445	470	495	525
Lunghezza Tubo Sterzo (mm)	95	100	110	120	130	140
Angolo Sterzo (degrees)	64.6	64.6	64.6	64.6	64.6	64.6
Altezza movimento centrale (mm)	343	348	348	348	348	348
B-B Drop (mm)	-34	-29	-29	-29	-29	-29
Trail (mm)	132	132	132	132	132	132
Lunghezza forcella (mm)	560	570	570	570	570	570
Offset Forcella/Rake (mm)	42	42	42	42	42	42
Avancorsa (mm)	726	752	776	806	835	869
Lunghezza Batticateni (mm)	433	432	432	432	432	432
Interasse (mm)	1158	1184	1208	1238	1267	1301
Lunghezza Tubo Orizz. virtuale (mm)	560	582	604	631	659	691
Altezza Standover (mm)	727	763	766	767	773	778
Lunghezza Sella (mm)	385	385	405	425	445	465
Angolo Sella (degrees)	75.8	75.8	75.8	75.8	75.8	75.8
Lunghezza pedivella (mm)	165	165	165	165	165	165
Larghezza Manubrio (mm)	780	780	800	800	800	800
Lunghezza Attacco man. (mm)	40	40	40	40	40	40
Larghezza Sella (mm)	155	155	143	143	143	143
Lunghezza Reggisella (mm)	125	150	170	200	200	200

SPECIFICHE TECNICHE	Specialized si riserva il diritto di modificare le caratteristiche senza preavviso.
Motore	Specialized 1.2 SL Custom Rx Trail Tuned Motor
Batteria	Specialized SL1-320, fully integrated, 320Wh
Interfaccia	Specialized MasterMind TCU, percentage of remaining charge, 120 possible display configurations, MicroTune assist adjustment, ANT+/Bluetooth®, w/Handlebar remote
Cablaggio	Custom Specialized wiring harness
Caricatore	Custom charger, 48V System w/ SL system charger plug
Telaio	Levo SL carbon Frame, Fact 11m carbon, alloy shock extension, 150mm travel, adjustable head angle, BB height, and compatible with 27.5 or 29" wheels.
Collarino Sella	Alloy, 38.6mm
Ammortizzatore	FOX FLOAT Performance Elite with Specialized GENIE Shock Tech, Ride Dynamics Trail Tune, 2-position lever w/3 setting Open mode tuning range, LSR adjustment, S1:210x52.5mm, S2-S6:210x55mm
Forcella	Fox 36 Performance Elite series, 29", Grip X2 damper, S1: 150mm, S2-S6: 160mm
Freno anteriore	SRAM Maven Bronze, 4-piston caliper, hydraulic disc, 200mm HS2 rotor
Freno posteriore	SRAM Maven Bronze, 4-piston caliper, hydraulic disc, 200mm HS2 rotor
Comandi cambio	SRAM AXS POD Controller
Cambio posteriore	SRAM GX Eagle Transmission Derailleur
Pacco Pignoni	SRAM GX Eagle Transmission Cassette, 12spd, 10-52t
Catena	SRAM GX Eagle Transmission Flattop Chain
Guarnitura	SRAM GX Eagle Crankset, 32T ring, Integrated Guard, 55mm Chainline, 165mm
Ingranaggi	SRAM T-type ring, 32t
Pneumatico anteriore	Butcher, GRID TRAIL casing, GRIPTON® T9 compound, 2Bliss Ready, 29x2.3"
Ruota anteriore	Royal Traverse Alloy 29"
Pneumatico posteriore	Eliminator, GRID GRAVITY casing, GRIPTON® T9/T7 compound, 2Bliss Ready, 27.5x2.3"
Ruota posteriore	Royal Traverse Alloy 27.5", XD freehub body
Camere d'aria	Standard, Presta Valve
Attacco Manubrio	Alloy Trail Stem, 35mm bar bore
Manubrio	Specialized, 6000 series alloy, 6-degree upsweep, 8-degree backsweep. S1-S2: 780 width, 20mm rise; S3-S4: 800 width, 30mm rise; S5-S6: 800 width, 40mm rise
Manopole	Specialized Trail Grips
Sella	Bridge Comp, Hollow Cr-mo rails, 155/143mm
Reggisella	PNW Loam post w/travel adjust S1: 125mm, S2: 150mm, S3: 170mm, S4/S5/S6: 200mm
Accessori SWAT	SWAT CC steerer tube integrated tool with chain tool and link
Identificativo	221300
Peso	18.98 kg (41 lb, 13.5 oz)
Misura pesata	S4

ART. NR.	DESCRIZIONE	COLORE	MISURA
96825-3002/5	LEVO SL EXPERT CARBON	OBSIDIAN / BRONZE	S2 - S5
<b>96825-3001/6</b>			<b>S1 - S6</b>
96825-3102/5	LEVO SL EXPERT	CHAMPAIGN / COOL GREY / METALLIC OBSIDIAN	S2 - S5
<b>96825-3101/6</b>			<b>S1 - S6</b>

Disponibile solo online & Pick up in Store

# TURBO LEVO SL COMP CARBON



CYPRESS METALLIC / CYPRESS / DARK MOSS GREEN



SPICE / MAROON / OBSIDIAN

TURBO LEVO SL COMP CARBON	S1	S2	S3	S4	S5	S6
Stack (mm)	609	617	626	635	645	654
Reach (mm)	405	425	445	470	495	525
Lunghezza Tubo Sterzo (mm)	95	100	110	120	130	140
Angolo Sterzo (degrees)	64.6	64.6	64.6	64.6	64.6	64.6
Altezza movimento centrale (mm)	343	348	348	348	348	348
B-B Drop (mm)	-34	-29	-29	-29	-29	-29
Trail (mm)	132	132	132	132	132	132
Lunghezza forcella (mm)	560	570	570	570	570	570
Offset Forcella/Rake (mm)	42	42	42	42	42	42
Avancorsa (mm)	726	752	776	806	835	869
Lunghezza Batticateni (mm)	433	432	432	432	432	432
Interasse (mm)	1158	1184	1208	1238	1267	1301
Lunghezza Tubo Orizz. virtuale (mm)	560	582	604	631	659	691
Altezza Standover (mm)	727	763	766	767	773	778
Lunghezza Piantone (mm)	385	385	405	425	445	465
Angolo Sella (degrees)	75.8	75.8	75.8	75.8	75.8	75.8
Lunghezza pedivella (mm)	165	165	165	165	165	165
Larghezza Manubrio (mm)	780	780	800	800	800	800
Lunghezza Attacco man. (mm)	40	40	40	40	40	40
Larghezza Sella (mm)	155	155	143	143	143	143
Lunghezza Reggisella (mm)	100	125	150	170	170	190

## SPECIFICHE TECNICHE

SPECIFICHE TECNICHE	Specialized si riserva il diritto di modificare le caratteristiche senza preavviso.
Motore	Specialized 1.2 SL Custom Rx Trail Tuned Motor
Batteria	Specialized SL1-320, fully integrated, 320Wh
Interfaccia	Specialized MasterMind TCU, percentage of remaining charge, 120 possible display configurations, MicroTune assist adjustment, over-the-air updates, ANT+/Bluetooth®, w/Handlebar remote
Cablaggio	Custom Specialized wiring harness
Caricatore	Custom charger, 48V System w/ SL system charger plug
Telaio	Levo SL carbon Frame, Fact 11m carbon, alloy shock extension, 150mm travel, adjustable head angle, BB height, and compatible with 27.5 or 29" wheels.
Collarino Sella	Alloy, 38.6mm
Ammortizzatore	FOX FLOAT Performance with Specialized GENIE Shock Tech, Ride Dynamics Trail Tune, 2-position lever w/ LSR adjustment, S1:210x52.5mm, S2-S6:210x55mm
Forcella	FOX FLOAT 36 Rhythm, GRIP damper, two position Sweep adjustment, 15x110mm QR axle, 44mm offset, S1:150mm of travel, S2-S6:160mm of travel
Freno anteriore	SRAM Maven Bronze, 4-piston caliper, hydraulic disc, 200mm Centerline rotor
Freno posteriore	SRAM Maven Bronze, 4-piston caliper, hydraulic disc, 200mm Centerline rotor
Comandi cambio	SRAM AXS POD Controller
Cambio posteriore	SRAM S1000 Eagle Transmission Derailleur
Pacco Pignoni	SRAM XS-1270 Transmission Cassette, 12spd, 10-52t
Catena	SRAM GX Eagle Transmission Flattop Chain
Guarnitura	SRAM S1000 Crankset, 32T ring, Integrated Guard, 55mm Chainline, 165mm
Ingranaggi	SRAM T-type ring, 32t
Cerchi	Specialized 29/27.5, hookless alloy, 30mm inner width, tubeless ready
Mozzo anteriore	Alloy, sealed cartridge bearings, 15x110mm thru-axle, 28h
Mozzo posteriore	Alloy, sealed cartridge bearings, 12x148mm thru-axle, 32h
Raggi	DT Swiss Industry
Pneumatico anteriore	Butcher, GRID TRAIL casing, GRIPTON® T9 compound, 2Bliss Ready, 29x2.3"
Pneumatico posteriore	Eliminator, GRID GRAVITY casing, GRIPTON® T9/T7 compound, 2Bliss Ready, 27.5x2.3"
Camere d'aria	Standard, Presta Valve
Attacco Manubrio	Alloy Trail Stem, 35mm bar bore
Manubrio	Specialized, 6000 series alloy, 6-degree upsweep, 8-degree backsweep. S1-S2: 780 width, 20mm rise; S3-S4: 800 width, 30mm rise; S5-S6: 800 width, 40mm rise
Manopole	Specialized Trail Grips
Sella	Bridge Comp, Hollow Cr-mo rails, 155/143mm
Reggisella	X-Fusion Manic, infinite adjustable, two-bolt head, bottom mount cable routing, remote SLR LE lever, 34.9, S1: 100mm, S2: 125mm, S3: 150mm, S4: 170mm, S5/S6: 190mm
Accessori SWAT	SWAT CC steerer tube integrated tool with chain tool and link
Identificativo	221301
Peso	19.11 kg (42 lb, 2.1 oz)
Misura pesata	S4

ART. NR.	DESCRIZIONE	COLORE	MISURA
96825-5201-5	LEVO SL COMP CARBON	CYPRESS METALLIC / CYPRESS	S1 - S5
96825-5206			S6
96825-5301/5	LEVO SL COMP CARBON	SPICE / MAROON / OBSIDIAN	S1 - S5
96825-5306			S6

# TURBO LEVO SL ÖHLINS COIL



SOLIDITY / MAROON / BURNT GOLD METALLIC

<b>TURBO LEVO SL ÖHLINS COIL</b>	<b>S2</b>	<b>S3</b>	<b>S4</b>	<b>S5</b>	<b>S6</b>
Stack (mm)	617	626	635	645	654
Reach (mm)	425	445	470	495	525
Lunghezza Tubo Sterzo (mm)	100	110	120	130	140
Angolo Sterzo (degrees)	64.6	64.6	64.6	64.6	64.6
Altezza movimento centrale (mm)	348	348	348	348	348
B-B Drop (mm)	-29	-29	-29	-29	-29
Trail (mm)	132	132	132	132	132
Lunghezza forcella (mm)	570	570	570	570	570
Offset Forcella/Rake (mm)	42	42	42	42	42
Avancorsa (mm)	752	776	806	835	869
Lunghezza Batticateni (mm)	432	432	432	432	432
Interasse (mm)	1184	1208	1238	1267	1301
Lunghezza Tubo Orizz. virtuale (mm)	582	604	631	659	691
Altezza Standover (mm)	763	766	767	773	778
Lunghezza Piantone (mm)	385	405	425	445	465
Angolo Sella (degrees)	75.8	75.8	75.8	75.8	75.8
Lunghezza pedivella (mm)	165	165	165	165	165
Larghezza Manubrio (mm)	800	800	800	800	800
Lunghezza Attacco man. (mm)	40	40	40	40	40
Larghezza Sella (mm)	155	143	143	143	143
Lunghezza Reggisella (mm)	125	160	185	213	213

<b>SPECIFICHE TECNICHE</b>	<b>Specialized si riserva il diritto di modificare le caratteristiche senza preavviso.</b>
Motore	Specialized 1.2 SL Custom Rx Trail Tuned Motor
Batteria	Specialized SL1-320, fully integrated, 320Wh
Interfaccia	Specialized MasterMind TCU, percentage of remaining charge, 120 possible display configurations, MicroTune assist adjustment, ANT+/Bluetooth®, w/Handlebar remote
Cablaggio	Custom Specialized wiring harness
Caricatore	Custom charger, 48V System w/ SL system charger plug
Telaio	Levo SL carbon Frame, Fact 11m carbon, alloy shock extension, 150mm travel, adjustable head angle, BB height, and compatible with 27.5 or 29" wheels.
Collarino Sella	Alloy, 38.6mm
Ammortizzatore	Ohlins TTX Coil shock, S2: 411lb, S3: 457lb, S4: 502lb, S5: 548lb, S6: 605lb
Forcella	Ohlins RXF 38, 160mm travel, 29"
Freno anteriore	Tekro DHR Evo brakes, w/220mm rotor
Freno posteriore	Tekro DHR Evo brakes, w/220mm rotor
Comandi cambio	SRAM AXS POD Controller
Cambio posteriore	SRAM GX Eagle Transmission Derailleur
Pacco Pignoni	SRAM GX Eagle Transmission Cassette, 12spd, 10-52t
Catena	SRAM GX Eagle Transmission Flattop Chain
Guarnitura	SRAM GX Eagle Crankset, 32T ring, Integrated Guard, 55mm Chainline, 165mm
Ingranaggi	SRAM T-type ring, 32t
Pneumatico anteriore	Butcher, GRID GRAVITY casing, GRIPTON® T9 compound, 2Bliss Ready, 29x2.3"
Ruota anteriore	Roval Traverse Alloy 29"
Pneumatico posteriore	Butcher, GRID GRAVITY casing, GRIPTON® T9 compound, 2Bliss Ready, 27.5x2.3"
Ruota posteriore	Roval Traverse Alloy 27.5", XD freehub body
Camere d'aria	Standard, Presta Valve
Attacco Manubrio	RaceFace Aeffect R 35mm bore, 40mm length
Manubrio	Raceface Turbine Alloy, 35mm dia, S1/S2: 20mm rise, 800mm width, S3-S6: 40mm rise, 800mm width
Manopole	Deity Grips
Sella	Specialized Bridge Mimic, hollow chromo rail
Reggisella	Bike Yoke, Revive Max, 34.9, S1: 125mm, S2: 160mm, S3-S4: 185mm, S5-S6: 213mm
Accessori SWAT	SWAT CC steerer tube integrated tool with chain tool and link
Identificativo	221991
Peso	19.61 kg (43 lb, 3.7 oz)
Misura pesata	S4

<b>ART. NR.</b>	<b>DESCRIZIONE</b>	<b>COLORE</b>	<b>MISURA</b>
96825-0002/6	LEVO SL ÖHLINS	COIL SOLIDITY / MAROON / BURNT GOLD METALLIC	S2 - S6

# TURBO LEVO SL COMP ALLOY



CAST BLUE METALLIC / DARK NAVY / WHITE MOUNTAINS



COOL GREY / ASHEN GREY / DUNE WHITE

TURBO LEVO SL COMP ALLOY	S1	S2	S3	S4	S5	S6
Stack (mm)	609	617	626	635	645	654
Reach (mm)	405	425	445	470	495	525
Lunghezza Tubo Sterzo (mm)	95	100	110	120	130	140
Angolo Sterzo (degrees)	64.6	64.6	64.6	64.6	64.6	64.6
Altezza movimento centrale (mm)	343	348	348	348	348	348
B-B Drop (mm)	-34	-29	-29	-29	-29	-29
Trail (mm)	132	132	132	132	132	132
Lunghezza forcella (mm)	560	570	570	570	570	570
Offset Forcella/Rake (mm)	42	42	42	42	42	42
Avancorsa (mm)	726	752	776	806	835	869
Lunghezza Batticateni (mm)	433	432	432	432	432	432
Interasse (mm)	1158	1184	1208	1238	1267	1301
Lunghezza Tubo Orizz. virtuale (mm)	560	582	604	631	659	691
Altezza Standover (mm)	727	763	766	767	773	778
Lunghezza Sella (mm)	385	385	405	425	445	465
Angolo Sella (degrees)	75.8	75.8	75.8	75.8	75.8	75.8
Lunghezza pedivella (mm)	165	165	165	165	165	165
Larghezza Manubrio (mm)	780	780	800	800	800	800
Lunghezza Attacco man. (mm)	40	40	40	40	40	40
Larghezza Sella (mm)	155	155	143	143	143	143
Lunghezza Reggisella (mm)	100	125	150	170	170	190

SPECIFICHE TECNICHE	Specialized si riserva il diritto di modificare le caratteristiche senza preavviso.		
Motore	Specialized 1.2 SL Custom Rx Trail Tuned Motor		
Batteria	Specialized SL1-320, fully integrated, 320Wh		
Interfaccia	Specialized MasterMind TCU, percentage of remaining charge, 120 possible display configurations, MicroTune assist adjustment, ANT+/Bluetooth®, w/Handlebar remote		
Cablaggio	Custom Specialized wiring harness		
Caricatore	Custom charger, 48V System w/ SL system charger plug		
Telaio	Levo SL Alloy Frame, M5 alloy, 150mm travel, adjustable head angle, BB height, and compatible with 27.5 or 29" wheels		
Collarino Sella	Alloy, 38.6mm		
Ammortizzatore	FOX FLOAT Performance with Specialized GENIE Shock Tech, Ride Dynamics Trail Tune, 2-position lever w/ LSR adjustment, S1:210x52.5mm, S2-S6:210x55mm		
Forcella	FOX FLOAT 36 Rhythm, GRIP damper, two position Sweep adjustment, 15x110mm QR axle, 44mm offset, S1:140mm of travel, S2-S6:150mm of travel		
Freno anteriore	SRAM Maven Bronze, 4-piston caliper, hydraulic disc, 200mm Centerline rotor		
Freno posteriore	SRAM Maven Bronze, 4-piston caliper, hydraulic disc, 200mm Centerline rotor		
Comandi cambio	SRAM GX Eagle, trigger, 12-speed, single click		
Cambio posteriore	Sram X01 Eagle, 12-speed		
Pacco Pignoni	Sram XG-1275, 12-speed, 10-52t		
Catena	SRAM GX Eagle, 12-speed		
Guarnitura	SRAM S1000 Crankset, 32T ring, Integrated Guard, 55mm Chainline, 165mm		
Ingranaggi	SRAM T-type ring, 32t		
Cerchi	Specialized 29/27.5, hookless alloy, 30mm inner width, tubeless ready		
Mozzo anteriore	Alloy, sealed cartridge bearings, 15x110mm thru-axle, 28h		
Mozzo posteriore	Alloy, sealed cartridge bearings, 12x148mm thru-axle, 32h		
Raggi	DT Swiss Industry		
Pneumatico anteriore	Butcher, GRID TRAIL casing, GRIPTON® T9 compound, 2Bliss Ready, 29x2.3"		
Pneumatico posteriore	Eliminator, GRID GRAVITY casing, GRIPTON® T9/T7 compound, 2Bliss Ready, 27.5x2.3"		
Camere d'aria	Standard, Presta Valve		
Attacco Manubrio	Alloy Trail Stem, 35mm bar bore		
Manubrio	Specialized, 6000 series alloy, 6-degree upsweep, 8-degree backsweep, S1-S2: 780 width, 20mm rise; S3-S4: 800 width, 30mm rise; S5-S6: 800 width, 40mm rise		
Manopole	Specialized Trail Grips		
Sella	Bridge Comp, Hollow Cr-mo rails, 155/143mm		
Reggisella	X-Fusion Manic, infinite adjustable, two-bolt head, bottom mount cable routing, remote SLR LE lever, 34.9, S1: 100mm, S2: 125mm, S3: 150mm, S4: 170mm, S5/S6: 190mm		
Accessori SWAT	SWAT CC steerer tube integrated tool with chain tool and link		
Identificativo	221303		
Peso	20.26 kg (44 lb, 10.7 oz)		
Misura pesata	S4		
ART. NR.	DESCRIZIONE	COLORE	MISURA
96825-5001/6	LEVO SL COMP ALLOY	CAST BLUE METALLIC / DARK NAVY / WHITE MOUNTAIN	S1 - S6
96825-5101/6	LEVO SL COMP ALLOY	COOL GREY / ASHENGREY / DUNE WHITE	S1 - S6

# TURBO LEVO COMP CARBON G3



BLACK / LIGHT SILVER / BLACK



CARBON / SMOKE / BLACK



HARVEST GOLD / OBSIDIAN

TURBO LEVO COMP CARBON	S1	S2	S3	S4	S5	S6
Stack (mm)	605	617	626	635	644	653
Reach (mm)	412	432	452	477	502	532
Lunghezza tubo sterzo (mm)	105	105	115	125	135	145
Angolo sterzo (degrees)	64.5	64.5	64.5	64.5	64.5	64.5
Altezza movimento centrale (mm)	352	350	350	350	350	350
BB Drop (mm)	25	27	27	27	27	27
Trail (mm)	130	130	130	130	130	130
Lunghezza forcella (mm)	557	567	567	567	567	567
Offset forcella/Rake (mm)	44	44	44	44	44	44
Avancorsa (mm)	738	760	784	814	843	878
Lunghezza Batticateni (mm)	442	442	442	442	442	442
Interasse (mm)	1179	1200	1225	1255	1284	1318
Altezza Standover (mm)	752	776	783	787	788	790
Lunghezza Piantone (mm)	380	390	405	425	445	465
Angolo sella (degrees)	78	77.2	76.7	76.2	76.2	76.2
Max. Inserimento Reggisella (mm)	210	220	240	255	275	295
Min. Inserimento Reggisella (mm)	80	80	80	80	80	80
Lunghezza pedivella (mm)	160	160	160	160	160	160
Larghezza Manubrio (mm)	800	800	800	800	800	800
Lunghezza Attacco man. (mm)	40	40	40	40	40	40
Larghezza Sella (mm)	155	155	143	143	143	143
Lunghezza Reggisella (mm)	100	125	150	170	170	190

SPECIFICHE TECNICHE	Specialized si riserva il diritto di modificare le caratteristiche senza preavviso.
Motore	Specialized 2.2 Custom Rx Trail Tuned Motor
Ingranaggi	SRAM X-Sync Eagle, 104 BCD, 32T, steel
Batteria	Specialized M3-700, Integrated battery, 700Wh
Interfaccia	Specialized MasterMind TCU, percentage of remaining charge, 120 possible display configurations, MicroTune assist adjustment, ANT+/Bluetooth®, w/Handlebar remote
Caricatore	Custom charger, 42V4A w/ Rosenberger plug, 100-240V
Cablaggio	Custom Specialized wiring harness
Telaio	FACT 11m full carbon, 29" front wheel, 27.5" rear wheel, full internal cable routing, 148mm spacing, fully sealed cartridge bearings, 150mm of travel, geo adjust head tube, geo adjust horst pivot
Collarino Sella	Alloy, 38.6mm
Ammortizzatore	FOX FLOAT X Performance, LSR, 2-position lever, 55x210mm
Forcella	Fox 36 Rhythm, 29", S2-S6: 160mm S1: 150mm, Grip damper
Freno anteriore	SRAM Maven Bronze, 220mm rotor, metallic pads
Freno posteriore	SRAM Maven Bronze, 200mm rotor, metallic pads
Comandi cambio	SRAM GX Eagle, trigger, 12-speed, single click
Cambio posteriore	Sram X01 Eagle, 12-speed
Pacco Pignoni	Sram XG-1275, 12-speed, 10-52t
Catena	SRAM GX Eagle, 12-speed
Guarnitura	Praxis forged M30, custom offset, 160mm
Cerchi	Specialized 29, hookless alloy, 30mm inner width, tubeless ready
Mozzo anteriore	Alloy, sealed cartridge bearings, 15x10mm thru-axle, 28h
Mozzo posteriore	Alloy, sealed cartridge bearings, 148mmx12mm thru-axle, 28h
Raggi	DT Swiss Industry
Pneumatico anteriore	Butcher, GRID GRAVITY casing, GRIPTON® T9 compound, 2Bliss Ready, 29x2.3"
Pneumatico posteriore	Eliminator, GRID GRAVITY casing, GRIPTON® T9/T7 compound, 27.5x2.3"
Camere d'aria	Standard, Presta Valve
Attacco Manubrio	Alloy Trail Stem, 35mm bar bore
Manubrio	6061 mtm bars, 35mm diameter, 8 degree back sweep, 6 degrees up sweep, 800mm width. S1/S2: 30mm rise, S3-S6: 40mm rise
Manopole	Specialized Trail Grips
Sella	Bridge Comp, Hollow Cr-mo rails, 155/143mm
Reggisella	X-Fusion Manic, infinite adjustable, two-bolt head, bottom mount cable routing, remote SLR LE lever, 34.9, S1: 100mm, S2: 125mm, S3: 150mm, S4/S5: 170mm, S6: 190mm
Accessori SWAT	SWAT CC steerer tube integrated tool with chain tool and link
Identificativo	274924

ART. NR.	DESCRIZIONE	COLORE	MISURA
95225-5401/6	LEVO COMP CARBON	BLACK / LIGHT SILVER / BLACK	S1-S6
95225-5501/6	LEVO COMP CARBON	CARBON / SMOKE / BLACK	S1-S6
95225-5601/6	LEVO COMP CARBON	HARVEST GOLD / OBSIDIAN	S1-S6

Disponibile solo online & Pick up in Store

# TURBO LEVO COMP ALLOY G3



Black / Dove Grey / Black



Sage Green / Cool Grey / Black



Satin Midnight Shadow / Harvest Gold Metallic

<b>SPECIFICHE TECNICHE</b>	<b>Specialized si riserva il diritto di modificare le caratteristiche senza preavviso.</b>
Telaio	Specialized M5 premium alloy, headset adjust, BB height adjust, S-Sizing, internal cable routing, 150mm travel, 148mm spacing
Ammortizzatore	FOX FLOAT X Performance, LSR, 2-position lever, 55x210mm
Forcella	2025, 36, A, FLOAT, 29in, Rhythm, 150/160, Grip, Sweep-Adj, Matte Blk, Std/Matte Blk Logo, Kabolt X 110, BLK, 1.5 T, 58HT, 44mm Rake, N/M OE; 2025, 36, A, FLOAT, 29in, Rhythm, 150/160, Grip, Sweep-Adj, Shiny Blk, Std/Gloss Blk Logo, Kabolt X 110, BLK, 1.5 T, 58HT, 44mm Rake, N/M OE
Attacco Manubrio	Alloy Trail Stem, 35mm bar bore
Manubrio	HANDLE BAR, JD-MTB585Q, 6061-T6.DOUBLE BUTTED,35MM,BACK SWEEP 8DEG,RISE 30MM,UP SWEEP 6DEG,800MM; HANDLE BAR, JD-MTB586Q,66, 6066-T6.DOUBLE BUTTED,35MM,BACK SWEEP 8DEG,RISE 40MM,UP SWEEP 6DEG,800MM
Manopole	Specialized Trail Grips
Sella	Bridge Comp, Hollow Cr-mo rails, 155/143mm
Freno anteriore	SRAM DB MVN BRZ SIN BDPA DIR
Freno posteriore	SRAM DB MVN BRZ SJ SIN BDPA DIR
Cambio posteriore	Sram X01 Eagle, 12-speed
Comandi cambio	SRAM GX Eagle, trigger, 12-speed, single click
Pacco Pignoni	Sram XG-1275, 12-speed, 10-52t
Catena	SRAM GX Eagle, 12-speed
Guarnitura	Praxis forged M30, custom offset, 160mm
Ingranaggi	SRAM X-Sync Eagle, 104 BCD, 32T, steel
Cerchi	Specialized 29, hookless alloy, 30mm inner width, tubeless ready
Mozzo anteriore	2018 TRAVERSE FRONT HUB 28 HOLE 15MM AXLE LG CAP BOOST
Mozzo posteriore	REAR HUB,BEAR PAWL BMB-00412PIC,SRAM XD STEEL FHB, 6 BOLT DISC,SEALED CARTRIDGE BEARING,28H,12MM STEEL AXLE,148MM SPACING
Raggi	DT Swiss Industry
Pneumatico anteriore	Butcher, GRID TRAIL casing, GRIPTON® T9 compound, 2Bliss Ready, 29x2.3"
Pneumatico posteriore	Eliminator, GRID GRAVITY casing, GRIPTON® T9/T7 compound, 27.5x2.3"
Camere d'aria	Standard, Presta Valve
Pedali	PEDAL, TEST RIDE PEDALS PROVIDED BY SPECIALIZED
Reggisella	X-Fusion Manic, infinite adjustable, two-bolt head, bottom mount cable routing, remote SLR LE lever, 34.9, S1: 100mm, S2: 125mm, S3: 150mm, S4/S5: 170mm, S6: 190mm
Collarino Sella	Alloy, 38.6mm
Motore	Specialized 2.1 Custom Rx Trail Tuned Motor
Interfaccia	Specialized MasterMind TCU, percentage of remaining charge, 120 possible display configurations, MicroTune assist adjustment, ANT+/Bluetooth®, w/Handlebar remote
Batteria	Specialized M3-700, Integrated battery, 700Wh
Caricatore	Custom charger, 42V4A w/ Rosenberger plug, 100-240V
Cablaggio	CLR,HARNESS,PA TRAIL FSR F1
Accessori	SWAT CC steerer tube integrated tool with chain tool and link

<b>ART. NR.</b>	<b>DESCRIZIONE</b>	<b>COLORE</b>	<b>MISURA</b>
95225-6301/6	LEVO COMP ALLOY G3 NB	Black / Dove Grey / Black	S1-S6
95225-6401/6	LEVO COMP ALLOY G3 NB	Sage Green / Cool Grey / Black	S1-S6
95225-6501/6	LEVO COMP ALLOY G3 NB	Satin Midnight Shadow / Harvest Gold Metallic	S1-S6

## TURBO LEVO ALLOY G3



TURBO LEVO ALLOY G3	S2	S3	S4	S5	S6
Stack (mm)	617	626	635	644	653
Reach (mm)	432	452	477	502	532
Lunghezza tubo sterzo (mm)	105	115	125	135	145
Angolo sterzo (degrees)	64.5	64.5	64.5	64.5	64.5
Altezza movimento centrale (mm)	350	350	350	350	350
BB Drop (mm)	27	27	27	27	27
Trail (mm)	130	130	130	130	130
Lunghezza forcella (mm)	567	567	567	567	567
Offset forcella/Rake (mm)	44	44	44	44	44
Avancorsa (mm)	760	784	814	843	878
Lunghezza Batticateni (mm)	442	442	442	442	442
Interasse (mm)	1200	1225	1255	1284	1318
Altezza Standover (mm)	776	783	787	788	790
Lunghezza piantone (mm)	390	405	425	445	465
Angolo Sella (degrees)	77.2	76.7	76.2	76.2	76.2
Max. Inserimento Reggisella (mm)	220	240	255	275	295
Min. Inserimento Reggisella (mm)	80	80	80	80	80
Lunghezza pedivella (mm)	160	160	160	160	160
Larghezza Manubrio (mm)	800	800	800	800	800
Lunghezza Attacco man. (mm)	40	40	40	40	40
Larghezza Sella (mm)	155	155	143	143	143
Lunghezza Reggisella (mm)	100	125	150	170	170

SPECIFICHE TECNICHE	Specialized si riserva il diritto di modificare le caratteristiche senza preavviso.
Telaio	Specialized M5 premium alloy, BB height adjust, S-Sizing, internal cable routing, 150mm travel, 148mm spacing
Ammortizzatore	Marzocchi Bomber inline, S2-6: 210x55mm, S1: 210x52.5, low speed rebound adjust
Forcella	Marzocchi Bomber Z1, 29", S2-S6: 160mm, S1: 150mm, sweep adjust compression
Attacco Manubrio	Alloy Trail Stem, 35mm bar bore
Manubrio	6061 mtn bars, 35mm diameter, 8 degree back sweep, 6 degrees up sweep, 800mm width. S1/S2: 30mm rise, S3-S6: 40mm rise
Manopole	Specialized Trail Grips
Freno anteriore	SRAM DB8, 220mm rotor
Freno posteriore	SRAM DB8, 200mm rotor
Cambio posteriore	SRAM GX Eagle, 12-speed
Comandi cambio	SRAM NX Eagle, single-click lever
Pacco Pignoni	SRAM NX Eagle, 12-speed, 11-50t
Guarnitura	Praxis forged M30, custom offset, 160mm
Catena	SRAM NX Eagle, 12-speed
Ingranaggi	SRAM X-Sync Eagle, 104 BCD, 32T, steel
Cerchi	Specialized 29, hookless alloy, 30mm inner width, tubeless ready
Mozzo anteriore	Alloy, sealed cartridge bearings, 15x110mm thru-axle, 28h
Raggi	DT Swiss Industry
Mozzo posteriore	Specialized Alloy Rear Hub Disc, Sealed Cartridge Bearings, 6-Bolt, 12x148mm Thru-Axle, 32H, Hd Steel Fhb
Pneumatico anteriore	Butcher, GRID TRAIL casing, GRIPTON® T9 compound, 2Bliss Ready, 29x2.3"
Pneumatico posteriore	Eliminator, GRID GRAVITY casing, GRIPTON® T9/T7 compound, 27.5x2.3"
Camere d'aria	Standard 40mm PV 29/27.5x1.75-2.4
Sella	Body Geometry Bridge Saddle, steel rails
Reggisella	TranzX dropper, 34.9mm, S1: 100mm, S2: 125mm, S3: 150mm, S4-S5: 170mm, S6- 200mm
Pedali	PEDAL, TEST RIDE PEDALS PROVIDED BY SPECIALIZED
Collarino Sella	Alloy, 38.6mm
Motore	Specialized 2.2 Custom Rx Trail Tuned Motor
INTERFACCIA	Specialized MasterMind TCU, percentage of remaining charge, 120 possible display configurations, MicroTune assist adjustment, ANT+/Bluetooth®, w/Handlebar remote
Batteria	Specialized M3-700, Integrated battery, 700Wh
Caricatore	Custom charger, 42V4A w/ Rosenberger plug, 100-240V
Cablaggio	Custom Specialized wiring harness
Accessori	SWAT CC steerer tube integrated tool with chain tool and link
Peso	24.21kg (53 lb, 6 oz)
Misura pesata	S4

ART. NR.	DESCRIZIONE	COLORE	MISURA
95225-8301/6	LEVO ALLOY G3 NB	Black / Light Silver / Black	S1 - S6
95225-8401/6	LEVO ALLOY G3 NB	Gloss Limestone / Black	S1 - S6
95225-8501/6	LEVO ALLOY G3 NB	Satin Dark Moss Green/Dune Wht	S1 - S6

## TURBO KENEVO SL 2 EXPERT



TURBO KENEVO SL 2 EXPERT	S2	S3	S4	S5
Stack (mm)	618	626	635	644
Reach (mm)	435	460	485	510
Lunghezza tubo sterzo (mm)	105	115	125	135
Angolo sterzo (degrees)	63.5	63.5	63.5	63.5
Altezza movimento centrale (mm)	350	350	350	350
BB Drop (mm)	25	25	25	25
Trail (mm)	136	136	136	136
Lunghezza forcella (mm)	579	579	579	579
Offset forcella/Rake (mm)	46	46	46	46
Avancorsa (mm)	782	812	841	871
Lunghezza Batticateni (mm)	447	447.3	447	447
Interasse (mm)	1228	1258	1287	1316
Altezza Standover (mm)	779	779	792	802
Lunghezza Piantone (mm)	400	420	440	465
Angolo sella (degrees)	76	76	76	76
Lunghezza pedivella (mm)	165	165	170	170
Larghezza Manubrio (mm)	780	800	800	800
Lunghezza Attacco man. (mm)	40	40	40	40
Larghezza Sella (mm)	155	143	143	143
Lunghezza Reggisella (mm)	125	150	170	200

SPECIFICHE TECNICHE	Specialized si riserva il diritto di modificare le caratteristiche senza preavviso.
Motore	Specialized 1.2 SL Custom Rx Trail Tuned Motor
Ruota anteriore	Traverse HD Alloy 29", DT Swiss 370
Ruota posteriore	Traverse HD Alloy 29", DT Swiss 370
Interfaccia	Specialized MasterMind TCU, percentage of remaining charge, 120 possible display configurations, MicroTune assist adjustment, over-the-air updates, ANT+/Bluetooth®, w/Handlebar remote
Batteria	Specialized SL1-320, fully integrated, 320Wh
Cablaggio	Custom Specialized wiring harness
Caricatore	Custom charger, 48V System w/ SL system charger plug
Telaio	FACT 11m full carbon, 29", full internal cable routing, 148mm spacing, fully sealed cartridge bearings, 170mm rear travel, geo adjust head tube, geo adjust horst pivot
Collarino Sella	Alloy, 38.6mm
Ammortizzatore	SRAM Vivid Select Plus, 230x62.5
Forcella	RockShox Zeb Select, Charger RC damper, 15x110mm, 44mm offset, 170mm of travel
Freno anteriore	SRAM Maven Bronze, 220mm rotor
Freno posteriore	SRAM Maven Bronze, 200mm rotor
Comandi cambio	SRAM AXS POD Controller
Cambio posteriore	SRAM GX Eagle Transmission Cassette, 12spd, 10-52t
Pacco Pignoni	SRAM GX Eagle Transmission Flattop Chain
Catena	SRAM GX Eagle Transmission Derailleur
Guarnitura	SRAM Alloy Crankset, Dub interface
Ingranaggi	104 BCD alloy spider, SRAM alloy T-Type chainring, 32t
Pneumatico anteriore	Butcher, GRID GRAVITY casing, GRIPTON® T9 compound, 2Bliss Ready, 29x2.3"
Pneumatico posteriore	Butcher, GRID GRAVITY casing, GRIPTON® T9 compound, 2Bliss Ready, 29x2.3"
Camere d'aria	Specialized Turbo Tube 29X1.75-2.4
Attacco Manubrio	Alloy Trail Stem, 35mm bar bore
Manubrio	Specialized, 6061 alloy, 6-degree upsweep, 8-degree backsweep, 30mm rise, 800mm width
Manopole	Deity Grips
Sella	Bridge Comp, Hollow Cr-mo rails, 155/143mm
Reggisella	PNW Loam dropper post, S2: 125mm, S3: 150, S4: 170mm, S5: 200mm
Accessori	SWAT CC, integrated tool and chain tool with spare link in steerer tube
Peso	20.32 kg (44 lb, 12.8 oz)
Misura pesata	S4

ART. NR.	DESCRIZIONE	COLORE	MISURA
98025-3002	TURBO KENEVO SL2 EXPERT	Cypress Metallic / Cast Lilac	S2
98025-3003			S3
98025-3004			S4
98025-3005			S5

Disponibile Online e Pickup in store

## TURBO KENEVO SL 2 OHLINS COIL



Charcoal Tint / Cool Grey Strata / Burnt Gold Metallic

TURBO KENEVO SL 2 OHLINS COIL	S2	S3	S4	S5
Stack (mm)	618	626	635	644
Reach (mm)	435	460	485	510
Lunghezza Tubo Sterzo (mm)	105	115	125	135
Angolo sterzo (degrees)	63.5	63.5	63.5	63.5
Altezza movimento centrale (mm)	350	350	350	350
BB Drop (mm)	25	25	25	25
Trail (mm)	136	136	136	136
Lunghezza forcella (mm)	579	579	579	579
Offset Forcella/Rake (mm)	46	46	46	46
Avancorsa (mm)	782	812	841	871
Lunghezza Batticateni (mm)	447	447.3	447	447
Interasse (mm)	1228	1258	1287	1316
Altezza Standover (mm)	779	779	792	802
Lunghezza Piantone (mm)	400	420	440	465
Angolo sella (degrees)	76	76	76	76

SPECIFICHE TECNICHE	Specialized si riserva il diritto di modificare le caratteristiche senza preavviso.
Motore	Specialized 1.2 SL Custom Rx Trail Tuned Motor
Batteria	Specialized SL1-320, fully integrated, 320Wh
Interfaccia	Specialized MasterMind TCU, percentage of remaining charge, 120 possible display configurations, MicroTune assist adjustment, ANT+/Bluetooth®, w/Handlebar remote
Cablaggio	Custom Specialized wiring harness
Caricatore	Custom charger, 48V System w/ SL system charger plug
Telaio	FACT 11m full carbon, 29", full internal cable routing, 148mm spacing, fully sealed cartridge bearings, 170mm rear travel, geo adjust head tube, geo adjust horst pivot
Collarino Sella	Alloy, 38.6mm
Ammortizzatore	Ohlins TTX coil shock, 230 x 62.5mm
Forcella	Ohlins RFX38 m.2, TTX 18 damper, 15x110mm, 44mm offset, 170mm of travel
Freno anteriore	TRP DH-R Evo brakes, 220mm rotor
Freno posteriore	TRP DH-R Evo brakes, 220mm rotor
Comandi cambio	SRAM AXS POD Controller
Cambio posteriore	SRAM GX Eagle Transmission Cassette, 12spd, 10-52t
Pacco Pignoni	SRAM GX Eagle Transmission Flattop Chain
Catena	SRAM GX Eagle Transmission Derailleur
Guarnitura	SRAM Alloy Crankset, Dub interface, S2/S3: 165mm, S4/S5: 170mm
Ingranaggi	104 BCD alloy spider, SRAM alloy T-Type chainring, 32t
Pneumatico anteriore	Butcher, GRID GRAVITY casing, GRIPTON® T9 compound, 2Bliss Ready, 29x2.3"
Ruota anteriore	Traverse HD Alloy 29", DT Swiss 370
Pneumatico posteriore	Butcher, GRID GRAVITY casing, GRIPTON® T9 compound, 2Bliss Ready, 29x2.3"
Ruota posteriore	Traverse HD Alloy 29", DT Swiss 370
Camere d'aria	Specialized Turbo Tube 29X1.75-2.4
Attacco Manubrio	RaceFace Aeffect R 35mm bore, 40mm length
Manubrio	Raceface Turbine Alloy, 35mm dia, S1/S2: 20mm rise, 800mm width, S3-S6: 40mm rise, 800mm width
Manopole	Deity Grips
Sella	Bridge Comp, Hollow Cr-mo rails, 155/143mm
Reggisella	Bike Yoke, Revive Max, 34.9, S1: 125mm, S2: 150mm, S3-S4: 185mm, S5-S6: 213mm
Accessori SWAT	SWAT CC, integrated tool and chain tool with spare link in steerer tube

ART. NR.	DESCRIZIONE	COLORE	MISURA
98025-0002	KENEVO SL 2 OHLINS Charcoal Tint / Cool Grey		S2
98025-0003			S3
98025-0004			S4
98025-0005			S5

Disponibile solo online & Pick up in Store

## TELAIO S-WORKS TURBO KENEVO SL 2



Champagne / Cool Grey Strata / Black

SPECIFICHE TECNICHE	Specialized si riserva il diritto di modificare le caratteristiche senza preavviso.
Motore	Specialized 1.2 SL Custom Rx Trail Tuned Motor
Batteria	Specialized SL1-320, fully integrated, 320Wh
Interfaccia	Specialized MasterMind TCU, percentage of remaining charge, 120 possible display configurations, MicroTune assist adjustment, ANT+/Bluetooth®, w/Handlebar remote
Cablaggio	Custom Specialized wiring harness
Caricatore	Custom charger, 48V System w/ SL system charger plug
Telaio	FACT 11m full carbon, 29", full internal cable routing, 148mm spacing, fully sealed cartridge bearings, 170mm rear travel, geo adjust head tube, geo adjust horst pivot
Collarino Sella	Alloy, 38.6mm
Ammortizzatore	Rockshox Vivid Ultimate, 230x62.5mm
Guarnitura	SRAM Carbon crankset, S2/S3: 165mm, S4/S5: 170mm
Ingranaggi	104 BCD alloy spider, SRAM alloy T-Type chainring, 32t
Accessori SWAT	SWAT CC, integrated tool and chain tool with spare link in steerer tube

TELAIO S-WORKS TURBO KENEVO SL 2	S3	S4
Stack (mm)	626	635
Reach (mm)	460	485
Lunghezza Tubo Sterzo (mm)	115	125
Angolo sterzo (degrees)	63.5	63.5
Altezza movimento centrale (mm)	350	350
BB Drop (mm)	25	25
Trail (mm)	136	136
Lunghezza forcella (mm)	579	579
Offset Forcella/Rake (mm)	46	46
Avancorsa (mm)	812	841
Lunghezza Batticateni (mm)	447.3	447
Interasse (mm)	1258	1287
Altezza Standover (mm)	779	792
Lunghezza Piantone (mm)	420	440
Angolo sella (degrees)	76	76

ART. NR.	DESCRIZIONE	COLORE	MISURA
78025-0003 SW	KENEVO SL 2 FRM	Champagne / Cool Grey	S3
78025-0004			S4

Disponibile online & Pick up in Store

## TURBO VADO SL 2 6.0 EQ CARBON



Satin Black Micro Speckle / Obsidian Frost

<b>TURBO VADO SL 2 6.0 EQ CARBON</b>	<b>S</b>	<b>M</b>	<b>L</b>	<b>XL</b>
Stack (mm)	600	628	660	698
Reach (mm)	375	405	430	450
Lunghezza Tubo Sterzo (mm)	155.55	185.55	220.55	260.55
Angolo Sterzo (degrees)	69	69	69	69
Altezza movimento centrale (mm)	291	291	291	291
B-B Drop (mm)	70	70	70	70
Trail (mm)	85	85	85	85
Lunghezza forcella (mm)	430	430	430	430
Offset forcella/Rake (mm)	50	50	50	50
Avancorsa (mm)	635.7	676.3	713.6	747.8
Lunghezza Batticateni (mm)	465	465	465	465
Interasse (mm)	1092	1132	1170	1204
Lunghezza Tubo Orizz. virtuale (mm)	547	585	619	650
Altezza Standover (mm)	755	781	824	869
Lunghezza Piantone (mm)	410	440	490	540
Angolo Sella (degrees)	74	74	74	74
Lunghezza pedivella (mm)	165	170	170	175
Larghezza Manubrio (mm)	680	680	680	680
Lunghezza Attacco man. (mm)	60	60	75	75
Larghezza Sella (mm)	155	155	155	155
Lunghezza Reggisella (mm)	350	350	400	400

<b>SPECIFICHE TECNICHE</b>	<b>Specialized si riserva il diritto di modificare le caratteristiche senza preavviso.</b>
Motore	Specialized 1.2 SL Custom Rx Trail Tuned Motor
Ruota anteriore	DT SWISS G540 Disc 24h - 700c X 24mm
Ruota posteriore	DT SWISS G540 Disc 24h - 700c X 24mm
Batteria	Specialized SL2-520, Fully Integrated, 520Wh
Interfaccia	Mastermind H3, W/Handlebar Remote, Ant+/Bluetooth®, Built-In System Lock Feature, Integrated Apple Find My, Coloured Customizable Display Pages, 2.1"
Caricatore	Custom charger, 48V System w/ SL system charger plug
Cablaggio	Custom Specialized wiring harness w/ chargeport
Telaio	2024 Vado SL
Collarino Sella	Specialized integrated
Forcella	Specialized Vado SL2 Carbon, Tubus front rack mounts up to 14kg
Freno anteriore	TRP HD-R803, hydraulic disc
Freno posteriore	TRP HD-R803, hydraulic disc
Comandi cambio	Shimano Deore XT, SL-M8100-IR, , Right, 12-Speed Rapidfire, W/O Optical Gear Display, I-Spec
Cambio posteriore	Shimano Deore XT 8100, 12-speed
Pacco Pignoni	Shimano SLX, CS-M7100, 12-speed, 10-51t
Catena	Shimano SLX, M7100, 12-speed
Guarnitura	SRAM FC S996 Carbon, S-165mm / M-L-170mm / XL-175mm
Ingranaggi	Praxis, CI 49.8mm, NW, 44T, Bcd 104mm
Pneumatico anteriore	Specialized Hemisphere flat protection, Reflective side walls, Wirebead, All terrain tire, 700x47c
Pneumatico posteriore	Specialized Hemisphere flat protection, Reflective side walls, Wirebead, All terrain tire, 700x47c
Camere d'aria	Specialized Turbo Tube 29X1.75-2.4
Attacco Manubrio	Specialized Stealth Stem, Alloy, 31.8mm, Integrated Display And Light Mount, Size S: 60mm 17 Deg, M/L/XL: 75mm 15.5 Deg
Manubrio	Specialized alloy, rise, 31.8mm, B-SWP 9-degree, rise 15mm, U-SWP 5-degree, 680mm.
Manopole	ERGON, GA30-S Custom, 134.8mm Length
Sella	Bridge Sport, hollow cr-mo rails, 155mm
Reggisella	Carbon Fiber, 30.9 mm, Offset 21mm
Pedali	Specialized Commuter w/ grip tape & reflectors
Fanale anteriore	Lezyne, Ebike Fusion Stvzo E500+, 500 Lumen, 50Cm Wire, With Reflector
Fanalino posteriore	Spanninga, Stvzo, Commuter Glow With Brake XEr
Portapacchi	Turbo SL Rack, MIK-Compatible, 25kg
Parafanghi	Specialized custom alloy Fender, Sandblast anodized black finish, 700c, integrated alloy stay
Cavalletto	Specialized kickstand, 40mm mount
Campanello	Specialized brass bell
Identificativo	221979
Peso	17.99 kg (39 lb, 10.6 oz)
Misura pesata	MD

<b>ART. NR.</b>	<b>DESCRIZIONE</b>	<b>COLORE</b>	<b>MISURA</b>
93924-1302/5	VADO SL 2 6.0 EQUIPPED	Satin Black Micro Speckle	S-XL

Disponibile Online e Pickup in store

# TURBO VADO SL 2 6.0 CARBON



Satin Black Micro Speckle / Obsidian Frost



Satin Red Sky / Red Onyx Frost

TURBO VADO SL 2 6.0 CARBON	S	M	L	XL
Stack (mm)	600	628	660	698
Reach (mm)	375	405	430	450
Lunghezza Tubo Sterzo (mm)	155.55	185.55	220.55	260.55
Angolo Sterzo (degrees)	69	69	69	69
Altezza movimento centrale (mm)	291	291	291	291
B-B Drop (mm)	70	70	70	70
Trail (mm)	85	85	85	85
Lunghezza forcella (mm)	430	430	430	430
Offset forcella/Rake (mm)	50	50	50	50
Avancorsa (mm)	635.7	676.3	713.6	747.8
Lunghezza Batticateni (mm)	465	465	465	465
Interasse (mm)	1092	1132	1170	1204
Lunghezza Tubo Orizz. virtuale (mm)	547	585	619	650
Altezza Standover (mm)	755	781	824	869
Lunghezza Piantone (mm)	410	440	490	540
Angolo Sella (degrees)	74	74	74	74
Lunghezza pedivella (mm)	165	170	170	175
Larghezza Manubrio (mm)	680	680	680	680
Lunghezza Attacco man. (mm)	60	60	75	75
Larghezza Sella (mm)	155	155	155	155
Lunghezza Reggisella (mm)	350	350	400	400

SPECIFICHE TECNICHE	Specialized si riserva il diritto di modificare le caratteristiche senza preavviso.
Motore	Specialized 1.2 SL Custom Rx Trail Tuned Motor
Ruota anteriore	DT SWISS G540 Disc 24h - 700c X 24mm
Ruota posteriore	DT SWISS G540 Disc 24h - 700c X 24mm
Batteria	Specialized SL2-520, Fully Integrated, 520Wh
Interfaccia	Mastermind H3, W/Handlebar Remote, Ant+/Bluetooth®, Built-In System Lock Feature, Integrated Apple Find My, Coloured Customizable Display Pages, 2.1"
Caricatore	Custom charger, 48V System w/ SL system charger plug
Cablaggio	Custom Specialized wiring harness w/ chargeport
Telaio	2024 Vado SL
Collarino Sella	Specialized integrated
Forcella	Specialized Vado SL2 Carbon, Tubus front rack mounts up to 14kg
Freno anteriore	TRP HD-R803, hydraulic disc
Freno posteriore	TRP HD-R803, hydraulic disc
Comandi cambio	Shimano Deore XT, SL-M8100-IR, , Right, 12-Speed Rapidfire, W/O Optical Gear Display, I-Spec
Cambio posteriore	Shimano Deore XT 8100, 12-speed
Pacco Pignoni	Shimano SLX, CS-M7100, 12-speed, 10-51t
Catena	Shimano SLX, M7100, 12-speed
Guarnitura	SRAM FC S996 Carbon, S-165mm / M-L-170mm / XL-175mm
Ingranaggi	Praxis, CI 49.8mm, NW, 44T, Bcd 104mm
Pneumatico anteriore	Specialized Hemisphere flat protection, Reflective side walls, Wirebead, All terrain tire, 700x47c
Pneumatico posteriore	Specialized Hemisphere flat protection, Reflective side walls, Wirebead, All terrain tire, 700x47c
Camere d'aria	Specialized Turbo Tube 29X1.75-2.4
Attacco Manubrio	Specialized Stealth Stem, Alloy, 31.8mm, Integrated Display And Light Mount, Size S: 60mm 17 Deg, M/L/XL: 75mm 15.5 Deg
Manubrio	Specialized alloy, rise, 31.8mm, B-SWP 9-degree, rise 15mm, U-SWP 5-degree, 680mm.
Manopole	ERGON, GA30-S Custom, 134.8mm Length
Sella	Bridge Sport, hollow cr-mo rails, 155mm
Reggisella	Carbon Fiber, 30.9 mm, Offset 21mm
Pedali	Specialized Commuter w/ grip tape & reflectors
Fanale anteriore	Lezyne, Ebike Fusion Stvzo E500+, 500 Lumen, 50Cm Wire, With Reflector
Fanalino posteriore	Specialized integrated saddle mount, LED Technology, 12V
Campanello	Specialized brass bell
Identificativo	206186
Peso	15.98 kg (35 lb, 3.7 oz)
Misura pesata	MD

ART. NR.	DESCRIZIONE	COLORE	MISURA
93924-1002/5	VADO SL 2 6.0	Satin Black Micro Speckle	S-XL
93924-1102/5	VADO SL 2 6.0	Satin Red Sky / Red Onyx Frost	S-XL

## TURBO VADO SL 2 CARBON LTD - FORWARD 50 COLLECTION



### TURBO VADO SL 2 CARBON LTD - FORWARD 50 COLLECTION

	S	M	L	XL
Stack (mm)	600	628	660	698
Reach (mm)	375	405	430	450
Lunghezza Tubo Sterzo (mm)	155.55	185.55	220.55	260.55
Angolo Sterzo (degrees)	69	69	69	69
Altezza movimento centrale (mm)	291	291	291	291
B-B Drop (mm)	70	70	70	70
Trail (mm)	85	85	85	85
Lunghezza forcella (mm)	430	430	430	430
Offset forcella/Rake (mm)	50	50	50	50
Avancorsa (mm)	635.7	676.3	713.6	747.8
Lunghezza Batticateni (mm)	465	465	465	465
Interasse (mm)	1092	1132	1170	1204
Lunghezza Tubo Orizz. virtuale (mm)	547	585	619	650
Altezza Standover (mm)	755	781	824	869
Lunghezza Piantone (mm)	410	440	490	540
Angolo Sella (degrees)	74	74	74	74
Lunghezza pedivella (mm)	165	170	170	175
Larghezza Manubrio (mm)	720	720	720	720
Lunghezza Attacco man. (mm)	60	60	75	75
Larghezza Sella (mm)	155	155	155	155
Lunghezza Reggisella (mm)	350	350	400	400

### SPECIFICHE TECNICHE

Specialized si riserva il diritto di modificare le caratteristiche senza preavviso.

Motore	New Specialized 1.2 SL Custom Rx Trail Tuned Motor
Ruota anteriore	Royal Terra Carbon CL, 25mm internal width, 32mm depth, 24h, Tubeless ready, DT for Roval 350 hub, Centerlock disc, DT Swiss Competition Race spokes
Batteria	Specialized SL2-520, Fully Integrated, 520Wh
Ruota posteriore	Royal Terra CL, 25mm internal width, 32mm depth, 24holes, Tubeless ready, DT for Roval 350 hub, Centerlock disc, DT Swiss Competition Race spokes
Interfaccia	Mastermind H3, W/Handlebar Remote, Ant+/Bluetooth®, Built-In System Lock Feature, Integrated Apple Find My, Coloured Customizable Display Pages, 2.1"
Caricatore	Custom charger, 48V System w/ SL system charger plug
Cablaggio	Custom Specialized wiring harness w/ chargeport
Telaio	2024 Vado SL CARBON
Collarino Sella	Specialized integrated
Forcella	Specialized Vado SL2 Carbon, Tubus front rack mounts up to 14kg
Freno anteriore	SRAM Level Silver Stealth
Freno posteriore	SRAM Level Silver Stealth
Comandi cambio	SRAM AXS POD Controller
Cambio posteriore	SRAM FORCE XPLR AXS D2 MAX 44T
Pacco Pignoni	SRAM XG 1251 D1 XPLR 10-44
Catena	SRAM CN Force 12-speed
Guarnitura	SRAM FC S996 Carbon, S-165mm / M-L-170mm / XL-175mm
Ingranaggi	SRAM 107BCD 44T Narrow Wide
Pneumatico anteriore	Specialized Hemisphere flat protection, Reflective side walls, Wirebead, All terrain tire, 700x47c
Pneumatico posteriore	Specialized Hemisphere flat protection, Reflective side walls, Wirebead, All terrain tire, 700x47c
Camere d'aria	Turbo Tube W/Talc 60mm 29X1.75-2.4
Attacco Manubrio	Specialized Stealth Stem, Alloy, 31.8mm, Integrated Display And Light Mount, Size S: 60mm 17 Deg, M/L/XL: 75mm 15.5 Deg
Manubrio	Specialized Carbon Handlebar, 10 Rise, 8 B-SWP, 6 U-SWP, 720mm, 31.8mm
Manopole	ERGON, GA30-S Custom, 134.8mm Length
Sella	Specialized Power Pro Mirror, Forward 50 limited edition, Nylon recycle base, Hollow-ti pink rail, 155mm
Reggisella	Royal Carbon Fiber, 30.9 mm, Offset 21mm
Pedali	Specialized Commuter w/ grip tape & reflectors
Fanale anteriore	Lezyne, Ebike Fusion Stvzo E500+, 500 Lumen, 50Cm Wire, With Reflector
Fanalino posteriore	Specialized integrated saddle mount, LED Technology, 12V
Campanello	Specialized brass bell
Peso	14.98 kg (33 lb, 0.4 oz)
Misura pesata	MD

ART. NR.	DESCRIZIONE	COLORE	MISURA
93925-1002/5	VADO SL 6.0 LTD FORWARD 50 COLLECTION		S-XL

Disponibile Online e Pickup in store



TURBO VADO 5.0	S	M	L	XL
Stack (mm)	625	639	652	676
Reach (mm)	423	444	464	481
Lunghezza tubo sterzo (mm)	135	150	165	190
Angolo sterzo (degrees)	68	68	68	68
Altezza movimento centrale (mm)	285	285	285	285
BB Drop (mm)	70	70	70	70
Trail (mm)	96	96	96	96
Lunghezza forcella (mm)	480	480	480	480
Offset forcella/Rake (mm)	44	44	44	44
Avancorsa (mm)	699	724	750	777
Lunghezza Batticateni (mm)	470	470	470	470
Interasse (mm)	1160	1186	1212	1239
Lunghezza Tubo Orizz. virtuale (mm)	585	615	645	675
Altezza Standover (mm)	735	771	771	805
Lunghezza Piantone (mm)	400	450	460	500
Angolo sella (Virtuale) (degrees)	75.5	75	74.5	74
Lunghezza pedivella (mm)	170	170	170	170
Larghezza Manubrio (mm)	680	680	680	680
Lunghezza Attacco man. (mm)	60	60	75	75
Larghezza Sella (mm)	155	155	155	155
Lunghezza Reggisella (mm)	375	375	375	375

ART. NR.	DESCRIZIONE	COLORE	MISURA
95025-2502	TURBO VADO 5.0		S
95025-2503			M
95025-2504			L
95025-2505			XL

SPECIFICHE TECNICHE	Specialized si riserva il diritto di modificare le caratteristiche senza preavviso.
Motore	Specialized 2.2, 90Nm torque, custom tuned motor, 250W nominal
Ingranaggi	48T
INTERFACCIA	MasterMind TCD, w/handlebar remote, built-in anti-theft feature, Bluetooth* connectivity, customizable display pages
Batteria	Specialized U2-710, alloy casing, state of charge display, 710Wh
Caricatore	Custom charger, 42V4A w/ Rosenberger plug, 100-240V
Telaio	E5 Aluminum, bottom bracket motor mount, fully integrated & lockable downtube battery, internal cable routing, lock and front rack mount, sliding dropout
Carter	Custom chaincover
Collarino Sella	Specialized Alloy 34.9, Steel Bolt
Forcella	Rockshox Recon Silver RL, 80mm travel, Motion-Control, fender-mounts
Freno anteriore	Shimano 4 pistons, CUES, BL-U8000, Br-U8020, Sm-Ma-F180P/P2
Freno posteriore	Shimano 4 pistons, CUES, BL-U8000, Br-U8020
Comandi cambio	Shimano, SL-U8000-11IR, CUES, Right, 11-Speed Rapidfire, W/O Optical Gear Display, I-Spec li
Cambio posteriore	Shimano, RD-U8000, CUES, Gs 11-Speed, Top Normal, Shadow Plus Design, Direct Attachment
Pacco Pignoni	Shimano, CS-LG400-11, CUES, 11-Speed, 11-50T
Catena	Shimano LG500
Guarnitura	Custom alloy forged crankarms, 170mm
Cerchi	650b disc, double-wall alloy, pinned, 32h
Mozzo anteriore	Specialized alloy front hub disc, sealed cartridge bearings, 6-bolt, 15x110mm thru-axle, 32h
Mozzo posteriore	Specialized Alloy Rear Hub Disc, Sealed Cartridge Bearings, 6-Bolt, 12X148mm Thru-Axle, 32H, Hd Steel Fhb
Raggi	DT Swiss Industry
Pneumatico anteriore	Pathfinder Sport Reflect, 650Bx2.3
Pneumatico posteriore	Pathfinder Sport Reflect, 650Bx2.3
Camere d'aria	Standard 40mm SV 650Bx1.75-2.4
Attacco Manubrio	Specialized Flowset, 3D-forged alloy, 20-degree rise, 31.8mm clamp
Manubrio	Specialized, alloy, 15-degree backsweep, 46mm rise, 31.8mm
Manopole	ERGON, GA30-S Custom, 134.8mm Length
Sella	Bridge Sport, Steel rails, 155mm
Reggisella	Cane Creek, Thudbuster St 30.9 mm
Pedali	Specialized Commuter w/ grip tape & reflectors
Radar	Integrated Garmin Radar, with custom information displayed directly on the Mastermind TCD
Fanale anteriore	LEZYNE Power StvZO E500+, 500 Lumens
Fanalino posteriore	Spanninga, Stvzo, Commuter Glow With Brake XEr
Portapacchi	Specialized rack, MIK HD interface, built-in pannier mounts, 27kg max load
Lucchetto	Turbo System Lock
Parafanghi	Specialized DRYTECH fenders, 65mm width, aluminum fenderstay
Cavalletto	Specialized kickstand, 40mm mount
Campanello	Specialized brass bell
Peso	25.9kg (57 lb, 1.6 oz)
Misura pesata	MD

# TURBO VADO 5.0 IGH



GLOSS CASTBLACK / SATIN SILVER REFLECTIVE



SATIN SEAFOAM / 25% LAPIS PEARL / GLACIAL METALLIC

TURBO VADO 5.0 IGH	S	M	L	XL
Stack (mm)	625	639	652	676
Reach (mm)	423	444	464	481
Lunghezza Tubo Sterzo (mm)	135	150	165	190
Angolo sterzo (degrees)	68	68	68	68
Altezza movimento centrale (mm)	285	285	285	285
BB Drop (mm)	70	70	70	70
Trail (mm)	96	96	96	96
Lunghezza forcella (mm)	480	480	480	480
Offset Forcella/Rake (mm)	44	44	44	44
Avancorsa (mm)	699	724	750	777
Lunghezza Batticateni (mm)	470	470	470	470
Interasse (mm)	1160	1186	1212	1239
Lunghezza Tubo Orizz. virtuale (mm)	585	615	645	675
Altezza Standover (mm)	735	771	771	805
Lunghezza Piantone (mm)	400	450	460	500
Angolo sella (Virtuale) (degrees)	75.5	75	74.5	74
Lunghezza pedivella (mm)	170	170	170	170
Larghezza Manubrio (mm)	680	680	680	680
Lunghezza Attacco man. (mm)	60	60	75	75
Larghezza Sella (mm)	155	155	155	155
Lunghezza Reggisella (mm)	375	375	375	375

ART. NR.	DESCRIZIONE	COLORE	MISURA
95025-3502	TURBO VADO 5.0 IGH	GLOSS CASTBLACK / SATIN SILVER	S
95025-3503			M
95025-3504			L
95025-3505			XL
95025-3702	TURBO VADO 5.0 IGH	SATIN SEAFOAM / LAPIS PEARL	S
95025-3703			M
95025-3704			L
95025-3705			XL

Disponibile online & Pick Up in Store

SPECIFICHE TECNICHE	Specialized si riserva il diritto di modificare le caratteristiche senza preavviso.
Motore	Specialized 2.2, 90Nm torque, custom tuned motor, 250W nominal
Batteria	Specialized U2-710, alloy casing, state of charge display, 710Wh
Interfaccia	MasterMind TCD, w/handlebar remote, built-in anti-theft feature, Bluetooth® connectivity, customizable display pages
Caricatore	Custom charger, 42V4A w/ Rosenberger plug, 100-240V
Telaio	E5 Aluminum, bottom bracket motor mount, fully integrated & lockable downtube battery, internal cable routing, lock and front rack mount, sliding dropout
Collarino Sella	Specialized Alloy 34.9, Steel Bolt
Forcella	Rockshox Recon Silver RL, 80mm travel, Motion-Control, fender-mounts
Freno anteriore	Shimano 4 pistons, CUES, BL-U8000, Br-U8020, Sm-Ma-F180P/P2
Freno posteriore	Shimano 4 pistons, CUES, BL-U8000, Br-U8020
Cambio posteriore	Automatic Hub Interface, AHI-PRO-40T-OE-1, envoilo Netherlands, 17NM, 40T Spline Compatible
Cambio anteriore	enviolo AUTOMATIq Pro shifting interface
Pacco Pignoni	Gates Carbon Drive CDX 22t sprocket, silver
Catena	Gates Carbon Drive CDX 122t belt, black
Guarnitura	Custom alloy forged crankarms, 170mm
Ingranaggi	Gates Carbon Drive CDX 50T chainring, black
Carter	Custom chaincover
Cerchi	650b disc, double-wall alloy, pinned, 32h
Mozzo anteriore	Specialized alloy front hub disc, sealed cartridge bearings, 6-bolt, 15x110mm thru-axle, 32h
Mozzo posteriore	enviolo Heavy Duty, 380% range, 6-bolt, 10x135mm, 32h
Raggi	DT Swiss Industry
Pneumatico anteriore	Pathfinder Sport Reflect, 650Bx2.3
Pneumatico posteriore	Pathfinder Sport Reflect, 650Bx2.3
Camere d'aria	Standard 40mm SV 650Bx1.75-2.4
Attacco Manubrio	Specialized Flowset, 3D-forged alloy, 20-degree rise, 31.8mm clamp
Manubrio	Specialized, alloy, 15-degree backsweep, 46mm rise, 31.8mm
Manopole	ERGON, GA30-S Custom, 134.8mm Length
Sella	Bridge Sport, Steel rails, 155mm
Reggisella	Cane Creek, Thudbuster St 30.9 mm
Pedali	Specialized Commuter w/ grip tape & reflectors
Radar	Integrated Garmin Radar, with custom information displayed directly on the Mastermind TCD
Accessori SWAT	Handlebar rear view mirror, aluminum
Fanale anteriore	LEZYNE Power StVZO E500+, 500 Lumens
Fanale posteriore	Spanninga, Stvzo, Commuter Glow With Brake XER
Portapacchi	Specialized rack, MIK HD interface, built-in pannier mounts, 27kg max load
Lucchetto	Turbo System Lock
Parafanghi	Specialized DRYTECH fenders, 65mm width, aluminum fenderstay
Cavalletto	Specialized kickstand, 40mm mount
Campanello	Specialized brass bell
Identificativo	221961
Peso	27.10 kg (59 lb, 11.92 oz)
Misura pesata	MD

## TURBO VADO 5.0 IGH STEP-THROUGH



GLOSS CASTBLACK / SATIN SILVER REFLECTIVE



SATIN SEAFOAM / 25% LAPIS PEARL / GLACIAL METALLIC

TURBO VADO 5.0 IGH STEP-THROUGH	S	M	L	XL
Stack (mm)	625	639	652	676
Reach (mm)	423	444	464	481
Lunghezza Tubo Sterzo (mm)	135	150	165	190
Angolo sterzo (degrees)	68	68	68	68
Altezza movimento centrale (mm)	285	285	285	285
BB Drop (mm)	70	70	70	70
Trail (mm)	96	96	96	96
Lunghezza forcella (mm)	480	480	480	480
Offset Forcella/Rake (mm)	44	44	44	44
Avancorsa (mm)	699	724	750	777
Lunghezza Batticateni (mm)	470	470	470	470
Interasse (mm)	1160	1186	1212	1239
Lunghezza Tubo Orizz. virtuale (mm)	585	615	645	675
Altezza Standover (mm)	618	617	617	626
Lunghezza Piantone (mm)	400	450	460	500
Angolo sella (Virtuale) (degrees)	75.5	75	74.5	74
Lunghezza pedivella (mm)	170	170	170	170
Larghezza Manubrio (mm)	680	680	680	680
Lunghezza Attacco man. (mm)	60	60	75	75
Larghezza Sella (mm)	155	155	155	155
Lunghezza Reggisella (mm)	375	375	375	375

ART. NR.	DESCRIZIONE	COLORE	MISURA
95025-4102	VADO 5.0 IGH STEP THROUGH	GLOSS CASTBLACK	S
95025-4103			M
95025-4104			L
95025-4105			XL
95025-4302	VADO 5.0 IGH STEP THROUGH	SATIN SEAFOAM	S
95025-4303			M
95025-4304			L
95025-4305			XL

Disponibile online & Pick Up in Store

### SPECIFICHE TECNICHE

Specialized si riserva il diritto di modificare le caratteristiche senza preavviso.

Motore	Specialized 2.2, 90Nm torque, custom tuned motor, 250W nominal
Ingranaggi	Gates Carbon Drive CDX 50T chainring, black
Batteria	Specialized U2-710, alloy casing, state of charge display, 710Wh
Interfaccia	MasterMind TCD, w/handlebar remote, built-in anti-theft feature, Bluetooth® connectivity, customizable display pages
Caricatore	Custom charger, 42V4A w/ Rosenberger plug, 100-240V
Telaio	E5 Aluminum, bottom bracket motor mount, fully integrated & lockable downtube battery, internal cable routing, lock and front rack mount, sliding dropout
Carter	Custom chaincover
Collarino Sella	Specialized Alloy 34.9, Steel Bolt
Forcella	Rockshox Recon Silver RL, 80mm travel, Motion-Control, fender-mounts
Freno anteriore	Shimano 4 pistons, CUES, BL-U8000, Br-U8020, Sm-Ma-F180P/P2
Freno posteriore	Shimano 4 pistons, CUES, BL-U8000, Br-U8020
Cambio posteriore	enviolo AUTOMATIq Pro shifting interface
Cambio anteriore	AUTOMATIC HUB INTERFACE, AHI-PRO-40T-OE-1, ENVILOLO NETHERLANDS, 17MM, 40T SPLINE COMPATIBLE
Pacco Pignoni	Gates Carbon Drive CDX 22t sprocket, silver
Catena	Gates Carbon Drive CDX 122t belt, black
Guarnitura	Custom alloy forged crankarms, 170mm
Cerchi	650b disc, double-wall alloy, pinned, 32h
Mozzo anteriore	Specialized alloy front hub disc, sealed cartridge bearings, 6-bolt, 15x110mm thru-axle, 32h
Mozzo posteriore	enviolo Heavy Duty, 380% range, 6-bolt, 10x135mm, 32h
Raggi	DT Swiss Industry
Pneumatico anteriore	Pathfinder Sport Reflect, 650Bx2.3
Pneumatico posteriore	Pathfinder Sport Reflect, 650Bx2.3
Camere d'aria	Standard 40mm SV 650Bx1.75-2.4
Attacco Manubrio	Specialized Flowset, 3D-forged alloy, 20-degree rise, 31.8mm clamp
Manubrio	Specialized, alloy, 15-degree backsweep, 46mm rise, 31.8mm
Manopole	ERGON, GA30-S Custom, 134.8mm Length
Sella	Bridge Sport, Steel rails, 155mm
Reggisella	Cane Creek, Thudbuster St 30.9 mm
Pedali	Specialized Commuter w/ grip tape & reflectors
Radar	Integrated Garmin Radar, with custom information displayed directly on the Mastermind TCD
Accessori SWAT	Handlebar rear view mirror, aluminum
Fanale anteriore	LEZYNE Power StVZO E500+, 500 Lumens
Fanale posteriore	Spanninga, StVZO, Commuter Glow With Brake XEr
Portapacchi	Specialized rack, MIK HD interface, built-in pannier mounts, 27kg max load
Lucchetto	Turbo System Lock
Parafanghi	Specialized DRYTECH fenders, 65mm width, aluminum fenderstay
Cavalletto	Specialized kickstand, 40mm mount
Campanello	Specialized brass bell
Identificativo	221964
Misura pesata	MD

## TURBO VADO 4.0 IGH



GLOSS CASTBLACK / SATIN SILVER REFLECTIVE

TURBO VADO 4.0 IGH	S	M	L	XL
Stack (mm)	625	639	652	676
Reach (mm)	423	444	464	481
Lunghezza tubo sterzo (mm)	135	150	165	190
Angolo sterzo (degrees)	68	68	68	68
Altezza movimento centrale (mm)	285	285	285	285
BB Drop (mm)	70	70	70	70
Trail (mm)	96	96	96	96
Lunghezza forcella (mm)	480	480	480	480
Offset forcella/Rake (mm)	44	44	44	44
Avancorsa (mm)	699	724	750	777
Lunghezza Batticateni (mm)	470	470	470	470
Interasse (mm)	1160	1186	1212	1239
Lunghezza Tubo Orizz. virtuale (mm)	585	615	645	675
Altezza standover (mm)	735	771	771	805
Lunghezza piantone (mm)	400	450	460	500
Angolo sella (virtuale) (degrees)	75.5	75	74.5	74
Lunghezza pedivella - translate here (mm)	170	170	170	170
Larghezza Manubrio (mm)	680	680	680	680
Lunghezza Attacco man. (mm)	60	60	75	75
Larghezza Sella (mm)	155	155	155	155
Lunghezza Reggisella (mm)	350	350	400	400

### SPECIFICHE TECNICHE

Specialized si riserva il diritto di modificare le caratteristiche senza preavviso.

Telaio	E5 Aluminum, bottom bracket motor mount, fully integrated & lockable downtube battery, internal cable routing, lock and front rack mount, sliding dropout
Forcella	SR Suntour MobieA32, 80mm travel, lockout, fender-mounts, integrated light mount
Attacco Manubrio	Specialized Flowset, 3D-forged alloy, 20-degree rise, 31.8mm clamp
Manubrio	Specialized, alloy, 15-degree backsweep, 46mm rise, 31.8mm
Manopole	Specialized Body Geometry Contour, lock-on
Freno anteriore	SRAM Level, 2-piston caliper, hydraulic disc, 180mm
Freno posteriore	SRAM Level, 2-piston caliper, hydraulic disc, 180mm
Cambio posteriore	enviolo CVP Multi-Turn
Comandi cambio	enviolo Twist Display Pure
Pacco Pignoni	Gates Carbon Drive CDX 22t sprocket, silver
Catena	Gates Carbon Drive CDX 122t belt, black
Guarnitura	Custom alloy forged crankarms
Ingranaggi	Gates Carbon Drive CDX 50T chainring, black
Pedali	Specialized Commuter w/ grip tape & reflectors
Cerchi	650b disc, double-wall alloy, pinned, 32h
Mozzo anteriore	Specialized alloy front hub disc, sealed cartridge bearings, 6-bolt, 15x110mm thru-axle, 32h
Mozzo posteriore	enviolo Trekking, 380% range, 6-bolt, 10x135mm, 32h
Raggi	DT Swiss Industry
Pneumatico anteriore	Pathfinder Sport Reflect, 650Bx2.3
Pneumatico posteriore	Pathfinder Sport Reflect, 650Bx2.3
Camere d'aria	Standard 40mm SV 650Bx1.75-2.4
Sella	Bridge Sport, Steel rails, 155mm
Reggisella	Spring suspension, alloy, 40mm travel, 30.9mm, 2-bolt clamp, 34.9mm sleeve
Collarino Sella	Alloy, bolt-type, 34.9mm
Motore	Specialized 2.0, 70Nm torque, custom tuned motor, 250W nominal
INTERFACCIA	MasterMind TCD, w/handlebar remote, built-in anti-theft feature, Bluetooth* connectivity, customizable display pages
Batteria	Specialized U2-710, alloy casing, state of charge display, 710Wh
Caricatore	Custom charger, 42V4A w/ Rosenberger plug, 100-240V
Cablaggio	Custom wire harness
Accessori	Handlebar rear view mirror, aluminum
Fanale anteriore	Lezyne, Ebike Hecto Stvzo E350+, 350 Lumen, 160Cm Wire, With Reflector
Fanalino posteriore	Spanninga, Stvzo, Commuter Glow With Brake XER
Carter	Custom chaincover
Cavalletto	Specialized kickstand, 40mm mount
Portapacchi	Specialized rack, MIK HD interface, built-in pannier mounts, 27kg max load
Parafanghi	Specialized DRYTECH fenders, 65mm width, aluminum fenderstay
Lucchetto	Turbo System Lock
Campanello	Simple bell

ART. NR.	DESCRIZIONE	COLORE	MISURA
95324-8402/5	VADO 4.0 IGH NB	GLOSS CASTBLACK / SATIN SILVER REFLECTIVE	S-XL

## TURBO VADO 4.0 IGH STEP THROUGH



GLOSS CASTBLACK / SATIN SILVER REFLECTIVE



SATIN SEAFOAM / 25% LAPIS PEARL / GLACIAL METALLIC

### TURBO VADO 4.0 IGH STEP THROUGH

	S	M	L	XL
Stack (mm)	625	639	652	676
Reach (mm)	423	444	464	481
Lunghezza Tubo Sterzo (mm)	135	150	165	190
Angolo sterzo (degrees)	68	68	68	68
Altezza movimento centrale (mm)	285	285	285	285
BB Drop (mm)	70	70	70	70
Trail (mm)	96	96	96	96
Lunghezza forcella (mm)	480	480	480	480
Offset Forcella/Rake (mm)	44	44	44	44
Avancorsa (mm)	699	724	750	777
Lunghezza Batticateni (mm)	470	470	470	470
Interasse (mm)	1160	1186	1212	1239
Lunghezza Tubo Orizz. virtuale (mm)	585	615	645	675
Altezza Standover (mm)	618	617	617	626
Lunghezza Piantone (mm)	400	450	460	500
Angolo sella (Virtuale) (degrees)	75.5	75	74.5	74
Lunghezza pedivella (mm)	170	170	170	170
Larghezza Manubrio (mm)	680	680	680	680
Lunghezza Attacco man. (mm)	60	60	75	75
Larghezza Sella (mm)	155	155	155	155
Lunghezza Reggisella (mm)	350	350	400	400

ART. NR.	DESCRIZIONE	COLORE	MISURA
95324-9402	VADO 4.0 IGH ST	GLOSS CASTBLACK / SATIN SILVER REFLECTIVE	S
95324-9403			M
95324-9404			L
95324-9405			XL
95025-7302	VADO 4.0 IGH ST	SATIN SEAFOAM / 25% LAPIS PEARL / GLMET.	S
95025-7303			M
95025-7304			L
95025-7305			XL

Disponibile Online e Pickup in store

### SPECIFICHE TECNICHE

SPECIFICHE TECNICHE	Specialized si riserva il diritto di modificare le caratteristiche senza preavviso.
Motore	Specialized 2.0, 70Nm torque, custom tuned motor, 250W nominal
Ingranaggi	Gates Carbon Drive CDX 50T chainring, black
Batteria	Specialized U2-710, alloy casing, state of charge display, 710Wh
Interfaccia	MasterMind TCD, w/handlebar remote, built-in anti-theft feature, Bluetooth® connectivity, customizable display pages
Cablaggio	Custom wire harness
Caricatore	Custom charger, 42V4A w/ Rosenberger plug, 100-240V
Telaio	E5 Aluminum, bottom bracket motor mount, fully integrated & lockable downtube battery, internal cable routing, lock and front rack mount, sliding dropout
Carter	Custom chaincover
Collarino Sella	Alloy, bolt-type, 34.9mm
Forcella	SR Suntour MobieA32, 80mm travel, lockout, fender-mounts, integrated light mount
Freno anteriore	SRAM Level, 2-piston caliper, hydraulic disc, 180mm
Freno posteriore	SRAM Level, 2-piston caliper, hydraulic disc, 180mm
Comandi cambio	enviolo Twist Display Pure
Cambio posteriore	enviolo CVP Multi-Turn
Pacco Pignoni	Gates Carbon Drive CDX 22t sprocket, silver
Catena	Gates Carbon Drive CDX 122t belt, black
Guarnitura	Custom alloy forged crankarms, 170mm
Cerchi	650b disc, double-wall alloy, pinned, 32h
Mozzo anteriore	Specialized alloy front hub disc, sealed cartridge bearings, 6-bolt, 15x110mm thru-axle, 32h
Mozzo posteriore	enviolo Trekking, 380% range, 6-bolt, 10x135mm, 32h
Raggi	DT Swiss Industry
Pneumatico anteriore	Pathfinder Sport Reflect, 650Bx2.3
Pneumatico posteriore	Pathfinder Sport Reflect, 650Bx2.3
Camere d'aria	Standard 40mm SV 650Bx1.75-2.4
Attacco Manubrio	Specialized Flowset, 3D-forged alloy, 20-degree rise, 31.8mm clamp
Manubrio	Specialized, alloy, 15-degree backsweep, 46mm rise, 31.8mm
Manopole	Specialized Body Geometry Contour, lock-on
Sella	Bridge Sport, Steel rails, 155mm
Reggisella	Spring suspension, alloy, 40mm travel, 30.9mm, 2-bolt clamp, 34.9mm sleeve
Pedali	Specialized Commuter w/ grip tape & reflectors
Accessori SWAT	Handlebar rear view mirror, aluminum
Fanale anteriore	Lezyne, Ebike Hecto Stvzo E350+, 350 Lumen, 160Cm Wire, With Reflector
Fanalino posteriore	Spanninga, Stvzo, Commuter Glow With Brake XEr
Portapacchi	Specialized rack, MIK HD interface, built-in pannier mounts, 27kg max load
Lucchetto	Turbo System Lock
Parafanghi	Specialized DRYTECH fenders, 65mm width, aluminum fenderstay
Cavalletto	Specialized kickstand, 40mm mount
Campanello	Specialized bell
Identificativo	260920
Peso	28.25 kg (62 lb, 4.5 oz)
Misura pesata	MD

# TURBO CREO EXPERT



BLACK PEARL BIRCH BLACK PEARL SPECKLE



Satin Cooper/Red Pearl/Doppio

TURBO CREO EXPERT	49	52	54	56	58	61
Stack (mm)	578	578	595	607	638	663
Reach (mm)	365	374	383	392	401	410
Lunghezza Tubo Sterzo (mm)	90	90	108	120	153	180
Angolo Sterzo (degrees)	71	71	71	71	71	71
Altezza movimento centrale (mm)	270	270	270	270	270	270
B-B Drop (mm)	80	80	80	80	80	80
Trail (mm)	62	62	62	62	62	62
Lunghezza forcella (mm)	405	405	405	405	405	405
Offset Forcella/Rake (mm)	55	55	55	55	55	55
Avancorsa (mm)	600.1	609	623.8	636.6	656.2	673.8
Lunghezza Batticateni (mm)	435	435	435	435	435	435
Interasse (mm)	1022	1031	1046	1059	1079	1097
Lunghezza Tubo Orizz. virtuale (mm)	531	540	554	572	590	613
Altezza Standover (mm)	731	743	773	793	824	852
Lunghezza Piantone (mm)	410	430	470	500	530	560
Angolo Sella (degrees)	74	74	74	73.5	73.5	73
Lunghezza pedivella (mm)	165	170	172.5	172.5	175	175
Larghezza Manubrio (mm)	380	400	420	420	440	440
Lunghezza Attacco man. (mm)	60	70	80	90	100	100
Larghezza Sella (mm)	155	155	143	143	143	143
Lunghezza Reggisella (mm)	350	350	350	400	400	400

SPECIFICHE TECNICHE	Specialized si riserva il diritto di modificare le caratteristiche senza preavviso.
Nastro Manubrio	Supacaz Super Sticky Kush
Motore	New Specialized 1.2 SL Custom Lightweight Motor
Batteria	Specialized SL1-320, fully integrated, 320Wh
Interfaccia	Specialized MasterMind TCU, percentage of remaining charge, 120 possible display configurations, MicroTune assist adjustment, over-the-air updates, ANT+/Bluetooth®, w/Handlebar remote
Caricatore	Custom charger, 48V System w/ SL system charger plug
Cablaggio	Custom Specialized wiring harness w/ charge port
Telaio	FACT 11r carbon, front/rear thru-axles, fully integrated down tube battery, internal cable routing, fender/rack mounts, 12x142mm
Collarino Sella	Specialized Alloy, 31.8
Forcella	Future Shock 3.3 w/ Smooth Boot, 12x100mm thru-axle, flat-mount disc
Freno anteriore	SRAM Rival, hydraulic disc, 180mm
Freno posteriore	SRAM Rival, hydraulic disc, 160mm
Comandi cambio	SRAM Rival eTap AXS, hydraulic disc
Cambio posteriore	SRAM GX Eagle AXS
Pacco Pignoni	SRAM PG1230, 12-Speed, 11-50t
Catena	SRAM GX Eagle
Guarnitura	SRAM Alloy DUB Crank Arms
Ingranaggi	SRAM X-Sync Eagle, 107 BCD, 44T
Pneumatico anteriore	Tracer Pro, 700x47c
Ruota anteriore	Roval Terra C, 25mm internal width carbon rim, 32mm depth, DT 370 hub, 24h, DT Swiss Comp Race spokes
Pneumatico posteriore	Tracer Pro, 700x47c
Ruota posteriore	Roval Terra C, 25mm internal width carbon rim, 32mm depth, DT 370 hub, 24h, DT Swiss Comp Race spokes
Camere d'aria	700x32/50mm, 48mm Presta valve
Attacco Manubrio	Future Stem Pro
Curva manubrio	Specialized Adventure Gear Hover, 103mm drop x 70mm reach x 12° flare
Sella	Body Geometry Power Expert
Reggisella	Trans-X Dropper, 50mm Travel
Identificativo	221799
Peso	13.96kg (30 lb, 12.4 oz)
Misura pesata	56

ART. NR.	DESCRIZIONE	COLORE	MISURA
98125-3149/61	CREO SL 2 EXPERT PEARL BIRCH SPECKLE		49 - 61
98125-3049/61	CREO SL 2 EXPERT Satin Cooper/Red Pearl/Doppio		49 - 61

## TURBO CREO COMP CARBON



CYPRESS METALLIC/BLACK LIQUID METAL



METALLIC DEEP LAKE/DEEP LAKE

<b>TURBO CREO COMP CARBON</b>	<b>49</b>	<b>52</b>	<b>54</b>	<b>56</b>	<b>58</b>	<b>61</b>
Stack (mm)	578	578	595	607	638	663
Reach (mm)	365	374	383	392	401	410
Lunghezza Tubo Sterzo (mm)	90	90	108	120	153	180
Angolo Sterzo (degrees)	71	71	71	71	71	71
Altezza movimento centrale (mm)	270	270	270	270	270	270
B-B Drop (mm)	80	80	80	80	80	80
Trail (mm)	62	62	62	62	62	62
Lunghezza forcella (mm)	405	405	405	405	405	405
Offset forcella/Rake (mm)	55	55	55	55	55	55
Avancorsa (mm)	600.1	609	623.8	636.6	656.2	673.8
Lunghezza Batticateni (mm)	435	435	435	435	435	435
Interasse (mm)	1022	1031	1046	1059	1079	1097
Lunghezza Tubo Orizz. virtuale (mm)	531	540	554	572	590	613
Altezza Standover (mm)	731	743	773	793	824	852
Lunghezza Piantone (mm)	410	430	470	500	530	560
Angolo Sella (degrees)	74	74	74	73.5	73.5	73
Lunghezza pedivella (mm)	165	170	172.5	172.5	175	175
Larghezza Manubrio (mm)	380	400	420	420	440	440
Lunghezza Attacco man. (mm)	60	70	80	90	100	100
Larghezza Sella (mm)	155	155	143	143	143	143
Lunghezza Reggisella (mm)	350	350	350	400	400	400

<b>SPECIFICHE TECNICHE</b>	<b>Specialized si riserva il diritto di modificare le caratteristiche senza preavviso.</b>
Nastro Manubrio	Supacaz Super Sticky Kush
Motore	New Specialized 1.2 SL Custom Lightweight Motor
Ruota anteriore	DT Swiss G540 rim, 24mm internal width, tubeless ready, 24h, Specialized full sealed bearing thru axle hub, centerlock disc, DT Swiss Champion 14G stainless steel spokes, DT Swiss brass nipples
Batteria	Specialized SL1-320, fully integrated, 320Wh
Ruota posteriore	DT Swiss G540 rim, 24mm internal width, tubeless ready, 24h, Specialized full sealed bearing thru axle hub, centerlock disc, DT Swiss Champion 14G stainless steel spokes, DT Swiss brass nipples
Interfaccia	Specialized MasterMind TCU, percentage of remaining charge, 120 possible display configurations, MicroTune assist adjustment, over-the-air updates, ANT+/Bluetooth®, w/Handlebar remote
Caricatore	Custom charger, 48V System w/ SL system charger plug
Cablaggio	Custom Specialized wiring harness w/ charge port
Telaio	FACT 11r carbon, front/rear thru-axles, fully integrated down tube battery, internal cable routing, fender/rack mounts, 12x142mm
Collarino Sella	Specialized Alloy, 31.8
Forcella	Future Shock 3.2 w/ Smooth Boot, 12x100mm thru-axle, flat-mount disc
Freno anteriore	SRAM Apex eTAP AXS, hydraulic disc
Freno posteriore	SRAM Apex eTAP AXS, hydraulic disc
Comandi cambio	SRAM Apex eTap AXS
Cambio posteriore	SRAM X1 Eagle AXS
Pacco Pignoni	SRAM PG1210, 12-Speed, 11-50t
Catena	SRAM NX Eagle, 12-Speed
Guarnitura	SRAM Alloy DUB Crank Arms
Ingranaggi	SRAM X-Sync Eagle, 107 BCD, 44T
Pneumatico anteriore	Tracer Pro, 700x42c
Pneumatico posteriore	Tracer Pro, 700x42c
Camere d'aria	700x32/50mm, 48mm Presta valve
Attacco Manubrio	Future Stem Comp
Curva manubrio	Specialized Adventure Gear Hover, 103mm drop x 70mm reach x 12° flare
Sella	Body Geometry Power Sport
Reggisella	Trans-X Dropper, 50mm Travel
Identificativo	221866
Peso	14.55kg (32 lb, 1.2 oz)
Misura pesata	56

<b>ART. NR.</b>	<b>DESCRIZIONE</b>	<b>COLORE</b>	<b>MISURA</b>
98125-5049	CREO COMP CARBON	CYPRESS METALLIC/BLACK	49
98125-5052			52
98125-5054			54
98125-5056			56
98125-5058			58
98125-5061			61
98125-5149	CREO COMP CARBON	METALLIC DEEP LAKE	49
98125-5152			52
98125-5154			54
98125-5156			56
98125-5158			58
98125-5161			61

## TURBO CREO 2 COMP E5



Gloss Metallic Dark Navy/Harvest Gold Metallic



Satin Taupe/Birch

<b>TURBO CREO 2 COMP E5</b>	<b>49</b>	<b>52</b>	<b>54</b>	<b>56</b>	<b>58</b>	<b>61</b>
Stack (mm)	571	577	590	608	630	655
Reach (mm)	365	374	383	392	401	410
Lunghezza Tubo Sterzo (mm)	99	104	116	133	159	185
Angolo sterzo (degrees)	70	70.5	71.25	72	72	72
Altezza BB (mm)	270	270	272	272	275	275
B-B Drop (mm)	80	80	78	78	76	76
Trail (mm)	69	66	61	57	57	58
Lunghezza forcella (mm)	389	389	389	389	389	389
Offset forcella/Rake (mm)	55	55	55	55	55	55
Avancorsa (mm)	607	614	620	629	646	664
Lunghezza Batticateni (mm)	440	440	440	440	440	440
Interasse (mm)	1035	1041	1048	1058	1075	1093
Lunghezza Tubo Orizz. virtuale (mm)	529	542	558	566	588	604
Altezza standover (mm)	705	718	746	772	800	826
Lunghezza piantone (mm)	390	430	470	500	530	560
Angolo sella (degrees)	74	73.75	73.5	73.5	73.5	73.5
Lunghezza pedivella (mm)	165	170	172.5	172.5	175	175
Larghezza Manubrio (mm)	380	400	420	420	440	440
Lunghezza Attacco man. (mm)	60	70	80	90	100	100
Larghezza Sella (mm)	155	155	143	143	143	143
Lunghezza Reggisella (mm)	350	350	350	400	400	400

### SPECIFICHE TECNICHE

Specialized si riserva il diritto di modificare le caratteristiche senza preavviso.

Telaio	Specialized E5 Premium Aluminum frame, front/rear thru-axles, fully integrated down tube battery, internal cable routing, fender/rack mounts, 12x142mm, flat-mount disc brakes
Forcella	Future Shock 3.1w/ Smooth Boot, 12x100mm thru-axle, flat-mount disc
Curva manubrio	Specialized Adventure Gear Hover, 103mm drop x 70mm reach x 12° flare
Attacco Manubrio	Future Stem Comp
Nastro Manubrio	Supacaz Suave
Reggisella	Carbon, single-bolt, 27.2mm
Freno anteriore	SRAM Apex, Hydraulic disc
Freno posteriore	SRAM Apex, Hydraulic disc
Cambio posteriore	SRAM Apex Eagle 12-Speed
Comandi cambio	SRAM Apex 12-Speed
Pacco Pignoni	SRAM PG1210, 12-Speed, 11-50t
Guarnitura	SRAM Alloy DUB Crank Arms
Catena	SRAM NX Eagle, 12-Speed
Ingranaggi	SRAM X-Sync Eagle, 107 BCD, 44T
Ruota anteriore	DT Swiss G540 rim, 24mm internal width, tubeless ready, 24h, Specialized full sealed bearing thru axle hub, centerlock disc, DT Swiss Champion 14G stainless steel spokes, DT Swiss brass nipples
Ruota posteriore	DT Swiss G540 rim, 24mm internal width, tubeless ready, 24h, Specialized full sealed bearing thru axle hub, centerlock disc, DT Swiss Champion 14G stainless steel spokes, DT Swiss brass nipples
Pneumatico anteriore	Pathfinder Pro 2Bliss Ready, 700x38c
Sella	Body Geometry Power Sport, steel rails
Pneumatico posteriore	Pathfinder Pro 2Bliss Ready, 700x38c
Camere d'aria	Presta valve, 48mm
Collarino Sella	Specialized Alloy, 31.8
Motore	New Specialized 1.2 SL Custom Lightweight Motor
INTERFACCIA	Specialized MasterMind TCU, percentage of remaining charge, 120 possible display configurations, MicroTune assist adjustment, over-the-air updates, ANT+/Bluetooth®, w/Handlebar remote
Batteria	Specialized SL1-320, fully integrated, 320Wh
Caricatore	Custom charger, 48V System w/ SL system charger plug
Cablaggio	Custom Specialized wiring harness w/ charge port
Peso	15.12kg (33 lb, 5.3 oz)
Misura pesata	56

ART. NR.	DESCRIZIONE	COLORE	MISURA
98124-5149	CREO SL E5 COMP	Gloss Metallic Dark Navy/Harve	49
98124-5152			52
98124-5154			54
98124-5156			56
98124-5158			58
98124-5161			61
98124-5049	CREO SL E5 COMP	Satin Taupe/Birch	49
98124-5052			52
98124-5054			54
98124-5056			56
98124-5058			58
98124-5061			61



TURBO COMO 4.0	S	M	L
Stack (mm)	650	671	682
Reach (mm)	441	465	486
Lunghezza Tubo Sterzo (mm)	150	170	180
Angolo sterzo (degrees)	67	67.5	68
Altezza movimento centrale (mm)	275	275	275
BB Drop (mm)	80	80	80
Trail (mm)	103	99	96
Lunghezza forcella (mm)	487	487	487
Offset Forcella/Rake (mm)	44	44	44
Avancorsa (mm)	735	762	781
Lunghezza Batticateni (mm)	470.4	470.4	470.4
Interasse (mm)	1194	1221	1241
Lunghezza Tubo Orizz. virtuale (mm)	630	666	695
Altezza Standover (mm)	355	355	355
Lunghezza Piantone (mm)	450	450	460
Angolo sella (Virtuale) (degrees)	73.8	73.3	73
Lunghezza pedivella (mm)	165	165	165
Larghezza Manubrio (mm)	680	680	680
Larghezza Sella (mm)	200	200	200
Lunghezza Reggisella (mm)	350	400	400

ART. NR.	DESCRIZIONE	COLORE	MISURA
90424-5402	TURBO COMO 4.0		S
90424-5403			M
90424-5404			L
90425-5502	TURBO COMO 4.0		S
90425-5503			M
90425-5504			L

SPECIFICHE TECNICHE	Specialized si riserva il diritto di modificare le caratteristiche senza preavviso.
Motore	Specialized 2.0, 70Nm torque, custom tuned motor, 250W nominal
Ingranaggi	40T
Batteria	Specialized U2-710, alloy casing, state of charge display, 710Wh
INTERFACCIA	MasterMind TCD, w/handlebar remote, built-in anti-theft feature, Bluetooth® connectivity, customizable display pages
Cablaggio	Custom wire harness
Caricatore	Custom charger, 42V4A w/ Rosenberger plug, 100-240V
Telaio	E5 Aluminum, bottom bracket motor mount, fully integrated & lockable downtube battery, internal cable routing, lock and front rack mount
Carter	Integrated Chaincover
Collarino Sella	Specialized bolt-type, alloy, 42.9mm
Forcella	SR Suntour MobieA32, 80mm travel, lockout, fender-mounts, integrated light mount
Freno anteriore	Shimano BR-MT200, hydraulic disc, 180mm
Freno posteriore	Shimano BR-MT200, hydraulic disc, 160mm
Comandi cambio	Shimano, SL-U4000-9R, CUES, Right, 9-Speed Rapidfire, W/ Optical Gear Display
Cambio posteriore	Shimano, RD-U4000, CUES, Gs 9-Speed, Top Normal, Shadow Design, Direct Attachment
Pacco Pignoni	Shimano, CS-LG300-9, CUES, 9-Speed, 11-41T
Catena	Shimano LG500
Guarnitura	Custom alloy forged crankarms
Cerchi	650b disc, double-wall alloy, pinned, 32h
Mozzo anteriore	Shimano Center Lock Disc 32H, 15mm Thru Type Axle, 100mm
Mozzo posteriore	Shimano Freehub, Center Lock Disc, 8-11-Speed 12mm Thru Type Axle, 32H, 148mm
Raggi	DT Swiss Industry
Pneumatico anteriore	Hemisphere Flat Protection Reflect, 650b X 2.3
Pneumatico posteriore	Hemisphere Flat Protection Reflect, 650b X 2.3
Camere d'aria	Standard 40mm SV 650Bx1.75-2.4
Attacco Manubrio	Specialized integrated stem
Manubrio	Specialized Como handlebar/stem combo
Manopole	Specialized Body Geometry Contour, lock-on
Sella	Body Geometry Comfort Gel, 200mm w/ SWAT™ Mount
Reggisella	Spring suspension, alloy, 40mm travel, 30.9mm, 2-bolt clamp, 34.9mm sleeve
Pedali	Specialized Commuter w/ grip tape & reflectors
Fanale anteriore	Lezyne, Ebike Mini Stvzo E300+, 300 Lumen, 160Cm Wire, With Reflector
Fanalino posteriore	Spanninga, Stvzo, Commuter Glow With Brake XEr
Portapacchi	Specialized rack, MIK HD interface, built-in pannier mounts, 27kg max load
Lucchetto	Turbo System Lock
Parafanghi	Specialized DRYTECH fenders, 65mm width, aluminum fenderstay
Cavalletto	Specialized kickstand, 40mm mount
Campanello	Simple bell
Identificativo	221909

## TURBO TERO 5.0 EQ



Red Onyx / Smoke

TURBO TERO 5.0 EQ	S	M	L	XL
Stack (mm)	637	651	664	687
Reach (mm)	405	426	446	462
Lunghezza Tubo Sterzo (mm)	135	150	165	190
Angolo sterzo (degrees)	66.4	66.4	66.4	66.4
Altezza movimento centrale (mm)	313	313	313	313
BB Drop (mm)	57	57	57	57
Trail (mm)	114	114	114	114
Lunghezza forcella (mm)	516	516	516	516
Offset Forcella/Rake (mm)	44	44	44	44
Avancorsa (mm)	709	736	761	787
Lunghezza Batticateni (mm)	470.4	470.4	470.4	470.4
Interasse (mm)	1173	1200	1226	1252
Lunghezza Tubo Orizz. virtuale (mm)	589	620	650	680
Altezza Standover (mm)	773	807	807	835
Lunghezza Piantone (mm)	400	450	460	500
Angolo sella (virtuale) (degrees)	73.9	73.4	72.9	72.4
Lunghezza pedivella (mm)	170	170	170	170
Larghezza Manubrio (mm)	720	750	750	750
Lunghezza Attacco man. (mm)	60	60	75	75
Larghezza Sella (mm)	155	155	155	155
Lunghezza Reggisella (mm)	360	400	400	400

### SPECIFICHE TECNICHE

Specialized si riserva il diritto di modificare le caratteristiche senza preavviso.

Motore	Specialized 2.2, 90Nm torque, custom tuned motor, 250W nominal
Batteria	Specialized U2-710, alloy casing, state of charge display, 710Wh
Interfaccia	MasterMind TCD, w/handlebar remote, built-in anti-theft feature, Bluetooth® connectivity, customizable display pages
Caricatore	Custom charger, 42V4A w/ Rosenberger plug, 100-240V
Telaio	E5 Aluminum, bottom bracket motor mount, fully integrated & lockable downtube battery, internal cable routing, lock and front rack mount
Collarino Sella	Specialized 34.9mm
Forcella	Rockshox Recon Silver RL, 110mm travel, Motion-Control
Freno anteriore	SRAM DB8 Stealth
Freno posteriore	SRAM DB8 Stealth
Comandi cambio	SRAM GX Eagle, trigger, 12-speed, single click
Cambio posteriore	SRAM GX Eagle, 12-speed
Pacco Pignoni	SRAM NX Eagle, 12-speed, 11-50t
Catena	SRAM GX Eagle, 12-speed
Guarnitura	Custom Alloy Forged Crankarms, Isis, 170mm, CI 50.73mm, BCD 104mm
Ingranaggi	40T
Carter	Custom chaincover
Cerchi	Stout XC 29, 25mm internal width, disc-specific
Mozzo anteriore	Specialized alloy front hub disc, sealed cartridge bearings, 6-bolt, 15x110mm thru-axle, 32h
Mozzo posteriore	Specialized Alloy Rear Hub Disc, Sealed Cartridge Bearings, 6-Bolt, 12x148mm Thru-Axle, 32H, Hd Steel Fhb
Raggi	DT Swiss Industry
Pneumatico anteriore	Ground Control, 2Bliss Ready, 29x2.35"
Pneumatico posteriore	Ground Control, 2Bliss Ready, 29x2.35"
Camere d'aria	Standard 40mm SV 29x1.75-2.4
Attacco Manubrio	Specialized Stealth Stem, alloy, 14 deg, 31.8mm, integrated TCD mount S-M 60mm, L-XL 75mm
Manubrio	Specialized Trail, 6061 alloy, 8-degree backsweep, 6-degree upsweep, 27mm rise, 31.8mm clamp, S 720mm, M-XL 750mm
Manopole	Ergon GA30-S
Sella	Bridge Sport, Steel rails, 155mm
Reggisella	JD Dropper, 30.9mm, S: 100mm, M-XL: 120mm
Pedali	Specialized Body Geometry Fitness, Platform, Plastic
Radar	Integrated Garmin Radar, with custom information displayed directly on the Mastermind TCD
Fanale anteriore	LEZYNE Power StVZO E500+, 500 Lumens
Fanalino posteriore	Spanninga LED Tail light with StVZO GLOW
Portapacchi	Specialized rack, MIK HD interface, built-in pannier mounts, 27kg max load
Lucchetto	Turbo System Lock
Parafanghi	Specialized DRYTECH fenders, 65mm width, alloy fenderstays
Cavalletto	Specialized kickstand, 40mm mount
Campanello	Specialized brass bell
Identificativo	262679
Peso	25.55 kg (56 lb, 5.2 oz)
Misura pesata	MD

ART. NR.	DESCRIZIONE	COLORE	MISURA
95125-4102/5	TERO 5.0 EQ NB KH	Red Onyx / Smoke	S-XL

# TURBO TERO 5.0 EQ STEP-THROUGH



GLOSS METALLIC DARK NAVY / SILVER DUST REFLECTIVE



GLOSS RED ONYX / SATIN SMOKE

TURBO TERO 5.0 EQ STEP-THROUGH	S	M	L	XL
Stack (mm)	637	651	664	687
Reach (mm)	405	426	446	462
Lunghezza Tubo Sterzo (mm)	135	150	165	190
Angolo sterzo (degrees)	66.4	66.4	66.4	66.4
Altezza movimento centrale (mm)	313	313	313	313
BB Drop (mm)	57	57	57	57
Trail (mm)	114	114	114	114
Lunghezza forcella (mm)	516	516	516	516
Offset Forcella/Rake (mm)	44	44	44	44
Avancorsa (mm)	709	736	761	787
Lunghezza Batticateni (mm)	470.4	470.4	470.4	470.4
Interasse (mm)	1173	1200	1226	1252
Lunghezza Tubo Orizz. virtuale (mm)	589	620	650	680
Altezza Standover (mm)	658	655	655	664
Lunghezza Piantone (mm)	400	450	460	500
Angolo sella (Virtuale) (degrees)	73.9	73.4	72.9	72.4
Lunghezza pedivella (mm)	170	170	170	170
Larghezza Manubrio (mm)	720	750	750	750
Lunghezza Attacco man. (mm)	60	60	75	75
Larghezza Sella (mm)	155	155	155	155
Lunghezza Reggisella (mm)	360	400	400	400

## SPECIFICHE TECNICHE

SPECIFICHE TECNICHE	Specialized si riserva il diritto di modificare le caratteristiche senza preavviso.
Motore	Specialized 2.2, 90Nm torque, custom tuned motor, 250W nominal
Batteria	Specialized U2-710, alloy casing, state of charge display, 710Wh
Interfaccia	MasterMind TCD, w/handlebar remote, built-in anti-theft feature, Bluetooth® connectivity, customizable display pages
Caricatore	Custom charger, 42V4A w/ Rosenberger plug, 100-240V
Telaio	E5 Aluminum, bottom bracket motor mount, fully integrated & lockable downtube battery, internal cable routing, lock and front rack mount
Collarino Sella	Specialized Alloy 34.9, Steel Bolt
Forcella	Rockshox Recon Silver RL, 110mm travel, Motion-Control
Freno anteriore	SRAM DB8 Stealth
Freno posteriore	SRAM DB8 Stealth
Comandi cambio	SRAM GX Eagle, trigger, 12-speed, single click
Cambio posteriore	SRAM GX Eagle, 12-speed
Pacco Pignoni	SRAM NX Eagle, 12-speed, 11-50t
Catena	SRAM GX Eagle, 12-speed
Guarnitura	Custom Alloy Forged Crankarms, Isis, 170mm, Cl50.73mm, BCD104mm
Ingranaggi	40T
Carter	Custom chaincover
Cerchi	Stout XC 29, 25mm internal width, disc-specific
Mozzo anteriore	Specialized alloy front hub disc, sealed cartridge bearings, 6-bolt, 15x110mm thru-axle, 32h
Mozzo posteriore	Specialized Alloy Rear Hub Disc, Sealed Cartridge Bearings, 6-Bolt, 12x148mm Thru-Axle, 32H, Hd Steel Fhb
Raggi	DT Swiss Industry
Pneumatico anteriore	Ground Control, 2Bliss Ready, 29x2.35"
Pneumatico posteriore	Ground Control, 2Bliss Ready, 29x2.35"
Camere d'aria	Specialized Turbo Tube 29X1.75-2.4
Attacco Manubrio	Specialized Stealth Stem, alloy, 14 deg, 31.8mm, integrated TCD mount S-M 60mm, L-XL 75mm
Manubrio	Specialized Trail, 6061 alloy, 8-degree backsweep, 6-degree upsweep, 27mm rise, 31.8mm clamp, S 720mm, M-XL 750mm
Manopole	ERGON, GA30-S Custom, 134.8mm Length
Sella	Bridge Sport, Steel rails, 155mm
Reggisella	JD Dropper, 30.9mm, S: 100mm, M-XL: 120mm
Pedali	Specialized Body Geometry Fitness, Platform, Plastic
Radar	Integrated Garmin Radar, with custom information displayed directly on the Mastermind TCD
Fanale anteriore	LEZYNE Power StvZO E500+, 500 Lumens
Fanalino posteriore	Spanninga, Stvzo, Commuter Glow With Brake XEr
Portapacchi	Specialized rack, MIKHD interface, built-in pannier mounts, 27kg max load
Lucchetto	Turbo System Lock
Parafanghi	Specialized DRYTECH fenders, 65mm width, alloy fenderstays
Cavalletto	Specialized kickstand, 40mm mount
Campanello	Specialized brass bell
Identificativo	263280
Peso	26.60kg (58 lb, 10.3 oz)
Misura pesata	MD

ART. NR.	DESCRIZIONE	COLORE	MISURA
95125-3602/5	TERO 5.0 ST EQ	GLOSS MET DARK NAVY/ SILVER DUST	S-XL
95125-3702/5	TERO 5.0 ST EQ	GLOSS RED ONYX / SATIN SMOKE	S-XL

Disponibile Online e Pickup in store

## TURBO TERO 4.0



Oak Green Metallic / Smoke



White Mountains / Gunmetal

TURBO TERO 4.0	S	M	L	XL
Stack (mm)	637	651	664	687
Reach (mm)	405	426	446	462
Lunghezza Tubo Sterzo (mm)	135	150	165	190
Angolo sterzo (degrees)	66.4	66.4	66.4	66.4
Altezza movimento centrale (mm)	313	313	313	313
BB Drop (mm)	57	57	57	57
Trail (mm)	114	114	114	114
Lunghezza forcella (mm)	516	516	516	516
Offset Forcella/Rake (mm)	44	44	44	44
Avancorsa (mm)	709	736	761	787
Lunghezza Batticateni (mm)	470.4	470.4	470.4	470.4
Interasse (mm)	1173	1200	1226	1252
Lunghezza Tubo Orizz. virtuale (mm)	589	620	650	680
Altezza Standover (mm)	773	807	807	835
Lunghezza Piantone (mm)	400	450	460	500
Angolo sella (Virtuale) (degrees)	73.9	73.4	72.9	72.4
Lunghezza pedivella (mm)	170	170	170	170
Larghezza Manubrio (mm)	720	750	750	750
Lunghezza Attacco man. (mm)	60	60	75	75
Larghezza Sella (mm)	155	155	155	155
Lunghezza Reggisella (mm)	360	400	400	400

ART. NR.	DESCRIZIONE	COLORE	MISURA
95125-7202	TERO 4.0 NB	Oak Green Metallic / Smoke	S
95125-7203			M
95125-7204			L
95125-7205			XL
95125-7302	TERO 4.0 NB KH	White Mountains / Gunmetal	S
95125-7303			M
95125-7304			L
95125-7305			XL

### SPECIFICHE TECNICHE

Specialized si riserva il diritto di modificare le caratteristiche senza preavviso.

Motore	Specialized 2.0, 70Nm torque, custom tuned motor, 250W nominal
Ingranaggi	40T
Batteria	Specialized 710Wh integrated battery
Batteria INTERFACCIA	Specialized U2-710, alloy casing, state of charge display, 710Wh MasterMind TCD, w/handlebar remote, built-in anti-theft feature, Bluetooth® connectivity, customizable display pages
Cablaggio	Custom wire harness
Caricatore	Custom charger, 42V4A w/ Rosenberger plug, 100-240V
Telaio	E5 Aluminum, bottom bracket motor mount, fully integrated & lockable downtube battery, internal cable routing, lock and front rack mount
Collarino Sella	Alloy, bolt-type, 34.9mm
Forcella	SR Suntour XCR34-Boost, 110mm Travel
Freno anteriore	Tektro HD-T280, hydraulic disc, 180mm
Freno posteriore	Tektro HD-T280, hydraulic disc, 180mm
Comandi cambio	Shimano Cues 9-speed w/ gear indicator
Cambio posteriore	Shimano Cues 9-speed, Shadow design
Pacco Pignoni	Shimano Cues 9-speed, 11-41
Catena	Shimano LG500
Guarnitura	Custom Alloy Forged Crankarms, Isis, 170mm, CI 50.73mm, BCD 104mm
Cerchi	Stout XC 29, 25mm internal width, disc-specific
Mozzo anteriore	Specialized alloy front hub, disc, sealed cartridge bearings, 6-bolt, 15x110mm thru-axle, 32h
Mozzo posteriore	Specialized Alloy Rear Hub Disc, Sealed Cartridge Bearings, 6-Bolt, 12x148mm Thru-Axle, 32H, Hd Steel Fhb
Raggi	DT Swiss Industry
Pneumatico anteriore	Ground Control, 2Bliss Ready, 29x2.35"
Pneumatico posteriore	Ground Control, 2Bliss Ready, 29x2.35"
Camere d'aria	Standard 40mm SV 29x1.75-2.4
Attacco Manubrio	Specialized Stealth Stem, alloy, 14 deg, 31.8mm, integrated TCD mount
Manubrio	Specialized Trail, 6061 alloy, 8-degree backsweep, 6-degree upsweep, 27mm rise, 31.8mm clamp, S 720mm, M-XL 750mm
Manopole	Specialized Trail Grips
Sella	Bridge Sport, Steel rails, 155mm
Reggisella	TranzX Dropper, 30.9mm, S: 100mm, M-XL: 120mm
Pedali	Specialized Body Geometry Fitness, Platform, Plastic
Lucchetto	Turbo System Lock
Campanello	Simple bell
Identificativo	262681
Peso	23.15kg (51 lb, .6 oz)
Misura pesata	MD

## TURBO TERO 4.0 STEP THROUGH



Oak Green Metallic / Smoke



White Mountains / Gunmetal

TURBO TERO 4.0 STEP THROUGH	S	M	L	XL
Stack (mm)	637	651	664	687
Reach (mm)	405	426	446	462
Lunghezza Tubo Sterzo (mm)	135	150	165	190
Angolo sterzo (degrees)	66.4	66.4	66.4	66.4
Altezza movimento centrale (mm)	313	313	313	313
BB Drop (mm)	57	57	57	57
Trail (mm)	114	114	114	114
Lunghezza forcella (mm)	516	516	516	516
Offset Forcella/Rake (mm)	44	44	44	44
Avancorsa (mm)	709	736	761	787
Lunghezza Batticateni (mm)	470.4	470.4	470.4	470.4
Interasse (mm)	1173	1200	1226	1252
Lunghezza Tubo Orizz. virtuale (mm)	589	620	650	680
Altezza Standover (mm)	658	655	655	664
Lunghezza Piantone (mm)	400	450	460	500
Angolo sella (Virtuale) (degrees)	73.9	73.4	72.9	72.4
Lunghezza pedivella (mm)	170	170	170	170
Larghezza Manubrio (mm)	720	750	750	750
Lunghezza Attacco man. (mm)	60	60	75	75
Larghezza Sella (mm)	155	155	155	155
Lunghezza Reggisella (mm)	360	400	400	400

SPECIFICHE TECNICHE	Specialized si riserva il diritto di modificare le caratteristiche senza preavviso.
Motore	Specialized 2.0, 70Nm torque, custom tuned motor, 250W nominal
Ingranaggi	40T
Batteria	Specialized 710Wh integrated battery
Batteria	Specialized U2-710, alloy casing, state of charge display, 710Wh
Interfaccia	MasterMind TCD, w/handlebar remote, built-in anti-theft feature, Bluetooth® connectivity, customizable display pages
Caricatore	Custom charger, 42V4A w/ Rosenberger plug, 100-240V
Telaio	E5 Aluminum, bottom bracket motor mount, fully integrated & lockable downtube battery, internal cable routing, lock and front rack mount
Collarino Sella	Alloy, bolt-type, 34.9mm
Forcella	SR Suntour XCR34-Boost, 110mm Travel
Freno anteriore	Tektro HD-M520
Freno posteriore	Tektro HD-M520
Comandi cambio	Shimano Cues 9-speed w/ gear indicator
Cambio posteriore	Shimano Cues 9-speed, Shadow design
Pacco Pignoni	Shimano Cues 9-speed, 11-41
Catena	Shimano LG500
Guarnitura	Custom Alloy Forged Crankarms, Isis, 170mm, CI 50.73mm, BCD 104mm
Cerchi	Stout XC 29, 25mm internal width, disc-specific
Mozzo anteriore	Specialized alloy front hub, disc, sealed cartridge bearings, 6-bolt, 15x110mm thru-axle, 32h
Mozzo posteriore	Specialized Alloy Rear Hub Disc, Sealed Cartridge Bearings, 6-Bolt, 12x148mm Thru-Axle, 32H, Hd Steel Fhb
Raggi	DT Swiss Industry
Pneumatico anteriore	Ground Control, 2Bliss Ready, 29x2.35"
Pneumatico posteriore	Ground Control, 2Bliss Ready, 29x2.35"
Camere d'aria	Standard 40mm SV 29x1.75-2.4
Attacco Manubrio	Specialized Stealth Stem, alloy, 14 deg, 31.8mm, integrated TCD mount, S-M 60mm, L-XL 75mm
Manubrio	Specialized Trail, 6061 alloy, 8-degree backsweep, 6-degree upsweep, 27mm rise, 31.8mm clamp, S 720mm, M-XL 750mm
Manopole	Specialized Trail Grips
Sella	Bridge Sport, Steel rails, 155mm
Reggisella	TranzX Dropper, 30.9mm, S: 100mm, M-XL: 120mm
Pedali	Specialized Body Geometry Fitness, Platform, Plastic
Lucchetto	Turbo System Lock
Campanello	Bell
Identificativo	262683

ART. NR.	DESCRIZIONE	COLORE	MISURA
95125-7602	TERO 4.0 ST NB KH	Oak Green Metallic / Smoke	S
95125-7603			M
95125-7604			L
95125-7605			XL
95125-7702	TERO 4.0 ST NB KH	White Mountains / Gunmetal	S
95125-7703			M
95125-7704			L
95125-7705			XL



Smoke / Black

<b>TURBO PORTO</b>	<b>one-size</b>
Stack (mm)	612
Reach (mm)	455
Lunghezza Tubo Sterzo (mm)	220
Angolo sterzo (degrees)	68
Altezza BB (mm)	285
B-B Drop (mm)	-9.5
Trail (mm)	80
Lunghezza forcella (mm)	413.9
Offset forcella/Rake (mm)	48
Avancorsa (mm)	739
Lunghezza Batticateni (mm)	702
Interasse (mm)	1439
Lunghezza Tubo Orizz. virtuale (mm)	654
Altezza standover (mm)	541
Lunghezza piantone (mm)	330
Angolo sterzo (degrees)	72
Lunghezza pedivella - translate here (mm)	165
Larghezza Manubrio (mm)	680
Lunghezza Attacco man. (mm)	77
Larghezza Sella (mm)	200
Lunghezza Reggisella (mm)	585

<b>SPECIFICHE TECNICHE</b>	<b>Specialized si riserva il diritto di modificare le caratteristiche senza preavviso.</b>		
Telaio	E5 Aluminum, bottom bracket motor mount,+D9:D44 fully integrated & lockable downtube battery, internal cable routing		
Forcella	E5 Aluminium, Integrated Ring Lock, 15x110mm Thru-Axle, Tubus Duo Side Rack Mounts.		
Attacco Manubrio	2 ways adjustable stem; quick height adjust with toolfree clamp, and bolt angle adjust, 77mm long		
Manopole	Ergon GA3 Twist Shift		
Manubrio	Specialized, alloy, 8-degree backsweep, 6-degree upsweep, 27mm rise, 31.8mm, 680mm wide		
Freno anteriore	Tektro Dorardo, Cargo Specific, Front Hydraulic Disc Brake, 4 Piston Caliper, 3 Fingers Lever, 203mm, 2.3 thickness		
Freno posteriore	Tektro Dorado, Cargo Specific, Rear Hydraulic Disc Brake, 4 Piston Caliper, 3 Fingers Lever, 203mm, 2.3 thickness		
Cambio posteriore	enviolo CVP Multi-Turn		
Comandi cambio	enviolo Twist Display Pure		
Pacco Pignoni	Gates Carbon Drive CDX 24t sprocket, silver		
Catena	Gates Carbon Drive CDX 166t belt, black		
Guarnitura	Custom alloy forged crankarms, 165mm		
Ingranaggi	Gates Carbon Drive CDX 48T chainring, black		
Pedali	Specialized Commuter w/ grip tape & reflectors		
Mozzo anteriore	Specialized alloy front hub disc, sealed cartridge bearings, 6-bolt, 15x110mm thru-axle, 32h		
Cerchi	24in Front 32h, 20in Rear 36h, double-wall alloy, pinned		
Mozzo posteriore	enviolo Heavy Duty, 380% range, 6-bolt, 10x135mm, 36h		
Raggi	DT Swiss Industry		
Pneumatico anteriore	Pathfinder Sport Reflect, 24X2.8		
Pneumatico posteriore	Pathfinder Sport Reflect, 20X2.8		
Camere d'aria	Standard 32mm SV 24X2.4-3.0, 20X2.4-3.0		
Sella	Body Geometry Comfort Gel, 200mm w/ Handle		
Reggisella	Double Extension Seatpost, 34.9mm, 585mm, 20mm Offset		
Collarino Sella	Specialized bolt-type, alloy, 39mm		
Radar	Integrated Garmin Radar, with custom information displayed directly on the Mastermind TCD		
Motore	Specialized 2.2 Cargo, 90Nm torque, custom tuned motor, 250W nominal		
INTERFACCIA	MasterMind TCD, w/handlebar remote, built-in anti-theft feature, Bluetooth® connectivity, customizable display pages		
Batteria	Specialized U2-710, alloy casing, state of charge display, 710Wh		
Caricatore	Custom charger, 42V4A w/ Rosenberger plug, 100-240V		
Accessori SWAT	Handlebar rear view mirror, aluminum		
Fanale anteriore	Lezyne EBIKE CLASSIC STVZO E500, 500 Lumens, 12V		
Fanalino posteriore	Spanninga Commuter Glow XE, brake alert, 12V		
Cavalletto	Double Leg, Center Mount M10, Cargo Specific Custom Design Kickstand		
Portapacchi	Specialized rack, MIK HD interface (3 Positions), built-in side pannier mounts, 60kg max load		
Parafanghi	Specialized DRYTECH Fenders, 78C, Front Aluminium Stays, Full Rear Wheel Coverage for child seating safety		
Lucchetto	Abus battery lock with lever and matching key for ring lock on the fork		
Campanello	Specialized brass bell		
Peso	39.60kg (87 lb, 4.8 oz) Including 3kg Front Rack		
Misura pesata	One Size		
<b>ART. NR.</b>	<b>DESCRIZIONE</b>	<b>COLORE</b>	<b>MISURA</b>
90823-5200	PORTO 4.0 NB	Smoke / Black	One Size